Software Interface
CCRTNGFC (WC-CP-FIO2)

PCIe Next Generation FPGA I/O Card

Driver	ccrtngfc (WC-CP-FIO2)	
Platform	RedHawk Linux® *(CentOS/Rocky/RHEL & Ubuntu)*, Native Ubuntu® and Native Red Hat Enterprise Linux®[1]	
Vendor	Concurrent Real-Time	
Hardware	PCIe Programmable Multi-Function Card (CP-FPGA-4 & 5)	
Author	Darius Dubash	
Date	February 10th, 2026	Rev 2026.1

[1] All trademarks are the property of their respective owners

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

This page intentionally left blank

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

Table of Contents

1. INTRODUCTION 7

1.1 Related Documents 7

2. SOFTWARE SUPPORT 7

2.1 Direct Driver Access 7
2.1.1 open(2) system call 7
2.1.2 ioctl(2) system call 8
2.1.3 mmap(2) system call 10
2.2 Application Program Interface (API) Access 11
2.2.1 ccrtNGFC_Add_Irq() 11
2.2.2 ccrtNGFC_BoardExpirationTimeRemaining() 11
2.2.3 ccrtNGFC_Clear_Driver_Error() 12
2.2.4 ccrtNGFC_Clear_Interrupt_Status() 12
2.2.5 ccrtNGFC_Clear_Lib_Error() 13
2.2.6 ccrtNGFC_Clock_Generator_Soft_Reset() 13
2.2.7 ccrtNGFC_Clock_Get_Generator_CSR() 13
2.2.8 ccrtNGFC_Clock_Get_Generator_Info() 14
2.2.9 ccrtNGFC_Clock_Get_Generator_Input_Clock_Enable() 17
2.2.10 ccrtNGFC_Clock_Get_Generator_Input_Clock_Select() 17
2.2.11 ccrtNGFC_Clock_Get_Generator_Input_Clock_Status() 18
2.2.12 ccrtNGFC_Clock_Get_Generator_M_Divider() 19
2.2.13 ccrtNGFC_Clock_Get_Generator_N_Divider() 19
2.2.14 ccrtNGFC_Clock_Get_Generator_Output_Config() 20
2.2.15 ccrtNGFC_Clock_Get_Generator_Output_Format() 20
2.2.16 ccrtNGFC_Clock_Get_Generator_Output_Mode() 21
2.2.17 ccrtNGFC_Clock_Get_Generator_Output_Mux() 22
2.2.18 ccrtNGFC_Clock_Get_Generator_P_Divider() 23
2.2.19 ccrtNGFC_Clock_Get_Generator_P_Divider_Enable() 23
2.2.20 ccrtNGFC_Clock_Get_Generator_R_Divider() 24
2.2.21 ccrtNGFC_Clock_Get_Generator_Revision() 24
2.2.22 ccrtNGFC_Clock_Get_Generator_Value() 25
2.2.23 ccrtNGFC_Clock_Get_Generator_Voltage_Select() 25
2.2.24 ccrtNGFC_Clock_Get_Generator_Zero_Delay() 26
2.2.25 ccrtNGFC_Clock_PLL_CSR() 26
2.2.26 ccrtNGFC_Clock_ReturnOutputFrequency() 27
2.2.27 ccrtNGFC_Clock_Set_Generator_CSR() 27
2.2.28 ccrtNGFC_Clock_Set_Generator_Input_Clock_Enable() 28
2.2.29 ccrtNGFC_Clock_Set_Generator_Input_Clock_Select() 29
2.2.30 ccrtNGFC_Clock_Set_Generator_M_Divider() 29
2.2.31 ccrtNGFC_Clock_Set_Generator_N_Divider() 30
2.2.32 ccrtNGFC_Clock_Set_Generator_Output_Config() 30
2.2.33 ccrtNGFC_Clock_Set_Generator_Output_Format() 31
2.2.34 ccrtNGFC_Clock_Set_Generator_Output_Mode() 32
2.2.35 ccrtNGFC_Clock_Set_Generator_Output_Mux() 33
2.2.36 ccrtNGFC_Clock_Set_Generator_P_Divider() 34
2.2.37 ccrtNGFC_Clock_Set_Generator_P_Divider_Enable() 34
2.2.38 ccrtNGFC_Clock_Set_Generator_R_Divider() 35
2.2.39 ccrtNGFC_Clock_Set_Generator_Value() 35
2.2.40 ccrtNGFC_Clock_Set_Generator_Voltage_Select() 36
2.2.41 ccrtNGFC_Clock_Set_Generator_Zero_Delay() 36
2.2.42 ccrtNGFC_Close() 37
2.2.43 ccrtNGFC_Compute_All_Output_Clocks() 37
2.2.44 ccrtNGFC_Convert_Physmem2avmm_Address() 38

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.45 ccrtNGFC_Create_UserLDioCosInterruptHandler() 39
2.2.46 ccrtNGFC_Create_UserProcess() 40
2.2.47 ccrtNGFC_DataToVolts() 41
2.2.48 ccrtNGFC_DataToVoltsLxxFormat() 42
2.2.49 ccrtNGFC_DaughterCard_EEPROM_Read() 42
2.2.50 ccrtNGFC_DaughterCard_EEPROM_Write() 43
2.2.51 ccrtNGFC_Destroy_AllUserProcess() 43
2.2.52 ccrtNGFC_Destroy_UserLDioCosInterruptHandler() 44
2.2.53 ccrtNGFC_Destroy_UserProcess() 44
2.2.54 ccrtNGFC_DIO_Get_Channels_Terminator() 44
2.2.55 ccrtNGFC_DIO_Get_Ports_Direction() 46
2.2.56 ccrtNGFC_DIO_Set_Channels_Terminator() 48
2.2.57 ccrtNGFC_DIO_Set_Channels_Terminator_To_Off() 50
2.2.58 ccrtNGFC_DIO_Set_Channels_Terminator_To_On() 51
2.2.59 ccrtNGFC_DIO_Set_Ports_Direction() 52
2.2.60 ccrtNGFC_DIO_Set_Ports_Direction_To_Input() 54
2.2.61 ccrtNGFC_DIO_Set_Ports_Direction_To_Output() 56
2.2.62 ccrtNGFC_Disable_Pci_Interrupts() 57
2.2.63 ccrtNGFC_Enable_Pci_Interrupts() 58
2.2.64 ccrtNGFC_Fast_Memcpy() 58
2.2.65 ccrtNGFC_Fast_Memcpy_Unlocked() 59
2.2.66 ccrtNGFC_Fast_Memcpy_Unlocked_FIFO() 59
2.2.67 ccrtNGFC_Fraction_To_Hex() 60
2.2.68 ccrtNGFC_Get_All_Boards_Driver_Info() 60
2.2.69 ccrtNGFC_Get_Board_CSR() 62
2.2.70 ccrtNGFC_Get_Board_Info() 62
2.2.71 ccrtNGFC_Get_Driver_Error() 63
2.2.72 ccrtNGFC_Get_Driver_Info() 64
2.2.73 ccrtNGFC_Get_Interrupt_Status() 66
2.2.74 ccrtNGFC_Get_Interrupt_Timeout_Seconds() 66
2.2.75 ccrtNGFC_Get_Lib_Error() 67
2.2.76 ccrtNGFC_Get_Lib_Error_Description() 69
2.2.77 ccrtNGFC_Get_Library_Info() 69
2.2.78 ccrtNGFC_Get_Mapped_Config_Ptr() 70
2.2.79 ccrtNGFC_Get_Mapped_Driver_Library_Ptr() 71
2.2.80 ccrtNGFC_Get_Mapped_Local_Ptr() 71
2.2.81 ccrtNGFC_Get_Open_File_Descriptor() 72
2.2.82 ccrtNGFC_Get_Physical_Memory() 72
2.2.83 ccrtNGFC_Get_PowerModule_Info() 73
2.2.84 ccrtNGFC_Get_RunCount_UserProcess() 73
2.2.85 ccrtNGFC_Get_Value() 74
2.2.86 ccrtNGFC_Hex_To_Fraction() 74
2.2.87 ccrtNGFC_Identify_Board() 74
2.2.88 ccrtNGFC_Initialize_Board() 75
2.2.89 ccrtNGFC_IpCore_Get_Info() 75
2.2.90 ccrtNGFC_IpCore_Get_Mapped_Ptr() 76
2.2.91 ccrtNGFC_LDIO_Activate() 77
2.2.92 ccrtNGFC_LDIO_Get_Channels_Polarity() 78
2.2.93 ccrtNGFC_LDIO_Get_COS_Channels_Edge_Sense() 80
2.2.94 ccrtNGFC_LDIO_Get_COS_Channels_Enable() 82
2.2.95 ccrtNGFC_LDIO_Get_COS_Channels_Mode() 84
2.2.96 ccrtNGFC_LDIO_Get_COS_Channels_Overflow() 86
2.2.97 ccrtNGFC_LDIO_Get_COS_Channels_Status() 88
2.2.98 ccrtNGFC_LDIO_Get_Input_Channels_Filter() 90
2.2.99 ccrtNGFC_LDIO_Get_Input_Snapshot() 92
2.2.100 ccrtNGFC_LDIO_Get_Output_Sync() 92

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.101 ccrtNGFC_LDIO_Read_Input_Channel_Registers() 93
2.2.102 ccrtNGFC_LDIO_Read_Output_Channel_Registers() 95
2.2.103 ccrtNGFC_LDIO_Set_Channels_Polarity() 97
2.2.104 ccrtNGFC_LDIO_Set_COS_Channels_Edge_Sense() 99
2.2.105 ccrtNGFC_LDIO_Set_COS_Channels_Enable() 101
2.2.106 ccrtNGFC_LDIO_Set_COS_Channels_Mode() 103
2.2.107 ccrtNGFC_LDIO_Set_Input_Channels_Filter() 105
2.2.108 ccrtNGFC_LDIO_Set_Input_Snapshot() 107
2.2.109 ccrtNGFC_LDIO_Set_Output_Sync() 108
2.2.110 ccrtNGFC_LDIO_Write_Output_Channel_Registers() 109
2.2.111 ccrtNGFC_LDIO_Write_Output_Channel_ Registers_High() 111
2.2.112 ccrtNGFC_LDIO_Write_Output_Channel_Registers_Low() 113
2.2.113 ccrtNGFC_LIO_On_Off() 115
2.2.114 ccrtNGFC_LIO_Get_Ports_Direction() 116
2.2.115 ccrtNGFC_LIO_Read_Output_Loopbacked_Channels() 117
2.2.116 ccrtNGFC_LIO_Set_Ports_Direction() 119
2.2.117 ccrtNGFC_LIO_Set_Ports_Direction_To_Input() 121
2.2.118 ccrtNGFC_LIO_Set_Ports_Direction_To_Output() 122
2.2.119 ccrtNGFC_MMap_Physical_Memory() 123
2.2.120 ccrtNGFC_MsgDma_Clone() *(US Patent No.: US 11,281,584 B1®)* 124
2.2.121 ccrtNGFC_MsgDma_Configure_Descriptor() 126
2.2.122 ccrtNGFC_MsgDma_Configure_Single() 128
2.2.123 ccrtNGFC_MsgDma_Fire() 129
2.2.124 ccrtNGFC_MsgDma_Fire_Fifo() 131
2.2.125 ccrtNGFC_MsgDma_Fire_Single() 132
2.2.126 ccrtNGFC_MsgDma_Free_Descriptor() 133
2.2.127 ccrtNGFC_MsgDma_Get_Descriptor() 133
2.2.128 ccrtNGFC_MsgDma_Get_Dispatcher_CSR() 135
2.2.129 ccrtNGFC_MsgDma_Get_Info() 136
2.2.130 ccrtNGFC_MsgDma_Get_Prefetcher_CSR() 137
2.2.131 ccrtNGFC_MsgDma_Release() 138
2.2.132 ccrtNGFC_MsgDma_Seize() 139
2.2.133 ccrtNGFC_MsgDma_Setup() 140
2.2.134 ccrtNGFC_Munmap_Physical_Memory() 141
2.2.135 ccrtNGFC_NanoDelay() 141
2.2.136 ccrtNGFC_Open() 141
2.2.137 ccrtNGFC_Pause_UserProcess() 142
2.2.138 ccrtNGFC_PowerModule_Control() 142
2.2.139 ccrtNGFC_Program_All_Output_Clocks() 143
2.2.140 ccrtNGFC_Read() 144
2.2.141 ccrtNGFC_Reload_Firmware() 145
2.2.142 ccrtNGFC_Remove_Irq() 145
2.2.143 ccrtNGFC_Reset_Board() 146
2.2.144 ccrtNGFC_Reset_Clock() 146
2.2.145 ccrtNGFC_Resume_UserProcess() 146
2.2.146 ccrtNGFC_Return_Board_Info_Description() 147
2.2.147 ccrtNGFC_Set_Board_CSR() 147
2.2.148 ccrtNGFC_Set_Interrupt_Timeout_Seconds() 148
2.2.149 ccrtNGFC_Set_Value() 148
2.2.150 ccrtNGFC_Transfer_Data() 148
2.2.151 ccrtNGFC_Update_Clock_Generator_Divider() 150
2.2.152 ccrtNGFC_UserProcess_Command() 151
2.2.153 ccrtNGFC_VoltsToData() 151
2.2.154 ccrtNGFC_Wait_For_Interrupt() 151

3. TEST PROGRAMS 153

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

3.1 Direct Driver Access Example Tests 153
3.1.1 ccrtngfc_chip_temperature 153
3.1.2 ccrtngfc_disp 154
3.1.3 ccrtngfc_dump 154
3.1.4 ccrtngfc_rdreg 158
3.1.5 ccrtngfc_reg 159
3.1.6 ccrtngfc_regedit 169
3.1.7 ccrtngfc_tst 169
3.1.8 ccrtngfc_wreg 170
3.1.9 Flash/ccrtngfc_flash 171
3.1.10 Flash/ccrtngfc_label 172
3.1.11 Flash/ccrtngfc_dump_license 173
3.2 Application Program Interface (API) Access Example Tests 174
3.2.1 lib/ccrtngfc_acquire_physmem 174
3.2.2 lib/ccrtngfc_adc 174
3.2.3 lib/ccrtngfc_adc_calibrate 177
3.2.4 lib/ccrtngfc_adc_fifo 178
3.2.5 lib/ccrtngfc_adc_sps 182
3.2.6 lib/ccrtngfc_check_bus 183
3.2.7 lib/ccrtngfc_clock 184
3.2.8 lib/ccrtngfc_compute_output_clock 185
3.2.9 lib/ccrtngfc_dac 187
3.2.10 lib/ccrtngfc_dac_calibrate 192
3.2.11 lib/ccrtngfc_dac_fifo 193
3.2.12 lib/ccrtngfc_dac_setchan 196
3.2.13 lib/ccrtngfc_daughtercard_info 199
3.2.14 lib/ccrtngfc_dio 200
3.2.15 lib/ccrtngfc_disp 201
3.2.16 lib/ccrtngfc_dma 203
3.2.17 lib/ccrtngfc_example 204
3.2.18 lib/ccrtngfc_expires 206
3.2.19 lib/ccrtngfc_identify 207
3.2.20 lib/ccrtngfc_info 208
3.2.21 lib/ccrtngfc_ldio_intr 210
3.2.22 lib/ccrtngfc_lio 215
3.2.23 lib/ccrtngfc_msgdma 217
3.2.24 lib/ccrtngfc_msgdma_clone 219
3.2.25 lib/ccrtngfc_msgdma_info 224
3.2.26 lib/ccrtngfc_msgdma_multi_clone 227
3.2.27 lib/ccrtngfc_sdc 230
3.2.28 lib/ccrtngfc_sensors 231
3.2.29 lib/ccrtngfc_smp_affinity 232
3.2.30 lib/ccrtngfc_transfer 232
3.2.31 lib/ccrtngfc_tst_lib 233

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

1. Introduction

This document provides the software interface to the ***ccrtngfc*** driver which communicates with the Concurrent Real-Time PCI Express Next Generation FPGA I/O Card (NGFC) and the Concurrent Real-Time PCI Express Single Daughter Card FPGA I/O Card (SDFC). Low-level programming is contained in the *Concurrent Real-Time PCIe Next Generation FPGA I/O Cards (NGFC) Design Specification* (No. *0610111*) and the *Concurrent Real-Time PCIe Single Daughter Card FPGA I/O Cards (SDFC) Design Specification* (No. *0610117*) which are CCRT internal documents that are not supplied to the customer.

The software package that accompanies this board provides the ability for advanced users to communicate directly with the board via the driver *ioctl(2)* and *mmap(2)* system calls. When programming in this mode, the user needs to be intimately familiar with both the hardware and the register programming interface to the board. Failure to adhere to correct programming will result in unpredictable behavior.

Additionally, the software package is accompanied with an extensive set of application programming interface (API) calls that allow the user to access all capabilities of the board. The API library also allows the user the ability to communicate directly with the board through the *ioctl(2)* and *mmap(2)* system calls. In this case, there is a risk of this direct access conflicting with API calls and therefore should only be used by advanced users who are intimately familiar with the hardware, board registers and the driver code.

Various example tests have been provided in the *test* and *test/lib* directories to assist the user in developing their applications.

1.1 Related Documents

- PCIe Next Generaton FPGA Driver Installation on RedHawk Release Notes by Concurrent Real-Time.
- PCIe Next Generation FPGA Driver Technical Guide by Concurrent Real-Time.
- PCIe Next Generation FPGA Card I/O (NGFC) Design Specification (No. *0610111*) by Concurrent Real-Time *(internal document)*.

2. Software Support

Software support is provided for users to communicate directly with the board using the kernel system calls *(Direct Driver Access)* or the supplied *API.* Both approaches are identified below to assist the user in software development.

2.1 Direct Driver Access

2.1.1 open(2) system call

In order to access the board, the user first needs to open the main device using the standard system call *open(2).*

```
int    fp;
fp = open("/dev/ccrtngfc0", O_RDWR);
```

The file pointer '*fp'* is then used as an argument to other system calls. The user can also supply the O_NONBLOCK flag if the user does not wish to block waiting for reads to complete. In that case, if the read is not satisfied, the call will fail. The device name specified is of the format "/dev/ccrtngfc<num>" where *num* is a digit 0..39 which represents the board number that is to be accessed. Basically, the driver only allows one application to open a board at a time. The reason for this is that the application can have full access to the card, even at the board and API level. If another application were to communicate with the same card concurrently, the results would be unpredictable unless proper synchronization between applications is performed external to the driver API.

This driver allows multiple applications to open the same board by specifying an additional *oflag O_APPEND*. It is then the responsibility of the user to ensure that the various applications communicating with the same cards are

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

properly synchronized. Various tests supplied in this package has the *O_APPEND* flags enabled, however, it is strongly recommended that only one application be run with a single card at a time, unless the user is well aware of how the applications are going to interact with each other and accept any unpredictable results.

Each Next Generation FPGA card can have installed in it one to two daughter cards that are capable of having their own unique capabilities. They can also be opened via the *open(2)* system call, however, there is a lot of dependendencies and interactions between the main and daughter cards, therefore, that information will not be discussed. In this case, when attempting to access daughter cards, you must open the main board and the daughter cards via the supplied API calls.

2.1.2 ioctl(2) system call

This system call provides the ability to control and get responses from the board. The nature of the control/response will depend on the specific *ioctl* command.

```
int   status;
int   arg;
status = ioctl(fp, <IOCTL_COMMAND>, &arg);
```

where, '*fp'* is the file pointer that is returned from the *open(2)* system call. <*IOCTL_COMMAND*> is one of the *ioctl* commands below and *arg* is a pointer to an argument that could be anything and is dependent on the command being invoked. If no argument is required for a specific command, then set to ***NULL*.**

Driver IOCTL command:

```
IOCTL_CCRTNGFC_ADD_IRQ
IOCTL_CCRTNGFC_DISABLE_PCI_INTERRUPTS
IOCTL_CCRTNGFC_ENABLE_PCI_INTERRUPTS
IOCTL_CCRTNGFC_GET_DRIVER_ERROR
IOCTL_CCRTNGFC_GET_DRIVER_INFO
IOCTL_CCRTNGFC_GET_PHYSICAL_MEMORY
IOCTL_CCRTNGFC_INIT_BOARD
IOCTL_CCRTNGFC_INTERRUPT_TIMEOUT_SECONDS
IOCTL_CCRTNGFC_MMAP_SELECT
IOCTL_CCRTNGFC_NO_COMMAND
IOCTL_CCRTNGFC_PCI_CONFIG_REGISTERS
IOCTL_CCRTNGFC_REMOVE_IRQ
IOCTL_CCRTNGFC_RESET_BOARD
IOCTL_CCRTNGFC_WAIT_FOR_INTERRUPT
IOCTL_CCRTNGFC_RELOAD_FIRMWARE
IOCTL_CCRTNGFC_GET_ALL_BOARDS_DRIVER_INFO
IOCTL_CCRTNGFC_LDIO_WAKEUP_COS_INTERRUPT
IOCTL_CCRTNGFC_LDIO_WAIT_FOR_COS_INTERRUPT
IOCTL_CCRTNGFC_WAIT_FOR_MSGDMA_INTERRUPT
```

IOCTL_CCRTNGFC_ADD_IRQ: This *ioctl* does not have any arguments. Its purpose is to setup the driver *interrupt handler* to handle interrupts. If support for MSI interrupts are configured, they will be enabled. Normally, there is no need to call this *ioctl* as the interrupt handler is already added when the driver is loaded. This *ioctl* should only be invoked if the user has issued the *IOCTL_CCRTNGFC_REMOVE_IRQ* call earlier to remove the interrupt handler.

IOCTL_CCRTNGFC_DISABLE_PCI_INTERRUPTS: This *ioctl* does not have any arguments. Its purpose is to disable PCI interrupts. This call shouldn't be used during normal reads or writes, as calls could time out. The driver handles enabling and disabling interrupts during its normal course of operation.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

IOCTL_CCRTNGFC_ENABLE_PCI_INTERRUPTS: This *ioctl* does not have any arguments. Its purpose is to enable PCI interrupts. This call shouldn't be used during normal reads or writes as calls could time out. The driver handles enabling and disabling interrupts during its normal course of operation.

IOCTL_CCRTNGFC_GET_DRIVER_ERROR: The argument supplied to this *ioctl* is a pointer to the *ccrtngfc_user_error_t* structure. Information on the structure is located in the *ccrtngfc_user.h* include file. The error returned is the last reported error by the driver. If the argument pointer is *NULL*, the current error is reset to *CCRTNGFC_SUCCESS.*

IOCTL_CCRTNGFC_GET_DRIVER_INFO: The argument supplied to this *ioctl* is a pointer to the *ccrtngfc_driver_info_t* structure. Information on the structure is located in the *ccrtngfc_user.h* include file. This *ioctl* provides useful driver information.

IOCTL_CCRTNGFC_GET_PHYSICAL_MEMORY: The argument supplied to this *ioctl* is a pointer to the *ccrtngfc_user_phys_mem_t* structure. Information on the structure is located in the *ccrtngfc_user.h* include file. If physical memory is not allocated, the call will fail; otherwise the call will return the physical memory address and size in bytes. The only reason to request and get physical memory from the driver is to allow the user to perform DMA operations and bypass the driver and library. Care must be taken when performing user level DMA, as incorrect programming could lead to unpredictable results, including but not limited to corrupting the kernel and any device connected to the system.

IOCTL_CCRTNGFC_INIT_BOARD: This *ioctl* does not have any arguments. This call resets the board to a known initial default state. This call is currently identical to the *IOCTL_CCRTNGFC_RESET_BOARD* call.

IOCTL_CCRTNGFC_INTERRUPT_TIMEOUT_SECONDS: The argument supplied to this *ioctl* is a pointer to an *int*. It allows the user to change the default time out from 30 seconds to user supplied time out. This is the time that the read call will wait before it times out. The call could time out if a DMA fails to complete. The device should have been opened in the block mode (*O_NONBLOCK* not set) for reads to wait for an operation to complete.

IOCTL_CCRTNGFC_MMAP_SELECT: The argument to this *ioctl* is a pointer to the *ccrtngfc_mmap_select_t* structure. Information on the structure is located in the *ccrtngfc_user.h* include file. This call needs to be made prior to the *mmap(2)* system call so as to direct the *mmap(2)* call to perform the requested mapping specified by this *ioctl*. The four possible mappings that are performed by the driver are to *mmap* the local register space *(CCRTNGFC_SELECT_LOCAL_MMAP)*, the configuration register space *(CCRTNGFC_SELECT_CONFIG_MMAP)* the physical memory *(CCRTNGFC_SELECT_PHYS_MEM_MMAP)* that is created by the *mmap(2)* system call and the driver/library mapping *(CCRTNGFC_SELECT_DRIVER_LIBRARY_MMAP)*.

IOCTL_CCRTNGFC_NO_COMMAND: This *ioctl* does not have any arguments. It is only provided for debugging purpose and should not be used as it serves no purpose for the application.

IOCTL_CCRTNGFC_PCI_CONFIG_REGISTERS: The argument supplied to this *ioctl* is a pointer to the *ccrtngfc_pci_config_reg_addr_mapping*_t structure whose definition is located in the *ccrtngfc_user.h* include file.

IOCTL_CCRTNGFC_REMOVE_IRQ: This *ioctl* does not have any arguments. Its purpose is to remove the interrupt handler that was previously setup. The interrupt handler is managed internally by the driver and the library. The user should not issue this call, otherwise reads will time out.

IOCTL_CCRTNGFC_RESET_BOARD: This *ioctl* does not have any arguments. This call resets the board to a known initial default state. This call is currently identical to the *IOCTL_CCRTNGFC_INIT_BOARD* call.

IOCTL_CCRTNGFC_WAIT_FOR_INTERRUPT: The argument to this *ioctl* is a pointer to the *ccrtngfc_driver_int_t* structure. Information on the structure is located in the *ccrtngfc_user.h* include file. The user can wait for a DMA or Analog signal complete interrupt. If a time out value greater than zero is specified, the call will time out after the specified seconds, otherwise it will not time out.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

IOCTL_CCRTNGFC_RELOAD_FIRMWARE: This *ioctl* does not have any arguments. This call performs a reload of the latest firmware that was loaded into the board. Typically, this is used after a new firmware has been installed. It eliminates the need to reboot the kernel after a firmware update.

IOCTL_CCRTNGFC_GET_ALL_BOARDS_DRIVER_INFO: The argument to this *ioctl* is a pointer to *ccrtngfc_all_boards_driver_info*. It provides the ability to supply all driver information for all the *ccrtngfc* cards in the system to the user.

IOCTL_CCRTNGFC_LDIO_WAKEUP_COS_INTERRUPT: This *ioctl* does not have any arguments The purpose of this call is to wake up a process that is blocked using the

IOCTL_CCRTNGFC_LDIO_WAIT_FOR_COS_INTERRUPT: This *ioctl* waits for a LIO/DIO change-of-state interrupt.
\
IOCTL_CCRTNGFC_LDIO_WAIT_FOR_COS_INTERRUPT: The argument to this *ioctl* is a pointer to the *ccrtngfc_driver_ldio_cos_int_t* structure. Information on the structure is located in the *ccrtngfc_user.h* include file. The user can wait for a LIO/DIO complete interrupt with the *WakeupInterruptMas* mask. This call blocks indefinitely until a LIO/DIO change-of-state interrupt occurs. If a change-of-state interrupt occurs, this call returns useful LIO/DIO related statistics to the user. To cancel a pending wait, users can use the *IOCTL_CCRTNGFC_LDIO_WAKEUP_COS_INTERRUPT ioctl()* call.

IOCTL_CCRTNGFC_WAIT_FOR_MSGDMA_INTERRUPT: This *ioctl* waits for a MsgDma interrupt. The argument to this *ioctl* is a pointer to the *ccrtngfc_driver_int_t* structure. Information on the structure is located in the *ccrtngfc_user.h* include file.

2.1.3 mmap(2) system call

This system call provides the ability to map either the local board registers, the configuration board registers, create and map a physical memory that can be used for user DMA or driver/library structure mapping. Prior to making this system call, the user needs to issue the *ioctl(2)* system call with the *IOCTL_CCRTNGFC_MMAP_SELECT* command. When mapping either the local board registers or the configuration board registers, the *ioctl* call returns the size of the register mapping which needs to be specified in the *mmap(2)* call. In the case of mapping a physical memory, the size of physical memory to be created is supplied to the *mmap(2)* call.

```
int *munmap_local_ptr;
ccrtngfc_local_ctrl_data_t  *local_ptr;
ccrtngfc_mmap_select_t      mmap_select;
unsigned long mmap_local_size;

mmap_select.select = CCRTNGFC_SELECT_LOCAL_MMAP;
mmap_select.offset = 0;
mmap_select.size   = 0;
ioctl(fp, IOCTL_CCRTNGFC_MMAP_SELECT,(void *)&mmap_select);
mmap_local_size = mmap_select.size;

munmap_local_ptr = (int *) mmap((caddr_t)0, map_local_size,
                   (PROT_READ|PROT_WRITE), MAP_SHARED, fp, 0);

local_ptr = (ccrtngfc_local_ctrl_data_t *)munmap_local_ptr;
local_ptr = (ccrtngfc_local_ctrl_data_t *)((char *)local_ptr + mmap_select.offset);
.
.
.

if(munmap_local_ptr != NULL)
    munmap((void *)munmap_local_ptr, mmap_local_size);
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2 Application Program Interface (API) Access

The API is the recommended method of communicating with the board for most users.

There are a lot of APIs that have multiple arguments to set various parameters. If the user only wishes to change certain parameters for the call, they need to get the current settings via a query API, change only those parameters that need to be modified and then invoke a setting API to update these parameters *(i.e. read/modify/write)*. This is a two API call operation.

A nice feature has been implemented in these APIs to simplify the user programming by having a common parameter CCRTNGFC_DO_NOT_CHANGE which is a #define, that can be used for a lot of these calls. Arguments with this parameter will therefore cause the API to perform the read/modify/write operation instead of the user performing the same function with two API calls. The drawback to this approach is that some compilers will complain about the use of this parameter and therefore the user will require appropriate casting to get rid of warnings/errors.

The following are a list of calls that are available.

2.2.1 ccrtNGFC_Add_Irq()

This call will add the driver interrupt handler if it has not been added. Normally, the user should not use this call unless they want to disable the interrupt handler and then re-enable it.

```
/************************************************************************
   int ccrtNGFC_Add_Irq(void *Handle)

   Description: By default, the driver assigns an interrupt handler to handle
                device interrupts. If the interrupt handler was removed using
                the ccrtNGFC_Remove_Irq(), then this call adds it back.

   Input:   void *Handle                        (Handle pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN          (library not open)
               # CCRTNGFC_LIB_IOCTL_FAILED      (driver ioctl call failed)
************************************************************************/
```

2.2.2 ccrtNGFC_BoardExpirationTimeRemaining()

This call provides useful information about the expiration date of the card if it has restricted licensing.

```
/************************************************************************
_ccrtngfc_lib_error_number_t
ccrtNGFC_BoardExpirationTimeRemaining(void                      *Handle,
                                      time_t                    *SecondsToExpire,
                                      ccrtngfc_date_string_t    *GmtDateTimeString,
                                      ccrtngfc_date_string_t    *LocalDateTimeString,
                                      _ccrtngfc_firmware_state  *FirmwareState)

   Description: Number of seconds to expire on a restricted card

   Input:   void                        *Handle             (Handle pointer)
   Output:  time_t                      *SecondsToExpire    (seconds to expire)
            ccrtngfc_date_string_t      *GmtDateTimeString  (GMT date/time
                                                             string)
               char  date[CCRTNGFC_DATE_TIME_STRING_SIZE]
            ccrtngfc_date_string_t      *LocalDateTimeString (Local date/time
                                                             string)
               char  date[CCRTNGFC_DATE_TIME_STRING_SIZE]
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            _ccrtngfc_firmware_state    *FirmwareState       (Firmware State)
               # CCRTNGFC_FIRMWARE_STATE_UNRESTRICTED
               # CCRTNGFC_FIRMWARE_STATE_RESTRICTED
               # CCRTNGFC_FIRMWARE_STATE_EXPIRED
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                 (successful)
               # CCRTNGFC_LIB_BAD_HANDLE               (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                 (library not open)
 ***************************************************************************/
```

Mandatory arguments to the call are **Handle* and **SecondsToExpire.* Rest of the arguments are optional and be set to *NULL.*

*SecondsToExpire – If the board has an expiration date, this call will return the number of seconds this card can be used before it expires. ***Once the card has expired, this call will not be reached as the device open will fail with an authorization error.***

It the board has no expiration date, this call will return zero as the number of seconds.

*GmtDateTimeString – If the board has an expiration date, this ascii GMT date representation of the expiration date is available in this variable if it is not NULL

*LocalDateTimeString – If the board has an expiration date, this ascii Local date representation of the expiration date is available in this variable if it is not NULL

*FirmwareState – This returns the current state of the installed firmware. I can be one of:

- CCRTNGFC_FIRMWARE_STATE_UNRESTRICTED. This firmware has no restrictions.
- CCRTNGFC_FIRMWARE_STATE_RESTRICTED. This firmware has restrictions. It is possible that and expiration date restriction is not present.
- CCRTNGFC_FIRMWARE_STATE_EXPIRED. This firmware has restrictions. One of the restrictions is the expiration date which has expired. Typically, you may not see this state as the utility will fail during the open with an authentication error.

2.2.3 ccrtNGFC_Clear_Driver_Error()

This call resets the last driver error that was maintained internally by the driver to *CCRTNGFC_SUCCESS*.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t ccrtNGFC_Clear_Driver_Error(void *Handle)

   Description: Clear any previously generated driver related error.

   Input:   void *Handle                        (Handle pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN          (device not open)
               # CCRTNGFC_LIB_IOCTL_FAILED      (driver ioctl call failed)
***************************************************************************/
```

2.2.4 ccrtNGFC_Clear_Interrupt_Status()

This call clears the interrupt status.

```
/***************************************************************************
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clear_Interrupt_Status (void                *Handle,
                                    ccrtngfc_interrupt_t *intr)

   Description: Clear Interrupt Status

   Input:   void                    *Handle       (handle pointer)
            ccrtngfc_interrupt_t    *intr         (pointer to interrupt status)
               _ccrtngfc_intsta_ldio_cos_t ldio_cos_module_int[CCRTNGFC_LDIO_MAX_MODULES];
                  # CCRTNGFC_INT_LDIO_COS_NONE
                  # CCRTNGFC_INT_LDIO_COS_RESET
                  # CCRTNGFC_INT_LDIO_COS_DO_NOT_CHANGE
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR            (successful)
               # CCRTNGFC_LIB_BAD_HANDLE          (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN            (device not open)
               # CCRTNGFC_LIB_NO_LOCAL_REGION     (local region error)
               # CCRTNGFC_LIB_INVALID_ARG         (invalid argument)
 ************************************************************************/
```

2.2.5 ccrtNGFC_Clear_Lib_Error()

This call resets the last library error that was maintained internally by the API.

```
/************************************************************************
   _ccrtngfc_lib_error_number_t ccrtNGFC_Clear_Lib_Error(void *Handle)

   Description: Clear any previously generated library related error.

   Input:   void *Handle                        (Handle pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN          (device not open)
************************************************************************/
```

2.2.6 ccrtNGFC_Clock_Generator_Soft_Reset()

Perform a soft clock reset on all the output clocks.

```
/************************************************************************
   _ccrtngfc_lib_error_number_t ccrtNGFC_Clock_Generator_Soft_Reset(void *Handle)

   Description: Perform Soft Reset to Clock Generator

   Input:   void *Handle                         (Handle pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
             # CCRTNGFC_LIB_NO_ERROR            (successful)
             # CCRTNGFC_LIB_BAD_HANDLE          (no/bad handler supplied)
             # CCRTNGFC_LIB_NOT_OPEN            (device not open)
             # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE (Clock is not active)
  ************************************************************************/
```

2.2.7 ccrtNGFC_Clock_Get_Generator_CSR()

Return the clock generator control and status register.

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   ccrtNGFC_Clock_Get_Generator_CSR (void                  *Handle,
                                    ccrtngfc_clkgen_csr_t *CgCsr)

   Description: Get Generator Control and Status information

   Input:   void                                    *Handle     (Handle pointer)
   Output:  ccrtngfc_clkgen_csr_t                   *CgCsr      (pointer to clock
                                                                 generator csr)
               _ccrtngfc_clkgen_interface_t             interface
                  # CCRTNGFC_CLOCK_GENERATOR_INTERFACE_IDLE
                  # CCRTNGFC_CLOCK_GENERATOR_INTERFACE_BUSY
               _ccrtngfc_clkgen_output_t                output
                  # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_DISABLE
                  # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_ENABLE
               _ccrtngfc_clkgen_state_t                 state
                  # CCRTNGFC_CLOCK_GENERATOR_ACTIVE
                  # CCRTNGFC_CLOCK_GENERATOR_RESET
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                        (successful)
               # CCRTNGFC_LIB_BAD_HANDLE                      (no/bad handler
                                                               supplied)
               # CCRTNGFC_LIB_NOT_OPEN                        (device not open)
               # CCRTNGFC_LIB_INVALID_ARG                     (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION                 (local region not
                                                               present)
 ****************************************************************************/
```

2.2.8 ccrtNGFC_Clock_Get_Generator_Info()

This call returns the clock generator information for the selected output.

```
/****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_Info (void                           *Handle,
                              _ccrtngfc_clock_generator_output_t   WhichOutput,
                              ccrtngfc_clock_generator_info_t      *CgInfo)

   Description: Get Clock Generator Information

   Input:   void                                     *Handle     (Handle pointer)
            _ccrtngfc_clock_generator_output_t       WhichOutput (select output)
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_0
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_1
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_2
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_3
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_4
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_5
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_6
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_7
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_8
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_9
   Output:  ccrtngfc_clock_generator_info_t   *CgInfo  (pointer to clock
                                                       generator info)
               __u64                                      M_divider_num
               __u32                                      M_divider_den
               __u64                                      N_divider_num
               __u32                                      N_divider_den
               __u32                                      R_divider_value
               __u32                                      R_divider
               _ccrtngfc_cg_zero_delay_t                  ZeroDelay
                  # CCRTNGFC_CG_ZERO_DELAY_MODE
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   # CCRTNGFC_CG_NORMAL_MODE
_ccrtngfc_cg_stat_ctrl_voltsel_t                Voltage_select
   # CCRTNGFC_CG_VOLTAGE_SELECT_1_8V
   # CCRTNGFC_CG_VOLTAGE_SELECT_3_3V
_ccrtngfc_cg_input_xaxb_extclk_sel_t          Input_xaxb_selection
   # CCRTNGFC_CG_INPUT_XAXB_USE_CRYSTAL
   # CCRTNGFC_CG_INPUT_XAXB_USE_EXTCLK_SOURCE
_ccrtngfc_cg_xaxb_power_down_t                  Input_xaxb_power
   # CCRTNGFC_CG_XAXB_POWER_DOWN
   # CCRTNGFC_CG_XAXB_DO_NOT_POWER_DOWN
ccrtngfc_clkgen_csr_t                           Clkcsr
   _ccrtngfc_clkgen_interface_t                 interface
      # CCRTNGFC_CLOCK_GENERATOR_INTERFACE_IDLE
      # CCRTNGFC_CLOCK_GENERATOR_INTERFACE_BUSY
   _ccrtngfc_clkgen_output_t                    output
      # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_DISABLE
      # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_ENABLE
   _ccrtngfc_clkgen_state_t                     state
      # CCRTNGFC_CLOCK_GENERATOR_ACTIVE
      # CCRTNGFC_CLOCK_GENERATOR_RESET
ccrtngfc_clkgen_output_config_t                 Config
   _ccrtngfc_cg_outcfg_force_rdiv2_t            force_rdiv2
      # CCRTNGFC_CG_OUTPUT_CONFIG_DONT_FORCE_RDIV2
      # CCRTNGFC_CG_OUTPUT_CONFIG_FORCE_RDIV2
   _ccrtngfc_cg_outcfg_enable_t                 enable
      # CCRTNGFC_CG_OUTPUT_CONFIG_DISABLE
      # CCRTNGFC_CG_OUTPUT_CONFIG_ENABLE
   _ccrtngfc_cg_outcfg_shutdown_t               shutdown
      # CCRTNGFC_CG_OUTPUT_CONFIG_POWER_UP
      # CCRTNGFC_CG_OUTPUT_CONFIG_SHUTDOWN
ccrtngfc_clkgen_output_format_t                 Format
   _ccrtngfc_cg_outfmt_cmos_drive_t             cmos_drive
      # CCRTNGFC_CG_OUTPUT_FORMAT_CMOS_DRIVE_LVDS
      # CCRTNGFC_CG_OUTPUT_FORMAT_CMOS_DRIVE_CMOS
   _ccrtngfc_cg_outfmt_disable_state_t          disable_state
      # CCRTNGFC_CG_OUTPUT_FORMAT_DISABLE_LOW
      # CCRTNGFC_CG_OUTPUT_FORMAT_DISABLE_HIGH
   _ccrtngfc_cg_outfmt_sync_t                   sync
      # CCRTNGFC_CG_OUTPUT_FORMAT_SYNC_DISABLE
      # CCRTNGFC_CG_OUTPUT_FORMAT_SYNC_ENABLE
   _ccrtngfc_cg_outfmt_format_t                 format
      # CCRTNGFC_CG_OUTPUT_FORMAT_FORMAT_LVDS
      # CCRTNGFC_CG_OUTPUT_FORMAT_FORMAT_CMOS
ccrtngfc_clkgen_output_mode_t                   Mode
   _ccrtngfc_cg_outmode_amplitude_t             amplitude
      # CCRTNGFC_CG_OUTPUT_AMPLITUDE_CMOS
      # CCRTNGFC_CG_OUTPUT_AMPLITUDE_LVDS
   _ccrtngfc_cg_outmode_common_t                common
      # CCRTNGFC_CG_OUTPUT_COMMON_CMOS
      # CCRTNGFC_CG_OUTPUT_COMMON_LVDS
      # CCRTNGFC_CG_OUTPUT_COMMON_LVPECL
ccrtngfc_clkgen_output_mux_t                    Mux
   _ccrtngfc_cg_outmux_inversion_t              inversion
      # CCRTNGFC_CG_OUTPUT_MUX_COMPLEMENTARY
      # CCRTNGFC_CG_OUTPUT_MUX_IN_PHASE
      # CCRTNGFC_CG_OUTPUT_MUX_INVERTED
      # CCRTNGFC_CG_OUTPUT_MUX_OUT_OF_PHASE
   _ccrtngfc_cg_outmux_ndiv_select_t            ndiv_mux
      # CCRTNGFC_CG_OUTPUT_MUX_NDIV_0
      # CCRTNGFC_CG_OUTPUT_MUX_NDIV_1
      # CCRTNGFC_CG_OUTPUT_MUX_NDIV_2
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
      # CCRTNGFC_CG_OUTPUT_MUX_NDIV_3
      # CCRTNGFC_CG_OUTPUT_MUX_NDIV_4
ccrtngfc_clkgen_input_clock_enable_t            Input_clock_enable
   _ccrtngfc_cg_input_clock_enable_t            input_0_clock
      # CCRTNGFC_CG_INPUT_CLOCK_DISABLE
      # CCRTNGFC_CG_INPUT_CLOCK_ENABLE
   _ccrtngfc_cg_input_clock_enable_t            input_1_clock
      # CCRTNGFC_CG_INPUT_CLOCK_DISABLE
      # CCRTNGFC_CG_INPUT_CLOCK_ENABLE
   _ccrtngfc_cg_input_clock_enable_t            input_2_clock
      # CCRTNGFC_CG_INPUT_CLOCK_DISABLE
      # CCRTNGFC_CG_INPUT_CLOCK_ENABLE
   _ccrtngfc_cg_input_clock_enable_t            input_fb_clock
      # CCRTNGFC_CG_INPUT_CLOCK_DISABLE
      # CCRTNGFC_CG_INPUT_CLOCK_ENABLE
ccrtngfc_clkgen_input_clock_select_t            Input_clock_select
   _ccrtngfc_cg_input_clock_select_control_t    control
      # CCRTNGFC_CG_INPUT_CLOCK_SELECT_PIN_CONTROL
      # CCRTNGFC_CG_INPUT_CLOCK_SELECT_REG_CONTROL
   _ccrtngfc_cg_input_clock_select_register_t   select
      # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN0
      # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN1
      # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN2
      # CCRTNGFC_CG_INPUT_CLOCK_SELECT_INXAXB
ccrtngfc_pdiv_all_info_t                        Pdiv_info
   __u64                                        Pfb_divider
   ccrtngfc_pdiv_info_t                         P0
      __u64                                     Divider
      _ccrtngfc_cg_pdiv_enable_t                Enable
         # CCRTNGFC_CG_PDIV_DISABLE
         # CCRTNGFC_CG_PDIV_ENABLE
      _ccrtngfc_cg_pdiv_input_state_t           State
         # CCRTNGFC_CG_PDIV_INPUT_UNUSED
         # CCRTNGFC_CG_PDIV_INPUT_DISABLED
         # CCRTNGFC_CG_PDIV_INPUT_SELECTED
   ccrtngfc_pdiv_info_t                         P1
      __u64                                     Divider
      _ccrtngfc_cg_pdiv_enable_t                Enable
         # CCRTNGFC_CG_PDIV_DISABLE
         # CCRTNGFC_CG_PDIV_ENABLE
      _ccrtngfc_cg_pdiv_input_state_t           State
         # CCRTNGFC_CG_PDIV_INPUT_UNUSED
         # CCRTNGFC_CG_PDIV_INPUT_DISABLED
         # CCRTNGFC_CG_PDIV_INPUT_SELECTED
   ccrtngfc_pdiv_info_t                         P2
      __u64                                     Divider
      _ccrtngfc_cg_pdiv_enable_t                Enable
         # CCRTNGFC_CG_PDIV_DISABLE
         # CCRTNGFC_CG_PDIV_ENABLE
      _ccrtngfc_cg_pdiv_input_state_t           State
         # CCRTNGFC_CG_PDIV_INPUT_UNUSED
         # CCRTNGFC_CG_PDIV_INPUT_DISABLED
         # CCRTNGFC_CG_PDIV_INPUT_SELECTED
   ccrtngfc_pdiv_info_t                         Pxaxb
      __u64                                     Divider
      _ccrtngfc_cg_pdiv_enable_t                Enable
         # CCRTNGFC_CG_PDIV_DISABLE
         # CCRTNGFC_CG_PDIV_ENABLE
      _ccrtngfc_cg_pdiv_input_state_t           State
         # CCRTNGFC_CG_PDIV_INPUT_UNUSED
         # CCRTNGFC_CG_PDIV_INPUT_DISABLED
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                        # CCRTNGFC_CG_PDIV_INPUT_SELECTED
                  int                                 Which_Pdiv_Selected
                  int                                 P_Divider
                  long double                         OutputClockFrequency;
                     # <valid positive output clock frequency>
                     # CCRTNGFC_CLOCK_ERROR_INVALID_P_DIVIDER
                     # CCRTNGFC_CLOCK_ERROR_VCO_CLOCK_NOT_IN_RANGE
                     # CCRTNGFC_CLOCK_ERROR_N_DIVIDER_NOT_IN_RANGE
                     # CCRTNGFC_CLOCK_ERROR_P_DIVIDER_NOT_IN_RANGE
                     # CCRTNGFC_CLOCK_ERROR_R_DIVIDER_NOT_IN_RANGE
                     # CCRTNGFC_CLOCK_ERROR_INVALID_CLOCK_FREQUENCY
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR               (successful)
               # CCRTNGFC_LIB_BAD_HANDLE             (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN               (device not open)
               # CCRTNGFC_LIB_INVALID_ARG            (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION        (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE    (Clock is not active)
*************************************************************************/
```

2.2.9 ccrtNGFC_Clock_Get_Generator_Input_Clock_Enable()

This call returns the status of all the input clocks.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_Input_Clock_Enable (void                *Handle,
                                ccrtngfc_clkgen_input_clock_enable_t   *InputClockEnable)

   Description: Return the Clock Generator Input Clock Enable

   Input:   void                                    *Handle        (Handle pointer)
   Output:  ccrtngfc_clkgen_input_clock_enable_t  *InputClockEnable (pointer to
                                                              input clock enable)
               _ccrtngfc_cg_input_clock_enable_t  input_0_clock
                  # CCRTNGFC_CG_INPUT_CLOCK_DISABLE
                  # CCRTNGFC_CG_INPUT_CLOCK_ENABLE
               _ccrtngfc_cg_input_clock_enable_t  input_1_clock
                  # CCRTNGFC_CG_INPUT_CLOCK_DISABLE
                  # CCRTNGFC_CG_INPUT_CLOCK_ENABLE
               _ccrtngfc_cg_input_clock_enable_t  input_2_clock
                  # CCRTNGFC_CG_INPUT_CLOCK_DISABLE
                  # CCRTNGFC_CG_INPUT_CLOCK_ENABLE
               _ccrtngfc_cg_input_clock_enable_t  input_fb_clock
                  # CCRTNGFC_CG_INPUT_CLOCK_DISABLE
                  # CCRTNGFC_CG_INPUT_CLOCK_ENABLE
   Return: _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN             (device not open)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION      (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE  (Clock is not active)
 *************************************************************************/
```

2.2.10 ccrtNGFC_Clock_Get_Generator_Input_Clock_Select()

This call returns the input clock selection.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   ccrtNGFC_Clock_Get_Generator_Input_Clock_Select (void             *Handle,
                            ccrtngfc_clkgen_input_clock_select_t   *ClkSel)

   Description: Get Input Clock Selection

   Input:   void                                          *Handle  (Handle pointer)
   Output:  ccrtngfc_clkgen_input_clock_select_t          *ClkSel  (pointer to
                                                             input clock selection)
               _ccrtngfc_cg_input_clock_select_control_t    control;
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_PIN_CONTROL
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_REG_CONTROL
               _ccrtngfc_cg_input_clock_select_register_t   select;
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN0
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN1
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN2
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_INXAXB
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                  (successful)
               # CCRTNGFC_LIB_BAD_HANDLE                (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                  (device not open)
               # CCRTNGFC_LIB_INVALID_ARG               (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION           (local region error)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE       (Clock is not active)
 ***************************************************************************/
```

2.2.11 ccrtNGFC_Clock_Get_Generator_Input_Clock_Status()

The call returns the input clock status.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_Input_Clock_Status (void                       *Handle,
                                      ccrtngfc_clkgen_input_clock_status_t   *ClkStatus)

   Description: Get Input Clock Status

   Input:   void                                  *Handle    (Handle pointer)
   Output:  ccrtngfc_clkgen_input_clock_status_t  *ClkSatus  (pointer to input
                                                               clock status)
               _ccrtngfc_cg_calibration_status_t            calstat
                  # CCRTNGFC_CG_STATUS_DEVICE_IS_NOT_CALIBRATING
                  # CCRTNGFC_CG_STATUS_DEVICE_IS_CALIBRATING
               _ccrtngfc_cg_lol_pll_locked_t               PLL_locked
                  # CCRTNGFC_CG_STATUS_LOL_PLL_LOCKED
                  # CCRTNGFC_CG_STATUS_LOL_PLL_NOT_LOCKED
               _ccrtngfc_cg_smbus_timeout_error_t          SMBUS_timeout
                  # CCRTNGFC_CG_STATUS_LOL_SMBUS_NOT_TIMEDOUT
                  # CCRTNGFC_CG_STATUS_LOL_SMBUS_TIMEDOUT
               _ccrtngfc_cg_los_signal_present_t           input_signal
                  # CCRTNGFC_CG_STATUS_LOS_SIGNAL_PRESENT
                  # CCRTNGFC_CG_STATUS_LOS_SIGNAL_NOT_PRESENT
               _ccrtngfc_cg_los_alarm_t                    input_0_clock
                  # CCRTNGFC_CG_LOS_INPUT_CLOCK_PRESENT
                  # CCRTNGFC_CG_LOS_INPUT_CLOCK_NOT_PRESENT
               _ccrtngfc_cg_los_alarm_t                    input_1_clock
                  # CCRTNGFC_CG_LOS_INPUT_CLOCK_PRESENT
                  # CCRTNGFC_CG_LOS_INPUT_CLOCK_NOT_PRESENT
               _ccrtngfc_cg_los_alarm_t                    input_2_clock
                  # CCRTNGFC_CG_LOS_INPUT_CLOCK_PRESENT
                  # CCRTNGFC_CG_LOS_INPUT_CLOCK_NOT_PRESENT
               _ccrtngfc_cg_los_alarm_t                    input_fb_clock
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                  # CCRTNGFC_CG_LOS_INPUT_CLOCK_PRESENT
                  # CCRTNGFC_CG_LOS_INPUT_CLOCK_NOT_PRESENT
               _ccrtngfc_cg_losxaxb_signal_present_t        input_xaxb_clock
                  # CCRTNGFC_CG_LOS_INPUT_CLOCK_PRESENT
                  # CCRTNGFC_CG_LOS_INPUT_CLOCK_NOT_PRESENT
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR               (successful)
               # CCRTNGFC_LIB_BAD_HANDLE             (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN               (device not open)
               # CCRTNGFC_LIB_INVALID_ARG            (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION        (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE    (Clock is not active)
 ************************************************************************/
```

2.2.12 ccrtNGFC_Clock_Get_Generator_M_Divider()

This call returns the M-Divider numerator, denominator and value.

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_M_Divider (void        *Handle,
                                          __u64       *Numerator,
                                          __u32       *Denominator,
                                          long double *Value)

   Description: Return Clock Generator M-Divider Numerator and Denominator

   Input:   void              *Handle             (Handle pointer)
   Output:  __u64             *Numerator          (pointer to Numerator)
            __u32             *Denominator        (pointer to Denominator)
            long double       *Value              (pointer to Value)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR            (successful)
               # CCRTNGFC_LIB_BAD_HANDLE          (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN            (device not open)
               # CCRTNGFC_LIB_INVALID_ARG         (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION     (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE (Clock is not active)
 ************************************************************************/
```

2.2.13 ccrtNGFC_Clock_Get_Generator_N_Divider()

This call returns the N-Divider numerator, denominator and value for the selected divider.

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_N_Divider (void                       *Handle,
                              _ccrtngfc_clock_generator_divider_t WhichDivider,
                              __u64                               *Numerator,
                              __u32                               *Denominator,
                              long double                         *Value)

   Description: Return Clock Generator N-Divider Numerator and Denominator

   Input:   void                                *Handle         (Handle pointer)
            _ccrtngfc_clock_generator_divider_t  WhichDivider    (select divider)
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N0
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N1
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N2
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N3
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N4
   Output:  __u64                        *Numerator    (pointer to Numerator)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
          __u32                        *Denominator  (pointer to Denominator)
          long double                  *Value        (pointer to Value)
   Return:  _ccrtngfc_lib_error_number_t
              # CCRTNGFC_LIB_NO_ERROR               (successful)
              # CCRTNGFC_LIB_BAD_HANDLE             (no/bad handler supplied)
              # CCRTNGFC_LIB_NOT_OPEN               (device not open)
              # CCRTNGFC_LIB_INVALID_ARG            (invalid argument)
              # CCRTNGFC_LIB_NO_LOCAL_REGION        (local region not present)
              # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE    (Clock is not active)
 ***************************************************************************/
```

2.2.14 ccrtNGFC_Clock_Get_Generator_Output_Config()

Return the clock generator output configuration for the selected output.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_Output_Config (void                *Handle,
                            _ccrtngfc_clock_generator_output_t  WhichOutput,
                            ccrtngfc_clkgen_output_config_t     *OutCfg)

   Description: Return Clock Generator Output Configuration

   Input:   void                                  *Handle     (Handle pointer)
            _ccrtngfc_clock_generator_output_t    WhichOutput (select output)
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_0
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_1
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_2
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_3
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_4
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_5
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_6
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_7
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_8
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_9
   Output:  ccrtngfc_clkgen_output_config_t   *OutCfg (pointer to output config)
               _ccrtngfc_cg_outcfg_force_rdiv2_t        force_rdiv2
                  # CCRTNGFC_CG_OUTPUT_CONFIG_DONT_FORCE_RDIV2
                  # CCRTNGFC_CG_OUTPUT_CONFIG_FORCE_RDIV2
               _ccrtngfc_cg_outcfg_enable_t             enable
                  # CCRTNGFC_CG_OUTPUT_CONFIG_DISABLE
                  # CCRTNGFC_CG_OUTPUT_CONFIG_ENABLE
               _ccrtngfc_cg_outcfg_shutdown_t           shutdown
                  # CCRTNGFC_CG_OUTPUT_CONFIG_POWER_UP
                  # CCRTNGFC_CG_OUTPUT_CONFIG_SHUTDOWN
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR               (successful)
               # CCRTNGFC_LIB_BAD_HANDLE             (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN               (device not open)
               # CCRTNGFC_LIB_INVALID_ARG            (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION        (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE    (Clock is not active)
 ***************************************************************************/
```

2.2.15 ccrtNGFC_Clock_Get_Generator_Output_Format()

Return the clock generator output format for the selected output.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_Output_Format (void               *Handle,
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                                _ccrtngfc_clock_generator_output_t  WhichOutput,
                                ccrtngfc_clkgen_output_format_t     *OutFmt)

   Description: Return Clock Generator Output Format

   Input:   void                                 *Handle     (Handle pointer)
            _ccrtngfc_clock_generator_output_t  WhichOutput (select output)
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_0
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_1
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_2
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_3
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_4
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_5
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_6
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_7
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_8
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_9
   Output:  ccrtngfc_clkgen_output_format_t    *OutFmt (pointer to output format)
               _ccrtngfc_cg_outfmt_cmos_drive_t         cmos_drive
                  # CCRTNGFC_CG_OUTPUT_FORMAT_CMOS_DRIVE_LVDS
                  # CCRTNGFC_CG_OUTPUT_FORMAT_CMOS_DRIVE_CMOS
               _ccrtngfc_cg_outfmt_disable_state_t      disable_state
                  # CCRTNGFC_CG_OUTPUT_FORMAT_DISABLE_LOW
                  # CCRTNGFC_CG_OUTPUT_FORMAT_DISABLE_HIGH
               _ccrtngfc_cg_outfmt_sync_t               sync
                  # CCRTNGFC_CG_OUTPUT_FORMAT_SYNC_DISABLE
                  # CCRTNGFC_CG_OUTPUT_FORMAT_SYNC_ENABLE
               _ccrtngfc_cg_outfmt_format_t             format
                  # CCRTNGFC_CG_OUTPUT_FORMAT_FORMAT_LVDS
                  # CCRTNGFC_CG_OUTPUT_FORMAT_FORMAT_CMOS
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR               (successful)
               # CCRTNGFC_LIB_BAD_HANDLE             (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN               (device not open)
               # CCRTNGFC_LIB_INVALID_ARG            (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION        (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE    (Clock is not active)
 ***************************************************************************/
```

2.2.16 ccrtNGFC_Clock_Get_Generator_Output_Mode()

Return the clock generator output mode for the selected output.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_Output_Mode (void               *Handle,
                        _ccrtngfc_clock_generator_output_t    WhichOutput,
                        ccrtngfc_clkgen_output_mode_t         *OutMode)

   Description: Return Clock Generator Output Mode

   Input:   void                                        *Handle     (Handle pointer)
            _ccrtngfc_clock_generator_output_t          WhichOutput (select output)
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_0
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_1
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_2
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_3
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_4
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_5
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_6
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_7
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_8
            # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_9
   Output:  ccrtngfc_clkgen_output_mode_t        *OutMode (pointer to output
                                                           amplitude/common mode)
            _ccrtngfc_cg_outmode_amplitude_t         amplitude
               # CCRTNGFC_CG_OUTPUT_AMPLITUDE_CMOS
               # CCRTNGFC_CG_OUTPUT_AMPLITUDE_LVDS
            _ccrtngfc_cg_outmode_common_t            common
               # CCRTNGFC_CG_OUTPUT_COMMON_CMOS
               # CCRTNGFC_CG_OUTPUT_COMMON_LVDS
               # CCRTNGFC_CG_OUTPUT_COMMON_LVPECL
   Return:  _ccrtngfc_lib_error_number_t
              # CCRTNGFC_LIB_NO_ERROR                 (successful)
              # CCRTNGFC_LIB_BAD_HANDLE               (no/bad handler supplied)
              # CCRTNGFC_LIB_NOT_OPEN                 (device not open)
              # CCRTNGFC_LIB_INVALID_ARG              (invalid argument)
              # CCRTNGFC_LIB_NO_LOCAL_REGION          (local region not present)
              # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE      (Clock is not active)
 ***************************************************************************/
```

2.2.17 ccrtNGFC_Clock_Get_Generator_Output_Mux()

Return the clock generator output mux for the selected output.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_Output_Mux (void                   *Handle,
                             _ccrtngfc_clock_generator_output_t WhichOutput,
                             ccrtngfc_clkgen_output_mux_t       *OutMux)

   Description: Return Clock Generator Output Mux

   Input:   void                                    *Handle     (Handle pointer)
            _ccrtngfc_clock_generator_output_t      WhichOutput (select output)
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_0
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_1
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_2
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_3
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_4
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_5
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_6
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_7
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_8
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_9
   Output:  ccrtngfc_clkgen_output_mux_t        *OutMux (pointer to output
                                                          inversion/N-divider mux)
              _ccrtngfc_cg_outmux_inversion_t       inversion
                 # CCRTNGFC_CG_OUTPUT_MUX_COMPLEMENTARY
                 # CCRTNGFC_CG_OUTPUT_MUX_IN_PHASE
                 # CCRTNGFC_CG_OUTPUT_MUX_INVERTED
                 # CCRTNGFC_CG_OUTPUT_MUX_OUT_OF_PHASE
              _ccrtngfc_cg_outmux_ndiv_select_t     ndiv_mux
                 # CCRTNGFC_CG_OUTPUT_MUX_NDIV_0
                 # CCRTNGFC_CG_OUTPUT_MUX_NDIV_1
                 # CCRTNGFC_CG_OUTPUT_MUX_NDIV_2
                 # CCRTNGFC_CG_OUTPUT_MUX_NDIV_3
                 # CCRTNGFC_CG_OUTPUT_MUX_NDIV_4
   Return:  _ccrtngfc_lib_error_number_t
              # CCRTNGFC_LIB_NO_ERROR                 (successful)
              # CCRTNGFC_LIB_BAD_HANDLE               (no/bad handler supplied)
              # CCRTNGFC_LIB_NOT_OPEN                 (device not open)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_LIB_INVALID_ARG           (invalid argument)
            # CCRTNGFC_LIB_NO_LOCAL_REGION       (local region not present)
            # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE   (Clock is not active)
 ***************************************************************************/
```

2.2.18 ccrtNGFC_Clock_Get_Generator_P_Divider()

Return the clock generator P-Divider.

```
/***************************************************************************
  _ccrtngfc_lib_error_number_t
  ccrtNGFC_Clock_Get_Generator_P_Divider (void                     *Handle,
                             _ccrtngfc_clock_generator_divider_t WhichDivider,
                             __u64                               *Divider)

   Description: Return Clock Generator P-Divider

   Input:   void                                 *Handle      (Handle pointer)
            _ccrtngfc_clock_generator_divider_t   WhichDivider (select divider)
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P0
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P1
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P2
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_PFB
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_PXAXB
   Output:  __u64                                *Divider    (pointer to
                                                              Divider)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR            (successful)
               # CCRTNGFC_LIB_BAD_HANDLE          (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN            (device not open)
               # CCRTNGFC_LIB_INVALID_ARG         (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION     (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE (Clock is not active)
 ***************************************************************************/
```

2.2.19 ccrtNGFC_Clock_Get_Generator_P_Divider_Enable()

Return the clock generator P-Divider Enable state.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_P_Divider_Enable (void              *Handle,
                             _ccrtngfc_clock_generator_divider_t  WhichDivider,
                             _ccrtngfc_cg_pdiv_enable_t           *Pdiv_Enable)

   Description: Return Clock Generator P-Divider Enable

   Input:   void                                 *Handle      (Handle pointer)
            _ccrtngfc_clock_generator_divider_t   WhichDivider (select divider)
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P0
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P1
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P2
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_PXAXB
   Output:  _ccrtngfc_cg_pdiv_enable_t           *Pdiv_Enable (pointer to enable
                                                               flag)
               # CCRTNGFC_CG_PDIV_DISABLE
               # CCRTNGFC_CG_PDIV_ENABLE
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR            (successful)
               # CCRTNGFC_LIB_BAD_HANDLE          (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN            (device not open)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_LIB_INVALID_ARG         (invalid argument)
            # CCRTNGFC_LIB_NO_LOCAL_REGION     (local region not present)
            # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE (Clock is not active)
 ***************************************************************************/
```

2.2.20 ccrtNGFC_Clock_Get_Generator_R_Divider()

Return the clock generator R-Divider for the selected divider.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_R_Divider (void                 *Handle,
                          _ccrtngfc_clock_generator_divider_t WhichDivider,
                          __u32                               *Divider)

   Description: Return Clock Generator R-Divider

   Input:   void                                *Handle      (Handle pointer)
            _ccrtngfc_clock_generator_divider_t  WhichDivider (select divider)
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R0
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R1
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R2
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R3
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R4
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R5
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R6
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R7
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R8
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R9
   Output:  __u32                               *Divider   (pointer to Divider)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR            (successful)
               # CCRTNGFC_LIB_BAD_HANDLE          (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN            (device not open)
               # CCRTNGFC_LIB_INVALID_ARG         (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION     (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE (Clock is not active)
 ***************************************************************************/
```

2.2.21 ccrtNGFC_Clock_Get_Generator_Revision()

Return the clock generator revision information.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_Revision (void                      *Handle,
                                          ccrtngfc_clock_revision_t *Revision)

   Description: Return Clock Generator Revision

   Input:   void                                *Handle      (Handle pointer)
   Output:  ccrtngfc_clock_revision_t           *Revision    (pointer to Divider)
             _ccrtngfc_cg_die_revision_t          DieRevision
                # CCRTNGFC_CG_SILICON_REVISION_A0
                # CCRTNGFC_CG_SILICON_REVISION_A1
             _ccrtngfc_convert_base_part_number_t BasePartNumber;
                u_short BPN
                u_char  NChar[2]
             _ccrtngfc_cg_clock_speed_grade_t     ClockSpeedGrade;
                # CCRTNGFC_CG_CLOCK_SPEED_GRADE_A
                # CCRTNGFC_CG_CLOCK_SPEED_GRADE_B
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                  # CCRTNGFC_CG_CLOCK_SPEED_GRADE_C
                  # CCRTNGFC_CG_CLOCK_SPEED_GRADE_D
               _ccrtngfc_cg_clock_revision_t        ClockRevision;
                  # CCRTNGFC_CG_CLOCK_REVISION_A
                  # CCRTNGFC_CG_CLOCK_REVISION_B
                  # CCRTNGFC_CG_CLOCK_REVISION_C
                  # CCRTNGFC_CG_CLOCK_REVISION_D
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR            (successful)
               # CCRTNGFC_LIB_BAD_HANDLE          (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN            (device not open)
               # CCRTNGFC_LIB_INVALID_ARG         (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION     (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE (Clock is not active)
*************************************************************************/
```

2.2.22 ccrtNGFC_Clock_Get_Generator_Value()

This is a generic call that can return the value of a valid clock generator address.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_Value (void    *Handle,
                                       int     address,
                                       u_char  *value)

   Description: Return the value of the specified Clock Generator register.

   Input:   void              *Handle             (Handle pointer)
            int               address             (clock gen address to display)
   Output:  u_char            *value;             (pointer to value)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR            (successful)
               # CCRTNGFC_LIB_BAD_HANDLE          (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN            (device not open)
               # CCRTNGFC_LIB_INVALID_ARG         (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION     (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE (Clock is not active)
 *************************************************************************/
```

2.2.23 ccrtNGFC_Clock_Get_Generator_Voltage_Select()

Return the clock generator Voltage Selection.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_Voltage_Select (void                  *Handle,
                                _ccrtngfc_cg_stat_ctrl_voltsel_t   *VoltSel)

   Description: Return the Clock Generator Voltage Selection

   Input:   void                             *Handle  (Handle pointer)
   Output:  _ccrtngfc_cg_stat_ctrl_voltsel_t *VoltSel (pointer to voltage select)
               # CCRTNGFC_CG_VOLTAGE_SELECT_1_8V
               # CCRTNGFC_CG_VOLTAGE_SELECT_3_3V
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR               (successful)
               # CCRTNGFC_LIB_BAD_HANDLE             (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN               (device not open)
               # CCRTNGFC_LIB_INVALID_ARG            (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION        (local region not present)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)
 ***************************************************************************/
```

2.2.24 ccrtNGFC_Clock_Get_Generator_Zero_Delay()

Return the clock generator Zero Delay status.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Get_Generator_Zero_Delay (void                    *Handle,
                                           _ccrtngfc_cg_zero_delay_t  *ZeroDelay)

   Description: Return the Clock Generator Zero Delay setting.

   Input:   void                        *Handle     (Handle pointer)
   Output:  _ccrtngfc_cg_zero_delay_t   *ZeroDelay  (pointer to zero delay)
               # CCRTNGFC_CG_ZERO_DELAY_MODE
               # CCRTNGFC_CG_NORMAL_MODE
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR              (successful)
               # CCRTNGFC_LIB_BAD_HANDLE            (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN              (device not open)
               # CCRTNGFC_LIB_INVALID_ARG           (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION       (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE   (Clock is not active)
 ***************************************************************************/
```

2.2.25 ccrtNGFC_Clock_PLL_CSR()

This call is provided to select either the clock generator or the clock oscillator as the source for the FPGA. By default, the FPGA firmware loads by using the clock oscillator and switches to the clock generator the moment any clocks are programmed by the user. When any clock is programmed, the software programs a reserved clock 5 (the generator source) to 100MHz. Once successfully programmed, the firmware automatically switches to this clock for all card access.

If for whatever reason, the customer wishes to use the clock oscillator instead of the clock generator, then they can use this call to accomplish it.

In addition to this clock source selection, this API also supplies useful information on the current status of the clock sources.

Note!!! This PLL Synchronization feature is not supported by the initial firmware release, it is supported by future releases.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_PLL_CSR (void                          *Handle,
                           _ccrtngfc_pll_clock_source_t  PLL_ClockSourceSelect,
                           ccrtngfc_clock_pll_status_t   *PLL_ClockStatus)

   Description: Clock PLL Control and Status

   Input:   void                          *Handle     (Handle pointer)
            _ccrtngfc_pll_clock_source_t  PLL_ClockSourceSelect
               # CCRTNGFC_PLL_CLOCK_GENERATOR_SOURCE
               # CCRTNGFC_PLL_CLOCK_OSCILLATOR_SOURCE
               # CCRTNGFC_PLL_CLOCK_STATE_DO_NOT_CHANGE


   Output:  ccrtngfc_clock_pll_status_t   *PLL_ClockStatus
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                ccrtngfc_bool_t                    PLL_firmware_support
                    # CCRTNGFC_TRUE
                    # CCRTNGFC_FALSE
                _ccrtngfc_pll_clock_source_t       clock_select
                    # CCRTNGFC_PLL_CLOCK_GENERATOR_SOURCE
                    # CCRTNGFC_PLL_CLOCK_OSCILLATOR_SOURCE
                _ccrtngfc_pll_unlock_error_t       PLL_unlock_error
                    # CCRTNGFC_PLL_NEVER_UNLOCKED
                    # CCRTNGFC_PLL_UNLOCKED_AT_SOME_POINT
                _ccrtngfc_pll_locked_status_t      PLL_locked_status
                    # CCRTNGFC_PLL_NOT_LOCKED_ON_FREQUENCY
                    # CCRTNGFC_PLL_LOCKED_ON_FREQUENCY
                _ccrtngfc_pll_clock_status_t       clock_status_0
                    # CCRTNGFC_PLL_CLOCK_BAD_OR_MISSING
                    # CCRTNGFC_PLL_CLOCK_PRESENT
                _ccrtngfc_pll_clock_status_t       clock_status_1
                    # CCRTNGFC_PLL_CLOCK_BAD_OR_MISSING
                    # CCRTNGFC_PLL_CLOCK_PRESENT
                _ccrtngfc_pll_active_clock_t       active_clock
                    # CCRTNGFC_PLL_CLOCK_GENERATOR_ACTIVE
                    # CCRTNGFC_PLL_CLOCK_OSCILLATOR_ACTIVE
            NULL
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR               (successful)
               # CCRTNGFC_LIB_BAD_HANDLE             (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN               (device not open)
               # CCRTNGFC_LIB_INVALID_ARG            (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION        (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE    (Clock is not active)
               # CCRTNGFC_LIB_PLL_SYNC_NOT_SUPPORTED (PLL Sync not supported)
 ****************************************************************************/
```

2.2.26 ccrtNGFC_Clock_ReturnOutputFrequency()

This call does not return the actual programmed frequency but instead returns the expected output frequency that would be generated if the specified user input parameters are supplied.

```
/****************************************************************************
   long double
   ccrtNGFC_Clock_ReturnOutputFrequency(double       InputClock,
                                        long double  Mdiv_value,
                                        long double  Ndiv_value,
                                        double       Pdiv_value,
                                        double       Rdiv_value)

   Description: Return output frequency

   Input:   double             InputClock  (input clock frequency in Hz)
            long double        Mdiv_value  (M-Divider value)
            long double        Ndiv_value  (N-Divider value)
            double             Pdiv_value  (P-Divider value)
            double             Rdiv_value  (R-Divider value)
   Output:  none
   Return:  long double        returned frequency
 ****************************************************************************/
```

2.2.27 ccrtNGFC_Clock_Set_Generator_CSR()

This call sets the clock generator control and status register.

```
/****************************************************************************
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_CSR (void                      *Handle,
                                    ccrtngfc_clkgen_csr_t     *CgCsr)

   Description: Set Clock Generator Control and Status information

   Input:   void                   *Handle      (Handle pointer)
            ccrtngfc_clkgen_csr_t  *CgCsr       (pointer to clock generator csr)
               _ccrtngfc_clkgen_output_t                    output
                  # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_DISABLE
                  # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_ENABLE
                  # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_DO_NOT_CHANGE
               _ccrtngfc_clkgen_state_t                     state
                  # CCRTNGFC_CLOCK_GENERATOR_ACTIVE
                  # CCRTNGFC_CLOCK_GENERATOR_RESET
                  # CCRTNGFC_CLOCK_GENERATOR_STATE_DO_NOT_CHANGE
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN          (device not open)
               # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
 ***************************************************************************/
```

2.2.28 ccrtNGFC_Clock_Set_Generator_Input_Clock_Enable()

This call sets the input clock status for the input clocks. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_Input_Clock_Enable (void       *Handle,
                       ccrtngfc_clkgen_input_clock_enable_t   *InputClockEnable)

   Description: Set Clock Generator Input Clock Enable

   Input:   void                                  *Handle            (Handle
                                                                      pointer)
            ccrtngfc_clkgen_input_clock_enable_t *InputClockEnable  (pointer to
                                                                    input clock enable)
               _ccrtngfc_cg_input_clock_enable_t    input_0_clock
                  # CCRTNGFC_CG_INPUT_CLOCK_DISABLE
                  # CCRTNGFC_CG_INPUT_CLOCK_ENABLE
                  # CCRTNGFC_CG_INPUT_CLOCK_DO_NOT_CHANGE
               _ccrtngfc_cg_input_clock_enable_t    input_1_clock
                  # CCRTNGFC_CG_INPUT_CLOCK_DISABLE
                  # CCRTNGFC_CG_INPUT_CLOCK_ENABLE
                  # CCRTNGFC_CG_INPUT_CLOCK_DO_NOT_CHANGE
               _ccrtngfc_cg_input_clock_enable_t    input_2_clock
                  # CCRTNGFC_CG_INPUT_CLOCK_DISABLE
                  # CCRTNGFC_CG_INPUT_CLOCK_ENABLE
                  # CCRTNGFC_CG_INPUT_CLOCK_DO_NOT_CHANGE
               _ccrtngfc_cg_input_clock_enable_t    input_fb_clock
                  # CCRTNGFC_CG_INPUT_CLOCK_DISABLE
                  # CCRTNGFC_CG_INPUT_CLOCK_ENABLE
                  # CCRTNGFC_CG_INPUT_CLOCK_DO_NOT_CHANGE
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
            # CCRTNGFC_LIB_NOT_OPEN                (device not open)
            # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
            # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
            # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)
 ************************************************************************/
```

2.2.29 ccrtNGFC_Clock_Set_Generator_Input_Clock_Select()

This call sets the input clock selection. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_Input_Clock_Select (void          *Handle,
                           ccrtngfc_clkgen_input_clock_select_t   *ClkSel)

   Description: Set Clock Generator Input Clock Selection

   Input:   void                                    *Handle (Handle pointer)
            ccrtngfc_clkgen_input_clock_select_t    *ClkSel (pointer to input
                                                             clock select)
               _ccrtngfc_cg_input_clock_select_control_t    control;
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_PIN_CONTROL
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_REG_CONTROL
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_CONTROL_DO_NOT_CHANGE
               _ccrtngfc_cg_input_clock_select_register_t   select;
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN0
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN1
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN2
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_INXAXB
                  # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN_DO_NOT_CHANGE
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                (device not open)
               # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)
 ************************************************************************/
```

2.2.30 ccrtNGFC_Clock_Set_Generator_M_Divider()

This call sets the clock generator M-Divider to the user specified Numerator and Denominator. If the Update flag is set, then the change will take place after the divider has been written to. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_M_Divider (void    *Handle,
                                          __u64   Numerator,
                                          __u32   Denominator,
                                          int     Update)

   Description: Set Clock Generator M-Divider Numerator and Denominator

   Input:   void             *Handle            (Handle pointer)
            __u64            Numerator          (Numerator)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
          __u32            Denominator         (Denominator)
          int              Update              (True=Update)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE (Clock is not active)
 ************************************************************************/
```

2.2.31 ccrtNGFC_Clock_Set_Generator_N_Divider()

This call sets the clock generator selected N-Divider to the user specified Numerator and Denominator. If the Update flag is set, then the change will take place after the divider has been written to. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/************************************************************************
   ccrtNGFC_Clock_Set_Generator_N_Divider()
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_N_Divider (void            *Handle,
                  _ccrtngfc_clock_generator_divider_t     WhichDivider,
                  __u64                                   Numerator,
                  __u32                                   Denominator,
                  int                                     Update)

   Description: Set Clock Generator N-Divider Numerator and Denominator

   Input:   void                                *Handle         (Handle pointer)
            _ccrtngfc_clock_generator_divider_t  WhichDivider    (select divider)
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N0
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N1
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N2
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N3
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N4
            __u64                                Numerator       (Numerator)
            __u32                                Denominator     (Denominator)
            int                                  Update          (True=Update)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                (device not open)
               # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)
 ************************************************************************/
```

2.2.32 ccrtNGFC_Clock_Set_Generator_Output_Config()

This call sets the clock generator Output Configuration for the selected output. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_Output_Config (void              *Handle,
                           _ccrtngfc_clock_generator_output_t  WhichOutput,
                           ccrtngfc_clkgen_output_config_t     *OutCfg)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   Description: Set Clock Generator Output Configuration

   Input:   void                                  *Handle         (Handle pointer)
            _ccrtngfc_clock_generator_output_t  WhichOutput     (select output)
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_0
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_1
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_2
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_3
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_4
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_5
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_6
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_7
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_8
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_9
            ccrtngfc_clkgen_output_config_t   *OutCfg  (pointer to output config)
               _ccrtngfc_cg_outcfg_force_rdiv2_t        force_rdiv2
                  # CCRTNGFC_CG_OUTPUT_CONFIG_DONT_FORCE_RDIV2
                  # CCRTNGFC_CG_OUTPUT_CONFIG_FORCE_RDIV2
                  # CCRTNGFC_CG_OUTPUT_CONFIG_FORCE_DO_NOT_CHANGE
               _ccrtngfc_cg_outcfg_enable_t             enable
                  # CCRTNGFC_CG_OUTPUT_CONFIG_DISABLE
                  # CCRTNGFC_CG_OUTPUT_CONFIG_ENABLE
                  # CCRTNGFC_CG_OUTPUT_CONFIG_ENABLE_DO_NOT_CHANGE
               _ccrtngfc_cg_outcfg_shutdown_t           shutdown
                  # CCRTNGFC_CG_OUTPUT_CONFIG_POWER_UP
                  # CCRTNGFC_CG_OUTPUT_CONFIG_SHUTDOWN
                  # CCRTNGFC_CG_OUTPUT_CONFIG_SHUTDOWN_DO_NOT_CHANGE
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                (device not open)
               # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)
 ***************************************************************************/
```

2.2.33 ccrtNGFC_Clock_Set_Generator_Output_Format()

This call sets the clock generator Output Format for the selected output. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_Output_Format (void                 *Handle,
                              _ccrtngfc_clock_generator_output_t  WhichOutput,
                              ccrtngfc_clkgen_output_format_t     *OutFmt)

   Description: Set Clock Generator Output Format

   Input:   void                                     *Handle     (Handle pointer)
            _ccrtngfc_clock_generator_output_t      WhichOutput (select output)
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_0
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_1
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_2
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_3
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_4
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_5
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_6
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_7
            # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_8
            # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_9
         ccrtngfc_clkgen_output_format_t         *OutFmt     (pointer to
                                                              output format)
            _ccrtngfc_cg_outfmt_cmos_drive_t         cmos_drive
               # CCRTNGFC_CG_OUTPUT_FORMAT_CMOS_DRIVE_LVDS
               # CCRTNGFC_CG_OUTPUT_FORMAT_CMOS_DRIVE_CMOS
               # CCRTNGFC_CG_OUTPUT_FORMAT_CMOS_DRIVE_DO_NOT_CHANGE
            _ccrtngfc_cg_outfmt_disable_state_t      disable_state
               # CCRTNGFC_CG_OUTPUT_FORMAT_DISABLE_LOW
               # CCRTNGFC_CG_OUTPUT_FORMAT_DISABLE_HIGH
               # CCRTNGFC_CG_OUTPUT_FORMAT_DISABLE_DO_NOT_CHANGE
            _ccrtngfc_cg_outfmt_sync_t               sync
               # CCRTNGFC_CG_OUTPUT_FORMAT_SYNC_DISABLE
               # CCRTNGFC_CG_OUTPUT_FORMAT_SYNC_ENABLE
               # CCRTNGFC_CG_OUTPUT_FORMAT_SYNC_DO_NOT_CHANGE
            _ccrtngfc_cg_outfmt_format_t             format
               # CCRTNGFC_CG_OUTPUT_FORMAT_FORMAT_LVDS
               # CCRTNGFC_CG_OUTPUT_FORMAT_FORMAT_CMOS
               # CCRTNGFC_CG_OUTPUT_FORMAT_FORMAT_DO_NOT_CHANGE
      Output:  none
   Return:  _ccrtngfc_lib_error_number_t
            # CCRTNGFC_LIB_NO_ERROR                (successful)
            # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
            # CCRTNGFC_LIB_NOT_OPEN                (device not open)
            # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
            # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
            # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)
*************************************************************************/
```

2.2.34 ccrtNGFC_Clock_Set_Generator_Output_Mode()

This call sets the clock generator Output Mode for the selected output. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_Output_Mode (void                  *Handle,
                           _ccrtngfc_clock_generator_output_t     WhichOutput,
                           ccrtngfc_clkgen_output_mode_t          *OutMode)

   Description: Set Clock Generator Output Mode

   Input:   void                                   *Handle     (Handle pointer)
            _ccrtngfc_clock_generator_output_t     WhichOutput (select output)
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_0
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_1
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_2
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_3
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_4
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_5
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_6
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_7
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_8
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_9
            ccrtngfc_clkgen_output_mode_t          *OutMode    (pointer to
                                                                output mode)
               _ccrtngfc_cg_outmode_amplitude_t         amplitude
                  # CCRTNGFC_CG_OUTPUT_AMPLITUDE_CMOS
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                # CCRTNGFC_CG_OUTPUT_AMPLITUDE_LVDS
                # CCRTNGFC_CG_OUTPUT_AMPLITUDE_DO_NOT_CHANGE
             _ccrtngfc_cg_outmode_common_t            common
                # CCRTNGFC_CG_OUTPUT_COMMON_CMOS
                # CCRTNGFC_CG_OUTPUT_COMMON_LVDS
                # CCRTNGFC_CG_OUTPUT_COMMON_LVPECL
                # CCRTNGFC_CG_OUTPUT_COMMON_DO_NOT_CHANGE
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                (device not open)
               # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)
 ***************************************************************************/
```

2.2.35 ccrtNGFC_Clock_Set_Generator_Output_Mux()

This call sets the clock generator Output Mux for the selected output. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_Output_Mux (void                  *Handle,
                         _ccrtngfc_clock_generator_output_t     WhichOutput,
                         ccrtngfc_clkgen_output_mux_t           *OutMux)

   Description: Set Clock Generator Output Mux

   Input:   void                                    *Handle     (Handle pointer)
            _ccrtngfc_clock_generator_output_t      WhichOutput (select output)
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_0
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_1
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_2
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_3
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_4
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_5
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_6
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_7
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_8
               # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_9
            ccrtngfc_clkgen_output_mux_t       *OutMux  (pointer to output
                                                         inversion/N-divider mux)
              _ccrtngfc_cg_outmux_inversion_t       inversion
                 # CCRTNGFC_CG_OUTPUT_MUX_COMPLEMENTARY
                 # CCRTNGFC_CG_OUTPUT_MUX_IN_PHASE
                 # CCRTNGFC_CG_OUTPUT_MUX_INVERTED
                 # CCRTNGFC_CG_OUTPUT_MUX_OUT_OF_PHASE
                 # CCRTNGFC_CG_OUTPUT_MUX_INVERSION_DO_NOT_CHANGE
              _ccrtngfc_cg_outmux_ndiv_select_t     ndiv_mux
                 # CCRTNGFC_CG_OUTPUT_MUX_NDIV_0
                 # CCRTNGFC_CG_OUTPUT_MUX_NDIV_1
                 # CCRTNGFC_CG_OUTPUT_MUX_NDIV_2
                 # CCRTNGFC_CG_OUTPUT_MUX_NDIV_3
                 # CCRTNGFC_CG_OUTPUT_MUX_NDIV_4
                 # CCRTNGFC_CG_OUTPUT_MUX_NDIV_DO_NOT_CHANGE
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_LIB_NOT_OPEN                (device not open)
            # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
            # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
            # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)
 ************************************************************************/
```

2.2.36 ccrtNGFC_Clock_Set_Generator_P_Divider()

This call sets the clock generator selected P-Divider to the user specified value. If the Update flag is set, then the change will take place after the divider has been written to. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_P_Divider (void                    *Handle,
                          _ccrtngfc_clock_generator_divider_t     WhichDivider,
                          __u64                                   Divider,
                          int                                     Update)

   Description: Set Clock Generator R-Divider
   Input:   void                                 *Handle       (Handle pointer)
            _ccrtngfc_clock_generator_divider_t  WhichDivider  (select divider)
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P0
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P1
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P2
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_PFB
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_PXAXB
            __u64                        Divider         (Divider)
            int                          Update          (True=Update)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                (device not open)
               # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)
 ************************************************************************/
```

2.2.37 ccrtNGFC_Clock_Set_Generator_P_Divider_Enable()

This call sets the state of the clock generator P-Divider. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_P_Divider_Enable (void            *Handle,
                           _ccrtngfc_clock_generator_divider_t   WhichDivider,
                           _ccrtngfc_cg_pdiv_enable_t            Pdiv_Enable)

   Description: Set Clock Generator P-Divider Enable

   Input:   void                                 *Handle         (Handle pointer)
            _ccrtngfc_clock_generator_divider_t  WhichDivider    (select divider)
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P0
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P1
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P2
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_PXAXB
            _ccrtngfc_cg_pdiv_enable_t           Pdiv_Enable     (enable flag)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_CG_PDIV_DISABLE
            # CCRTNGFC_CG_PDIV_ENABLE
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
            # CCRTNGFC_LIB_NO_ERROR                (successful)
            # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
            # CCRTNGFC_LIB_NOT_OPEN                (device not open)
            # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
            # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
            # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)
 ***************************************************************************/
```

2.2.38 ccrtNGFC_Clock_Set_Generator_R_Divider()

This call sets the clock generator selected R-Divider to the user specified value. If the output clock is running, the new clock frequency will take affect immediately or on the next clock cycle depending on the output configuration. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_R_Divider (void                    *Handle,
                        _ccrtngfc_clock_generator_divider_t     WhichDivider,
                        __u32                                   Divider)

   Description: Set Clock Generator R-Divider

   Input:   void                                *Handle        (Handle pointer)
            _ccrtngfc_clock_generator_divider_t  WhichDivider   (select divider)
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R0
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R1
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R2
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R3
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R4
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R5
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R6
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R7
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R8
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_R9
            __u32                                  Divider         (Divider)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                (device not open)
               # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)
 ***************************************************************************/
```

2.2.39 ccrtNGFC_Clock_Set_Generator_Value()

This is a generic call that can program a valid clock generator address to a desired value. User must be intimately familiar with the hardware before programming the values. In-correct programming could result in unpredictable results. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_Value (void    *Handle,
                                       int     address,
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                                        u_char  value)

   Description: Set the value of the specified Clock Generator register.

   Input:   void              *Handle             (Handle pointer)
            int               address             (clock gen address to set)
            u_char            value;              (value to write)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR            (successful)
               # CCRTNGFC_LIB_BAD_HANDLE          (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN            (device not open)
               # CCRTNGFC_LIB_INVALID_ARG         (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION     (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE (Clock is not active)
 ***************************************************************************/
```

2.2.40 ccrtNGFC_Clock_Set_Generator_Voltage_Select()

Program the clock generator voltage selection. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_Voltage_Select (void               *Handle,
                               _ccrtngfc_cg_stat_ctrl_voltsel_t   VoltSel)

   Description: Set Clock Generator voltage selection

   Input:   void                              *Handle   (Handle pointer)
            _ccrtngfc_cg_stat_ctrl_voltsel_t VoltSel   (voltage selection)
               # CCRTNGFC_CG_VOLTAGE_SELECT_1_8V
               # CCRTNGFC_CG_VOLTAGE_SELECT_3_3V
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                (device not open)
               # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)

 ***************************************************************************/
```

2.2.41 ccrtNGFC_Clock_Set_Generator_Zero_Delay()

Program the clock generator zero delay. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Clock_Set_Generator_Zero_Delay (void                    *Handle,
                                      _ccrtngfc_cg_zero_delay_t  ZeroDelay)

   Description: Set Clock Generator Zero Delay selection

   Input:   void                             *Handle    (Handle pointer)
            _ccrtngfc_cg_zero_delay_t        ZeroDelay  (zero delay selection)
               # CCRTNGFC_CG_ZERO_DELAY_MODE
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_CG_NORMAL_MODE
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                (device not open)
               # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
               # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE     (Clock is not active)
 ***************************************************************************/
```

2.2.42 ccrtNGFC_Close()

This call is used to close an already opened device using the *ccrtNGFC_Open()* call.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t ccrtNGFC_Close(void *Handle)
   Description: Close a previously opened device.

   Input:   void *Handle                    (Handle pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR      (successful)
               # CCRTNGFC_LIB_BAD_HANDLE    (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN      (device not open)
 ***************************************************************************/
```

2.2.43 ccrtNGFC_Compute_All_Output_Clocks()

This call does not program the clock outputs but instead returns to the user whether the board can be programmed with the user selected output clock frequencies. Additionally, useful information is returned to the user in a structure for each clock that was computed.

```
/***************************************************************************

   ccrtNGFC_Compute_All_Output_Clocks()

   Description: Compute All Output Clocks

   Input:   void                        *Handle             (Handle pointer)
            double                      InputClockFrequency (Input clock
                                                             frequency)
            ccrtngfc_compute_all_output_clocks_t *AllClocks (Pointer to all
                                                             output clocks info)
               ccrtngfc_compute_single_output_clock_t       *Clock
                  long double                               DesiredFrequency
                  double                                    DesiredTolerancePPT
   Output:  ccrtngfc_compute_all_output_clocks_t            *AllClocks
               (Pointer to returned output clocks info)
               __u32                                        NumberOfNdividers
               ccrtngfc_compute_single_output_clock_t       *Clock
                  _ccrtngfc_clock_generator_output_t        OutputClock
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_0
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_1
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_2
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_3
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_4
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_5
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_6
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_7
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_8
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                  # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_9
                double                                      InputClockFrequency
                long double                                 FrequencyDeviation
                int                                         FrequencyFound
                long double                                 ActualFrequency
                double                                      ActualTolerancePPT
                __u64                                       Mdiv_Numerator
                __u32                                       Mdiv_Denominator
                __u64                                       Ndiv_Numerator
                __u32                                       Ndiv_Denominator
                _ccrtngfc_cg_outmux_ndiv_select_t           Ndiv_ToUse
                   # CCRTNGFC_CG_OUTPUT_MUX_NDIV_0
                   # CCRTNGFC_CG_OUTPUT_MUX_NDIV_1
                   # CCRTNGFC_CG_OUTPUT_MUX_NDIV_2
                   # CCRTNGFC_CG_OUTPUT_MUX_NDIV_3
                   # CCRTNGFC_CG_OUTPUT_MUX_NDIV_4
                __u32                                       Rdiv_value
                __u32                                       Rdivider
                __u32                                       Pdivider
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                     (successful)
               # CCRTNGFC_LIB_BAD_HANDLE                   (no/bad handler
                                                            supplied)
               # CCRTNGFC_LIB_NOT_OPEN                     (library not open)
               # CCRTNGFC_LIB_NO_LOCAL_REGION              (local region error)
               # CCRTNGFC_LIB_IO_ERROR                     (device not ready)
               # CCRTNGFC_LIB_N_DIVIDERS_EXCEEDED          (number of N-Dividers
                                                            exceeded)
               # CCRTNGFC_LIB_CANNOT_COMPUTE_OUTPUT_FREQ   (cannot compute
                                                            output freq)
               # CCRTNGFC_LIB_INVALID_ARG                  (invalid argument)
 ***************************************************************************/
```

2.2.44 ccrtNGFC_Convert_Physmem2avmm_Address()

This call is used to supply the user with an Avalon equivalent Address for the supplied Physical DMA memory. This Avalon equivalent address can then be supplied to the DMA engine to perform DMA operations.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Convert_Physmem2avmm_Address(void        *Handle,
                                         uint        *PhysDmaMemPtr,
                                         uint        *AvalonAddress)

   Description: Get the converted value of Physical DMA memory to Avalon address
                to be supplied as address for DMA operations.

   Input:   void                    *Handle           (Handle pointer)
            uint                    *PhysDmaMemPtr    (pointer to physical DMA
                                                       memory
   Output:  uint                    *AvalonAddress    (pointer to Avalon
                                                       Address).
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                 (successful)
               # CCRTNGFC_LIB_BAD_HANDLE               (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                 (library not open)
               # CCRTNGFC_LIB_INVALID_ARG              (invalid argument)
               # CCRTNGFC_LIB_AVALON_TRANSLATION_TABLE (avalon translation table
                                                       error)
               # CCRTNGFC_LIB_ADDRESS_RANGE_ERROR      (address range error)
 ***************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.45 ccrtNGFC_Create_UserLDioCosInterruptHandler()

This call provides the ability for a user to get notification when a LIO/DIO change-of-state interrupt occurs. Prior to invoking this call, the user needs to create an *interrupt callback* function which is supplied to this call as one of its inputs. Additionally, the user selects a set of LDIO COS wakeup masks to enter the user supplied callback when a corresponding interrupt occurs. On successful completion of this call, a real-time high priority thread is created and blocked waiting for LIO/DIO COS interrupts. When a LIO/DIO COS interrupt occurs, the driver will wake up this thread which in turn execute the user supplied *interrupt callback* function. Various LIO/DIO COS statistics will be returned to the user as an argument ***driver_ldio_cos_int*** supplied to the *interrupt callback* routine everytime a wakeup occurs. The user needs to ensure that the processing within this *interrupt callback* should be completed in as short a time as possible for the thread to be ready in time to accept the next DIO COS interrupt. Failure to do so will result in missed change-of-state interrupts.

If the interrupt handler has already been created for a device, then the user will be unable to create another one as only one interrupt handler is assigned to each device. User will need to destroy the interrupt handler with the *ccrtNGFC_Destroy_UserDioCosInterruptHandler()* call prior to creating a new one.

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Create_UserLDioCosInterruptHandler(void     *Handle,
                                               void     CallBack(),
                                               u_int    LdioCosWakeupInterruptMask
                                               int      SchedulePolicy,
                                               int      SchedulePriority)

   Description: Create a User DIO COS Interrupt Handler

   Input:   void                *Handle                       (Handle pointer)
            void                CallBack()                    (user callback function)
            u_int               LDioCosWakeupInterruptMask    (wakeup interrupt mask)
               # CCRTNGFC_LDIO_MODULE_0_INTMASK
               # CCRTNGFC_LDIO_MODULE_1_INTMASK
               # CCRTNGFC_LDIO_MODULE_2_INTMASK
               # CCRTNGFC_LDIO_MODULE_3_INTMASK
            int                 SchedulePolicy
               # SCHED_FIFO
               # SCHED_RR
               # SCHED_OTHER
            int                 SchedulePriority
               # 1..99 for SCHED_FIFO or SCHED_RR
               # 0     for SCHED_OTHER
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                 (successful)
               # CCRTNGFC_LIB_BAD_HANDLE               (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                 (device not open)
               # CCRTNGFC_LIB_INTHDLR_CREATE_FAILURE   (failed to create
                                                        interrupt handler)
               # CCRTNGFC_LIB_INTHDLR_ALREADY_RUNNING  (interrupt hdlr already
                                                        running)
               # CCRTNGFC_LIB_IOCTL_FAILED             (ioctl failed)
               # CCRTNGFC_LIB_INVALID_ARG              (invalid argument)
 *****************************************************************************/
```

// User interrupt callback()

```
void LDioCosUserCallback(void                          *Handle,
                         ccrtngfc_driver_ldio_cos_int_t *driver_ldio_cos_int)
{
    // User supplied code for handling interrupt
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
}

// Interrupt Counters
typedef struct
{
    long long unsigned  LDIO_COS_WakeupUserCounter;
    long long unsigned  LDIO_COS_ChannelsCount[CCRTNGFC_LDIO_MAX_MODULES];
    long long unsigned  LDIO_COS_ChannelsOverflowCount[CCRTNGFC_LDIO_MAX_MODULES];
    int RESERVED[128];
} ccrtngfc_interrupt_ldio_cos_counters_t;

typedef u_int32_t   ccrtngfc_ldio_modules_t[CCRTNGFC_LDIO_MAX_MODULES];

// LDIO COS Interrupt
typedef struct
{
    uint           InterruptsOccurredMask;
    uint           WakeupInterruptMask;

    // LDIO Current information
    ccrtngfc_ldio_modules_t LDIO_COS_ChannelsStatus;
    ccrtngfc_ldio_modules_t LDIO_COS_ChannelsOverflow;

    // LDIO Queued 1-deep information
    ccrtngfc_ldio_modules_t LDIO_COS_Queued1ChannelsStatus;

    // LDIO Queued 2-deep information
    ccrtngfc_ldio_modules_t LDIO_COS_Queued2ChannelsStatus;

    ccrtngfc_interrupt_ldio_cos_counters_t   counters;
    int RESERVED[220];
} ccrtngfc_driver_ldio_cos_int_t;
```

2.2.46 ccrtNGFC_Create_UserProcess()

Typically reads from the card take a finite time to complete. If the user has a process that is time critical and needs to read the latest data faster, they may use a new approach called Hyper-Drive. In this case, the user defines a thread with this call, which continuously reads the data from the board and holds the latest values. The user process can then access this latest data at substantially faster rates. The two drawbacks to this approach is that the excessive bus assess is made and dedicated CPUs are required.

This call is used to create this User Process looping thread which can be controlled by the user via the returned handle. *(This is an experimental API for debugging and testing).*

```
/*************************************************************************
  _ccrtngfc_lib_error_number_t
  ccrtNGFC_Create_UserProcess(void                        *Handle,
                              _ccrtngfc_UserFunction_t    *UFunc,
                              _ccrtngfc_UserFunction_t    **UFuncHandle)

   Description: Create a User Process for user defined processing

   Input:   void                        *Handle         (Handle pointer)
            _ccrtngfc_UserFunction_t    *UFunc          (pointer to user
                                                         information structure)
   Output:  _ccrtngfc_UserFunction_t    **UFuncHandle   (pointer to user function
                                                         struct handle)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                 (successful)
               # CCRTNGFC_LIB_BAD_HANDLE               (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                 (device not open)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                # CCRTNGFC_LIB_NO_RESOURCE              (cannot allocate memory)
                # CCRTNGFC_LIB_INTERNAL_ERROR           (pthread attr failed)
                # CCRTNGFC_LIB_THREAD_CREATE_FAILED     (failed to create thread)
*************************************************************************/

typedef struct
{
    int Magic;
    void                            (*UserFunction) (void *hdl);
    pthread_t                       UserFunction_Thread_id;
    pid_t                           Pid;
    pthread_mutex_t                 lock;               /* lock this structure */
    pthread_cond_t                  wait;               /* wait for command */
    pthread_mutex_t                 cmd_lock;           /* lock this structure */
    pthread_cond_t                  cmd_wait;           /* wait for command */
    pthread_mutex_t                 user_lock;          /* lock this structure */
    pthread_cond_t                  user_wait;          /* wait for command */
    pthread_mutex_t                 user_mem_lock;      /* lock this structure */
    pthread_cond_t                  user_mem_wait;      /* wait for command */
    volatile int                    cpuAffinity;        /* CPU on which Thread
                                                           will run */
    volatile int                    cpuCount;           /* no. of cpus to run on
                                                           starting at base */
    volatile void                   *Handle;
    volatile void                   **Args;
    volatile int                    SchedulePolicy;
    volatile int                    SchedulePriority;
    volatile int                    ScheduleSelf;       /* 1=(Use
                                                           SchedulePriority-
                                                           1),0=no change */
    volatile ccrtngfc_uf_action_t   Action;
    volatile ccrtngfc_uf_state_t    State;
    volatile int                    CommandPending;
    volatile void                   *Next_UserFunction;
    volatile unsigned int long long RunCount;
    volatile int                    Pause;
} _ccrtngfc_UserFunction_t;
```

2.2.47 ccrtNGFC_DataToVolts()

This routine takes a raw analog input data value and converts it to a floating point voltage based on the supplied format. Format can be *CCRTNGFC_TWOS_COMPLEMENT* or *CCRTNGFC_OFFSET_BINARY*. The data supplied in *us_data* must not be greater than the hardware resolution bits *CCRTNGFC_ADC_RESOLUTION_BITS* supported by the board. Data greater than this will be masked out.

```
/*************************************************************************
   double ccrtNGFC_DataToVolts(int us_data, ccrtngfc_volt_convert_t *conv)

   Description: Convert Data to volts

   Input:   int                                 us_data       (data to convert)
            ccrtngfc_volt_convert_t             *conv         (pointer to
                                                               conversion struct)
               double                           VoltageRange  (maximum voltage
                                                               range)
               _ccrtngfc_csr_dataformat_t       Format        (format)
                  # CCRTNGFC_OFFSET_BINARY
                  # CCRTNGFC_TWOS_COMPLEMENT
               ccrtngfc_bool                    BiPolar       (bi-polar)
                  # CCRTNGFC_TRUE
                  # CCRTNGFC_FALSE
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            int                                 ResolutionBits (Number of
                                                                resolution bits)
  Output:  none
  Return:  double                               volts          (returned volts)
 ****************************************************************************/
```

2.2.48 ccrtNGFC_DataToVoltsLxxFormat()

This routine takes the various raw data maintained by the power module and converts to a floating point format for user display. The *LxxFormat* value to be selected is specific to the data being collected.

```
/****************************************************************************
   double
   ccrtNGFC_DataToVoltsLxxFormat (int                                us_data,
                                  _ccrtngfc_floating_point_format_t LxxFormat)

   Description: Convert Data to volts in L11 or L16 format

   Input:   uint                                us_data         (data to convert)
            _ccrtngfc_floating_point_format_t   LxxFormat       (L11 or L16 format)
                # CCRTNGFC_FLOATING_POINT_FORMAT_L11
                # CCRTNGFC_FLOATING_POINT_FORMAT_L16
   Output:  none
   Return:  double                              volts          (returned volts)
 ****************************************************************************/
```

2.2.49 ccrtNGFC_DaughterCard_EEPROM_Read()

The purpose of this call is to read the EEPROM contents of the daughter card installed on the board. The user needs to select the daughter card, the address within the EEPROM and the size to read. Normally, this call is not to be used by the user as the EEPROM data has been setup by Concurrent Real-Time.

```
/****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_DaughterCard_EEPROM_Read(void                    *Handle,
                                     ccrtngfc_dc_eeprom_io_t *eeprom_read)

   Description: Daughter Card EEPROM Read

   Input:    void                                            *Handle   (handle pointer)
             ccrtngfc_dc_eeprom_io_t                         *eeprom_read
                - _ccrtngfc_dc_eeprom_daughter_card_select_t   DaughterCardSelect
                    # CCRTNGFC_DCE_DAUGHTER_CARD_0
                    # CCRTNGFC_DCE_DAUGHTER_CARD_1
                - uint Address
                - uint Size
                - uint FirmwareId
   Output:   ccrtngfc_dc_eeprom_io_t    *eeprom_read
                - char *DataPtr
   Return:   _ccrtngfc_lib_error_number_t
                # CCRTNGFC_LIB_NO_ERROR           (successful)
                # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
                # CCRTNGFC_LIB_NOT_OPEN           (library not open)
                # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
                # CCRTNGFC_LIB_CANNOT_OPEN_FILE   (cannot open calib. file)
                # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
                # CCRTNGFC_LIB_DC_EEPROM_FAILURE  (Daughter Card EEPROM Failure)
                # CCRTNGFC_LIB_DC_EEPROM_BUSY     (Daughter Card EEPROM Busy)
                # CCRTNGFC_LIB_NO_DAUGHTER_CARD_PRESENT
                                                  (Daughter Card Not Present)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
*************************************************************************/
```

2.2.50 ccrtNGFC_DaughterCard_EEPROM_Write()

The purpose of this call is to write to the EEPROM of the daughter card installed on the board. The user needs to select the daughter card, the address within the EEPROM, the size to read and the data to be written. Normally, this call is not to be used by the user as the EEPROM data has been setup by Concurrent Real-Time. If its contents is changed, it is possible that the driver may no longer be able to access the card.

Normally, the routine does a read of the data at the EEPROM offset and only writes to the the EEPROM if the value to be written is different from that of what is already there. If for whatever reason, the user wishes to force a write of the location (bad EEPROM?) then the ForceWriteToEEPROM argument allows the user to do that.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_DaughterCard_EEPROM_Write(void                    *Handle,
                                      ccrtngfc_dc_eeprom_io_t *eeprom_write,
                                      int                      ForceWriteToEEPROM)

   Description: Daughter Card EEPROM Write

   Input:    void                                             *Handle   (handle pointer)
             ccrtngfc_dc_eeprom_io_t                          *eeprom_write
                - _ccrtngfc_dc_eeprom_daughter_card_select_t  DaughterCardSelect
                    # CCRTNGFC_DCE_DAUGHTER_CARD_0
                    # CCRTNGFC_DCE_DAUGHTER_CARD_1
                - uint Address
                - uint Size
                - char *DataPtr
             int                                              ForceWriteToEEPROM)
   Output:   none
   Return:   _ccrtngfc_lib_error_number_t
                # CCRTNGFC_LIB_NO_ERROR           (successful)
                # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
                # CCRTNGFC_LIB_NOT_OPEN           (library not open)
                # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
                # CCRTNGFC_LIB_CANNOT_OPEN_FILE   (cannot open calib. file)
                # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
                # CCRTNGFC_LIB_DC_EEPROM_FAILURE  (Daughter Card EEPROM Failure)
                # CCRTNGFC_LIB_DC_EEPROM_BUSY     (Daughter Card EEPROM Busy)
                # CCRTNGFC_LIB_NO_DAUGHTER_CARD_PRESENT
                                                  (Daughter Card Not Present)
 *************************************************************************/
```

2.2.51 ccrtNGFC_Destroy_AllUserProcess()

The purpose of this call is to destroy all User Processes that have been previously created by the *ccrtNGFC_Create_UserProcess()* command. *(This is an experimental API for debugging and testing).*

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t ccrtNGFC_Destroy_AllUserProcess(void *Handle)

   Description: Destroy all created  user processes

   Input:   void                      *Handle      (Handle pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
 *************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.52 ccrtNGFC_Destroy_UserLDioCosInterruptHandler()

The purpose of this call is to destroy the User LDIO COS Interrupt handler that was created earlier with the *ccrtNGFC_Create_UserLDioCosInterruptHandler()* call.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Destroy_UserLDioCosInterruptHandler(void *Handle)

   Description: Destroy a previously created User LDIO COS Interrupt Handler

   Input:   void                 *Handle              (Handle pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR               (successful)
               # CCRTNGFC_LIB_BAD_HANDLE             (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN               (device not open)
               # CCRTNGFC_LIB_IOCTL_FAILED           (ioctl failed)
               # CCRTNGFC_LIB_IO_ERROR               (failed to terminate
                                                      handler)
 *************************************************************************/
```

2.2.53 ccrtNGFC_Destroy_UserProcess()

The purpose of this call is to destroy the User Process that have been previously created by the *ccrtNGFC_Create_UserProcess()* call. *(This is an experimental API for debugging and testing).*

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t ccrtNGFC_Destroy_UserProcess(void *Handle,
                                  _ccrtngfc_UserFunction_t **UFuncHandle)

   Description: Destroy an already created  user process

   Input:   void                      *Handle          (Handle pointer)
            _ccrtngfc_UserFunction_t  **UFuncHandle    (pointer to user handle)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR               (successful)
               # CCRTNGFC_LIB_BAD_HANDLE             (no/bad handler supplied)
 *************************************************************************/
```

2.2.54 ccrtNGFC_DIO_Get_Channels_Terminator()

This call returns to the user the Digital I/O channel terminators. The ChannelSelectMask is used to select up to 32 channels.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0. The CCRTNGFC_MAIN_LIO_MODULE_1 is for the LIO module that is located on the mother-board and is therefore invalid for this DIO API. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_DIO_Get_Channels_Terminator(void                     *Handle,
                                       ccrtngfc_ldio_modules_t   DIO_ChannelsTerminator,
                                       ccrtngfc_ldio_modules_t   ChannelSelectMask)

   Description: Get DIO Channels Terminator Mask

   Input:   void                       *Handle               (handle pointer)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                ccrtngfc_ldio_modules_t      ChannelSelectMask       (channel selection mask)
                    # NULL                                          (select all channels)
                    # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                        # CCRTNGFC_LDIO_CHANNEL_MASK_0
                        # CCRTNGFC_LDIO_CHANNEL_MASK_1
                        # CCRTNGFC_LDIO_CHANNEL_MASK_2
                        # CCRTNGFC_LDIO_CHANNEL_MASK_3
                        # CCRTNGFC_LDIO_CHANNEL_MASK_4
                        # CCRTNGFC_LDIO_CHANNEL_MASK_5
                        # CCRTNGFC_LDIO_CHANNEL_MASK_6
                        # CCRTNGFC_LDIO_CHANNEL_MASK_7
                        # CCRTNGFC_LDIO_CHANNEL_MASK_8
                        # CCRTNGFC_LDIO_CHANNEL_MASK_9
                        # CCRTNGFC_LDIO_CHANNEL_MASK_10
                        # CCRTNGFC_LDIO_CHANNEL_MASK_11
                        # CCRTNGFC_LDIO_CHANNEL_MASK_12
                        # CCRTNGFC_LDIO_CHANNEL_MASK_13
                        # CCRTNGFC_LDIO_CHANNEL_MASK_14
                        # CCRTNGFC_LDIO_CHANNEL_MASK_15
                        # CCRTNGFC_LDIO_CHANNEL_MASK_16
                        # CCRTNGFC_LDIO_CHANNEL_MASK_17
                        # CCRTNGFC_LDIO_CHANNEL_MASK_18
                        # CCRTNGFC_LDIO_CHANNEL_MASK_19
                        # CCRTNGFC_LDIO_CHANNEL_MASK_20
                        # CCRTNGFC_LDIO_CHANNEL_MASK_21
                        # CCRTNGFC_LDIO_CHANNEL_MASK_22
                        # CCRTNGFC_LDIO_CHANNEL_MASK_23
                        # CCRTNGFC_LDIO_CHANNEL_MASK_24
                        # CCRTNGFC_LDIO_CHANNEL_MASK_25
                        # CCRTNGFC_LDIO_CHANNEL_MASK_26
                        # CCRTNGFC_LDIO_CHANNEL_MASK_27
                        # CCRTNGFC_LDIO_CHANNEL_MASK_28
                        # CCRTNGFC_LDIO_CHANNEL_MASK_29
                        # CCRTNGFC_LDIO_CHANNEL_MASK_30
                        # CCRTNGFC_LDIO_CHANNEL_MASK_31
                        # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                    CCRTNGFC_LDIO_MAX_MODULES can be one of:
                        # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                        # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                        # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                        # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
Output:  ccrtngfc_ldio_modules_t      DIO_ChannelsTerminator  (DIO Channels Terminator)
                                      - CCRTNGFC_DIO_TERMINATOR_OFF   = (0)
                                      - CCRTNGFC_DIO_TERMINATOR_ON    = (1)
                    # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                        # CCRTNGFC_LDIO_CHANNEL_MASK_0
                        # CCRTNGFC_LDIO_CHANNEL_MASK_1
                        # CCRTNGFC_LDIO_CHANNEL_MASK_2
                        # CCRTNGFC_LDIO_CHANNEL_MASK_3
                        # CCRTNGFC_LDIO_CHANNEL_MASK_4
                        # CCRTNGFC_LDIO_CHANNEL_MASK_5
                        # CCRTNGFC_LDIO_CHANNEL_MASK_6
                        # CCRTNGFC_LDIO_CHANNEL_MASK_7
                        # CCRTNGFC_LDIO_CHANNEL_MASK_8
                        # CCRTNGFC_LDIO_CHANNEL_MASK_9
                        # CCRTNGFC_LDIO_CHANNEL_MASK_10
                        # CCRTNGFC_LDIO_CHANNEL_MASK_11
                        # CCRTNGFC_LDIO_CHANNEL_MASK_12
                        # CCRTNGFC_LDIO_CHANNEL_MASK_13
                        # CCRTNGFC_LDIO_CHANNEL_MASK_14
                        # CCRTNGFC_LDIO_CHANNEL_MASK_15
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN          (device not open)
               # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ***************************************************************************/
```

2.2.55 ccrtNGFC_DIO_Get_Ports_Direction()

This call returns to the user the direction of the Digital I/O channels.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0. The CCRTNGFC_MAIN_LIO_MODULE_1 is for the LIO module that is located on the mother-board and is therefore invalid for this DIO API. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed.

The DIO that is located on the mother-board has each of the 32 channels controlled by 32 independent ports. Hence, each channels direction can be controlled independent of each other. The optional DIO daughter card has groups of 4 channels controlled by a single port. Hence the direction of the channels must be controlled in groups of 4 adjacent channels.

When the direction for channels are set to output, then reading the channels input registers will result in acquiring what was written to the output (loopback). When the direction for the channels are set as inputs, then reading the channels input registers will result in acquiring signals coming into the board from the external digital lines.

```
/***************************************************************************

   ccrtNGFC_DIO_Get_Ports_Direction()

   Description: Get DIO Ports Direction Mask

   Input:   void                        *Handle                 (handle pointer)
            ccrtngfc_dio_ports_t        PortSelectionMask       (port selection mask)
               # NULL                                           (select all ports)
               # _ccrtngfc_dio_port_mask_t  ccrtngfc_dio_ports_t[CCRTNGFC_LDIO_MAX_MODULES]
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_DIO_PORT_MASK_P0
                    # CCRTNGFC_DIO_PORT_MASK_P1
                    # CCRTNGFC_DIO_PORT_MASK_P2
                    # CCRTNGFC_DIO_PORT_MASK_P3
                    # CCRTNGFC_DIO_PORT_MASK_P4
                    # CCRTNGFC_DIO_PORT_MASK_P5
                    # CCRTNGFC_DIO_PORT_MASK_P6
                    # CCRTNGFC_DIO_PORT_MASK_P7
                    # CCRTNGFC_DIO_PORT_MASK_P8         - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P9         - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P10        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P11        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P12        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P13        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P14        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P15        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P16        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P17        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P18        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P19        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P20        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P21        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P22        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P23        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P24        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P25        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P26        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P27        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P28        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P29        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P30        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P31        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_ALL_PORTS_MASK       - valid for Main DIO only
                    # CCRTNGFC_DC_DIO_ALL_PORTS_MASK    - valid for Daughter Card DIO only
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
Output:  ccrtngfc_dio_ports_t         DIO_PortDirection             (port direction)
                                      - CCRTNGFC_LDIO_DIRECTION_INPUT    = (0)
                                      - CCRTNGFC_LDIO_DIRECTION_OUTPUT   = (1)
                # _ccrtngfc_dio_port_mask_t ccrtngfc_dio_ports_t[CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_DIO_PORT_MASK_P0
                    # CCRTNGFC_DIO_PORT_MASK_P1
                    # CCRTNGFC_DIO_PORT_MASK_P2
                    # CCRTNGFC_DIO_PORT_MASK_P3
                    # CCRTNGFC_DIO_PORT_MASK_P4
                    # CCRTNGFC_DIO_PORT_MASK_P5
                    # CCRTNGFC_DIO_PORT_MASK_P6
                    # CCRTNGFC_DIO_PORT_MASK_P7
                    # CCRTNGFC_DIO_PORT_MASK_P8         - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P9         - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P10        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P11        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P12        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P13        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P14        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P15        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P16        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P17        - not valid for Daughter Card DIO
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_DIO_PORT_MASK_P18        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P19        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P20        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P21        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P22        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P23        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P24        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P25        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P26        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P27        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P28        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P29        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P30        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P31        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_ALL_PORTS_MASK       - valid for Main DIO only
                    # CCRTNGFC_DC_DIO_ALL_PORTS_MASK    - valid for Daughter Card DIO only
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
*************************************************************************/
```

2.2.56 ccrtNGFC_DIO_Set_Channels_Terminator()

This call sets the Digital I/O channel terminators to ON or OFF for the selected channels.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0. The CCRTNGFC_MAIN_LIO_MODULE_1 is for the LIO module that is located on the mother-board and is therefore invalid for this DIO API. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed.

When issuing this call, the users must initialize *all* available DIO modules properly, otherwise the call will fail. If an DIO module is to be skipped in this call, the *ChannelSelectMask* for a DIO module must be set to zero *(i.e. no channels are selected)*.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_DIO_Set_Channels_Terminator(void                      *Handle,
                                       ccrtngfc_ldio_modules_t   DIO_ChannelsTerminator,
                                       ccrtngfc_ldio_modules_t   ChannelSelectMask)

   Description: Set DIO Channels Terminator Mask

   Input:   void                         *Handle                (handle pointer)
            ccrtngfc_ldio_modules_t      DIO_ChannelsTerminator (DIO Channels Terminator)
                                         - CCRTNGFC_DIO_TERMINATOR_OFF   = (0)
                                         - CCRTNGFC_DIO_TERMINATOR_ON    = (1)
               # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                   # CCRTNGFC_LDIO_CHANNEL_MASK_0
                   # CCRTNGFC_LDIO_CHANNEL_MASK_1
                   # CCRTNGFC_LDIO_CHANNEL_MASK_2
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_LDIO_CHANNEL_MASK_3
            # CCRTNGFC_LDIO_CHANNEL_MASK_4
            # CCRTNGFC_LDIO_CHANNEL_MASK_5
            # CCRTNGFC_LDIO_CHANNEL_MASK_6
            # CCRTNGFC_LDIO_CHANNEL_MASK_7
            # CCRTNGFC_LDIO_CHANNEL_MASK_8
            # CCRTNGFC_LDIO_CHANNEL_MASK_9
            # CCRTNGFC_LDIO_CHANNEL_MASK_10
            # CCRTNGFC_LDIO_CHANNEL_MASK_11
            # CCRTNGFC_LDIO_CHANNEL_MASK_12
            # CCRTNGFC_LDIO_CHANNEL_MASK_13
            # CCRTNGFC_LDIO_CHANNEL_MASK_14
            # CCRTNGFC_LDIO_CHANNEL_MASK_15
            # CCRTNGFC_LDIO_CHANNEL_MASK_16
            # CCRTNGFC_LDIO_CHANNEL_MASK_17
            # CCRTNGFC_LDIO_CHANNEL_MASK_18
            # CCRTNGFC_LDIO_CHANNEL_MASK_19
            # CCRTNGFC_LDIO_CHANNEL_MASK_20
            # CCRTNGFC_LDIO_CHANNEL_MASK_21
            # CCRTNGFC_LDIO_CHANNEL_MASK_22
            # CCRTNGFC_LDIO_CHANNEL_MASK_23
            # CCRTNGFC_LDIO_CHANNEL_MASK_24
            # CCRTNGFC_LDIO_CHANNEL_MASK_25
            # CCRTNGFC_LDIO_CHANNEL_MASK_26
            # CCRTNGFC_LDIO_CHANNEL_MASK_27
            # CCRTNGFC_LDIO_CHANNEL_MASK_28
            # CCRTNGFC_LDIO_CHANNEL_MASK_29
            # CCRTNGFC_LDIO_CHANNEL_MASK_30
            # CCRTNGFC_LDIO_CHANNEL_MASK_31
            # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
        CCRTNGFC_LDIO_MAX_MODULES can be one of:
            # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
            # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
            # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
            # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
    ccrtngfc_ldio_modules_t      ChannelSelectMask       (channel selection mask)
        # NULL                                           (select all channels)
        # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
            # CCRTNGFC_LDIO_CHANNEL_MASK_0
            # CCRTNGFC_LDIO_CHANNEL_MASK_1
            # CCRTNGFC_LDIO_CHANNEL_MASK_2
            # CCRTNGFC_LDIO_CHANNEL_MASK_3
            # CCRTNGFC_LDIO_CHANNEL_MASK_4
            # CCRTNGFC_LDIO_CHANNEL_MASK_5
            # CCRTNGFC_LDIO_CHANNEL_MASK_6
            # CCRTNGFC_LDIO_CHANNEL_MASK_7
            # CCRTNGFC_LDIO_CHANNEL_MASK_8
            # CCRTNGFC_LDIO_CHANNEL_MASK_9
            # CCRTNGFC_LDIO_CHANNEL_MASK_10
            # CCRTNGFC_LDIO_CHANNEL_MASK_11
            # CCRTNGFC_LDIO_CHANNEL_MASK_12
            # CCRTNGFC_LDIO_CHANNEL_MASK_13
            # CCRTNGFC_LDIO_CHANNEL_MASK_14
            # CCRTNGFC_LDIO_CHANNEL_MASK_15
            # CCRTNGFC_LDIO_CHANNEL_MASK_16
            # CCRTNGFC_LDIO_CHANNEL_MASK_17
            # CCRTNGFC_LDIO_CHANNEL_MASK_18
            # CCRTNGFC_LDIO_CHANNEL_MASK_19
            # CCRTNGFC_LDIO_CHANNEL_MASK_20
            # CCRTNGFC_LDIO_CHANNEL_MASK_21
            # CCRTNGFC_LDIO_CHANNEL_MASK_22
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ***************************************************************************/
```

2.2.57 ccrtNGFC_DIO_Set_Channels_Terminator_To_Off()

This call sets the Digital I/O channel terminators to OFF for the selected channels.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0. The CCRTNGFC_MAIN_LIO_MODULE_1 is for the LIO module that is located on the mother-board and is therefore invalid for this DIO API. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed.

In order to skip a DIO module, simply set *DIO_ChannelsOffTerminator* to zero for that module.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_DIO_Set_Channels_Terminator_To_Off(void                    *Handle,
                                               ccrtngfc_ldio_modules_t DIO_ChannelsOffTerminator)

   Description: Set DIO Channels Terminator Off Mask

   Input:   void                        *Handle                   (handle pointer)
            ccrtngfc_ldio_modules_t     DIO_ChannelsOffTerminator (DIO Channels Terminator)
               # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
   Output: none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ***************************************************************************/
```

2.2.58 ccrtNGFC_DIO_Set_Channels_Terminator_To_On()

This call sets the Digital I/O channel terminators to ON for the selected channels.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0. The CCRTNGFC_MAIN_LIO_MODULE_1 is for the LIO module that is located on the mother-board and is therefore invalid for this DIO API. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed.

In order to skip a DIO module, simply set *DIO_ChannelsOnTerminator* to zero for that module.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_DIO_Set_Channels_Terminator_To_On(void                    *Handle,
                                              ccrtngfc_ldio_modules_t DIO_ChannelsOnTerminator)

   Description: Set DIO Channels Terminator On Mask

   Input:   void                        *Handle                  (handle pointer)
            ccrtngfc_ldio_modules_t     DIO_ChannelsOnTerminator (DIO Channels Terminator)
               # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                   # CCRTNGFC_LDIO_CHANNEL_MASK_0
                   # CCRTNGFC_LDIO_CHANNEL_MASK_1
                   # CCRTNGFC_LDIO_CHANNEL_MASK_2
                   # CCRTNGFC_LDIO_CHANNEL_MASK_3
                   # CCRTNGFC_LDIO_CHANNEL_MASK_4
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
  Output: none
  Return:  _ccrtngfc_lib_error_number_t
              # CCRTNGFC_LIB_NO_ERROR           (successful)
              # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
              # CCRTNGFC_LIB_NOT_OPEN           (device not open)
              # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
              # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
              # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
*************************************************************************/
```

2.2.59 ccrtNGFC_DIO_Set_Ports_Direction()

This call sets the direction of the Digital I/O channels.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0. The CCRTNGFC_MAIN_LIO_MODULE_1 is for the LIO module that is located on the mother-board and is therefore invalid for this DIO API. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed.

The DIO that is located on the mother-board has each of the 32 channels controlled by 32 independent ports. Hence, each channels direction can be controlled independent of each other. The optional DIO daughter card has groups of 4 channels controlled by a single port. Hence the direction of the channels must be controlled in groups of 4 adjacent channels.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

When the direction for channels are set to output, then reading the channels input registers will result in acquiring what was written to the output (loopback). When the direction for the channels are set as inputs, then reading the channels input registers will result in acquiring signals coming into the board from the external digital lines.

When issuing this call, the users must initialize *all* available DIO modules properly, otherwise the call will fail. If an DIO module is to be skipped in this call, the *PortSelectionMask* for a DIO module must be set to zero *(i.e. no ports are selected)*.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_DIO_Set_Ports_Direction(void                      *Handle,
                                    ccrtngfc_dio_ports_t      DIO_PortDirection,
                                    ccrtngfc_dio_ports_t      PortSelectionMask)

   Description: Set DIO Ports Direction Mask

   Input:   void                              *Handle                    (handle pointer)
            ccrtngfc_dio_ports_t              DIO_PortDirection          (port direction)
                                          - CCRTNGFC_LDIO_DIRECTION_INPUT    = (0)
                                          - CCRTNGFC_LDIO_DIRECTION_OUTPUT   = (1)
               # _ccrtngfc_dio_port_mask_t  ccrtngfc_dio_ports_t[CCRTNGFC_LDIO_MAX_MODULES]
                   # CCRTNGFC_DIO_PORT_MASK_P0
                   # CCRTNGFC_DIO_PORT_MASK_P1
                   # CCRTNGFC_DIO_PORT_MASK_P2
                   # CCRTNGFC_DIO_PORT_MASK_P3
                   # CCRTNGFC_DIO_PORT_MASK_P4
                   # CCRTNGFC_DIO_PORT_MASK_P5
                   # CCRTNGFC_DIO_PORT_MASK_P6
                   # CCRTNGFC_DIO_PORT_MASK_P7
                   # CCRTNGFC_DIO_PORT_MASK_P8         - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P9         - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P10        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P11        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P12        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P13        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P14        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P15        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P16        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P17        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P18        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P19        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P20        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P21        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P22        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P23        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P24        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P25        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P26        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P27        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P28        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P29        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P30        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_PORT_MASK_P31        - not valid for Daughter Card DIO
                   # CCRTNGFC_DIO_ALL_PORTS_MASK       - valid for Main DIO only
                   # CCRTNGFC_DC_DIO_ALL_PORTS_MASK    - valid for Daughter Card DIO only
               CCRTNGFC_LDIO_MAX_MODULES can be one of:
                   # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                   # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                   # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                   # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
            ccrtngfc_dio_ports_t         PortSelectionMask          (port selection mask)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                # NULL                                                  (select all ports)
                # _ccrtngfc_dio_port_mask_t  ccrtngfc_dio_ports_t[CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_DIO_PORT_MASK_P0
                    # CCRTNGFC_DIO_PORT_MASK_P1
                    # CCRTNGFC_DIO_PORT_MASK_P2
                    # CCRTNGFC_DIO_PORT_MASK_P3
                    # CCRTNGFC_DIO_PORT_MASK_P4
                    # CCRTNGFC_DIO_PORT_MASK_P5
                    # CCRTNGFC_DIO_PORT_MASK_P6
                    # CCRTNGFC_DIO_PORT_MASK_P7
                    # CCRTNGFC_DIO_PORT_MASK_P8         - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P9         - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P10        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P11        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P12        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P13        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P14        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P15        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P16        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P17        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P18        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P19        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P20        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P21        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P22        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P23        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P24        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P25        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P26        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P27        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P28        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P29        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P30        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P31        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_ALL_PORTS_MASK       - valid for Main DIO only
                    # CCRTNGFC_DC_DIO_ALL_PORTS_MASK    - valid for Daughter Card DIO only
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
  Output:  none
  Return:  _ccrtngfc_lib_error_number_t
              # CCRTNGFC_LIB_NO_ERROR           (successful)
              # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
              # CCRTNGFC_LIB_NOT_OPEN           (device not open)
              # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
              # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
              # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
*************************************************************************/
```

2.2.60 ccrtNGFC_DIO_Set_Ports_Direction_To_Input()

This call sets the direction of the Digital I/O channels to Inputs.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0. The CCRTNGFC_MAIN_LIO_MODULE_1 is for the LIO module that is located on the mother-board and is therefore invalid for this DIO API. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

The DIO that is located on the mother-board has each of the 32 channels controlled by 32 independent ports. Hence, each channels direction can be controlled independent of each other. The optional DIO daughter card has groups of 4 channels controlled by a single port. Hence the direction of the channels must be controlled in groups of 4 adjacent channels.

When the direction for the channels are set as inputs, then reading the channels input registers will result in acquiring signals coming into the board from the external digital lines.

In order to skip a DIO module, simply set *DIO_InputPortDirection* to zero for that module.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_DIO_Set_Ports_Direction_To_Input(void                  *Handle,
                                            ccrtngfc_dio_ports_t  DIO_InputPortDirection)

   Description: Set DIO Port Direction to Input Mask

   Input:   void                         *Handle                   (handle pointer)
            ccrtngfc_dio_ports_t         DIO_InputPortDirection    (input port direction)
                # _ccrtngfc_dio_port_mask_t ccrtngfc_dio_ports_t[CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_DIO_PORT_MASK_P0
                    # CCRTNGFC_DIO_PORT_MASK_P1
                    # CCRTNGFC_DIO_PORT_MASK_P2
                    # CCRTNGFC_DIO_PORT_MASK_P3
                    # CCRTNGFC_DIO_PORT_MASK_P4
                    # CCRTNGFC_DIO_PORT_MASK_P5
                    # CCRTNGFC_DIO_PORT_MASK_P6
                    # CCRTNGFC_DIO_PORT_MASK_P7
                    # CCRTNGFC_DIO_PORT_MASK_P8         - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P9         - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P10        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P11        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P12        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P13        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P14        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P15        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P16        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P17        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P18        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P19        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P20        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P21        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P22        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P23        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P24        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P25        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P26        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P27        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P28        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P29        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P30        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P31        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_ALL_PORTS_MASK       - valid for Main DIO only
                    # CCRTNGFC_DC_DIO_ALL_PORTS_MASK    - valid for Daughter Card DIO only
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
   Output:  none
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ************************************************************************/
```

2.2.61 ccrtNGFC_DIO_Set_Ports_Direction_To_Output()

This call sets the direction of the Digital I/O channels to Outputs.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0. The CCRTNGFC_MAIN_LIO_MODULE_1 is for the LIO module that is located on the mother-board and is therefore invalid for this DIO API. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed.

The DIO that is located on the mother-board has each of the 32 channels controlled by 32 independent ports. Hence, each channels direction can be controlled independent of each other. The optional DIO daughter card has groups of 4 channels controlled by a single port. Hence the direction of the channels must be controlled in groups of 4 adjacent channels.

When the direction for channels are set to output, then reading the channels input registers will result in acquiring what was written to the output (readback).

In order to skip a DIO module, simply set *DIO_OutputPortDirection* to zero for that module.

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_DIO_Set_Ports_Direction_To_Output(void                  *Handle,
                                              ccrtngfc_dio_ports_t  DIO_OutputPortDirection)

   Description: Set DIO Port Direction to Output Mask

   Input:   void                         *Handle                  (handle pointer)
            ccrtngfc_dio_ports_t         DIO_OutputPortDirection  (output port direction)
                # _ccrtngfc_dio_port_mask_t ccrtngfc_dio_ports_t[CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_DIO_PORT_MASK_P0
                    # CCRTNGFC_DIO_PORT_MASK_P1
                    # CCRTNGFC_DIO_PORT_MASK_P2
                    # CCRTNGFC_DIO_PORT_MASK_P3
                    # CCRTNGFC_DIO_PORT_MASK_P4
                    # CCRTNGFC_DIO_PORT_MASK_P5
                    # CCRTNGFC_DIO_PORT_MASK_P6
                    # CCRTNGFC_DIO_PORT_MASK_P7
                    # CCRTNGFC_DIO_PORT_MASK_P8         - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P9         - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P10        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P11        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P12        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P13        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P14        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P15        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P16        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P17        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P18        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P19        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P20        - not valid for Daughter Card DIO
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_DIO_PORT_MASK_P21        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P22        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P23        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P24        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P25        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P26        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P27        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P28        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P29        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P30        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_PORT_MASK_P31        - not valid for Daughter Card DIO
                    # CCRTNGFC_DIO_ALL_PORTS_MASK       - valid for Main DIO only
                    # CCRTNGFC_DC_DIO_ALL_PORTS_MASK    - valid for Daughter Card DIO only
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ***************************************************************************/
```

2.2.62 ccrtNGFC_Disable_Pci_Interrupts()

The purpose of this call is to disable PCI interrupts. This call shouldn't be used during normal reads as calls could time out. The driver handles enabling and disabling interrupts during its normal course of operation.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Disable_Pci_Interrupts(void                          *Handle,
                                   _ccrtngfc_all_interrupts_mask interrupt_mask))

   Description: Disable interrupts being generated by the board.

   Input:   void                          *Handle         (Handle pointer)
            _ccrtngfc_all_interrupts_mask interrupt_mask  (interrupt mask)
               # CCRTNGFC_MSGDMA0_INTMASK
               # CCRTNGFC_MSGDMA1_INTMASK
               # CCRTNGFC_MSGDMA2_INTMASK
               # CCRTNGFC_MSGDMA3_INTMASK
               # CCRTNGFC_MSGDMA4_INTMASK
               # CCRTNGFC_MSGDMA5_INTMASK
               # CCRTNGFC_LDIO_MODULE_0_INTMASK
               # CCRTNGFC_LDIO_MODULE_1_INTMASK
               # CCRTNGFC_LDIO_MODULE_2_INTMASK
               # CCRTNGFC_LDIO_MODULE_3_INTMASK
               # CCRTNGFC_ADC0_FIFO_INTMASK
               # CCRTNGFC_DAC0_FIFO_INTMASK
               # CCRTNGFC_ADC1_FIFO_INTMASK
               # CCRTNGFC_DAC1_FIFO_INTMASK
               # CCRTNGFC_ALL_MSGDMA_INTMASK
               # CCRTNGFC_ALL_ANALOG_INTMASK
               # CCRTNGFC_ALL_LDIO_INTMASK
               # CCRTNGFC_ALL_INTMASK
   Output:  none
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                (device not open)
               # CCRTNGFC_LIB_IOCTL_FAILED            (driver ioctl call failed)
 ***************************************************************************/
```

2.2.63 ccrtNGFC_Enable_Pci_Interrupts()

The purpose of this call is to enable PCI interrupts. This call shouldn't be used during normal reads as calls could time out. The driver handles enabling and disabling interrupts during its normal course of operation.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Enable_Pci_Interrupts (void                          *Handle,
                                   _ccrtngfc_all_interrupts_mask interrupt_mask)

   Description: Enable interrupts being generated by the board.

   Input:   void                          *Handle         (Handle pointer)
            _ccrtngfc_all_interrupts_mask interrupt_mask  (interrupt mask)
               # CCRTNGFC_MSGDMA0_INTMASK
               # CCRTNGFC_MSGDMA1_INTMASK
               # CCRTNGFC_MSGDMA2_INTMASK
               # CCRTNGFC_MSGDMA3_INTMASK
               # CCRTNGFC_MSGDMA4_INTMASK
               # CCRTNGFC_MSGDMA5_INTMASK
               # CCRTNGFC_LDIO_MODULE_0_INTMASK
               # CCRTNGFC_LDIO_MODULE_1_INTMASK
               # CCRTNGFC_LDIO_MODULE_2_INTMASK
               # CCRTNGFC_LDIO_MODULE_3_INTMASK
               # CCRTNGFC_ADC0_FIFO_INTMASK
               # CCRTNGFC_DAC0_FIFO_INTMASK
               # CCRTNGFC_ADC1_FIFO_INTMASK
               # CCRTNGFC_DAC1_FIFO_INTMASK
               # CCRTNGFC_ALL_MSGDMA_INTMASK
               # CCRTNGFC_ALL_ANALOG_INTMASK
               # CCRTNGFC_ALL_LDIO_INTMASK
               # CCRTNGFC_ALL_INTMASK
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR      (successful)
               # CCRTNGFC_LIB_BAD_HANDLE    (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN      (device not open)
               # CCRTNGFC_LIB_IOCTL_FAILED  (driver ioctl call failed)
 ***************************************************************************/
```

2.2.64 ccrtNGFC_Fast_Memcpy()

The purpose of this call is to provide a fast mechanism to copy between hardware and memory using programmed I/O. The library performs appropriate locking while the copying is taking place. If the board provides support for double word transfers, this call will utilize it.

```
/***************************************************************************
   ccrtNGFC_Fast_Memcpy(void          *Handle,
                        volatile void  *Destination,
                        volatile void  *Source,
                        int           SizeInBytes)

   Description: Perform fast copy to/from buffer using Programmed I/O
                (WITH LOCKING)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   Input:   void          *Handle           (Handle pointer)
            volatile void *Source           (pointer to source buffer)
            int            SizeInBytes      (transfer size in bytes)
   Oupput:  volatile void *Destination      (pointer to destination buffer)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR      (successful)
               # CCRTNGFC_LIB_BAD_HANDLE    (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN      (device not open)
 ****************************************************************************/
```

2.2.65 ccrtNGFC_Fast_Memcpy_Unlocked()

The purpose of this call is to provide a fast mechanism to copy between hardware and memory using programmed I/O. The library does not perform any locking. User needs to provide external locking instead. If the board provides support for double word transfers, this call will utilize it. The *double_word_support* field in the driver information structure *ccrtngfc_driver_info_t* indicates whether the double word support is available in the hardware.

```
/****************************************************************************
   void
   ccrtNGFC_Fast_Memcpy_Unlocked(volatile void *Destination,
                                 volatile void *Source,
                                 int           SizeInBytes
                                 int           DoubleWordSupport)

   Description: Perform fast copy to/from buffer using Programmed I/O (WITHOUT LOCKING)

   Input:   volatile void *Source               (pointer to source buffer)
            int            SizeInBytes          (transfer size in bytes)
            int            DoubleWordSupport    (double word support flag)
               # CCRTNGFC_FALSE                 (h/w double word transfers not supported)
               # CCRTNGFC_TRUE                  (h/w double word transfers supported)
   Oupput:  volatile void *Destination          (pointer to destination buffer)
   Return:  none
****************************************************************************/
```

2.2.66 ccrtNGFC_Fast_Memcpy_Unlocked_FIFO()

The purpose of this call is to provide a simple mechanism to copy between hardware FIFO and memory using programmed I/O. The library does not perform any locking. User needs to provide external locking instead. If the board provides support for double word transfers, this call will utilize it. The *double_word_support* field in the driver information structure *ccrtngfc_driver_info_t* indicates whether the double word support is available in the hardware.

```
/****************************************************************************
   void
   ccrtNGFC_Fast_Memcpy_Unlocked_FIFO(volatile void *Destination,
                                      volatile void *Source,
                                      int           SizeInWords,
                                      int           PioControl,
                                      int           DoubleWordSupport)

   Description: Perform fast copy to/from FIFO buffer using Programmed I/O (WITHOUT LOCKING)

   Input:   volatile void *Source               (pointer to source buffer)
            int            SizeInWords          (transfer size in words)
            int            PioControl           (PIO Control)
               # CCRTNGFC_PIO_CONTROL_RCON      (read constant)
               # CCRTNGFC_PIO_CONTROL_WCON      (write constant)
               # CCRTNGFC_PIO_CONTROL_INCREMENT (read/write increment)
            int            DoubleWordSupport    (double word support flag)
               # CCRTNGFC_FALSE                 (h/w double word transfers not supported)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_TRUE                 (h/w double word transfers supported)
  Oupput:  volatile void *Destination       (pointer to destination buffer)
  Return:  none
 ****************************************************************************/
```

2.2.67 ccrtNGFC_Fraction_To_Hex()

This converts a fractional decimal to a hexadecimal value.

```
/****************************************************************************
   int
   ccrtNGFC_Fraction_To_Hex (double Fraction,
                             uint   *value)

   Description: Convert Fractional Decimal to Hexadecimal

   Input:       double   Fraction       (fraction to convert)
   Output:      uint     *value;        (converted hexadecimal value)
   Return:      1                       (call failed)
                0                       (good return)
 ****************************************************************************/
```

2.2.68 ccrtNGFC_Get_All_Boards_Driver_Info()

This call returns driver information for all the *ccrtngfc* cards that have been found in the system.

```
/****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_All_Boards_Driver_Info (void                           *Handle,
                                        ccrtngfc_all_boards_driver_info *all_boards_info)

   Description: Get device information from driver for all boards.

   Input:   void                           *Handle          (Handle pointer)
   Output:  ccrtngfc_driver_info_t         *all_boards_info (info struct pointer)
               char                               version[12]
               char                               built[32]
               char                               module_name[16]
               int                                board_index
               int                                table_index
               char                               board_desc[32]
               int                                bus
               int                                slot
               int                                func
               int                                vendor_id
               int                                sub_vendor_id
               int                                sub_device_id
               union {
                   u_int                          BoardInfo
                   ccrtngfc_boardinfo_t           BInfo
               }
               union {
                   u_int                          FirmwareDate
                   ccrtngfc_firmware_date_t       FmDate
               }
               union {
                   u_int                          FirmwareRevision
                   ccrtngfc_firmware_revision_t   FmRev
               }
               int                                msi_support
               int                                irqlevel
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
double                                  calibration_reference_voltage

// MsgDMA
ccrtngfc_driver_msgdma_info_t           msgdma_info

// Interrupt
ccrtngfc_driver_int_t                   interrupt

// LDIO COS Interrupt
ccrtngfc_driver_ldio_cos_int_t          ldio_cos_interrupt

int                                     Ccrtngfc_Max_Region

// Memory Region
ccrtngfc_dev_region_t                   mem_region[CCRTNGFC_MAX_REGION]

// ADC
ccrtngfc_driver_adc_info_t              adc_info

// DAC
ccrtngfc_driver_dac_info_t              dac_info

// LDIO
int                                     ldio_max_modules
ccrtngfc_driver_ldio_info_t             ldio_info[CCRTNGFC_LDIO_MAX_MODULES]

// CLOCK
ccrtngfc_driver_clock_info_t            clock_info
 u_int                                   board_serial_number;

// Chip Temperature
ccrtngfc_chip_temperature_t             fpga_chip_temperature

ccrtngfc_chip_voltages_t                fpga_chip_volts

char                                    double_word_support
char                                    FpgawbSupport

union {
    u_int                               FirmwareTime
    ccrtngfc_firmware_time_t            FmTime
}
union {
    u_int                               FirmwareFlavorCode
    ccrtngfc_firmware_option_code_t     FmOptionCode
}
u_int                                   NumberAdvancedIPCores

u_short                                 RunLevelSectorNumber
char                                    FirmwareReloadFailed
char                                    MultiFirmwareSupport

union {
    _ccrtngfc_ipcore_t                  IpCore[CCRTNGFC_MAX_IO_CORES_ORIG]
    _ccrtngfc_ipcore_t                  IpCore_Orig[CCRTNGFC_MAX_IO_CORES_ORIG]
}

union {
    u_int                               Dummy_time_t[2]
    time_t                              DriverLoadCurrentTime
}
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                u_int32_t                           FirmwareBoardSerialNumber

                u_int32_t                           MaxMsgDmaDescriptors
                ccrtngfc_msgdma_specific_t          MsgDmaSpecific[CCRTNGFC_MAX_MSGDMA_ENGINES]

                u_int32_t                           FpgawbRevision

                _ccrtngfc_ipcore_t                  IpCore[CCRTNGFC_TOTAL_NUMBER_OF_IP_CORES]

                int                                 CloningSupport

                u_short                             MaximumLinkWidth
                u_short                             NegotiatedLinkWidth
   Return:  _ccrtngfc_lib_error_number_t
                # CCRTNGFC_LIB_NO_ERROR      (successful)
                # CCRTNGFC_LIB_BAD_HANDLE    (no/bad handler supplied)
                # CCRTNGFC_LIB_NOT_OPEN      (device not open)
                # CCRTNGFC_LIB_INVALID_ARG   (invalid argument)
                # CCRTNGFC_LIB_IOCTL_FAILED  (driver ioctl call failed)
 ************************************************************************/
```

2.2.69 ccrtNGFC_Get_Board_CSR()

This call returns information from the board status register.

```
/************************************************************************
  _ccrtngfc_lib_error_number_t
  ccrtNGFC_Get_Board_CSR (void                    *Handle,
                          ccrtngfc_board_csr_t    *bcsr)

   Description: Get Board Control and Status information

   Input:   void                                *Handle    (Handle pointer)
   Output:  ccrtngfc_board_csr_t                *bcsr      (pointer to board csr)
               _ccrtngfc_bcsr_identify_board_t  identify_board
                  # CCRTNGFC_BCSR_IDENTIFY_BOARD_DISABLE
                  # CCRTNGFC_BCSR_IDENTIFY_BOARD_ENABLE
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                (device not open)
               # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
 ************************************************************************/
```

2.2.70 ccrtNGFC_Get_Board_Info()

This call returns the board id, the board type and the firmware revision level for the selected board. This board id is *0x9277* and board type is *0x1* or *0x9278* with a board type of *0x2*.

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Board_Info (void                    *Handle,
                            ccrtngfc_board_info_t  *binfo)
   Description: Get Board Information

   Input:   void                    *Handle        (Handle pointer)
   Output:  ccrtngfc_board_info_t   *binfo         (pointer to board info)
               int                                 vendor_id
               int                                 sub_vendor_id
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
               int                                 sub_device_id
               ccrtngfc_boardinfo_t                BInfo
                  u_char  Function
                  u_char  Type
                  u_short Id
               ccrtngfc_firmware_date_t            FmDate
                  u_short Year
                  u_char  Day
                  u_char  Month
               ccrtngfc_firmware_revision_t        FmRev
                  u_short Minor
                  u_short Major
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN             (device not open)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION      (local region not present)
 ***************************************************************************/
```

2.2.71 ccrtNGFC_Get_Driver_Error()

This call returns the last error generated by the driver.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Driver_Error (void                    *Handle,
                              ccrtngfc_user_error_t   *ret_err)

   Description: Get the last error generated by the driver.

   Input:   void                  *Handle             (Handle pointer)
   Output:  ccrtngfc_user_error_t *ret_err            (error struct pointer)
               uint error;                            (error number)
               char name[CCRTNGFC_ERROR_NAME_SIZE]    (error name used in driver)
               char desc[CCRTNGFC_ERROR_DESC_SIZE]    (error description)
               uint error_line_number                 (error line number)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                (device not open)
               # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
               # CCRTNGFC_LIB_IOCTL_FAILED            (driver ioctl call failed)
 ***************************************************************************/

#define CCRTNGFC_ERROR_NAME_SIZE        64
#define CCRTNGFC_ERROR_DESC_SIZE        128
#define CCRTNGFC_DRIVER_ERROR_FUNC_SIZE 200

typedef struct _ccrtngfc_user_error_t
{
    uint error;                             /* error number */
    char name[CCRTNGFC_ERROR_NAME_SIZE];    /* error name used in driver */
    char desc[CCRTNGFC_ERROR_DESC_SIZE];    /* error description */
    uint error_line_number;                 /* error line number */
    char error_function[CCRTNGFC_DRIVER_ERROR_FUNC_SIZE];
    int  RESERVED[100];
} ccrtngfc_user_error_t;

enum
{
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
    CCRTNGFC_SUCCESS = 0,
    CCRTNGFC_INVALID_PARAMETER,
    CCRTNGFC_OPERATION_CANCELLED,
    CCRTNGFC_RESOURCE_ALLOCATION_ERROR,
    CCRTNGFC_INVALID_REQUEST,
    CCRTNGFC_FAULT_ERROR,
    CCRTNGFC_BUSY,
    CCRTNGFC_ADDRESS_IN_USE,
    CCRTNGFC_USER_INTERRUPT_TIMEOUT,
    CCRTNGFC_DATA_UNDERFLOW,
    CCRTNGFC_DATA_OVERFLOW,:
    CCRTNGFC_IO_FAILURE,
    CCRTNGFC_OPERATION_NOT_SUPPORTED,
    CCRTNGFC_ADC_FIFO_THRESHOLD_TIMEOUT,
    CCRTNGFC_DAC_FIFO_THRESHOLD_TIMEOUT,
    CCRTNGFC_INTERRUPT_HANDLER_NOT_ENABLED,
    CCRTNGFC_FIRMWARE_RELOAD_FAILED,
    CCRTNGFC_DEVICE_AUTHORIZATION_FAILED,
    CCRTNGFC_DAUGHTER_CARD_NOT_PRESENT,
    CCRTNGFC_DAUGHTER_CARD_BUSY,
    CCRTNGFC_BOARD_NOT_OPENED_FIRST,
};
```

2.2.72 ccrtNGFC_Get_Driver_Info()

This call returns internal information that is maintained by the driver.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Driver_Info (void                      *Handle,
                             ccrtngfc_driver_info_t    *info)

   Description: Get device information from driver.

   Input:   void                            *Handle     (Handle pointer)
   Output:  ccrtngfc_driver_info_t          *all_boards_info (info struct pointer)
               char                                 version[12]
               char                                 built[32]
               char                                 module_name[16]
               int                                  board_index
               int                                  table_index
               char                                 board_desc[32]
               int                                  bus
               int                                  slot
               int                                  func
               int                                  vendor_id
               int                                  sub_vendor_id
               int                                  sub_device_id
               union {
                   u_int                            BoardInfo
                   ccrtngfc_boardinfo_t             BInfo
               }
               union {
                   u_int                            FirmwareDate
                   ccrtngfc_firmware_date_t         FmDate
               }
               union {
                   u_int                            FirmwareRevision
                   ccrtngfc_firmware_revision_t     FmRev
               }
               int                                  msi_support
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
int                                 irqlevel
double                              calibration_reference_voltage

// MsgDMA
ccrtngfc_driver_msgdma_info_t       msgdma_info

// Interrupt
ccrtngfc_driver_int_t               interrupt

// LDIO COS Interrupt
ccrtngfc_driver_ldio_cos_int_t      ldio_cos_interrupt

int                                 Ccrtngfc_Max_Region

// Memory Region
ccrtngfc_dev_region_t               mem_region[CCRTNGFC_MAX_REGION]

// ADC
ccrtngfc_driver_adc_info_t          adc_info

// DAC
ccrtngfc_driver_dac_info_t          dac_info

// LDIO
int                                 ldio_max_modules
ccrtngfc_driver_ldio_info_t         ldio_info[CCRTNGFC_LDIO_MAX_MODULES]

// CLOCK
ccrtngfc_driver_clock_info_t        clock_info
 u_int                               board_serial_number;

// Chip Temperature
ccrtngfc_chip_temperature_t         fpga_chip_temperature

ccrtngfc_chip_voltages_t            fpga_chip_volts

char                                double_word_support
char                                FpgawbSupport

union {
    u_int                           FirmwareTime
    ccrtngfc_firmware_time_t        FmTime
}
union {
    u_int                           FirmwareFlavorCode
    ccrtngfc_firmware_option_code_t FmOptionCode
}
u_int                               NumberAdvancedIPCores

u_short                             RunLevelSectorNumber
char                                FirmwareReloadFailed
char                                MultiFirmwareSupport

union {
    _ccrtngfc_ipcore_t              IpCore[CCRTNGFC_MAX_IO_CORES_ORIG]
    _ccrtngfc_ipcore_t              IpCore_Orig[CCRTNGFC_MAX_IO_CORES_ORIG]
}

union {
    u_int                           Dummy_time_t[2]
    time_t                          DriverLoadCurrentTime
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                }

                u_int32_t                           FirmwareBoardSerialNumber

                u_int32_t                           MaxMsgDmaDescriptors
                ccrtngfc_msgdma_specific_t          MsgDmaSpecific[CCRTNGFC_MAX_MSGDMA_ENGINES]

                u_int32_t                           FpgawbRevision

                _ccrtngfc_ipcore_t                  IpCore[CCRTNGFC_TOTAL_NUMBER_OF_IP_CORES]

                int                                 CloningSupport

                u_short                             MaximumLinkWidth
                u_short                             NegotiatedLinkWidth
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR      (successful)
               # CCRTNGFC_LIB_BAD_HANDLE    (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN      (device not open)
               # CCRTNGFC_LIB_INVALID_ARG   (invalid argument)
               # CCRTNGFC_LIB_IOCTL_FAILED  (driver ioctl call failed)
*************************************************************************/
```

2.2.73 ccrtNGFC_Get_Interrupt_Status()

This call returns the current status of the various interrupts.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Interrupt_Status (void                *Handle,
                                  ccrtngfc_interrupt_t *intr)

   Description: Get Interrupt Status information

   Input:   void                    *Handle       (handle pointer)
   Output:  ccrtngfc_interrupt_t    *intr         (pointer to interrupt status)
               _ccrtngfc_intsta_ldio_cos_t ldio_cos_module_int[CCRTNGFC_LDIO_MAX_MODULES];
                  # CCRTNGFC_INT_LDIO_COS_NONE
                  # CCRTNGFC_INT_LDIO_COS_OCCURRED
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR            (successful)
               # CCRTNGFC_LIB_BAD_HANDLE          (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN            (device not open)
               # CCRTNGFC_LIB_NO_LOCAL_REGION     (local region error)
               # CCRTNGFC_LIB_INVALID_ARG         (invalid argument)
 *************************************************************************/
```

2.2.74 ccrtNGFC_Get_Interrupt_Timeout_Seconds()

This call returns the read time out maintained by the driver. It is the time that the read call will wait before it times out. The call could time out because a DMA fails to complete. The device should have been opened in the block mode (*O_NONBLOCK* not set) for reads to wait for the operation to complete.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Interrupt_Timeout_Seconds (void    *Handle,
                                           int     *int_timeout_secs)

   Description: Get Interrupt Timeout Seconds

   Input:   void            *Handle              (Handle pointer)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   Output:  int             *int_timeout_secs    (pointer to int tout secs)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_IOCTL_FAILED       (ioctl error)
 ****************************************************************************/
```

2.2.75 ccrtNGFC_Get_Lib_Error()

This call provides detailed information about the last library error that was maintained by the API. The call itself can fail with a return code if an invalid handle is provided, the device is not open or device authorization has failed. If the call succeeds *CCRTNGFC_LIB_NO_ERROR*, the last library error information is supplied to the user in the *ccrtngfc_lib_error_t* structure.

```
/****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Lib_Error (void                    *Handle,
                           ccrtngfc_lib_error_t    *lib_error)

   Description: Get last error generated by the library.

   Input:   void                *Handle                 (Handle pointer)
   Output:  ccrtngfc_lib_error_t *lib_error             (error struct pointer)
               -- uint error                            (last library error number)
               -- char name[CCRTNGFC_LIB_ERROR_NAME_SIZE] (last library error name)
               -- char desc[CCRTNGFC_LIB_ERROR_DESC_SIZE] (last library error description)
               -- int  line_number                      (last library error line number in lib)
               -- char function[CCRTNGFC_LIB_ERROR_FUNC_SIZE]
                                                        (library function in error)
               -- ccrtngfc_lib_error_backtrace_t BT[CCRTNGFC_BACK_TRACE_DEPTH]
                                                        (backtrace of errors)
                  -- int  line_number                   (line number in library)
                  -- char function[CCRTNGFC_LIB_ERROR_FUNC_SIZE]
                                                        (library function)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                 (successful)
               # CCRTNGFC_LIB_BAD_HANDLE               (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                 (device not open)
               # CCRTNGFC_LIB_AUTHORIZATION_FAILURE    (device authorization failure)
 ****************************************************************************/

typedef struct
{
    int  line_number;                               /* line number in library */
    char function[CCRTNGFC_LIB_ERROR_FUNC_SIZE]; /* library function */
    uint RESERVED_INT[256];                         /* Spare registers for future use */
} ccrtngfc_lib_error_backtrace_t;
typedef struct
{
    uint error;                                     /* last library error number */
    char name[CCRTNGFC_LIB_ERROR_NAME_SIZE];     /* last library error name */
    char desc[CCRTNGFC_LIB_ERROR_DESC_SIZE];     /* last libarary error description */
    int  line_number;                               /* last library  error line number in lib */
    char function[CCRTNGFC_LIB_ERROR_FUNC_SIZE]; /* library function in error */
    uint RESERVED_INT[256];                         /* Spare registers for future use */

    ccrtngfc_lib_error_backtrace_t BT[CCRTNGFC_BACK_TRACE_DEPTH];
                                                    /* backtrace of errors */
} ccrtngfc_lib_error_t;
```

Possible library errors:

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
CCRTNGFC_LIB_NO_ERROR                       =  0,  /* Successful */
CCRTNGFC_LIB_INVALID_ARG                    = -1,  /* Invalid argument */
CCRTNGFC_LIB_ALREADY_OPEN                   = -2,  /* Already open */
CCRTNGFC_LIB_OPEN_FAILED                    = -3,  /* Open failed */
CCRTNGFC_LIB_BAD_HANDLE                     = -4,  /* Bad handle */
CCRTNGFC_LIB_NOT_OPEN                       = -5,  /* Device not opened */
CCRTNGFC_LIB_MMAP_SELECT_FAILED             = -6,  /* Mmap selection failed */
CCRTNGFC_LIB_MMAP_FAILED                    = -7,  /* Mmap failed */
CCRTNGFC_LIB_MUNMAP_FAILED                  = -8,  /* Munmap failed */
CCRTNGFC_LIB_NOT_MAPPED                     = -9,  /* Not mapped */
CCRTNGFC_LIB_ALREADY_MAPPED                 = -10, /* Device already mapped */
CCRTNGFC_LIB_IOCTL_FAILED                   = -11, /* Device IOCTL failed */
CCRTNGFC_LIB_IO_ERROR                       = -12, /* I/O error */
CCRTNGFC_LIB_INTERNAL_ERROR                 = -13, /* Internal library error */
CCRTNGFC_LIB_NOT_IMPLEMENTED                = -14, /* Call not implemented */
CCRTNGFC_LIB_LOCK_FAILED                    = -15, /* Failed to get lib lock */
CCRTNGFC_LIB_NO_LOCAL_REGION                = -16, /* Local region not present */
CCRTNGFC_LIB_NO_CONFIG_REGION               = -17, /* Config region not present */
CCRTNGFC_LIB_NO_SOLUTION_FOUND              = -18, /* No solution found */
CCRTNGFC_LIB_NO_RESOURCE                    = -19, /* Resource not available */
CCRTNGFC_LIB_CANNOT_OPEN_FILE               = -20, /* Cannot open file */
CCRTNGFC_LIB_MSGDMA_BUSY                    = -21, /* MSGDMA busy */
CCRTNGFC_LIB_AVALON_TRANSLATION_TABLE       = -22, /* Avalon translation table error */
CCRTNGFC_LIB_ADDRESS_RANGE_ERROR            = -23, /* Physical DMA address exceeds memory size */
CCRTNGFC_LIB_NO_SPACE_IN_TABLE              = -24, /* No space available to allocate any more
                                                      physical memory */
CCRTNGFC_LIB_CANNOT_ALLOCATE_PHYS_MEM       = -25, /* Cannot allocate physical memory */
CCRTNGFC_LIBMSG_MSGDMA_FAILED               = -26, /* MSGDMA failed */
CCRTNGFC_LIB_THREAD_CREATE_FAILED           = -27, /* Thread Creation failed */
CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE            = -28, /* Clock Generator is not active */
CCRTNGFC_LIB_CANNOT_COMPUTE_OUTPUT_FREQ     = -29, /* Cannot compute output frequency */
CCRTNGFC_LIB_N_DIVIDERS_EXCEEDED            = -30, /* Number of N-Dividers exceeded */
CCRTNGFC_LIB_CLOCK_GENERATION_FAILED        = -31, /* Clock generation failed */
CCRTNGFC_LIB_CALIBRATION_RANGE_ERROR        = -32, /* Calibration voltage out of range */
CCRTNGFC_LIB_BAD_DATA_IN_CAL_FILE           = -33, /* Bad data in calibration file */
CCRTNGFC_LIB_VOLTAGE_NOT_IN_RANGE           = -34, /* Voltage not in range */
CCRTNGFC_LIB_ADC_IS_NOT_ACTIVE              = -35, /* ADC is not active */
CCRTNGFC_LIB_DAC_IS_NOT_ACTIVE              = -36, /* DAC is not active */
CCRTNGFC_LIB_ADC_INCORRECTLY_CONFIGURED     = -37, /* ADC incorrectly configured for DAC readback
                                                       */
CCRTNGFC_LIB_LIO_TEST_MODE_SETTING_ERROR    = -39, /* Only one output port must be set in LIO test
                                                      mode */
CCRTNGFC_LIB_DAC_FIFO_UNDERFLOW             = -40, /* DAC FIFO underflow */
CCRTNGFC_LIB_DAC_FIFO_OVERFLOW              = -41, /* DAC FIFO overflow */
CCRTNGFC_LIB_DAC_IS_BUSY                    = -42, /* DAC is busy */
CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE             = -43, /* LDIO is not active */
CCRTNGFC_LIB_SERIAL_PROM_FAILURE            = -44, /* Serial PROM failure - malfunction or not
                                                      present */
CCRTNGFC_LIB_SERIAL_PROM_BUSY               = -45, /* Serial PROM busy */
CCRTNGFC_LIB_SERIAL_PROM_WRITE_PROTECTED    = -46, /* Serial PROM is write protected */
CCRTNGFC_LIB_AUTHORIZATION_FAILURE          = -47, /* Failure to authorize opening of device */
CCRTNGFC_LIB_INTHDLR_CREATE_FAILURE         = -48, /* Interrupt handler creation failure */
CCRTNGFC_LIB_INTHDLR_ALREADY_RUNNING        = -49, /* Interrupt handler already running */
CCRTNGFC_LIB_IPCORE_COS_IS_NOT_ACTIVE       = -50, /* IP Core COS is Not active */
CCRTNGFC_LIB_NO_FREE_DESCRIPTORS_AVAILABLE = -51, /* No Free Descriptors Available */
CCRTNGFC_LIB_ERROR_IN_DESCRIPTOR_LIST       = -52, /* Error in Descriptor List */
CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED           = -53, /* Modular Scatter-Gather DMA Not Supported */
CCRTNGFC_LIB_MSGDMA_READS_NOT_ALLOWED_FOR_SELECTED_ADDRESS
                                            = -54, /* MSG DMA Reads Not Allowed for Selected
                                                      Address */
CCRTNGFC_LIB_NOT_OWNER_OF_MSGDMA            = -55, /* Not Owner of Modular Scatter-Gather DMA */
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   CCRTNGFC_LIB_MSGDMA_IN_USE                  = -56, /* Modular Scatter-Gather DMA In Use */
   CCRTNGFC_LIB_MSGDMA_NOT_SETUP               = -57, /* Modular Scatter-Gather DMA not setup */
   CCRTNGFC_LIB_MSGDMA_FAILED                  = -58, /* Modular Scatter-Gather DMA failed */
   CCRTNGFC_LIB_MSGDMA_ACCESS_NOT_ALLOWED_FOR_SELECTED_ADDRESS
                                               = -59, /* MSGDMA access not allowed for selected
                                                         address */
   CCRTNGFC_LIB_REGION_ADDRESSING_NOT_SUPPORTED
                                               = -60, /* Region addressing not supported by driver */
   CCRTNGFC_LIB_CLONING_NOT_SUPPORTED          = -61, /* Cloning not supported by the card */
   CCRTNGFC_LIB_SERIAL_PROM_NOT_PRESENT        = -62, /* Serial PROM not present */
   CCRTNGFC_LIB_DC_EEPROM_FAILURE              = -63, /* Daughter Card EEPROM Failure */
   CCRTNGFC_LIB_DC_EEPROM_BUSY                 = -64, /* Daughter Card EEPROM Busy */
   CCRTNGFC_LIB_MODULE_NOT_OPEN                = -65, /* Module needs to be opened first */
   CCRTNGFC_LIB_MODULE_ALREADY_OPEN            = -66, /* Module Already Open */
   CCRTNGFC_LIB_MODULE_NOT_PRESENT             = -67, /* Module Not Present */
   CCRTNGFC_LIB_INVALID_MODULE                 = -68, /* Invalid Module */
   CCRTNGFC_LIB_DC_BAD_HANDLE                  = -69, /* Bad daughter card handle supplied */
   CCRTNGFC_LIB_INSTEAD_OF_DC_HANDLE           = -70, /* Library instead of daughter card handle
                                                         supplied */
   CCRTNGFC_LIB_MODULE_OPEN_FAILED             = -71, /* Module Open Failed */
   CCRTNGFC_LIB_DATA_WIDTH_NOT_MULTIPLE_OR_ALIGNED
                                               = -72, /* Data Width Not Multiple or Aligned */
   CCRTNGFC_LIB_FPGA_PM_FAILURE                = -73, /* FPGA Power Module Failure */
   CCRTNGFC_LIB_FPGA_PM_BUSY                   = -74, /* FPGA Power Module Busy */
   CCRTNGFC_LIB_NO_DAUGHTER_CARD_PRESENT       = -75, /* No Daughter Card Present */
   CCRTNGFC_LIB_PLL_SYNC_NOT_SUPPORTED         = -76, /* PLL Synchronization not supported */
```

2.2.76 ccrtNGFC_Get_Lib_Error_Description()

This call returns the library error name and description for the supplied error number.

```
/*****************************************************************************
   void
   ccrtNGFC_Get_Lib_Error_Description (int                                ErrorNumber,
                                       ccrtngfc_lib_error_description_t   *lib_error_desc)

   Description: Get Error Description of supplied error number.

   Input:   int                                ErrorNumber     (Library error number)
   Output:  ccrtngfc_lib_error_description_t   *lib_error_desc (error description struct pointer)
               -- int  found
               -- char name[CCRTNGFC_LIB_ERROR_NAME_SIZE] (last library error name)
               -- char desc[CCRTNGFC_LIB_ERROR_DESC_SIZE] (last library error description)
   Return:  none
 *****************************************************************************/
```

2.2.77 ccrtNGFC_Get_Library_Info()

This call returns useful library information to the user.

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Library_Info (void                     *Handle,
                              ccrtngfc_library_info_t  *info)

   Description: Get library information

   Input:   void                                   *Handle     (Handle pointer)
   Output:  ccrtngfc_library_info_t                *info       (info struct pointer)
               int                                 fp
               ccrtngfc_local_ctrl_data_t          *local_ptr
                  -- structure in ccrtngfc_user.h
               void                                *munmap_local_ptr
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                int                                 local_mmap_size
                ccrtngfc_config_local_data_t        *config_ptr
                   -- structure in ccrtngfc_user.h
                void                                *munmap_config_ptr
                int                                 config_mmap_size
                ccrtngfc_user_phys_mem_t    PhysMem[CCRTNGFC_MAX_AVALON_NUM_TRANS_TBL_ENTRIES]
                   -- structure in ccrtngfc_user.h
                ccrtngfc_driver_library_common_t    *driver_lib_ptr
                   -- structure in ccrtngfc_user.h
                void                                *munmap_driver_lib_ptr
                int                                 driver_lib_mmap_size
                void                                *FpgaWbLib;
                _ccrtngfc_ipcore_t          IpCoreSpecific[CCRTNGFC_TOTAL_NUMBER_OF_IP_CORES];
                uint                                UserPid;
                void                                *IpCore_0_ptr
                void                                *IpCore_1_ptr
                void                                *IpCore_2_ptr
                void                                *IpCore_3_ptr
                void                                *IpCore_4_ptr
                void                                *IpCore_5_ptr
                void                                *IpCore_6_ptr
                void                                *IpCore_7_ptr
                void                                *IpCore_8_ptr
                void                                *IpCore_9_ptr
                void                                *IpCore_10_ptr
                .
                .
                .
                void                                *IpCore_140_ptr
                void                                *IpCore_141_ptr
                void                                *IpCore_142_ptr
                void                                *IpCore_143_ptr
                void                                *IpCore_144_ptr
                void                                *IpCore_145_ptr
                void                                *IpCore_146_ptr
                void                                *IpCore_147_ptr
                u_short     IpCore_MaxChannels_In_License[CCRTNGFC_TOTAL_NUMBER_OF_IP_CORES];

   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN             (device not open)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
*************************************************************************/
```

2.2.78 ccrtNGFC_Get_Mapped_Config_Ptr()

If the user wishes to bypass the API and communicate directly with the board configuration registers, then they can use this call to acquire a pointer to these registers. Please note that any type of access (read or write) by bypassing the API could compromise the API and results could be unpredictable. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the hardware programming registers before attempting to access these registers. For information on the registers, refer to the *ccrtngfc_user.h* include file that is supplied with the driver.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Mapped_Config_Ptr (void                            *Handle,
                                   ccrtngfc_config_local_data_t    **config_ptr)

   Description: Get mapped configuration pointer.
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   Input:   void                            *Handle         (Handle pointer)
   Output:  ccrtngfc_config_local_data_t    **config_ptr    (config struct ptr)
               -- structure in ccrtngfc_user.h
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR               (successful)
               # CCRTNGFC_LIB_BAD_HANDLE             (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN               (device not open)
               # CCRTNGFC_LIB_INVALID_ARG            (invalid argument)
               # CCRTNGFC_LIB_NO_CONFIG_REGION       (config region not present)
*************************************************************************/
```

2.2.79 ccrtNGFC_Get_Mapped_Driver_Library_Ptr()

The driver and library share a common structure. This call returns a pointer to the shared driver/library structure.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Mapped_Driver_Library_Ptr (void                *Handle,
                           ccrtngfc_driver_library_common_t    **driver_lib_ptr)

   Description: Get mapped Driver/Library structure pointer.

   Input:   void                              *Handle          (Handle pointer)
   Output:  ccrtngfc_driver_library_common_t  **driver_lib_ptr  (driver_lib struct ptr)
               -- structure in ccrtngfc_user.h
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR               (successful)
               # CCRTNGFC_LIB_BAD_HANDLE             (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN               (device not open)
               # CCRTNGFC_LIB_INVALID_ARG            (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION        (local region not present)
 *************************************************************************/
```

2.2.80 ccrtNGFC_Get_Mapped_Local_Ptr()

If the user wishes to bypass the API and communicate directly with the board control and data registers, then they can use this call to acquire a pointer to these registers. Please note that any type of access (read or write) by bypassing the API could compromise the API and results could be unpredictable. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the hardware programming registers before attempting to access these registers. For information on the registers, refer to the *ccrtngfc_user.h* include file that is supplied with the driver.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Mapped_Local_Ptr (void                       *Handle,
                                  ccrtngfc_local_ctrl_data_t   **local_ptr)

   Description: Get mapped local pointer.

   Input:   void                         *Handle     (Handle pointer)
   Output:  ccrtngfc_local_ctrl_data_t  **local_ptr (local struct ptr)
               -- structure in ccrtngfc_user.h
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR              (successful)
               # CCRTNGFC_LIB_BAD_HANDLE            (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN              (device not open)
               # CCRTNGFC_LIB_INVALID_ARG           (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION       (local region not present)
 *************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.81 ccrtNGFC_Get_Open_File_Descriptor()

When the library *ccrtNGFC_Open()* call is successfully invoked, the board is opened using the system call *open(2)*. The file descriptor associated with this board is returned to the user with this call. This call allows advanced users to bypass the library and communicate directly with the driver with calls like *read(2), ioctl(2),* etc. Normally, this is not recommended as internal checking and locking is bypassed and the library calls can no longer maintain integrity of the functions. This is only provided for advanced users who want more control and are aware of the implications.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Open_File_Descriptor (void *Handle,
                                      int  *fd)

   Description: Get Open File Descriptor

   Input:   void                  *Handle  (Handle pointer)
   Output:  int                   *fd      (open file descriptor)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR      (successful)
               # CCRTNGFC_LIB_BAD_HANDLE    (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN      (device not open)
               # CCRTNGFC_LIB_INVALID_ARG   (invalid argument)
 *************************************************************************/
```

2.2.82 ccrtNGFC_Get_Physical_Memory()

This call returns to the user the physical memory pointer and size that was previously allocated by the *ccrtNGFC_Mmap_Physical_Memory()* call. The physical memory is allocated by the user when they wish to perform their own DMA and bypass the API. If user specified a mmaped user memory pointer, search for it, otherwise, simply return the contents of the physical memory list specified by a valid entry_num_in_tran_table. Once again, this call is only useful for advanced users.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Physical_Memory (void                      *Handle,
                                 ccrtngfc_user_phys_mem_t  *phys_mem)

   Description: Get previously mmapped() physical memory address and size

   Input:   void                     *Handle                (Handle pointer)
            ccrtngfc_user_phys_mem_t *phys_mem              (mem struct pointer)
               void                  *mmaped_user_mem_ptr   (mmaped user virtual memory)
               uint                  entry_num_in_tran_table (entry number in translation table)
   Output:  ccrtngfc_user_phys_mem_t *phys_mem              (mem struct pointer)
               uint                     user_pid
               void                     *phys_mem_ptr
               void                     *driver_virt_mem_ptr
               void                     *mmaped_user_mem_ptr
               uint                     phys_mem_size
               uint                     phys_mem_size_freed
               uint                     entry_num_in_tran_table
               uint                     num_of_entries_used
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR               (successful)
               # CCRTNGFC_LIB_BAD_HANDLE             (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN               (device not open)
               # CCRTNGFC_LIB_INVALID_ARG            (invalid argument)
               # CCRTNGFC_LIB_IOCTL_FAILED           (driver ioctl call failed)
 *************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.83 ccrtNGFC_Get_PowerModule_Info()

Get useful Power Module Information.

```
/*****************************************************************************
    ccrtNGFC_Get_PowerModule_Info()

    Description: Get Power Module Information

    Input:  void                            *Handle         (Handle pointer)
            ccrtngfc_power_module_info_t    *PM_Info        (power module info)
                _ccrtngfc_fpga_pm_command_t          Command;               // input
                    # CCRTNGFC_PM_CMD_INPUT_SUPPLY_VOLTAGE
                    # CCRTNGFC_PM_CMD_OUTPUT_VOLTAGE
                    # CCRTNGFC_PM_CMD_OUTPUT_CURRENT
                    # CCRTNGFC_PM_CMD_OUTPUT_TEMPERATURE
                    # CCRTNGFC_PM_CMD_DIE_TEMPERATURE
                    # CCRTNGFC_PM_CMD_PWM_FREQUENCY
                    # CCRTNGFC_PM_CMD_OUTPUT_POWER
                    # CCRTNGFC_PM_CMD_PEAK_OUTPUT_CURRENT
                _ccrtngfc_fpga_pm_module_select_t    ModuleSelect;          // input
                    # CCRTNGFC_FPGA_PM_MODULE_0
                    # CCRTNGFC_FPGA_PM_MODULE_1
                _ccrtngfc_fpga_pm_xfer_size_t        XferSize;              // input
                # CCRTNGFC_FPGA_PM_WORD_TRANSFER
                # CCRTNGFC_FPGA_PM_BYTE_TRANSFER
    Output: ccrtngfc_power_module_info_t    *PM_Info        (power module info)
                uint                                 AlertStatus;           // output
                uint                                 RawValue;              // output
                double                               FormattedValue;        // output
    Return: _ccrtngfc_lib_error_number_t
                # CCRTNGFC_LIB_NO_ERROR                  (successful)
                # CCRTNGFC_LIB_INVALID_ARG               (invalid argument)
                # CCRTNGFC_LIB_BAD_HANDLE                (no/bad handler supplied)
                # CCRTNGFC_LIB_NOT_OPEN                  (device not open)
                # CCRTNGFC_LIB_NO_LOCAL_REGION           (local region not present)
                # CCRTNGFC_LIB_FPGA_PM_BUSY              (power module busy)
                # CCRTNGFC_LIB_FPGA_PM_FAILURE           (power module failure)
 *****************************************************************************/
```

2.2.84 ccrtNGFC_Get_RunCount_UserProcess()

This call returns to the user a count of the number of times the User Process has entered. *(This is an experimental API for debugging and testing).*

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_RunCount_UserProcess(void                   *UFuncHandle,
                                     unsigned int long long *RunCount)

   Description: Get run count in user process

   Input:   void                       *UFuncHandle (UF Handle pointer))
   Output:  unsigned int long long     *RunCount    (pointer to run count)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR              (successful)
               # CCRTNGFC_LIB_BAD_HANDLE            (no/bad handler supplied)
 *****************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.85 ccrtNGFC_Get_Value()

This call allows the user to read the board registers. The actual data returned will depend on the command register information that is requested. Refer to the hardware manual for more information on what is being returned. Most commands return a pointer to an unsigned integer.

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Get_Value (void                *Handle,
                       CCRTNGFC_CONTROL    cmd,
                       void                *value)

   Description: Return the value of the specified board register.

   Input:   void                *Handle         (Handle pointer)
            CCRTNGFC_CONTROL    cmd             (register definition)
               -- structure in ccrtngfc_lib.h
   Output:  void                *value;         (pointer to value)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN          (device not open)
               # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
 *****************************************************************************/
```

2.2.86 ccrtNGFC_Hex_To_Fraction()

This call converts a hexadecimal value to a fractional decimal.

```
/*****************************************************************************
   double
   ccrtNGFC_Hex_To_Fraction (uint value)

   Description: Convert Hexadecimal to Fractional Decimal

   Input:       uint     value                 (hexadecimal to convert)
   Output:      none
   Return:      double   Fraction              (converted fractional value)
 *****************************************************************************/
```

2.2.87 ccrtNGFC_Identify_Board()

This call is useful in identifying a physical board via software control. It causes the front LED to either blink or turn off. Users can also specify the number of seconds they wish to blink the LED.

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Identify_Board (void                   *Handle,
                            _ccrtngfc_identify_t  Identify)

   Description: Identify the board by setting the front LED

   Input:   void                 *Handle              (Handle pointer)
            _ccrtngfc_identify_t Identify             (Identify board settings)
               # CCRTNGFC_IDENTIFY_OFF
               # CCRTNGFC_IDENTIFY_ON
               # Number of seconds to blink
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR               (successful)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
            # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
            # CCRTNGFC_LIB_NOT_OPEN                (device not open)
            # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
 ***************************************************************************/
```

2.2.88 ccrtNGFC_Initialize_Board()

This call initializes the driver structures to a default state and then resets the hardware.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Initialize_Board (void *Handle)

   Description: Initialize the board.

   Input:   void            *Handle             (Handle pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
            # CCRTNGFC_LIB_NO_ERROR          (successful)
            # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
            # CCRTNGFC_LIB_NOT_OPEN          (device not open)
            # CCRTNGFC_LIB_IOCTL_FAILED      (driver ioctl call failed)
            # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
 ***************************************************************************/
```

2.2.89 ccrtNGFC_IpCore_Get_Info()

This call returns information of all the IP Core modules available.

This call also returns to the user a memory mapped pointer address that the user can use to directly access the IP Core and bypass the driver and API. This type of access to the hardware should only be performed by Advanced users who are extremely familiar with both the hardware and internals of the core, otherwise, the system operation could be compromised. Note that the IpCoreCodes below can be renamed from their default names to the new names as and when new Ip Codes are implemented.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_IpCore_Get_Info (void                      *Handle,
                             ccrtngfc_ipcore_info_t    *ip_info)

   Description: Get IP Core Information

   Input:   void                                      *Handle  (Handle pointer)
   Output:  ccrtngfc_ipcore_info_t                    *ip_info (pointer to Ip Core Struct)
            u_int32_t                  NumberAdvancedIPCores;
            _ccrtngfc_ipcore_info_t    IpInfo[CCRTNGFC_TOTAL_NUMBER_OF_IP_CORES]
                _ccrtngfc_ipcore_t IpCore;
                    u_int32_t   IpCoreCode
                       # CCRTNGFC_IPCODE_0
                       # CCRTNGFC_IPCODE_1
                       # CCRTNGFC_IPCODE_2
                       # CCRTNGFC_IPCODE_3
                       # CCRTNGFC_IPCODE_4
                       # CCRTNGFC_IPCODE_5
                       # CCRTNGFC_IPCODE_6
                       # CCRTNGFC_IPCODE_7
                       # CCRTNGFC_IPCODE_8
                       # CCRTNGFC_IPCODE_9
                       .
                       .
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                        .
                        # CCRTNGFC_IPCODE_140
                        # CCRTNGFC_IPCODE_141
                        # CCRTNGFC_IPCODE_142
                        # CCRTNGFC_IPCODE_143
                        # CCRTNGFC_IPCODE_144
                        # CCRTNGFC_IPCODE_145
                        # CCRTNGFC_IPCODE_146
                        # CCRTNGFC_IPCODE_147
                      union {
                          u_int32_t                   IpCoreRevision
                          ccrtngfc_ipcore_revision_t IpCRev
                      }
                      u_int32_t   IpCoreOffset
                      u_int32_t   IpCoreInformation
                 void       *IpCoreMappedPtr
                 char        IpCoreName[CCRTNGFC_IPCORE_NAME_SIZE]
                 char        IpCoreDescription[CCRTNGFC_IPCORE_DESC_SIZE]
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN             (device not open)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION      (local region not present)
    ************************************************************************/
```

2.2.90 ccrtNGFC_IpCore_Get_Mapped_Ptr()

This call returns to the user a memory mapped pointer address that the user can use to directly access the IP Core and bypass the driver and API. This type of access to the hardware should only be performed by Advanced users who are extremely familiar with both the hardware and internals of the core, otherwise, the system operation could be compromised. Note that the IpCoreCodes below can be renamed from their default names to the new names as and when new Ip Codes are implemented.

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_IpCore_Get_Mapped_Ptr (void       *Handle,
                                   u_int32_t   IpCoreCode,
                                   void       **ipcore_ptr)

   Description: Get mapped requested IP Core pointer.

   Input:   void                       *Handle      (Handle pointer)
            u_int32_t                  IpCoreCode
               # CCRTNGFC_IPCODE_0
               # CCRTNGFC_IPCODE_1
               # CCRTNGFC_IPCODE_2
               # CCRTNGFC_IPCODE_3
               # CCRTNGFC_IPCODE_4
               # CCRTNGFC_IPCODE_5
               # CCRTNGFC_IPCODE_6
               # CCRTNGFC_IPCODE_7
               # CCRTNGFC_IPCODE_8
               # CCRTNGFC_IPCODE_9
               .
               .
               .
               # CCRTNGFC_IPCODE_140
               # CCRTNGFC_IPCODE_141
               # CCRTNGFC_IPCODE_142
               # CCRTNGFC_IPCODE_143
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_IPCODE_144
            # CCRTNGFC_IPCODE_145
            # CCRTNGFC_IPCODE_146
            # CCRTNGFC_IPCODE_147
   Output:  void                        **ipcore_ptr (ipcore ptr)
            -- structure in ccrtngfc_user.h
   Return:  _ccrtngfc_lib_error_number_t
            # CCRTNGFC_LIB_NO_ERROR             (successful)
            # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
            # CCRTNGFC_LIB_NOT_OPEN             (device not open)
            # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
            # CCRTNGFC_LIB_NO_LOCAL_REGION      (local region not present)
            # CCRTNGFC_LIB_NO_RESOURCE          (Ip core not present)
 ***************************************************************************/
```

2.2.91 ccrtNGFC_LDIO_Activate()

This call must be the first call to activate and de-activate LVDS and Digital I/O modules. Without activation, all other calls to the LIO/DIO will fail. The user can also use this call to return the current state of the LIO/DIO without any change by specifying a pointer to *current_state* and setting *activate* to *CCRTNGFC_LDIO_MODULE_DO_NOT_CHANGE*. If the LIO/DIO is already active and the user issues a *CCRTNGFC_LDIO_MODULE_ENABLE*, no additional activation will be performed. To cause the LIO/DIO to go through a full reset, the user needs to issue the *CCRTNGFC_LDIO_MODULE_RESET* which will cause the LIO/DIO to disable and then re-enable, setting all its LIO/DIO values to a default state.

Currently, there are only two LDIO modules available and reside on the FPGA mother board. DIO Module 0, and LIO Module 1. In the future we could have additional DIO and LIO modules in the form of add-on daughter cards. This call Enables and Disables ALL available LDIO modules. There is no ability to enable/disable an individual module.

If *current_state* is set to NULL, then no current state information is returned.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Activate (void                            *Handle,
                           _ccrtngfc_ldio_module_enable_t  activate,
                           _ccrtngfc_ldio_module_enable_t  *current_state)

   Description: Activate/DeActivate LVDS and Digital I/O module

   Input:   void                                    *Handle         (Handle pointer)
            _ccrtngfc_ldio_module_enable_t          activate        (activate/deactivate)
               # CCRTNGFC_LDIO_MODULE_DISABLE
               # CCRTNGFC_LDIO_MODULE_ENABLE
               # CCRTNGFC_LDIO_MODULE_RESET         (disable followed by enable)
               # CCRTNGFC_LDIO_MODULE_DO_NOT_CHANGE
   Output:  _ccrtngfc_ldio_module_enable_t          *current_state  (active/deactive)
               # CCRTNGFC_LDIO_MODULE_DISABLE
               # CCRTNGFC_LDIO_MODULE_ENABLE
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                 (successful)
               # CCRTNGFC_LIB_BAD_HANDLE               (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                 (device not open)
               # CCRTNGFC_LIB_INVALID_ARG              (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION          (local region not present)
 ***************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.92 ccrtNGFC_LDIO_Get_Channels_Polarity()

This call allows the user to get the polarity for all the LVDS and DIO channels. The *ChannelSelectMask* is used to retrieve polarity settings for selected channels.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

For input channels, a value of *CCRTNGFC_LDIO_INPUT_LOW_TRUE* or *'0'* for polarity indicates low true, while a value of *CCRTNGFC_LDIO_INPUT_HIGH_TRUE* or *'1'* for polarity indicates high true.

For output channels, a value of *CCRTNGFC_LDIO_OUTPUT_LOW* or *'0'* for polarity indicates low or 0 volts, while a value of *CCRTNGFC_LDIO_OUTPUT_HIGH* or *'1'* for polarity indicates high or +5 volts.

```
/*****************************************************************************
  _ccrtngfc_lib_error_number_t
  ccrtNGFC_LDIO_Get_Channels_Polarity(void                      *Handle,
                                      ccrtngfc_ldio_modules_t  LDIO_ChannelsPolarity,
                                      ccrtngfc_ldio_modules_t  ChannelSelectMask)

   Description: Get Channels Polarity

   Input:   void                          *Handle               (handle pointer)
            ccrtngfc_ldio_modules_t        ChannelSelectMask    (custom channel selection)
                # NULL                                          (select all channels)
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
Output:  ccrtngfc_ldio_modules_t  LDIO_ChannelsPolarity  (channels polarity registers)
                                - CCRTNGFC_LDIO_INPUT_LOW_TRUE   = (0)  // input direction
                                - CCRTNGFC_LDIO_INPUT_HIGH_TRUE  = (1)  // input direction
                                - CCRTNGFC_LDIO_OUTPUT_LOW       = (0)  // output direction
                                - CCRTNGFC_LDIO_OUTPUT_HIGH      = (1)  // output direction
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
Return:  _ccrtngfc_lib_error_number_t
                # CCRTNGFC_LIB_NO_ERROR          (successful)
                # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
                # CCRTNGFC_LIB_NOT_OPEN          (device not open)
                # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
                # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ***************************************************************************/
```

2.2.93 ccrtNGFC_LDIO_Get_COS_Channels_Edge_Sense()

This call returns to the user the settings for the change-of-state to sense the rising or falling edge of the signal on input for all the LVDS and DIO channels. The *ChannelSelectMask* is used to retrieve edge sense settings for selected channels. A value of *CCRTNGFC_LDIO_COS_FALLING_EDGE* or '0' represents sensing of falling edge of input signal while a value of *CCRTNGFC_LDIO_COS_RISING_EDGE* or '1' represents sensing of rising edge of input signal.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Get_COS_Channels_Edge_Sense(void                    *Handle,
                                             ccrtngfc_ldio_modules_t  LDIO_COS_ChannelsEdgeSense,
                                             ccrtngfc_ldio_modules_t  ChannelSelectMask)

   Description: Get COS Channels Edge Sense

   Input:   void                         *Handle               (handle pointer)
            ccrtngfc_ldio_modules_t       ChannelSelectMask    (custom channel selection)
                # NULL                                        (select all channels)
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
Output:  ccrtngfc_ldio_modules_t LDIO_COS_ChannelsEdgeSense (COS channels edge sense
                                                             registers)
                                    - CCRTNGFC_LDIO_COS_FALLING_EDGE   = (0)
                                    - CCRTNGFC_LDIO_COS_RISING_EDGE    = (1)
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
*****************************************************************************/
```

2.2.94 ccrtNGFC_LDIO_Get_COS_Channels_Enable()

This call returns to the user the settings for the change-of-state enable registers all the LVDS and DIO channels. The *ChannelSelectMask* is used to retrieve enable settings for selected channels. A value of *CCRTNGFC_LDIO_COS_IGNORE* or '0' ignores change-of-state while a value of *CCRTNGFC_LDIO_COS_ENABLE* or '1' represents enabling change-of-state for the selected channels.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Get_COS_Channels_Enable(void                    *Handle,
                                         ccrtngfc_ldio_modules_t   LDIO_COS_ChannelsEnable,
                                         ccrtngfc_ldio_modules_t   ChannelSelectMask)

   Description: Get COS Channels Enable Setting

   Input:   void                         *Handle               (handle pointer)
            ccrtngfc_ldio_modules_t       ChannelSelectMask    (custom channel selection)
                # NULL                                        (select all channels)
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
  Output:  ccrtngfc_ldio_modules_t LDIO_COS_ChannelsEnable  (COS channels Enable registers)
                                       - CCRTNGFC_LDIO_COS_IGNORE   = (0)
                                       - CCRTNGFC_LDIO_COS_ENABLE   = (1)
               # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
               CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
  Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ***************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.95 ccrtNGFC_LDIO_Get_COS_Channels_Mode()

This call returns to the user the settings for the change-of-state mode registers all the LVDS and DIO channels. The *ChannelSelectMask* is used to retrieve mode settings for selected channels. A value of *CCRTNGFC_LDIO_COS_ANY_TRANSITION* or '0' detects change-of-state on any edge transition while a value of *CCRTNGFC_LDIO_COS_RISING_OR_FALLING_TRANSITION* or '1' represents enabling change-of-state for either rising edge or falling edge depending on the channel edge sense setting for the selected channels.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Get_COS_Channels_Mode(void                    *Handle,
                                      ccrtngfc_ldio_modules_t  LDIO_COS_ChannelsMode,
                                      ccrtngfc_ldio_modules_t  ChannelSelectMask)

   Description: Get COS Channels Mode

   Input:   void                         *Handle               (handle pointer)
            ccrtngfc_ldio_modules_t       ChannelSelectMask    (custom channel selection)
                # NULL                                        (select all channels)
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
  Output:  ccrtngfc_ldio_modules_t       LDIO_COS_ChannelsMode (COS channels Mode registers)
                                         - CCRTNGFC_LDIO_COS_ANY_TRANSITION               = (0)
                                         - CCRTNGFC_LDIO_COS_RISING_OR_FALLING_TRANSITION = (1)
               # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
               CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
  Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
*************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.96 ccrtNGFC_LDIO_Get_COS_Channels_Overflow()

This call returns to the user the state of the change-of-state overflow registers for all the LVDS and DIO channels. The *ChannelSelectMask* is used to retrieve overflow settings for selected channels. A value of *CCRTNGFC_LDIO_COS_ OVERFLOW_DID_NOT_OCCUR* or '0' indicates that no overflow occurred while a value of *CCRTNGFC_LDIO_COS_OVERFLOW_OCCURRED* or '1' indicates that an overflow condition occurred for the selected channels. An overflow condition is set when a change-of-state condition is detected on a channel that previously detected a change-of-state condition without its COS status being cleared. Any read of this register will automatically clear the change of state overflow bits that were set in the read data.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Get_COS_Channels_Overflow(void                     *Handle,
                                          ccrtngfc_ldio_modules_t  LDIO_COS_ChannelsOverflow,
                                          ccrtngfc_ldio_modules_t  ChannelSelectMask)

   Description: Get COS Channels Overflow

   Input:   void                          *Handle               (handle pointer)
            ccrtngfc_ldio_modules_t        ChannelSelectMask    (custom channel selection)
                # NULL                                          (select all channels)
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
  Output:  ccrtngfc_ldio_modules_t   LDIO_COS_ChannelsOverflow (COS channels overflow registers)
                                     - CCRTNGFC_LDIO_COS_OVERFLOW_DID_NOT_OCCUR = (0)
                                     - CCRTNGFC_LDIO_COS_OVERFLOW_OCCURRED      = (1)
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
  Return:  _ccrtngfc_lib_error_number_t
                # CCRTNGFC_LIB_NO_ERROR           (successful)
                # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
                # CCRTNGFC_LIB_NOT_OPEN           (device not open)
                # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
                # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
                # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
*************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.97 ccrtNGFC_LDIO_Get_COS_Channels_Status()

This call returns to the user the state of the change-of-state status registers for all the LVDS and DIO channels. The *ChannelSelectMask* is used to retrieve status settings for selected channels. A value of *CCRTNGFC_LDIO_COS_DID_NOT_OCCUR* or '0' indicates that no change-of-state occurred while a value of *CCRTNGFC_LDIO_COS_OCCURRED* or '1' indicates that a change-of-state condition occurred for the selected channels. A change-of-state status is set when the hardware is enabled to detect a change of input signal transition and an input signal is received with the monitored transition. Any read of this register will automatically clear the change of state status bits that were set in the read data.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Get_COS_Channels_Status(void                     *Handle,
                                         ccrtngfc_ldio_modules_t  LDIO_COS_ChannelsStatus,
                                         ccrtngfc_ldio_modules_t  ChannelSelectMask)

   Description: Get COS Channels Status

   Input:   void                         *Handle               (handle pointer)
            ccrtngfc_ldio_modules_t       ChannelSelectMask    (custom channel selection)
                # NULL                                         (select all channels)
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
    Output:  ccrtngfc_ldio_modules_t LDIO_COS_ChannelsStatus    (COS channels Status registers)
                                     - CCRTNGFC_LDIO_COS_DID_NOT_OCCUR    = (0)
                                     - CCRTNGFC_LDIO_COS_OCCURRED         = (1)
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
    Return:  _ccrtngfc_lib_error_number_t
                # CCRTNGFC_LIB_NO_ERROR           (successful)
                # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
                # CCRTNGFC_LIB_NOT_OPEN           (device not open)
                # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
                # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
                # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
***************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.98 ccrtNGFC_LDIO_Get_Input_Channels_Filter()

This call allows the user to get the settings for all the LVDS and DIO channels input filters. The *ChannelSelectMask* is used to retrieve filter settings for selected channels. A value of *CCRTNGFC_LDIO_INPUT_FILTER_ENABLED* or *'1'* for filter indicates that the 100 nanosecond filter is enabled for the selected channel, while a value of *CCRTNGFC_LDIO_INPUT_FILTER_DISABLED* or *'0'* indicates that the filter is disabled. On powerup, filter for all channels are enabled.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Get_Input_Channels_Filter(void                    *Handle,
                                           ccrtngfc_ldio_modules_t   LDIO_InputChannelsFilter,
                                           ccrtngfc_ldio_modules_t   ChannelSelectMask)

   Description: Get Input Channels Filter

   Input:   void                         *Handle               (handle pointer)
            ccrtngfc_ldio_modules_t       ChannelSelectMask    (custom channel selection)
                # NULL                                        (select all channels)
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
  Output:  ccrtngfc_ldio_modules_t  LDIO_InputChannelsFilter       (input channel registers)
                                        - CCRTNGFC_LDIO_INPUT_FILTER_DISABLED   = (0)
                                        - CCRTNGFC_LDIO_INPUT_FILTER_ENABLED    = (1)
               # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
               CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
  Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
*************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.99 ccrtNGFC_LDIO_Get_Input_Snapshot()

This call returns the Input Snapshot state for all the LVDS and DIO modules. The purpose of this snapshot feature is to allow the user to read the input channels without the firmware updating them in the middle of the reads. In this way, they can ensure that all channels data are in sync.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Get_Input_Snapshot(void                              *Handle,
                                    _ccrtngfc_ldio_input_snapshot_t  *ldio_snapshot)

   Description: Get LDIO Input Snapshot

   Input:   void                              *Handle            (handle pointer)
   Output:  _ccrtngfc_ldio_input_snapshot_t *ldio_snapshot     (LVDS and Digital I/O snapshot)
               # CCRTNGFC_LDIO_INPUT_OPERATION_CONTINUOUS
               # CCRTNGFC_LDIO_INPUT_OPERATION_SNAPSHOT
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (DIO is not active)
*************************************************************************/
```

2.2.100 ccrtNGFC_LDIO_Get_Output_Sync()

This call returns the current state of the output sync flag for all the LVDS and DIO modules. The purpose of the output sync feature is to ensure that the user can safely program all the output channels prior to directing the firmware to send them out simultaneously.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Get_Output_Sync(void                             *Handle,
                                 _ccrtngfc_ldio_output_sync_t   *ldio_sync)

   Description: Get LVDS and Digital I/O Output Sync

   Input:   void                              *Handle          (handle pointer)
   Output:  _ccrtngfc_ldio_output_sync_t    *ldio_sync       (LVDS and Digital I/O sync)
               # CCRTNGFC_LDIO_OUTPUT_OPERATION_CONTINUOUS = (0)
               # CCRTNGFC_LDIO_OUTPUT_OPERATION_SYNC       = (1)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 *************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.101 ccrtNGFC_LDIO_Read_Input_Channel_Registers()

This call reads the contents of the input channel registers for all the LVDS and DIO modules and returns to the user. There are two modes of operation for this call. (1) Continuous (2) Snapshot.

When the user selects the *continuous* operation, this call immediately returns to the user whatever is available on the input registers as they are being received by the hardware. There is therefore no synchronizing occurring between the varions LDIO modules. For performance improvements with *this* operational mode, it is recommended that the user sets the continuous option using the *ccrtNGFC_LDIO_Set_Input_Snapshot()* call once and then supply *CCRTNGFC_LDIO_INPUT_OPERATION_DO_NOT_CHANGE* to this call for more reads. In this way, an additional register access will not occur everytime this call is issued.

When the user decides to use the *snapshot* operation instead, there is no need to issue the *ccrtNGFC_LDIO_Set_Input_Snapshot().* All that is required is to supply the *CCRTNGFC_LDIO_INPUT_OPERATION_SNAPSHOT* option when issuing this call. The result is that all the LDIO module channels will be captured instantaneously *(in sync)* by the firmware and returned to the user.

Obviously, the *snapshot* operation is only meaningful if the user selects channels *(using the channel selection mask)* that reside in at least two different LDIO modules.

The *skip_ldio_disable_check* (when set to *CCRTNGFC_FALSE*) causes the call to test for the LDIO being enabled prior to proceeding. If this option is set to *CCRTNGFC_TRUE*, then no validation is performed. If the LDIO has not been enabled, input reads will be invalid. The only reason for providing this option to disable the check in order to improve the performance of the call. If the user can ensure that the LDIO is enabled prior to issuing this call, they can set this option to *CCRTNGFC_TRUE* so that no validation is performed and hence, improve performance.

When the direction for the channels are set as inputs, then reading the channels input registers will result in acquiring signals coming into the board from the external digital lines.

In the case of Digital I/O module, when the direction for channels are set to output, then reading the channels input registers will result in acquiring what was written to the output (loopback).

In the case of LVDS I/O module, when the direction for channels are set to output, then reading the channels input registers will result in invalid channel information being returned as the only way to read back (loopback) the channel information is to use the LIO Test Mode as specified with the *ccrtNGFC_LIO_Set_Ports_Direction()* call. If the user wishes to read back (loopback) the channel information for the LVDS I/O module, then they will need to use the specific *ccrtNGFC_LIO_Read_Output_Loopbacked_Channels()* call as that is specifically written for this purpose.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Read_Input_Channel_Registers(void                              *Handle,
                                              _ccrtngfc_ldio_input_snapshot_t ldio_snapshot,
                                              ccrtngfc_bool        skip_ldio_disabled_check,
                                              ccrtngfc_ldio_modules_t    LDIO_InputChannels,
                                               ccrtngfc_ldio_modules_t    ChannelSelectMask)

   Description: Read LDIO Input Channel Registers

   Input:   void                              *Handle           (handle pointer)
            _ccrtngfc_ldio_input_snapshot_t  ldio_snapshot     (ldio_snapshot operation)
                # CCRTNGFC_LDIO_INPUT_OPERATION_CONTINUOUS
                # CCRTNGFC_LDIO_INPUT_OPERATION_SNAPSHOT
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_INPUT_OPERATION_DO_NOT_CHANGE
                ccrtngfc_bool                   skip_ldio_disabled_check (skip LVDS and Digital
                                                                          I/O disabled check)
                    # CCRTNGFC_TRUE
                    # CCRTNGFC_FALSE
                ccrtngfc_ldio_modules_t         ChannelSelectMask (custom channel selection)
                    # NULL                                          (select all channels)
                    # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                        # CCRTNGFC_LDIO_CHANNEL_MASK_0
                        # CCRTNGFC_LDIO_CHANNEL_MASK_1
                        # CCRTNGFC_LDIO_CHANNEL_MASK_2
                        # CCRTNGFC_LDIO_CHANNEL_MASK_3
                        # CCRTNGFC_LDIO_CHANNEL_MASK_4
                        # CCRTNGFC_LDIO_CHANNEL_MASK_5
                        # CCRTNGFC_LDIO_CHANNEL_MASK_6
                        # CCRTNGFC_LDIO_CHANNEL_MASK_7
                        # CCRTNGFC_LDIO_CHANNEL_MASK_8
                        # CCRTNGFC_LDIO_CHANNEL_MASK_9
                        # CCRTNGFC_LDIO_CHANNEL_MASK_10
                        # CCRTNGFC_LDIO_CHANNEL_MASK_11
                        # CCRTNGFC_LDIO_CHANNEL_MASK_12
                        # CCRTNGFC_LDIO_CHANNEL_MASK_13
                        # CCRTNGFC_LDIO_CHANNEL_MASK_14
                        # CCRTNGFC_LDIO_CHANNEL_MASK_15
                        # CCRTNGFC_LDIO_CHANNEL_MASK_16
                        # CCRTNGFC_LDIO_CHANNEL_MASK_17
                        # CCRTNGFC_LDIO_CHANNEL_MASK_18
                        # CCRTNGFC_LDIO_CHANNEL_MASK_19
                        # CCRTNGFC_LDIO_CHANNEL_MASK_20
                        # CCRTNGFC_LDIO_CHANNEL_MASK_21
                        # CCRTNGFC_LDIO_CHANNEL_MASK_22
                        # CCRTNGFC_LDIO_CHANNEL_MASK_23
                        # CCRTNGFC_LDIO_CHANNEL_MASK_24
                        # CCRTNGFC_LDIO_CHANNEL_MASK_25
                        # CCRTNGFC_LDIO_CHANNEL_MASK_26
                        # CCRTNGFC_LDIO_CHANNEL_MASK_27
                        # CCRTNGFC_LDIO_CHANNEL_MASK_28
                        # CCRTNGFC_LDIO_CHANNEL_MASK_29
                        # CCRTNGFC_LDIO_CHANNEL_MASK_30
                        # CCRTNGFC_LDIO_CHANNEL_MASK_31
                        # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                    CCRTNGFC_LDIO_MAX_MODULES can be one of:
                        # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                        # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                        # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                        # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                        # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                        # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Output:  ccrtngfc_ldio_modules_t       LDIO_InputChannels             (input channel
registers)
                    # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                        # CCRTNGFC_LDIO_CHANNEL_MASK_0
                        # CCRTNGFC_LDIO_CHANNEL_MASK_1
                        # CCRTNGFC_LDIO_CHANNEL_MASK_2
                        # CCRTNGFC_LDIO_CHANNEL_MASK_3
                        # CCRTNGFC_LDIO_CHANNEL_MASK_4
                        # CCRTNGFC_LDIO_CHANNEL_MASK_5
                        # CCRTNGFC_LDIO_CHANNEL_MASK_6
                        # CCRTNGFC_LDIO_CHANNEL_MASK_7
                        # CCRTNGFC_LDIO_CHANNEL_MASK_8
                        # CCRTNGFC_LDIO_CHANNEL_MASK_9
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ***************************************************************************/
```

2.2.102 ccrtNGFC_LDIO_Read_Output_Channel_Registers()

This call reads the contents of the output channel registers for all the LVDS and DIO modules and returns to the user. This simply represents the contents of the last write to the output registers.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Read_Output_Channel_Registers(void                    *Handle,
                                               ccrtngfc_ldio_modules_t  LDIO_OutputChannels,
                                               ccrtngfc_ldio_modules_t  ChannelSelectMask)

   Description: Read LDIO Output Channel Registers

   Input:   void                         *Handle              (handle pointer)
            ccrtngfc_ldio_modules_t       ChannelSelectMask   (custom channel selection)
               # NULL                                         (select all channels)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
Output:  ccrtngfc_ldio_modules_t   LDIO_OutputChannels      (output channel registers)
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ***************************************************************************/
```

2.2.103 ccrtNGFC_LDIO_Set_Channels_Polarity()

This call allows the user to set the polarity for the channels of all the LVDS and DIO modules. The *ChannelSelectMask* is used to retrieve polarity settings for selected channels.

For input channels, a value of *CCRTNGFC_LDIO_INPUT_LOW_TRUE* or *'0'* for polarity indicates low true, while a value of *CCRTNGFC_LDIO_INPUT_HIGH_TRUE* or *'1'* for polarity indicates high true.

For output channels, a value of *CCRTNGFC_LDIO_OUTPUT_LOW* or *'0'* for polarity indicates low or 0 volts, while a value of *CCRTNGFC_LDIO_OUTPUT_HIGH* or *'1'* for polarity indicates high or +5 volts.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Set_Channels_Polarity(void                    *Handle,
                                      ccrtngfc_ldio_modules_t  LDIO_ChannelsPolarity,
                                      ccrtngfc_ldio_modules_t  ChannelSelectMask)

   Description: Set Channels Polarity

   Input:   void                        *Handle               (handle pointer)
            ccrtngfc_ldio_modules_t     LDIO_ChannelsPolarity (channels polarity registers)
                                - CCRTNGFC_LDIO_INPUT_LOW_TRUE   = (0)  // input direction
                                - CCRTNGFC_LDIO_INPUT_HIGH_TRUE  = (1)  // input direction
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                        - CCRTNGFC_LDIO_OUTPUT_LOW       = (0)  // output direction
                        - CCRTNGFC_LDIO_OUTPUT_HIGH      = (1)  // output direction
    # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
        # CCRTNGFC_LDIO_CHANNEL_MASK_0
        # CCRTNGFC_LDIO_CHANNEL_MASK_1
        # CCRTNGFC_LDIO_CHANNEL_MASK_2
        # CCRTNGFC_LDIO_CHANNEL_MASK_3
        # CCRTNGFC_LDIO_CHANNEL_MASK_4
        # CCRTNGFC_LDIO_CHANNEL_MASK_5
        # CCRTNGFC_LDIO_CHANNEL_MASK_6
        # CCRTNGFC_LDIO_CHANNEL_MASK_7
        # CCRTNGFC_LDIO_CHANNEL_MASK_8
        # CCRTNGFC_LDIO_CHANNEL_MASK_9
        # CCRTNGFC_LDIO_CHANNEL_MASK_10
        # CCRTNGFC_LDIO_CHANNEL_MASK_11
        # CCRTNGFC_LDIO_CHANNEL_MASK_12
        # CCRTNGFC_LDIO_CHANNEL_MASK_13
        # CCRTNGFC_LDIO_CHANNEL_MASK_14
        # CCRTNGFC_LDIO_CHANNEL_MASK_15
        # CCRTNGFC_LDIO_CHANNEL_MASK_16
        # CCRTNGFC_LDIO_CHANNEL_MASK_17
        # CCRTNGFC_LDIO_CHANNEL_MASK_18
        # CCRTNGFC_LDIO_CHANNEL_MASK_19
        # CCRTNGFC_LDIO_CHANNEL_MASK_20
        # CCRTNGFC_LDIO_CHANNEL_MASK_21
        # CCRTNGFC_LDIO_CHANNEL_MASK_22
        # CCRTNGFC_LDIO_CHANNEL_MASK_23
        # CCRTNGFC_LDIO_CHANNEL_MASK_24
        # CCRTNGFC_LDIO_CHANNEL_MASK_25
        # CCRTNGFC_LDIO_CHANNEL_MASK_26
        # CCRTNGFC_LDIO_CHANNEL_MASK_27
        # CCRTNGFC_LDIO_CHANNEL_MASK_28
        # CCRTNGFC_LDIO_CHANNEL_MASK_29
        # CCRTNGFC_LDIO_CHANNEL_MASK_30
        # CCRTNGFC_LDIO_CHANNEL_MASK_31
        # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
    CCRTNGFC_LDIO_MAX_MODULES can be one of:
        # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
        # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
        # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
        # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
        # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
        # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
ccrtngfc_ldio_modules_t   ChannelSelectMask        (custom channel selection)
    # NULL                                         (select all channels)
    # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
        # CCRTNGFC_LDIO_CHANNEL_MASK_0
        # CCRTNGFC_LDIO_CHANNEL_MASK_1
        # CCRTNGFC_LDIO_CHANNEL_MASK_2
        # CCRTNGFC_LDIO_CHANNEL_MASK_3
        # CCRTNGFC_LDIO_CHANNEL_MASK_4
        # CCRTNGFC_LDIO_CHANNEL_MASK_5
        # CCRTNGFC_LDIO_CHANNEL_MASK_6
        # CCRTNGFC_LDIO_CHANNEL_MASK_7
        # CCRTNGFC_LDIO_CHANNEL_MASK_8
        # CCRTNGFC_LDIO_CHANNEL_MASK_9
        # CCRTNGFC_LDIO_CHANNEL_MASK_10
        # CCRTNGFC_LDIO_CHANNEL_MASK_11
        # CCRTNGFC_LDIO_CHANNEL_MASK_12
        # CCRTNGFC_LDIO_CHANNEL_MASK_13
        # CCRTNGFC_LDIO_CHANNEL_MASK_14
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN          (device not open)
               # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ***************************************************************************/
```

2.2.104 ccrtNGFC_LDIO_Set_COS_Channels_Edge_Sense()

This call sets the change-of-state to sense the rising or falling edge of the signal on input for the channels of all the LVDS and DIO modules. The *ChannelSelectMask* is used to set the edge sense settings for selected channels. A value of *CCRTNGFC_LDIO_COS_FALLING_EDGE* or '0' represents sensing of falling edge of input signal while a value of *CCRTNGFC_LDIO_COS_RISING_EDGE* or '1' represents sensing of rising edge of input signal.

For edge sensing to occur, the *CCRTNGFC_LDIO_COS_RISING_OR_FALLING_TRANSITION* bit needs to be set for the corresponding channels using the *ccrtNGFC_LDIO_Set_COS_Channels_Mode()* call.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Set_COS_Channels_Edge_Sense(void                    *Handle,
                                             ccrtngfc_ldio_modules_t LDIO_COS_ChannelsEdgeSense,
                                             ccrtngfc_ldio_modules_t ChannelSelectMask)

   Description: Set COS Channels Edge Sense

   Input:   void                        *Handle                   (handle pointer)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
ccrtngfc_ldio_modules_t    LDIO_COS_ChannelsEdgeSense (COS channels edge sense
                                                       registers)
                              - CCRTNGFC_LDIO_COS_FALLING_EDGE   = (0)
                              - CCRTNGFC_LDIO_COS_RISING_EDGE    = (1)
    # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
        # CCRTNGFC_LDIO_CHANNEL_MASK_0
        # CCRTNGFC_LDIO_CHANNEL_MASK_1
        # CCRTNGFC_LDIO_CHANNEL_MASK_2
        # CCRTNGFC_LDIO_CHANNEL_MASK_3
        # CCRTNGFC_LDIO_CHANNEL_MASK_4
        # CCRTNGFC_LDIO_CHANNEL_MASK_5
        # CCRTNGFC_LDIO_CHANNEL_MASK_6
        # CCRTNGFC_LDIO_CHANNEL_MASK_7
        # CCRTNGFC_LDIO_CHANNEL_MASK_8
        # CCRTNGFC_LDIO_CHANNEL_MASK_9
        # CCRTNGFC_LDIO_CHANNEL_MASK_10
        # CCRTNGFC_LDIO_CHANNEL_MASK_11
        # CCRTNGFC_LDIO_CHANNEL_MASK_12
        # CCRTNGFC_LDIO_CHANNEL_MASK_13
        # CCRTNGFC_LDIO_CHANNEL_MASK_14
        # CCRTNGFC_LDIO_CHANNEL_MASK_15
        # CCRTNGFC_LDIO_CHANNEL_MASK_16
        # CCRTNGFC_LDIO_CHANNEL_MASK_17
        # CCRTNGFC_LDIO_CHANNEL_MASK_18
        # CCRTNGFC_LDIO_CHANNEL_MASK_19
        # CCRTNGFC_LDIO_CHANNEL_MASK_20
        # CCRTNGFC_LDIO_CHANNEL_MASK_21
        # CCRTNGFC_LDIO_CHANNEL_MASK_22
        # CCRTNGFC_LDIO_CHANNEL_MASK_23
        # CCRTNGFC_LDIO_CHANNEL_MASK_24
        # CCRTNGFC_LDIO_CHANNEL_MASK_25
        # CCRTNGFC_LDIO_CHANNEL_MASK_26
        # CCRTNGFC_LDIO_CHANNEL_MASK_27
        # CCRTNGFC_LDIO_CHANNEL_MASK_28
        # CCRTNGFC_LDIO_CHANNEL_MASK_29
        # CCRTNGFC_LDIO_CHANNEL_MASK_30
        # CCRTNGFC_LDIO_CHANNEL_MASK_31
        # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
    CCRTNGFC_LDIO_MAX_MODULES can be one of:
        # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
        # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
        # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
        # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
        # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
        # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
ccrtngfc_ldio_modules_t       ChannelSelectMask    (custom channel selection)
    # NULL                                         (select all channels)
    # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
        # CCRTNGFC_LDIO_CHANNEL_MASK_0
        # CCRTNGFC_LDIO_CHANNEL_MASK_1
        # CCRTNGFC_LDIO_CHANNEL_MASK_2
        # CCRTNGFC_LDIO_CHANNEL_MASK_3
        # CCRTNGFC_LDIO_CHANNEL_MASK_4
        # CCRTNGFC_LDIO_CHANNEL_MASK_5
        # CCRTNGFC_LDIO_CHANNEL_MASK_6
        # CCRTNGFC_LDIO_CHANNEL_MASK_7
        # CCRTNGFC_LDIO_CHANNEL_MASK_8
        # CCRTNGFC_LDIO_CHANNEL_MASK_9
        # CCRTNGFC_LDIO_CHANNEL_MASK_10
        # CCRTNGFC_LDIO_CHANNEL_MASK_11
        # CCRTNGFC_LDIO_CHANNEL_MASK_12
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN          (device not open)
               # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ***************************************************************************/
```

2.2.105 ccrtNGFC_LDIO_Set_COS_Channels_Enable()

If the user wishes to monitor change-of-state for a channel, then need to enable the change-of-state detection for the respective channels of all the LVDS and DIO modules using this call. Without the channel being enabled, no change-of-state detection will occur. The *ChannelSelectMask* is used to set enable settings for selected channels. A value of *CCRTNGFC_LDIO_COS_IGNORE* or '0' ignores change-of-state while a value of *CCRTNGFC_LDIO_COS_ENABLE* or '1' represents enabling change-of-state for the selected channels.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Set_COS_Channels_Enable (void                     *Handle,
                                          ccrtngfc_ldio_modules_t  LDIO_COS_ChannelsEnable,
                                          ccrtngfc_ldio_modules_t  ChannelSelectMask)

   Description: Set COS Channels Enable

   Input:   void                          *Handle                 (handle pointer)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
ccrtngfc_ldio_modules_t       LDIO_COS_ChannelsEnable (COS channels enable registers)
                              - CCRTNGFC_LDIO_COS_IGNORE   = (0)
                              - CCRTNGFC_LDIO_COS_ENABLE   = (1)
    # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
        # CCRTNGFC_LDIO_CHANNEL_MASK_0
        # CCRTNGFC_LDIO_CHANNEL_MASK_1
        # CCRTNGFC_LDIO_CHANNEL_MASK_2
        # CCRTNGFC_LDIO_CHANNEL_MASK_3
        # CCRTNGFC_LDIO_CHANNEL_MASK_4
        # CCRTNGFC_LDIO_CHANNEL_MASK_5
        # CCRTNGFC_LDIO_CHANNEL_MASK_6
        # CCRTNGFC_LDIO_CHANNEL_MASK_7
        # CCRTNGFC_LDIO_CHANNEL_MASK_8
        # CCRTNGFC_LDIO_CHANNEL_MASK_9
        # CCRTNGFC_LDIO_CHANNEL_MASK_10
        # CCRTNGFC_LDIO_CHANNEL_MASK_11
        # CCRTNGFC_LDIO_CHANNEL_MASK_12
        # CCRTNGFC_LDIO_CHANNEL_MASK_13
        # CCRTNGFC_LDIO_CHANNEL_MASK_14
        # CCRTNGFC_LDIO_CHANNEL_MASK_15
        # CCRTNGFC_LDIO_CHANNEL_MASK_16
        # CCRTNGFC_LDIO_CHANNEL_MASK_17
        # CCRTNGFC_LDIO_CHANNEL_MASK_18
        # CCRTNGFC_LDIO_CHANNEL_MASK_19
        # CCRTNGFC_LDIO_CHANNEL_MASK_20
        # CCRTNGFC_LDIO_CHANNEL_MASK_21
        # CCRTNGFC_LDIO_CHANNEL_MASK_22
        # CCRTNGFC_LDIO_CHANNEL_MASK_23
        # CCRTNGFC_LDIO_CHANNEL_MASK_24
        # CCRTNGFC_LDIO_CHANNEL_MASK_25
        # CCRTNGFC_LDIO_CHANNEL_MASK_26
        # CCRTNGFC_LDIO_CHANNEL_MASK_27
        # CCRTNGFC_LDIO_CHANNEL_MASK_28
        # CCRTNGFC_LDIO_CHANNEL_MASK_29
        # CCRTNGFC_LDIO_CHANNEL_MASK_30
        # CCRTNGFC_LDIO_CHANNEL_MASK_31
        # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
    CCRTNGFC_LDIO_MAX_MODULES can be one of:
        # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
        # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
        # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
        # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
        # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
        # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
ccrtngfc_ldio_modules_t       ChannelSelectMask        (custom channel selection)
    # NULL                                             (select all channels)
    # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
        # CCRTNGFC_LDIO_CHANNEL_MASK_0
        # CCRTNGFC_LDIO_CHANNEL_MASK_1
        # CCRTNGFC_LDIO_CHANNEL_MASK_2
        # CCRTNGFC_LDIO_CHANNEL_MASK_3
        # CCRTNGFC_LDIO_CHANNEL_MASK_4
        # CCRTNGFC_LDIO_CHANNEL_MASK_5
        # CCRTNGFC_LDIO_CHANNEL_MASK_6
        # CCRTNGFC_LDIO_CHANNEL_MASK_7
        # CCRTNGFC_LDIO_CHANNEL_MASK_8
        # CCRTNGFC_LDIO_CHANNEL_MASK_9
        # CCRTNGFC_LDIO_CHANNEL_MASK_10
        # CCRTNGFC_LDIO_CHANNEL_MASK_11
        # CCRTNGFC_LDIO_CHANNEL_MASK_12
        # CCRTNGFC_LDIO_CHANNEL_MASK_13
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN          (device not open)
               # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ***************************************************************************/
```

2.2.106 ccrtNGFC_LDIO_Set_COS_Channels_Mode()

This call sets the change-of-state mode registers for all the channels of all the LVDS and DIO modules. The *ChannelSelectMask* is used to set the mode settings for selected channels. A value of *CCRTNGFC_LDIO_COS_ANY_TRANSITION* or '0' sets change-of-state on any edge transition while a value of *CCRTNGFC_LDIO_COS_RISING_OR_FALLING_TRANSITION* or '1' represents enabling change-of-state for either rising edge or falling edge depending on the channel edge sense setting for the selected channels.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Set_COS_Channels_Mode(void                      *Handle,
                                      ccrtngfc_ldio_modules_t   LDIO_COS_ChannelsMode,
                                      ccrtngfc_ldio_modules_t   ChannelSelectMask)

   Description: Set COS Channels Mode

   Input:   void                        *Handle               (handle pointer)
            ccrtngfc_ldio_modules_t      LDIO_COS_ChannelsMode (COS channels mode registers)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                                    - CCRTNGFC_LDIO_COS_ANY_TRANSITION               = (0)
                                    - CCRTNGFC_LDIO_COS_RISING_OR_FALLING_TRANSITION = (1)
        # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
            # CCRTNGFC_LDIO_CHANNEL_MASK_0
            # CCRTNGFC_LDIO_CHANNEL_MASK_1
            # CCRTNGFC_LDIO_CHANNEL_MASK_2
            # CCRTNGFC_LDIO_CHANNEL_MASK_3
            # CCRTNGFC_LDIO_CHANNEL_MASK_4
            # CCRTNGFC_LDIO_CHANNEL_MASK_5
            # CCRTNGFC_LDIO_CHANNEL_MASK_6
            # CCRTNGFC_LDIO_CHANNEL_MASK_7
            # CCRTNGFC_LDIO_CHANNEL_MASK_8
            # CCRTNGFC_LDIO_CHANNEL_MASK_9
            # CCRTNGFC_LDIO_CHANNEL_MASK_10
            # CCRTNGFC_LDIO_CHANNEL_MASK_11
            # CCRTNGFC_LDIO_CHANNEL_MASK_12
            # CCRTNGFC_LDIO_CHANNEL_MASK_13
            # CCRTNGFC_LDIO_CHANNEL_MASK_14
            # CCRTNGFC_LDIO_CHANNEL_MASK_15
            # CCRTNGFC_LDIO_CHANNEL_MASK_16
            # CCRTNGFC_LDIO_CHANNEL_MASK_17
            # CCRTNGFC_LDIO_CHANNEL_MASK_18
            # CCRTNGFC_LDIO_CHANNEL_MASK_19
            # CCRTNGFC_LDIO_CHANNEL_MASK_20
            # CCRTNGFC_LDIO_CHANNEL_MASK_21
            # CCRTNGFC_LDIO_CHANNEL_MASK_22
            # CCRTNGFC_LDIO_CHANNEL_MASK_23
            # CCRTNGFC_LDIO_CHANNEL_MASK_24
            # CCRTNGFC_LDIO_CHANNEL_MASK_25
            # CCRTNGFC_LDIO_CHANNEL_MASK_26
            # CCRTNGFC_LDIO_CHANNEL_MASK_27
            # CCRTNGFC_LDIO_CHANNEL_MASK_28
            # CCRTNGFC_LDIO_CHANNEL_MASK_29
            # CCRTNGFC_LDIO_CHANNEL_MASK_30
            # CCRTNGFC_LDIO_CHANNEL_MASK_31
            # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
        CCRTNGFC_LDIO_MAX_MODULES can be one of:
            # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
            # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
            # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
            # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
            # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
            # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
    ccrtngfc_ldio_modules_t       ChannelSelectMask    (custom channel selection)
        # NULL                                         (select all channels)
        # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
            # CCRTNGFC_LDIO_CHANNEL_MASK_0
            # CCRTNGFC_LDIO_CHANNEL_MASK_1
            # CCRTNGFC_LDIO_CHANNEL_MASK_2
            # CCRTNGFC_LDIO_CHANNEL_MASK_3
            # CCRTNGFC_LDIO_CHANNEL_MASK_4
            # CCRTNGFC_LDIO_CHANNEL_MASK_5
            # CCRTNGFC_LDIO_CHANNEL_MASK_6
            # CCRTNGFC_LDIO_CHANNEL_MASK_7
            # CCRTNGFC_LDIO_CHANNEL_MASK_8
            # CCRTNGFC_LDIO_CHANNEL_MASK_9
            # CCRTNGFC_LDIO_CHANNEL_MASK_10
            # CCRTNGFC_LDIO_CHANNEL_MASK_11
            # CCRTNGFC_LDIO_CHANNEL_MASK_12
            # CCRTNGFC_LDIO_CHANNEL_MASK_13
            # CCRTNGFC_LDIO_CHANNEL_MASK_14
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN          (device not open)
               # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ************************************************************************/
```

2.2.107 ccrtNGFC_LDIO_Set_Input_Channels_Filter()

This call allows the user to set or reset filters for a selected set of input channels of all the LVDS and DIO modules. The *ChannelSelectMask* is used to select channels for filter settings. A value of *CCRTNGFC_LDIO_INPUT_FILTER_ENABLE* or *'1'* for filter indicates that the 100 nanosecond filter is enabled for the selected channel, while a value of *CCRTNGFC_LDIO_INPUT_FILTER_DISABLE* or *'0'* indicates that the filter is disabled. On powerup, filter for all channels are enabled.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Set_Input_Channels_Filter(void                    *Handle,
                                          ccrtngfc_ldio_modules_t   LDIO_InputChannelsFilter,
                                          ccrtngfc_ldio_modules_t   ChannelSelectMask)

   Description: Set Input Channels Filter

   Input:   void                         *Handle                      (handle pointer)
            ccrtngfc_ldio_modules_t       LDIO_InputChannelsFilter     (input channel registers)
                                          - CCRTNGFC_LDIO_INPUT_FILTER_DISABLE   = (0)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                                - CCRTNGFC_LDIO_INPUT_FILTER_ENABLE    = (1)
        # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
            # CCRTNGFC_LDIO_CHANNEL_MASK_0
            # CCRTNGFC_LDIO_CHANNEL_MASK_1
            # CCRTNGFC_LDIO_CHANNEL_MASK_2
            # CCRTNGFC_LDIO_CHANNEL_MASK_3
            # CCRTNGFC_LDIO_CHANNEL_MASK_4
            # CCRTNGFC_LDIO_CHANNEL_MASK_5
            # CCRTNGFC_LDIO_CHANNEL_MASK_6
            # CCRTNGFC_LDIO_CHANNEL_MASK_7
            # CCRTNGFC_LDIO_CHANNEL_MASK_8
            # CCRTNGFC_LDIO_CHANNEL_MASK_9
            # CCRTNGFC_LDIO_CHANNEL_MASK_10
            # CCRTNGFC_LDIO_CHANNEL_MASK_11
            # CCRTNGFC_LDIO_CHANNEL_MASK_12
            # CCRTNGFC_LDIO_CHANNEL_MASK_13
            # CCRTNGFC_LDIO_CHANNEL_MASK_14
            # CCRTNGFC_LDIO_CHANNEL_MASK_15
            # CCRTNGFC_LDIO_CHANNEL_MASK_16
            # CCRTNGFC_LDIO_CHANNEL_MASK_17
            # CCRTNGFC_LDIO_CHANNEL_MASK_18
            # CCRTNGFC_LDIO_CHANNEL_MASK_19
            # CCRTNGFC_LDIO_CHANNEL_MASK_20
            # CCRTNGFC_LDIO_CHANNEL_MASK_21
            # CCRTNGFC_LDIO_CHANNEL_MASK_22
            # CCRTNGFC_LDIO_CHANNEL_MASK_23
            # CCRTNGFC_LDIO_CHANNEL_MASK_24
            # CCRTNGFC_LDIO_CHANNEL_MASK_25
            # CCRTNGFC_LDIO_CHANNEL_MASK_26
            # CCRTNGFC_LDIO_CHANNEL_MASK_27
            # CCRTNGFC_LDIO_CHANNEL_MASK_28
            # CCRTNGFC_LDIO_CHANNEL_MASK_29
            # CCRTNGFC_LDIO_CHANNEL_MASK_30
            # CCRTNGFC_LDIO_CHANNEL_MASK_31
            # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
        CCRTNGFC_LDIO_MAX_MODULES can be one of:
            # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
            # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
            # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
            # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
            # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
            # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
    ccrtngfc_ldio_modules_t       ChannelSelectMask    (custom channel selection)
        # NULL                                         (select all channels)
        # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
            # CCRTNGFC_LDIO_CHANNEL_MASK_0
            # CCRTNGFC_LDIO_CHANNEL_MASK_1
            # CCRTNGFC_LDIO_CHANNEL_MASK_2
            # CCRTNGFC_LDIO_CHANNEL_MASK_3
            # CCRTNGFC_LDIO_CHANNEL_MASK_4
            # CCRTNGFC_LDIO_CHANNEL_MASK_5
            # CCRTNGFC_LDIO_CHANNEL_MASK_6
            # CCRTNGFC_LDIO_CHANNEL_MASK_7
            # CCRTNGFC_LDIO_CHANNEL_MASK_8
            # CCRTNGFC_LDIO_CHANNEL_MASK_9
            # CCRTNGFC_LDIO_CHANNEL_MASK_10
            # CCRTNGFC_LDIO_CHANNEL_MASK_11
            # CCRTNGFC_LDIO_CHANNEL_MASK_12
            # CCRTNGFC_LDIO_CHANNEL_MASK_13
            # CCRTNGFC_LDIO_CHANNEL_MASK_14
            # CCRTNGFC_LDIO_CHANNEL_MASK_15
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
  Output:  none
  Return:  _ccrtngfc_lib_error_number_t
              # CCRTNGFC_LIB_NO_ERROR          (successful)
              # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
              # CCRTNGFC_LIB_NOT_OPEN          (device not open)
              # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
              # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
              # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
*************************************************************************/
```

2.2.108 ccrtNGFC_LDIO_Set_Input_Snapshot()

This call allows the user to set the board in snapshot mode where the channel inputs to all the LDIO modules are acquired simultaneously (in sync) by the hardware and presented to the user. Mainly, this particular call is only useful for setting the operation to continuous mode. There is no need to set to snapshot mode as the read input registers call *ccrtNGFC_LDIO_Read_Input_Channel_Registers()* has an option to set it in the call.

If the user wants to collect data in the continuous mode, they should issue this call once with the *CCRTNGFC_LDIO_INPUT_OPERATION_CONTINUOUS* option and then call the read of the input channels with the *CCRTNGFC_DO_NOT_CHANGE* option. In this way, there is no un-necessary overhead in setting the board into continuous mode once it has already been set.

Recommended procedure for continuous mode is to issue this call only once with the *CCRTNGFC_LDIO_INPUT_OPERATION_CONTINUOUS* option and then followup with continuous input channel reads using the *ccrtNGFC_LDIO_Read_Input_Channel_Register()* call with the *CCRTNGFC_LDIO_INPUT_OPERATION_DO_NOT_CHANGE* option for *ldio_snapshot.*

Recommended procedure for snapshot mode is to issue continuous input channel reads using the *ccrtNGFC_LDIO_Read_Input_Channel_Register()* call with the *CCRTNGFCL_LDIO_INPUT_OPERATION_SNAPSHOT* option for *ldio_snapshot.* In this case, there is really no need to issue this *ccrtNGFC_LDIO_Set_Input_Snapshot()* call.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Set_Input_Snapshot(void                                *Handle,
                                    _ccrtngfc_ldio_input_snapshot_t   ldio_snapshot)

   Description: Set LDIO Input Snapshot

   Input:   void                              *Handle        (handle pointer)
   Output:  _ccrtngfc_ldio_input_snapshot_t  ldio_snapshot  (LVDS and Digital I/O snapshot)
               # CCRTNGFC_LDIO_INPUT_OPERATION_CONTINUOUS
               # CCRTNGFC_LDIO_INPUT_OPERATION_SNAPSHOT
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 *************************************************************************/
```

2.2.109 ccrtNGFC_LDIO_Set_Output_Sync()

This call allows the user to set the digital output channels to either *continuous* mode or *sync* mode for all the LVDS and DIO modules. When the board is in *continuous* mode, any update to anyof the LDIO modules will be immediately sent to the output lines. There will be no synchronization between the LDIO modules. When the sync mode is selected, no output is sent while updating the output registers. Once the output sync flag is set, the contents of all the LDIO modules will be sent simultaneously to the output lines.

Recommended procedure for *continuous* mode is to issue this call only once with the *CCRTNGFC_LDIO_OUTPUT_OPERATION_CONTINUOUS* option and then followup with continuous output channel writes using the *ccrtNGFC_LDIO_Write_Output_Channel_Register()* call with the *CCRTNGFC_LDIO_INPUT_OPERATION_DO_NOT_CHANGE* option for *ldio_sync.*

Recommended procedure for *sync* mode is to issue this call only once with the *CCRTNGFC_LDIO_OUTPUT_OPERATION_SYNC* option and then followed up with continuous output channel writes using the *ccrtNGFC_LDIO_Write_Output_Channel_Register()* call with the *CCRTNGFC_LDIO_OUTPUT_OPERATION_SYNC* option for *ldio_sync.*

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Set_Output_Sync(void                          *Handle,
                                 _ccrtngfc_ldio_output_sync_t   ldio_sync)

   Description: Set LDIO Output Sync

   Input:   void                              *Handle          (handle pointer)
            _ccrtngfc_ldio_output_sync_t    ldio_sync        (LVDS and Digital I/O sync)
               # CCRTNGFC_LDIO_OUTPUT_OPERATION_CONTINUOUS
               # CCRTNGFC_LDIO_OUTPUT_OPERATION_SYNC
   Output:  none
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ************************************************************************/
```

2.2.110 ccrtNGFC_LDIO_Write_Output_Channel_Registers()

This call writes the user supplied channel settings to the output channel registers for all the LVDS and DIO modules. There are two modes of operation for this call. (1) Continuous (2) Sync.

When the user selects the *continuous* operation, this call immediately sends out the channel data to the output lines as they are written to the output registers. There is therefore no synchronizing occurring between the LDIO modules. For performance improvements with this operational mode, it is recommended that the user sets the *continuous* option using the *ccrtNGFC_LDIO_Set_Output_Sync()* call once and then supply *CCRTNGFC_LDIO_OUTPUT_OPERATION_DO_NOT_CHANGE* to this call for more writes. In this way, an additional register access will not occur everytime this call is issued.

When the user selects the *sync* operation, they need to issue the *ccrtNGFC_LDIO_Set_Output_Sync()* call once with the *CCRTNGFC_LDIO_OUTPUT_OPERATION_*SYNC option, followed by issuing this call with the *CCRTNGFC_LDIO_OUTPUT_OPERATION_*SYNC option in *ldio_sync.*

Obviously, the *sync* option is only meaningful if the user selects channels *(using the channel selection mask)* that reside in at least two different LDIO modules.

The *skip_ldio_disable_check* (when set to *CCRTNGFC_FALSE*) causes the call to test for LDIO being enabled prior to proceeding. If this option is set to *CCRTNGFC_TRUE*, then no validation is performed. If the LDIO has not been enabled, output writes will not take place. The only reason for providing the option to disable the check is to improve the performance of the call. If the user can ensure that the LDIO is enabled prior to issuing this call, they can set this option to *CCRTNGFC_TRUE* so that no validation is performed and hence, improve performance.

In order to skip a LDIO module, simply set *ChannelSelectMask* to zero for that module. If *ChannelSelectMask* is set to NULL, then all channels for all LDIO modules are selected.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Write_Output_Channel_Registers(void                        *Handle,
                                                _ccrtngfc_ldio_output_sync_t ldio_sync,
                                                ccrtngfc_bool   skip_ldio_disabled_check,
                                                ccrtngfc_ldio_modules_t LDIO_OutputChannels,
                                                ccrtngfc_ldio_modules_t ChannelSelectMask)

   Description: Write LDIO Output Channel Registers

   Input:   void                          *Handle                        (handle pointer)
            _ccrtngfc_ldio_output_sync_t  ldio_sync                      (ldio_sync operation)
                # CCRTNGFC_LDIO_OUTPUT_OPERATION_CONTINUOUS
                # CCRTNGFC_LDIO_OUTPUT_OPERATION_SYNC
                # CCRTNGFC_LDIO_OUTPUT_OPERATION_DO_NOT_CHANGE
            ccrtngfc_bool                skip_ldio_disabled_check  (skip LVDS and Digital
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                                                                I/O disabled check)
    # CCRTNGFC_TRUE
    # CCRTNGFC_FALSE
ccrtngfc_ldio_modules_t  LDIO_OutputChannels      (output channel registers)
    # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
        # CCRTNGFC_LDIO_CHANNEL_MASK_0
        # CCRTNGFC_LDIO_CHANNEL_MASK_1
        # CCRTNGFC_LDIO_CHANNEL_MASK_2
        # CCRTNGFC_LDIO_CHANNEL_MASK_3
        # CCRTNGFC_LDIO_CHANNEL_MASK_4
        # CCRTNGFC_LDIO_CHANNEL_MASK_5
        # CCRTNGFC_LDIO_CHANNEL_MASK_6
        # CCRTNGFC_LDIO_CHANNEL_MASK_7
        # CCRTNGFC_LDIO_CHANNEL_MASK_8
        # CCRTNGFC_LDIO_CHANNEL_MASK_9
        # CCRTNGFC_LDIO_CHANNEL_MASK_10
        # CCRTNGFC_LDIO_CHANNEL_MASK_11
        # CCRTNGFC_LDIO_CHANNEL_MASK_12
        # CCRTNGFC_LDIO_CHANNEL_MASK_13
        # CCRTNGFC_LDIO_CHANNEL_MASK_14
        # CCRTNGFC_LDIO_CHANNEL_MASK_15
        # CCRTNGFC_LDIO_CHANNEL_MASK_16
        # CCRTNGFC_LDIO_CHANNEL_MASK_17
        # CCRTNGFC_LDIO_CHANNEL_MASK_18
        # CCRTNGFC_LDIO_CHANNEL_MASK_19
        # CCRTNGFC_LDIO_CHANNEL_MASK_20
        # CCRTNGFC_LDIO_CHANNEL_MASK_21
        # CCRTNGFC_LDIO_CHANNEL_MASK_22
        # CCRTNGFC_LDIO_CHANNEL_MASK_23
        # CCRTNGFC_LDIO_CHANNEL_MASK_24
        # CCRTNGFC_LDIO_CHANNEL_MASK_25
        # CCRTNGFC_LDIO_CHANNEL_MASK_26
        # CCRTNGFC_LDIO_CHANNEL_MASK_27
        # CCRTNGFC_LDIO_CHANNEL_MASK_28
        # CCRTNGFC_LDIO_CHANNEL_MASK_29
        # CCRTNGFC_LDIO_CHANNEL_MASK_30
        # CCRTNGFC_LDIO_CHANNEL_MASK_31
        # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
    CCRTNGFC_LDIO_MAX_MODULES can be one of:
        # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
        # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
        # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
        # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
        # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
        # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
ccrtngfc_ldio_modules_t  ChannelSelectMask       (output channel selection)
    # NULL                                       (select all channels)
    # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
        # CCRTNGFC_LDIO_CHANNEL_MASK_0
        # CCRTNGFC_LDIO_CHANNEL_MASK_1
        # CCRTNGFC_LDIO_CHANNEL_MASK_2
        # CCRTNGFC_LDIO_CHANNEL_MASK_3
        # CCRTNGFC_LDIO_CHANNEL_MASK_4
        # CCRTNGFC_LDIO_CHANNEL_MASK_5
        # CCRTNGFC_LDIO_CHANNEL_MASK_6
        # CCRTNGFC_LDIO_CHANNEL_MASK_7
        # CCRTNGFC_LDIO_CHANNEL_MASK_8
        # CCRTNGFC_LDIO_CHANNEL_MASK_9
        # CCRTNGFC_LDIO_CHANNEL_MASK_10
        # CCRTNGFC_LDIO_CHANNEL_MASK_11
        # CCRTNGFC_LDIO_CHANNEL_MASK_12
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
  Output:  none
  Return:  _ccrtngfc_lib_error_number_t
              # CCRTNGFC_LIB_NO_ERROR          (successful)
              # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
              # CCRTNGFC_LIB_NOT_OPEN          (device not open)
              # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
              # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
              # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
*************************************************************************/
```

2.2.111 ccrtNGFC_LDIO_Write_Output_Channel_ Registers_High()

This call writes a selected set of channels to high outputs for all the LVDS and DIO modules. Rest of the channels are not affected. There are two modes of operation for this call. (1) Continuous (2) Sync.

When the user selects the *continuous* operation, this call immediately sends out the channel high data to the selected output lines as they are written to the output registers. There is therefore no synchronizing occurring between all the LDIO modules. For performance improvements with this operational mode, it is recommended that the user sets the continuous option using the *ccrtNGFC_LDIO_Set_Output_Sync()* call once and then supply *CCRTNGFC_LDIO_OUTPUT_OPERATION_DO_NOT_CHANGE* to this call for more writes. In this way, an additional register access will not occur everytime this call is issued.

When the user selects the *sync* operation, they need to issue the *ccrtNGFC_LDIO_Set_Output_Sync()* call once with the *CCRTNGFC_LDIO_OUTPUT_OPERATION*_SYNC option, followed by issuing this call with the *CCRTNGFC_LDIO_OUTPUT_OPERATION*_SYNC option in *ldio_sync.*

Obviously, the *sync* option is only meaningful if the user selects channels *(sets channels for high)* that reside in at least two different LDIO modules.

The *skip_ldio_disable_check (*when set to *CCRTNGFC_FALSE)* causes the call to test for LDIO being enabled prior to proceeding. If this option is set to *CCRTNGFC_TRUE*, then no validation is performed. If the LDIO has not been enabled, output writes will not take place. The only reason for providing the option to disable the check is to improve

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

the performance of the call. If the user can ensure that the LDIO is enabled prior to issuing this call, they can set this option to *CCRTNGFC_TRUE* so that no validation is performed and hence, improve performance.

In order to skip a LDIO module, simply set *LDIO_OutputChannels* to zero for that module.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Write_Output_Channel_Registers_High(void                        *Handle,
                                                     _ccrtngfc_ldio_output_sync_t ldio_sync,
                                                     ccrtngfc_bool skip_ldio_disabled_check,
                                                     ccrtngfc_ldio_modules_t LDIO_OutputChannels)

   Description: Write LDIO Output Channel to Registers High

   Input:   void                          *Handle                  (handle pointer)
            _ccrtngfc_ldio_output_sync_t  ldio_sync                (ldio_sync operation)
                # CCRTNGFC_LDIO_OUTPUT_OPERATION_CONTINUOUS
                # CCRTNGFC_LDIO_OUTPUT_OPERATION_SYNC
                # CCRTNGFC_LDIO_OUTPUT_OPERATION_DO_NOT_CHANGE
            ccrtngfc_bool                 skip_ldio_disabled_check (skip LVDS and Digital
                                                                    I/O disabled check)
                # CCRTNGFC_TRUE
                # CCRTNGFC_FALSE
            ccrtngfc_ldio_modules_t   LDIO_OutputChannels      (output channel registers)
                # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LDIO_CHANNEL_MASK_0
                    # CCRTNGFC_LDIO_CHANNEL_MASK_1
                    # CCRTNGFC_LDIO_CHANNEL_MASK_2
                    # CCRTNGFC_LDIO_CHANNEL_MASK_3
                    # CCRTNGFC_LDIO_CHANNEL_MASK_4
                    # CCRTNGFC_LDIO_CHANNEL_MASK_5
                    # CCRTNGFC_LDIO_CHANNEL_MASK_6
                    # CCRTNGFC_LDIO_CHANNEL_MASK_7
                    # CCRTNGFC_LDIO_CHANNEL_MASK_8
                    # CCRTNGFC_LDIO_CHANNEL_MASK_9
                    # CCRTNGFC_LDIO_CHANNEL_MASK_10
                    # CCRTNGFC_LDIO_CHANNEL_MASK_11
                    # CCRTNGFC_LDIO_CHANNEL_MASK_12
                    # CCRTNGFC_LDIO_CHANNEL_MASK_13
                    # CCRTNGFC_LDIO_CHANNEL_MASK_14
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                    # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ************************************************************************/
```

2.2.112 ccrtNGFC_LDIO_Write_Output_Channel_Registers_Low()

This call writes a selected set of channels to low outputs for all the LVDS and DIO modules. Rest of the channels are not affected. There are two modes of operation for this call. (1) Continuous (2) Sync.

When the user selects the *continuous* operation, this call immediately sends out the channel low data to the output lines as they are written to the output registers. There is therefore no synchronizing occurring between all the LDIO modules. For performance improvements with this operational mode, it is recommended that the user sets the *continuous* option using the *ccrtNGFC_LDIO_Set_Output_Sync()* call once and then supply *CCRTNGFC_LDIO_OUTPUT_OPERATION_DO_NOT_CHANGE* to this call for more writes. In this way, an additional register access will not occur everytime this call is issued.

When the user selects the *sync* operation, they need to issue the *ccrtNGFC_LDIO_Set_Output_Sync()* call once with the *CCRTNGFC_LDIO_OUTPUT_OPERATION_*SYNC option, followed by issuing this call with the *CCRTNGFC_LDIO_OUTPUT_OPERATION_*SYNC option in *ldio_sync.*

Obviously, the *sync* option is only meaningful if the user selects channels *(sets channels for low)* that reside in at least two different LDIO mdoules.

The *skip_ldio_disable_check* (when set to *CCRTNGFC_FALSE*) causes the call to test for LDIO being enabled prior to proceeding. If this option is set to *CCRTNGFC_TRUE*, then no validation is performed. If the LDIO has not been enabled, output writes will not take place. The only reason for providing the option to disable the check is to improve the performance of the call. If the user can ensure that the LDIO is enabled prior to issuing this call, they can set this option to *CCRTNGFC_TRUE* so that no validation is performed and hence, improve performance.

In order to skip a LDIO module, simply set *LDIO_OutputChannels* to zero for that module.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. Additionally, if an optional DIO daughter-card is installed, then it can be selected by the CCRTNGFC_DC_DIO_MODULE_2 and/or CCRTNGFC_DC_DIO_MODULE_3 option depending on where the daughter-card is installed. *Currently there is not LIO daughter-card available.*

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LDIO_Write_Output_Channel_Registers_Low(void                          *Handle,
                                                   _ccrtngfc_ldio_output_sync_t ldio_sync,
                                                   ccrtngfc_bool skip_ldio_disabled_check,
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                                                    ccrtngfc_ldio_modules_t LDIO_OutputChannels)

Description: Write LDIO Output Channel to Registers Low

Input:   void                          *Handle                   (handle pointer)
         _ccrtngfc_ldio_output_sync_t  ldio_sync                 (ldio_sync operation)
             # CCRTNGFC_LDIO_OUTPUT_OPERATION_CONTINUOUS
             # CCRTNGFC_LDIO_OUTPUT_OPERATION_SYNC
             # CCRTNGFC_LDIO_OUTPUT_OPERATION_DO_NOT_CHANGE
         ccrtngfc_bool             skip_ldio_disabled_check     (skip LVDS and Digital
                                                                 I/O disabled check)
             # CCRTNGFC_TRUE
             # CCRTNGFC_FALSE
         ccrtngfc_ldio_modules_t    LDIO_OutputChannels    (output channel registers)
             # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                 # CCRTNGFC_LDIO_CHANNEL_MASK_0
                 # CCRTNGFC_LDIO_CHANNEL_MASK_1
                 # CCRTNGFC_LDIO_CHANNEL_MASK_2
                 # CCRTNGFC_LDIO_CHANNEL_MASK_3
                 # CCRTNGFC_LDIO_CHANNEL_MASK_4
                 # CCRTNGFC_LDIO_CHANNEL_MASK_5
                 # CCRTNGFC_LDIO_CHANNEL_MASK_6
                 # CCRTNGFC_LDIO_CHANNEL_MASK_7
                 # CCRTNGFC_LDIO_CHANNEL_MASK_8
                 # CCRTNGFC_LDIO_CHANNEL_MASK_9
                 # CCRTNGFC_LDIO_CHANNEL_MASK_10
                 # CCRTNGFC_LDIO_CHANNEL_MASK_11
                 # CCRTNGFC_LDIO_CHANNEL_MASK_12
                 # CCRTNGFC_LDIO_CHANNEL_MASK_13
                 # CCRTNGFC_LDIO_CHANNEL_MASK_14
                 # CCRTNGFC_LDIO_CHANNEL_MASK_15
                 # CCRTNGFC_LDIO_CHANNEL_MASK_16
                 # CCRTNGFC_LDIO_CHANNEL_MASK_17
                 # CCRTNGFC_LDIO_CHANNEL_MASK_18
                 # CCRTNGFC_LDIO_CHANNEL_MASK_19
                 # CCRTNGFC_LDIO_CHANNEL_MASK_20
                 # CCRTNGFC_LDIO_CHANNEL_MASK_21
                 # CCRTNGFC_LDIO_CHANNEL_MASK_22
                 # CCRTNGFC_LDIO_CHANNEL_MASK_23
                 # CCRTNGFC_LDIO_CHANNEL_MASK_24
                 # CCRTNGFC_LDIO_CHANNEL_MASK_25
                 # CCRTNGFC_LDIO_CHANNEL_MASK_26
                 # CCRTNGFC_LDIO_CHANNEL_MASK_27
                 # CCRTNGFC_LDIO_CHANNEL_MASK_28
                 # CCRTNGFC_LDIO_CHANNEL_MASK_29
                 # CCRTNGFC_LDIO_CHANNEL_MASK_30
                 # CCRTNGFC_LDIO_CHANNEL_MASK_31
                 # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
             CCRTNGFC_LDIO_MAX_MODULES can be one of:
                 # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                 # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                 # CCRTNGFC_DC_DIO_MODULE_2      // optional DIO Daughter Card
                 # CCRTNGFC_DC_DIO_MODULE_3      // optional DIO Daughter Card
                 # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                 # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
Output:  none
Return:  _ccrtngfc_lib_error_number_t
            # CCRTNGFC_LIB_NO_ERROR          (successful)
            # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
            # CCRTNGFC_LIB_NOT_OPEN          (device not open)
            # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)

 ***************************************************************************/
```

2.2.113 ccrtNGFC_LIO_On_Off()

This call is to turn ON or OFF the LVDS DIO Module. Normally, if the LVDS module is not used, it needs to be set to OFF as it generates a lot of heat.

The module selection for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. The CCRTNGFC_MAIN_DIO_MODULE_0 is for the DIO module that is located on the mother-board and is therefore invalid for this LIO API. *Currently there is no LIO daughter-card available.*

If the user needs to only inquire about the current state of a LVDS module, they need to call this API with *lio_on_off* set to *CCRTNGFC_LIO_MODULE_DO_NOT_CHANGE* for the selected module. Its current state is returned in *lio_state.*

If *lio_state* is set to NULL, then no current state information is returned.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 which is not valid for this API, and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. *Currently there is not LIO daughter-card available.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LIO_On_Off (void                          *Handle,
                        ccrtngfc_ldio_modules_t       lio_on_off,
                        ccrtngfc_ldio_modules_t       lio_state)

   Description: Turn On/Off LVDS I/O module

   Input:   void                                      *Handle         (Handle pointer)
            ccrtngfc_ldio_modules_t                   lio_on_off      (turn on/off LVDS module)
               # CCRTNGFC_LIO_MODULE_OFF
               # CCRTNGFC_LIO_MODULE_ON
               # CCRTNGFC_LIO_MODULE_DO_NOT_CHANGE
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card

   Output:  ccrtngfc_ldio_modules_t                   *lio_state     (on/off LVDS Module)
               # CCRTNGFC_LIO_MODULE_OFF
               # CCRTNGFC_LIO_MODULE_ON
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR              (successful)
               # CCRTNGFC_LIB_BAD_HANDLE            (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN              (device not open)
               # CCRTNGFC_LIB_INVALID_ARG           (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION       (local region not present)
 ***************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.114 ccrtNGFC_LIO_Get_Ports_Direction()

This call returns to the user the direction of the LVDS I/O channels.

The module selection for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. The CCRTNGFC_MAIN_DIO_MODULE_0 is for the DIO module that is located on the mother-board and is therefore invalid for this LIO API. *Currently there is no LIO daughter-card available.*

Unlike the Digital I/O ports where each Digital I/O ports is on a per channel basis, the LVDS I/O ports are grouped into 4 channels each. E.g. CCRTNGFC_LIO_PORT_MASK_P0 controls channels 0..3, CCRTNGFC_LIO_PORT_MASK_P1 controls channels 4..7, etc.

The LIO test mode register determines whether a LIO port of LVDS signals are in test mode or not. The test mode is used to turn-around a single LIO port *(four channel group).* It is used in conjunction with only ONE direction port setting at a time to test the LVDS drivers and receivers. Any attempt to turn-around more than one LIO port at a time will be ignored.

When the direction for the channels are set as inputs, then reading the channels input registers will result in acquiring signals coming into the board from the external LVDS I/O lines.

When the direction for channels are set to output, then reading the channels input registers will result in invalid channel information being returned as the only way to read back (loopback) the channel information is to use the LIO Test Mode as specified with the *ccrtNGFC_LIO_Set_Ports_Direction()* call and select only ONE port to read at a time. If the user wishes to read back (loopback) the channel information for the LVDS I/O module, then they will need to use the specific *ccrtNGFC_LIO_Read_Output_Loopbacked_Channels()* call as that is specifically written for this purpose.

The module selection for the DIO located on the mother-board is CCRTNGFC_MAIN_DIO_MODULE_0 which is not valid for this API, and for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. *Currently there is not LIO daughter-card available.*

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LIO_Get_Ports_Direction(void                       *Handle,
                                    ccrtngfc_lio_test_modes_t  LIO_TestMode,
                                    ccrtngfc_lio_ports_t       LIO_PortDirection,
                                    ccrtngfc_lio_ports_t       PortSelectionMask)

   Description: Get LIO Ports Direction Mask

   Input:   void                          *Handle                  (handle pointer)
            ccrtngfc_lio_ports_t          PortSelectionMask        (port selection mask)
                # NULL                                             (select all ports)
                # _ccrtngfc_lio_port_mask_t
ccrtngfc_lio_ports_t[CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LIO_PORT_MASK_P0
                    # CCRTNGFC_LIO_PORT_MASK_P1
                    # CCRTNGFC_LIO_PORT_MASK_P2
                    # CCRTNGFC_LIO_PORT_MASK_P3
                    # CCRTNGFC_LIO_PORT_MASK_P4
                    # CCRTNGFC_LIO_PORT_MASK_P5
                    # CCRTNGFC_LIO_PORT_MASK_P6
                    # CCRTNGFC_LIO_PORT_MASK_P7
                    # CCRTNGFC_LIO_ALL_PORTS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   Output:  ccrtngfc_lio_test_modes_t       LIO_TestMode             (LVDS I/O test mode)
               # NULL Pointer                                       (skip testmode)
               # _ccrtngfc_lio_port_mode_t ccrtngfc_lio_test_modes_t[CCRTNGFC_LDIO_MAX_MODULES]
                   # CCRTNGFC_LIO_NORMAL_MODE
                   # CCRTNGFC_LIO_TEST_MODE
            ccrtngfc_lio_ports_t         LIO_PortDirection              (port direction)
                                         - CCRTNGFC_LDIO_DIRECTION_INPUT    = (0)
                                         - CCRTNGFC_LDIO_DIRECTION_OUTPUT   = (1)
               # _ccrtngfc_lio_port_mask_t ccrtngfc_lio_ports_t[CCRTNGFC_LDIO_MAX_MODULES]
                   # CCRTNGFC_LIO_PORT_MASK_P0
                   # CCRTNGFC_LIO_PORT_MASK_P1
                   # CCRTNGFC_LIO_PORT_MASK_P2
                   # CCRTNGFC_LIO_PORT_MASK_P3
                   # CCRTNGFC_LIO_PORT_MASK_P4
                   # CCRTNGFC_LIO_PORT_MASK_P5
                   # CCRTNGFC_LIO_PORT_MASK_P6
                   # CCRTNGFC_LIO_PORT_MASK_P7
                   # CCRTNGFC_LIO_ALL_PORTS_MASK
               CCRTNGFC_LDIO_MAX_MODULES can be one of:
                   # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                   # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                   # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                   # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN          (device not open)
               # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
               # CCRTNGFC_LIB_LIO_IS_NOT_ACTIVE (LIO is not active)
 ************************************************************************/
```

2.2.115 ccrtNGFC_LIO_Read_Output_Loopbacked_Channels()

This call returns to the user the loopbacked channel information for the selected the LVDS I/O modules.

The module selection for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. The CCRTNGFC_MAIN_DIO_MODULE_0 is for the DIO module that is located on the mother-board and is therefore invalid for this LIO API. *Currently there is no LIO daughter-card available.*

The LVDS I/O module is unable to read loopback information from channels in the normally way as is done by the Digital I/O module due to hardware limitations. For this reason, a special routine is written to read loopbacked channel information.

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LIO_Read_Output_Loopbacked_Channels(void                              *Handle,
                                                _ccrtngfc_ldio_input_snapshot_t  ldio_snapshot,
                                                ccrtngfc_bool         skip_ldio_disabled_check,
                                                ccrtngfc_ldio_modules_t LIO_LoopbackedChannels,
                                                ccrtngfc_ldio_modules_t      ChannelSelectMask)

   Description: Read LIO Output Loopbacked Channels

   Input:   void                              *Handle           (handle pointer)
            _ccrtngfc_ldio_input_snapshot_t  ldio_snapshot     (ldio_snapshot operation)
               # CCRTNGFC_LDIO_INPUT_OPERATION_CONTINUOUS
               # CCRTNGFC_LDIO_INPUT_OPERATION_SNAPSHOT
               # CCRTNGFC_LDIO_INPUT_OPERATION_DO_NOT_CHANGE
            ccrtngfc_bool         skip_ldio_disabled_check     (skip LVDS and Digital
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                                                                I/O disabled check)
            # CCRTNGFC_TRUE
            # CCRTNGFC_FALSE
        ccrtngfc_ldio_modules_t       ChannelSelectMask    (custom channel selection)
            # NULL                                        (select all channels)
            # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                # CCRTNGFC_LDIO_CHANNEL_MASK_0
                # CCRTNGFC_LDIO_CHANNEL_MASK_1
                # CCRTNGFC_LDIO_CHANNEL_MASK_2
                # CCRTNGFC_LDIO_CHANNEL_MASK_3
                # CCRTNGFC_LDIO_CHANNEL_MASK_4
                # CCRTNGFC_LDIO_CHANNEL_MASK_5
                # CCRTNGFC_LDIO_CHANNEL_MASK_6
                # CCRTNGFC_LDIO_CHANNEL_MASK_7
                # CCRTNGFC_LDIO_CHANNEL_MASK_8
                # CCRTNGFC_LDIO_CHANNEL_MASK_9
                # CCRTNGFC_LDIO_CHANNEL_MASK_10
                # CCRTNGFC_LDIO_CHANNEL_MASK_11
                # CCRTNGFC_LDIO_CHANNEL_MASK_12
                # CCRTNGFC_LDIO_CHANNEL_MASK_13
                # CCRTNGFC_LDIO_CHANNEL_MASK_14
                # CCRTNGFC_LDIO_CHANNEL_MASK_15
                # CCRTNGFC_LDIO_CHANNEL_MASK_16
                # CCRTNGFC_LDIO_CHANNEL_MASK_17
                # CCRTNGFC_LDIO_CHANNEL_MASK_18
                # CCRTNGFC_LDIO_CHANNEL_MASK_19
                # CCRTNGFC_LDIO_CHANNEL_MASK_20
                # CCRTNGFC_LDIO_CHANNEL_MASK_21
                # CCRTNGFC_LDIO_CHANNEL_MASK_22
                # CCRTNGFC_LDIO_CHANNEL_MASK_23
                # CCRTNGFC_LDIO_CHANNEL_MASK_24
                # CCRTNGFC_LDIO_CHANNEL_MASK_25
                # CCRTNGFC_LDIO_CHANNEL_MASK_26
                # CCRTNGFC_LDIO_CHANNEL_MASK_27
                # CCRTNGFC_LDIO_CHANNEL_MASK_28
                # CCRTNGFC_LDIO_CHANNEL_MASK_29
                # CCRTNGFC_LDIO_CHANNEL_MASK_30
                # CCRTNGFC_LDIO_CHANNEL_MASK_31
                # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
            CCRTNGFC_LDIO_MAX_MODULES can be one of:
                # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
Output:  ccrtngfc_ldio_modules_t   LIO_LoopbackedChannels    (LIO Loopbacked channels)
            # u_int32_t   ccrtngfc_ldio_modules_t [CCRTNGFC_LDIO_MAX_MODULES]
                # CCRTNGFC_LDIO_CHANNEL_MASK_0
                # CCRTNGFC_LDIO_CHANNEL_MASK_1
                # CCRTNGFC_LDIO_CHANNEL_MASK_2
                # CCRTNGFC_LDIO_CHANNEL_MASK_3
                # CCRTNGFC_LDIO_CHANNEL_MASK_4
                # CCRTNGFC_LDIO_CHANNEL_MASK_5
                # CCRTNGFC_LDIO_CHANNEL_MASK_6
                # CCRTNGFC_LDIO_CHANNEL_MASK_7
                # CCRTNGFC_LDIO_CHANNEL_MASK_8
                # CCRTNGFC_LDIO_CHANNEL_MASK_9
                # CCRTNGFC_LDIO_CHANNEL_MASK_10
                # CCRTNGFC_LDIO_CHANNEL_MASK_11
                # CCRTNGFC_LDIO_CHANNEL_MASK_12
                # CCRTNGFC_LDIO_CHANNEL_MASK_13
                # CCRTNGFC_LDIO_CHANNEL_MASK_14
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                    # CCRTNGFC_LDIO_CHANNEL_MASK_15
                    # CCRTNGFC_LDIO_CHANNEL_MASK_16
                    # CCRTNGFC_LDIO_CHANNEL_MASK_17
                    # CCRTNGFC_LDIO_CHANNEL_MASK_18
                    # CCRTNGFC_LDIO_CHANNEL_MASK_19
                    # CCRTNGFC_LDIO_CHANNEL_MASK_20
                    # CCRTNGFC_LDIO_CHANNEL_MASK_21
                    # CCRTNGFC_LDIO_CHANNEL_MASK_22
                    # CCRTNGFC_LDIO_CHANNEL_MASK_23
                    # CCRTNGFC_LDIO_CHANNEL_MASK_24
                    # CCRTNGFC_LDIO_CHANNEL_MASK_25
                    # CCRTNGFC_LDIO_CHANNEL_MASK_26
                    # CCRTNGFC_LDIO_CHANNEL_MASK_27
                    # CCRTNGFC_LDIO_CHANNEL_MASK_28
                    # CCRTNGFC_LDIO_CHANNEL_MASK_29
                    # CCRTNGFC_LDIO_CHANNEL_MASK_30
                    # CCRTNGFC_LDIO_CHANNEL_MASK_31
                    # CCRTNGFC_LDIO_ALL_CHANNELS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
  Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
 ************************************************************************/
```

2.2.116 ccrtNGFC_LIO_Set_Ports_Direction()

This call sets the direction of the LVDS I/O channels.

The module selection for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. The CCRTNGFC_MAIN_DIO_MODULE_0 is for the DIO module that is located on the mother-board and is therefore invalid for this LIO API. *Currently there is no LIO daughter-card available.*

Unlike the Digital I/O ports where each Digital I/O ports is on a per channel basis, the LVDS I/O ports are grouped into 4 channels each. E.g. CCRTNGFC_LIO_PORT_MASK_P0 controls channels 0..3, CCRTNGFC_LIO_PORT_MASK_P1 controls channels 4..7, etc.

The LIO test mode register determines whether a LIO port of LVDS signals are in test mode or not. The test mode is used to turn-around a single LIO port *(four channel group).* It is used in conjunction with only ONE direction port setting at a time to test the LVDS drivers and receivers. Any attempt to turn-around more than one LIO port at a time will be ignored.

When the direction for the channels are set as inputs, then reading the channels input registers will result in acquiring signals coming into the board from the external LVDS I/O lines.

When the direction for channels are set to output, then reading the channels input registers will result in invalid channel information being returned as the only way to read back (loopback) the channel information is to use the LIO Test Mode as specified with the *ccrtNGFC_LIO_Set_Ports_Direction()* call and select only ONE port to read at a time. If the user wishes to read back (loopback) the channel information for the LVDS I/O module, then they will need to use the specific *ccrtNGFC_LIO_Read_Output_Loopbacked_Channels()* call as that is specifically written for this purpose.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

When issuing this call, the users must initialize *all* available LIO modules properly, otherwise the call will fail. If an LIO module is to be skipped in this call, the *LDIO_PortSelectionMask* for a LIO module must be set to zero *(i.e. no ports are selected)*.

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LIO_Set_Ports_Direction(void                      *Handle,
                                    ccrtngfc_lio_test_modes_t LIO_TestMode,
                                    ccrtngfc_lio_ports_t      LIO_PortDirection,
                                    ccrtngfc_lio_ports_t      PortSelectionMask)

   Description: Set LIO Port Direction Mask

   Input:   void                          *Handle                    (handle pointer)
            ccrtngfc_lio_test_modes_t     LIO_TestMode               (LVDS I/O test mode)
                # _ccrtngfc_lio_port_mode_t ccrtngfc_lio_test_modes_t[CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LIO_NORMAL_MODE
                    # CCRTNGFC_LIO_TEST_MODE
            ccrtngfc_lio_ports_t          LIO_PortDirection          (port direction)
                                          - CCRTNGFC_LDIO_DIRECTION_INPUT    = (0)
                                          - CCRTNGFC_LDIO_DIRECTION_OUTPUT   = (1)
                # _ccrtngfc_lio_port_mask_t   ccrtngfc_lio_ports_t[CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LIO_PORT_MASK_P0
                    # CCRTNGFC_LIO_PORT_MASK_P1
                    # CCRTNGFC_LIO_PORT_MASK_P2
                    # CCRTNGFC_LIO_PORT_MASK_P3
                    # CCRTNGFC_LIO_PORT_MASK_P4
                    # CCRTNGFC_LIO_PORT_MASK_P5
                    # CCRTNGFC_LIO_PORT_MASK_P6
                    # CCRTNGFC_LIO_PORT_MASK_P7
                    # CCRTNGFC_LIO_ALL_PORTS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
            ccrtngfc_lio_ports_t          PortSelectionMask          (port selection mask)
                # NULL                                               (select all ports)
                # _ccrtngfc_lio_port_mask_t   ccrtngfc_lio_ports_t[CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LIO_PORT_MASK_P0
                    # CCRTNGFC_LIO_PORT_MASK_P1
                    # CCRTNGFC_LIO_PORT_MASK_P2
                    # CCRTNGFC_LIO_PORT_MASK_P3
                    # CCRTNGFC_LIO_PORT_MASK_P4
                    # CCRTNGFC_LIO_PORT_MASK_P5
                    # CCRTNGFC_LIO_PORT_MASK_P6
                    # CCRTNGFC_LIO_PORT_MASK_P7
                    # CCRTNGFC_LIO_ALL_PORTS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_LIB_LIO_TEST_MODE_SETTING_ERROR
                                                (Only one output port must be set)
 ***************************************************************************/
```

2.2.117 ccrtNGFC_LIO_Set_Ports_Direction_To_Input()

This call sets the direction of the LVDS I/O channels to input.

The module selection for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. The CCRTNGFC_MAIN_DIO_MODULE_0 is for the DIO module that is located on the mother-board and is therefore invalid for this LIO API. *Currently there is no LIO daughter-card available.*

Unlike the Digital I/O ports where each Digital I/O ports is on a per channel basis, the LVDS I/O ports are grouped into 4 channels each. E.g. CCRTNGFC_LIO_PORT_MASK_P0 controls channels 0..3, CCRTNGFC_LIO_PORT_MASK_P1 controls channels 4..7, etc.

When the direction for channels are set to output, then reading the channels input registers will result in invalid channel information being returned as the only way to read back (loopback) the channel information is to use the LIO Test Mode as specified with the *ccrtNGFC_LIO_Set_Ports_Direction()* call and select only ONE port to read at a time. If the user wishes to read back (loopback) the channel information for the LVDS I/O module, then they will need to use the specific *ccrtNGFC_LIO_Read_Output_Loopbacked_Channels()* call as that is specifically written for this purpose.

If the LIO test mode is previously set, then only one port (4 channels) can be set for output. If more than one port is set or no ports are set for output, then the firmware action is unpredictable.
In order to skip a DIO module, simply set *LIO_InputPortDirection* to zero for that module.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LIO_Set_Ports_Direction_To_Input(void                  *Handle,
                                             ccrtngfc_lio_ports_t  LIO_InputPortDirection)

      Description: Set LIO Port Direction To Input

   Input:   void                        *Handle                      (handle pointer)
            ccrtngfc_lio_ports_t        LIO_InputPortDirection       (input port direction)
                # _ccrtngfc_lio_port_mask_t   ccrtngfc_lio_ports_t[CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LIO_PORT_MASK_P0
                    # CCRTNGFC_LIO_PORT_MASK_P1
                    # CCRTNGFC_LIO_PORT_MASK_P2
                    # CCRTNGFC_LIO_PORT_MASK_P3
                    # CCRTNGFC_LIO_PORT_MASK_P4
                    # CCRTNGFC_LIO_PORT_MASK_P5
                    # CCRTNGFC_LIO_PORT_MASK_P6
                    # CCRTNGFC_LIO_PORT_MASK_P7
                    # CCRTNGFC_LIO_ALL_PORTS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
               # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
               # CCRTNGFC_LIB_LIO_TEST_MODE_SETTING_ERROR
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                                                    (Only one output port must be set)

*****************************************************************************/
```

2.2.118 ccrtNGFC_LIO_Set_Ports_Direction_To_Output()

This call sets the direction of the LVDS I/O channels to output.

The module selection for the LIO located on the mother-board is CCRTNGFC_MAIN_LIO_MODULE_1. The CCRTNGFC_MAIN_DIO_MODULE_0 is for the DIO module that is located on the mother-board and is therefore invalid for this LIO API. *Currently there is no LIO daughter-card available.*

Unlike the Digital I/O ports where each Digital I/O ports is on a per channel basis, the LVDS I/O ports are grouped into 4 channels each. E.g. CCRTNGFC_LIO_PORT_MASK_P0 controls channels 0..3, CCRTNGFC_LIO_PORT_MASK_P1 controls channels 4..7, etc.

When the direction for channels are set to output, then reading the channels input registers will result in invalid channel information being returned as the only way to read back (loopback) the channel information is to use the LIO Test Mode as specified with the *ccrtNGFC_LIO_Set_Ports_Direction()* call and select only ONE port to read at a time. If the user wishes to read back (loopback) the channel information for the LVDS I/O module, then they will need to use the specific *ccrtNGFC_LIO_Read_Output_Loopbacked_Channels()* call as that is specifically written for this purpose.

If the LIO test mode is previously set, then only one port (4 channels) can be set for output. If more than one port is set or no ports are set for output, then the firmware action is unpredictable.

In order to skip a DIO module, simply set *LIO_OutputPortDirection* to zero for that module.

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_LIO_Set_Ports_Direction_To_Output(void                  *Handle,
                                              ccrtngfc_lio_ports_t  LIO_OutputPortDirection)

   Description: Set LIO Port Direction To Output

   Input:   void                       *Handle                     (handle pointer)
            ccrtngfc_lio_ports_t       LIO_OutputPortDirection     (output port direction)
                # _ccrtngfc_lio_port_mask_t   ccrtngfc_lio_ports_t[CCRTNGFC_LDIO_MAX_MODULES]
                    # CCRTNGFC_LIO_PORT_MASK_P0
                    # CCRTNGFC_LIO_PORT_MASK_P1
                    # CCRTNGFC_LIO_PORT_MASK_P2
                    # CCRTNGFC_LIO_PORT_MASK_P3
                    # CCRTNGFC_LIO_PORT_MASK_P4
                    # CCRTNGFC_LIO_PORT_MASK_P5
                    # CCRTNGFC_LIO_PORT_MASK_P6
                    # CCRTNGFC_LIO_PORT_MASK_P7
                    # CCRTNGFC_LIO_ALL_PORTS_MASK
                CCRTNGFC_LDIO_MAX_MODULES can be one of:
                    # CCRTNGFC_MAIN_DIO_MODULE_0    // On Main Board - DIO
                    # CCRTNGFC_MAIN_LIO_MODULE_1    // On Main Board - LIO
                    # CCRTNGFC_DC_LIO_MODULE_2      // optional LIO Daughter Card
                    # CCRTNGFC_DC_LIO_MODULE_3      // optional LIO Daughter Card
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR           (successful)
               # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN           (device not open)
               # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION    (local region not present)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                # CCRTNGFC_LIB_LDIO_IS_NOT_ACTIVE (LDIO is not active)
                # CCRTNGFC_LIB_LIO_TEST_MODE_SETTING_ERROR
                                                (Only one output port must be set)
 ***************************************************************************/
```

2.2.119 ccrtNGFC_MMap_Physical_Memory()

This call is provided for advanced users to create a physical memory of specified size that can be used for DMA or MsgDMA. The allocated DMA memory is rounded to a page size. If a physical memory is not available, this call will fail, at which point the user will need to issue the *ccrtNGFC_Munmap_Physical_Memory()* API call to remove any previously allocated physical memory.

When user wishes to allocate a physical memory, they must make sure that the ***phys_mem_ptr*** in the ***ccrtngfc_user_phys_mem_t*** structure is set to 0, otherwise the call will fail.

Instead of creating a physical memory, this same call can be used to map a user specified region if ***region addressing*** support is enabled as part of the Cloning feature. In this case, the user will need to supply a valid physical address of a Cloning Region to the ***phys_mem_ptr*** argument in this call.

Additionally, it is meaningless to perform Cloning on a FIFO region for two reasons. Firstly, each data in a FIFO is synchronous, however, the Cloned region is accessed asynchronously. Secondly, when the FIFO runs empty *(underflow)* or cannot accept more data *(overflow)* the results are unpredictable.

Caution: Since physical addresses are supplied for the MsgDma operation, care must be taken to ensure that the supplied addresses are valid and that while DMA is in progress, the memory regions must not be freed or made inactive, otherwise, the results could be unpredictable and could lead to the possible corruption of the system.

If the user supplies a non-zero ***phys_mem_ptr*** argument, the driver will attempt to request access to the memory region supplied by the user. If access to the region is denied, the call will fail. Reasons for access being denied is because the region has been reserved by some other process and is possibly in use. In this case, if the user still wishes to get access to the region, they can do so *at their own risk* by supplying the *CCRTNGFC_DISABLE_REGION_PROTECTION* flag to the *flags* argument. If the call still fails, there is no way for the user to access the memory region as the kernel controls this access. One such reason is that the user is trying to access an invalid region.

Whether a physical memory is acquired by the driver or supplied by the user, the driver by default *caches* the memory region and returns a mapped virtual address to the user. If the user does not wish the region to be *cached*, they can supply the *CCRTNGFC_DISABLE_ADDRESS_CACHE* flag to the *flags* argument. This may be useful if the user is running into problems with the region being *cached,* however, a noticeable performance degredation will be observed when accessing the region.

The *CCRTNGFC_DEVICE_ADDRESS_ENTRY* is used internally by the driver and is only available as information to the user.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MMap_Physical_Memory (void                        *Handle,
                                  int                         size,
                                  ccrtngfc_user_phys_mem_t    *phys_mem)

   Description: Allocate a physical DMA memory for size bytes.

   Input:   void                        *Handle          (Handle pointer)
            int                         size             (size in bytes)
   Output:  ccrtngfc_user_phys_mem_t    *phys_mem        (mem struct pointer)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                uint                    user_pid
                void                    *phys_mem_ptr
                void                    *driver_virt_mem_ptr
                void                    *mmaped_user_mem_ptr
                uint                    phys_mem_size
                uint                    phys_mem_size_freed
                uint                    entry_num_in_tran_table
                ushort                  flags
                   # CCRTNGFC_DEVICE_ADDRESS_ENTRY
                   # CCRTNGFC_DISABLE_ADDRESS_CACHE
                   # CCRTNGFC_DISABLE_REGION_PROTECTION
                ushort                  num_of_entries_used
   Return:  _ccrtngfc_lib_error_number_t
                # CCRTNGFC_LIB_NO_ERROR           (successful)
                # CCRTNGFC_LIB_BAD_HANDLE         (no/bad handler supplied)
                # CCRTNGFC_LIB_NOT_OPEN           (device not open)
                # CCRTNGFC_LIB_INVALID_ARG        (invalid argument)
                # CCRTNGFC_LIB_MMAP_SELECT_FAILED (mmap selection failed)
                # CCRTNGFC_LIB_MMAP_FAILED        (mmap failed)
                # CCRTNGFC_LIB_NO_SPACE_IN_TABLE  (no space in phys memory table)
                # CCRTNGFC_LIB_REGION_ADDRESSING_NOT_SUPPORTED
                                                  (region addressing not
                                                   supported by the card)
                # CCRTNGFC_LIB_MSGDMA_ACCESS_NOT_ALLOWED_FOR_SELECTED_ADDRESS
                                                  (access not allowed for selected address)
*****************************************************************************/
```

2.2.120 ccrtNGFC_MsgDma_Clone() *(US Patent No.: US 11,281,584 B1®)*

This call allows the user to Clone a transfer so that the process is continuously performing MsgDma once it has started until the Cloning operation is stopped by the user. This approach is different from standard MsgDma where a user has to re-initiate a MsgDma transfer every time it completes.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE*. In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

The following are the operation modes for this call:

- CCRTNGFC_MSGDMA_CLONE_INITIALIZE
- CCRTNGFC_MSGDMA_CLONE_ONE_CYCLE_WAIT
- CCRTNGFC_MSGDMA_CLONE_START
- CCRTNGFC_MSGDMA_CLONE_STOP

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

In order to perform a Cloning operation, the user first performs the same functions of MsgDma to seize, configure descriptors and MsgDma setup using the *ccrtNGFC_MsgDma_Seize(), ccrtNGFC_MsgDma_Configure_Descriptor()* and *ccrtNGFC_MsgDma_Setup()* calls. Once that is done, the user needs to stop any previous MsgDma operation and initialize the cloning operation using (*CCRTNGFC_MSGDMA_CLONE_STOP | CCRTNGFC_MSGDMA_CLONE_INITIALIZE*) modes.

Now, whenever the user is ready, they can commence cloning operation with the *CCRTNGFC_MSGDMA_CLONE_START* mode. At this point, MsgDma transfers start occurring continuously at the hardware level. If a chained MsgDma is configured, the entire chain is completed before it is repeated. Once Cloning has commenced, it can me stopped with the help of the *CCRTNGFC_MSGDMA_CLONE_STOP* mode.

Once the operation has started with the *CCRTNGFC_MSGDMA_CLONE_START* mode, it will run continuously under hardware control until stopped. There is no way to determine precisely how long a single descriptor cycle takes to complete. If the *CCRTNGFC_MSGDMA_CLONE_ONE_CYCLE_WAIT* mode is set along with the *CCRTNGFC_MSGDMA_CLONE_START* mode, the call will be blocked for the first transfer until the full descriptor cycle has completed. This approximate duration is also saved internally in the driver and is available to the user in the *CloneArgs->MsgDmaExtDesOnlyCycleDelay* argument. Anytime the user wishes to block their application for a duration of approximately one cycle delay, they can invoke this call with the *CCRTNGFC_MSGDMA_CLONE_ONE_CYCLE_WAIT* as the only mode. If the user wishes to block more or less than the one cycle delay whenever the call is issued, they can specify the number of additional nano-seconds to block in the *CloneArgs->AdditionalOneCycleDelay.* A negative value will reduce the delay while a positive value will increase it. This call will have no effect on the Cloning operation in progress.

This Cloning feature can prove very helpful to users who don't want to perform single MsgDma calls to transfer a region from a card to a physical memory that is continuously changing. They can basically Clone the two regions and simply read the physical memory while the hardware is continuously updating it with the latest data from the card region at MsgDma rate. There is no CPU overhead during Cloning, however, it will be utilizing the PCI bus during its operation.

Since there are more than one MsgDMA engines, several Cloning or MsgDma operation can be active at a given time. Additionally, it is meaningless to perform Cloning on a FIFO region for two reasons. Firstly, each data in a FIFO is synchronous, however, the Cloned region is accessed asynchronously. Secondly, when the FIFO runs empty *(underflow)* or cannot accept more data *(overflow)* the results are unpredictable.

<u>Caution</u>: Since physical addresses are supplied for the MsgDma operation, care must be taken to ensure that the supplied addresses are valid and that while Cloning is in progress, the memory regions must not be freed or made inactive, otherwise, the results could be unpredictable and could lead to the possible corruption of the system.

```
/*****************************************************************************
   ccrtNGFC_MsgDma_Clone()
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Clone(void                                  *Handle,
                         _ccrtngfc_msgdma_engine_t             MsgDmaEngine,
                         _ccrtngfc_msgdma_clone_mode_mask_t    ModeMask,
                         ccrtngfc_msgdma_clone_args_t          *CloneArgs)

   Description: Clone Modular Scatter-Gather DMA

   Input:   void                                    *Handle  (Handle pointer)
            _ccrtngfc_msgdma_engine_t               MsgDmaEngine
               # CCRTNGFC_MSGDMA_ENGINE_0       // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1       // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2       // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3       // NGFC quad-word, SDFC double-word transfers
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                  # CCRTNGFC_MSGDMA_ENGINE_4       // single-word transfers
                  # CCRTNGFC_MSGDMA_ENGINE_5       // single-word transfers
               _ccrtngfc_msgdma_clone_mode_mask_t      ModeMask (Mode Mask)
                  # CCRTNGFC_MSGDMA_CLONE_INITIALIZE
                  # CCRTNGFC_MSGDMA_CLONE_ONE_CYCLE_WAIT
                  # CCRTNGFC_MSGDMA_CLONE_START
                  # CCRTNGFC_MSGDMA_CLONE_STOP
               ccrtngfc_msgdma_clone_args_t            *CloneArgs
                  - unsigned long long                 AdditionalOneCycleDelay
                                                       (Additional blocking for One Cycle Delay
                                                        (nanoseconds))
      Output:  ccrtngfc_msgdma_clone_args_t            *CloneArgs
                  - unsigned long long                 MsgDmaExtDesOneCycleDelay
                                                       (MsgDma Extended Descriptor One Cycle
                                                        Delay (nanoseconds))
      Return:  _ccrtngfc_lib_error_number_t
                  # CCRTNGFC_LIB_NO_ERROR              (successful)
                  # CCRTNGFC_LIB_INVALID_ARG           (invalid argument)
                  # CCRTNGFC_LIB_MSGDMA_FAILED         (MsgDma failed)
                  # CCRTNGFC_LIB_MSGDMA_IN_USE         (MsgDma in use)
                  # CCRTNGFC_LIB_MSGDMA_NOT_SETUP      (MsgDma not setup)
                  # CCRTNGFC_LIB_NOT_OWNER_OF_MSGDMA   (not owner of MsgDma)
                  # CCRTNGFC_LIB_MSGDMA_FAILED         (MsgDma failed to start)
                  # CCRTNGFC_LIB_MSGDMA_ACCESS_NOT_ALLOWED_FOR_SELECTED_ADDRESS
                                                       (MsgDma not allowed for selected address)
                  # CCRTNGFC_LIB_CLONING_NOT_SUPPORTED (Cloning not supported by the card)
   ************************************************************************/
```

2.2.121 ccrtNGFC_MsgDma_Configure_Descriptor()

This call assists the user in setting up modular scatter-gather DMA descriptors. It allows the user to specify a read and write address offset along with length of transfer. Additionally, the call also provides the option to attach to other previously created descriptor blocks for scatter-gather operation. To perform scatter-gather DMA operation, the user creates a chain of descriptors, each having its own read/write/length information along with a start and end of the chain. The DMA operation is started from the first descriptor block in the chain and sequentially processes the descriptor blocks until the last descriptor block in the chain is processed.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE*. In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

To distinguish between descriptors, they are labeled with descriptor ID's. They range from ID 1 to 31. Users can supply a valid specific ID to this call or let the call itself find a free descriptor ID available. It is entirely left up to the user to determine how to manage the various descriptors and their relative linkages.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

If the user wishes to have a previously created descriptor to point to a newly created descriptor, they can supply the previously created descriptor ID to the *AttachToDescriptorID* argument in the newly created descriptor. The newly created descriptor will not point to any descriptor and will always be the last descriptor in the chain.

DMA transfers can occur from either of the following:

1. Physical PCIe memory to Physical PCIe memory
2. Physical PCIe memory to Avalon Memory
3. Avalon Memory to Physical PCIe memory
4. Avalon Memory to Avalon Memory

There are certain restrictions and limitations to this scatter-gather operation:

1. Scatter-gather DMA is only supported in certain FPGA cards
2. Invalid physical memory and/or Avalon memory address supplied could result in the scatter-gather IP to lock up and the only way to recover will be to reload the driver or reboot the system.
3. Read and write addresses must be at a minimum full-word aligned and for maximum performance, it is recommended to be quad-word aligned.
4. Lengths are in bytes and must be at a minimum a multiple of a full-word and for maximum performance, it is recommended to be quad-word multiple.
5. You cannot cause a chain of descriptors to loop on itself.

```
/*****************************************************************************
   ccrtNGFC_MsgDma_Configure_Descriptor()
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Configure_Descriptor (void                                *Handle,
                                         _ccrtngfc_msgdma_engine_t          MsgDmaEngine,
                                         _ccrtngfc_msgdma_descriptors_id_t *DescriptorID,
                                         ccrtngfc_msgdma_descriptor_t      *Descriptor,
                                         _ccrtngfc_msgdma_descriptors_id_t
                                                                           AttachToDescriptorID)

   Description: Configure Modular Scatter-Gather DMA descriptor

   Input:   void                                    *Handle (Handle pointer)
            _ccrtngfc_msgdma_engine_t               MsgDmaEngine
               # CCRTNGFC_MSGDMA_ENGINE_0          // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1          // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2          // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3          // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_4          // single-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_5          // single-word transfers

            _ccrtngfc_msgdma_descriptors_id_t *DescriptorID (Set to NULL or valid ID)
               # 0                                  (let function find a free ID)
               # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_1 ... CCRTNGFC_MSGDMA_DESCRIPTOR_ID_31
            ccrtngfc_msgdma_descriptor_t *Descriptor (pointer to descriptor)
               __u64  ReadAddress
               __u64  WriteAddress
               __u32  Length
            _ccrtngfc_msgdma_descriptors_id_t AttachToDescriptorID  (Attach to descriptor ID)
               # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_1 ... CCRTNGFC_MSGDMA_DESCRIPTOR_ID_31
   Output:  _ccrtngfc_msgdma_descriptors_id_t *DescriptorID (returned ID)
               # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_1 ... CCRTNGFC_MSGDMA_DESCRIPTOR_ID_31
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN             (device not open)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
               # CCRTNGFC_LIB_NO_FREE_DESCRIPTORS_AVAILABLE (no free descriptors available)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED (modular scatter-gather DMA not supported)
                # CCRTNGFC_LIB_MSGDMA_READS_NOT_ALLOWED_FOR_SELECTED_ADDRESS
                                                (MSG DMA Reads not allowed for selected
                                                 address)
                # CCRTNGFC_LIB_MSGDMA_BUSY      (MsgDma Busy, cannot be reset)
                # CCRTNGFC_LIB_NOT_OWNER_OF_MSGDMA   (not owner of modular scatter-gather)
                # CCRTNGFC_LIB_DATA_WIDTH_NOT_MULTIPLE_OR_ALIGNED
                                                (Data Width Not Multiple or Aligned)
 ***************************************************************************/
```

2.2.122 ccrtNGFC_MsgDma_Configure_Single()

This call performs a similar function to the *ccrtNGFC_MsgDma_Configure()* call with the exception that no DMA chaining is performed and only the single descriptor ID-1 is used to perform the DMA operation. The user has the option to supply a valid descriptor block when using the *ccrtNGFC_MsgDma_Configure_Single()* API or a *NULL* pointer to the descriptor as an argument when using the *ccrtNGFC_Transfer_Data()* API to perform the transfer.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE*. In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

Normally this call needs to be issued once with a *NULL* pointer for the *Descriptor (i.e. during initialization)* prior to using the *ccrtNGFC_Transfer_Data()* call with the *LibMode* set to *CCRTNGFC_LIBRARY_MSGDMA_MOD*. In this way, the descriptor ID-1 will be set up correctly prior to the transfer.

If instead, the user wishes to perform the DMA operation using the *ccrtNGFC_MsgDma_Fire_Single()* call, they need to issue the *ccrtNGFC_MsgDma_Configure_Single()* call with a valid descriptor block, otherwise, results will be unpredictable.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Configure_Single (void                                  *Handle,
                                     _ccrtngfc_msgdma_engine_t             MsgDmaEngine,
                                     ccrtngfc_msgdma_descriptor_t          *Descriptor)

   Description: Configure Single Modular Scatter-Gather DMA descriptor

   Input:   void                                 *Handle (Handle pointer)
            _ccrtngfc_msgdma_engine_t            MsgDmaEngine
               # CCRTNGFC_MSGDMA_ENGINE_0        // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1        // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2        // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3        // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_4        // single-word transfers
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_MSGDMA_ENGINE_5          // single-word transfers
          ccrtngfc_msgdma_descriptor_t *Descriptor (pointer to descriptor)
             __u64  ReadAddress
             __u64  WriteAddress
             __u32  Length
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
             # CCRTNGFC_LIB_NO_ERROR             (successful)
             # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
             # CCRTNGFC_LIB_NOT_OPEN             (device not open)
             # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
             # CCRTNGFC_LIB_MSGDMA_BUSY          (MsgDma Busy, cannot be reset)
             # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED (modular scatter-gather DMA not supported)
             # CCRTNGFC_LIB_MSGDMA_READS_NOT_ALLOWED_FOR_SELECTED_ADDRESS
                                                 (MSG DMA Reads not allowed for selected
                                                  address)
             # CCRTNGFC_LIB_MSGDMA_BUSY          (MsgDma Busy, cannot be reset)
             # CCRTNGFC_LIB_NOT_OWNER_OF_MSGDMA  (not owner of modular scatter-gather)
             # CCRTNGFC_LIB_DATA_WIDTH_NOT_MULTIPLE_OR_ALIGNED
                                                 (Data Width Not Multiple or Aligned)
*****************************************************************************/
```

2.2.123 ccrtNGFC_MsgDma_Fire()

This call initiates a scatter-gather DMA operation that has been previously configured and setup by the *ccrtNGFC_MsgDma_Configure()* and *ccrtNGFC_MsgDma_Setup()* call.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE*. In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

The *StartDescriptorID* can be set to either '0' or a valid Descriptor ID. Normally, the user will set the *StartDescriptiorID* in the *ccrtNGFC_MsgDma_Setup()* API during initialization and set it to '0' in this *ccrtNGFC_MsgDma_Fire()* API. In this way, this call will not suffer the overhead of loading the *StartDescriptorID* in the internal prefetcher register when repeatedly calling the *ccrtNGFC_MsgDma_Fire()* API. If the user specifies a valid *StartDescriptorID* that is already setup as a scatter-gather chain using the *ccrtNGFC_MsgDma_Configure()* call, then this *ccrtNGFC_MsgDma_Fire()* API will initiate the DMA starting with the user supplied start descriptor ID.

The *DescriptorIDMask* is a mask of all the valid descriptor ID's specified in the scatter-gather chain that was created earlier with the *ccrtNGFC_MsgDma_Configure()* API. If this is incorrectly specified, the DMA operation will be unpredictable. This *ccrtNGFC_MsgDma_Fire()* API call uses this mask to set the *ControlWord* for each of the IDs. Specifying this mask reduces the overhead in the call by not searching the scatter-gather chain to set the individual control words.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

ControlWord for each descriptor is set based on the *DescriptorIDMask* mask. Normally, the following two flags are set:

- CCRTNGFC_MSGD_DESC_CONTROL_GO
- CCRTNGFC_MSGD_DESC_CONTROL_OWNED_BY_HW

LastIdForInterrupts is set to 0 if the DMA operation will use polling instead of using interrupts to detect completion of the operation. If interrupts are to be used, the ID of the last descriptor in the DMA chain is to be specified. This is the ID that will be interrupted when the entire chain is completed. Incorrect ID entered will result in unpredictable results. Normally, interrupt handling adds additional overhead and reduces performance, however, it reduces the overhead experienced by the CPU and PCIe bus during polling.

Once the scatter-gather DMA operation commences, it performs DMA operations starting with the *StartDescriptorID* and traversing through the chain sequentially until it reaches the last descriptor ID in the chain, at which point the DMA operation concludes.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Fire (void                                    *Handle,
                         _ccrtngfc_msgdma_engine_t               MsgDmaEngine,
                         _ccrtngfc_msgdma_descriptors_id_t       StartDescriptorID,
                         _ccrtngfc_msgdma_descriptors_id_mask_t DescriptorIDMask,
                         int                                     ControlWord,
                         _ccrtngfc_msgdma_descriptors_id_t       LastIdForInterrupts)

   Description: Fire Modular Scatter-Gather DMA descriptor

   Input:   void                                  *Handle (Handle pointer)
            _ccrtngfc_msgdma_engine_t             MsgDmaEngine
               # CCRTNGFC_MSGDMA_ENGINE_0         // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1         // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2         // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3         // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_4         // single-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_5         // single-word transfers
            _ccrtngfc_msgdma_descriptors_id_t     StartDescriptorID (Set to valid ID)
               # 0                                (don't set start descriptor ID in prefetcher)
               # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_1 ... CCRTNGFC_MSGDMA_DESCRIPTOR_ID_31
            _ccrtngfc_msgdma_descriptors_id_mask_t DescriptorIDMask (descriptor ID mask)
               # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_1_MASK ...
CCRTNGFC_MSGDMA_DESCRIPTOR_ID_31_MASK
               # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_ALL_MASK
            int                                   ControlWord
               # CCRTNGFC_MSGD_DESC_CONTROL_GO
               # CCRTNGFC_MSGD_DESC_CONTROL_OWNED_BY_HW
            _ccrtngfc_msgdma_descriptors_id_t     LastIdForInterrupts (Set 0 or Last ID
                                                                       for interrupts)
               # 0                                (don't fire interrupts)
               # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_1 ... CCRTNGFC_MSGDMA_DESCRIPTOR_ID_31
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR            (successful)
               # CCRTNGFC_LIB_INVALID_ARG         (invalid argument)
               # CCRTNGFC_LIB_MSGDMA_FAILED       (MsgDma failed)
               # CCRTNGFC_LIB_MSGDMA_BUSY         (MsgDma Busy, cannot be reset)
               # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED (modular scatter-gather DMA not supported)
               # CCRTNGFC_LIB_NOT_OWNER_OF_MSGDMA  (not owner of modular scatter-gather)
 *************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.124 ccrtNGFC_MsgDma_Fire_Fifo()

This call is similar in functionality to the *ccrtNGFC_MsgDma_Fire()* call with the exception that it expects the entire memory area for transfer to be a read or write FIFO. It can be used when users need to perform FIFO transfers. This call can be called once the *ccrtNGFC_MsgDma_Configure_Descriptor()* call has been issued to set up the read/write address offset and length of transfer. Unless the read/write address offset or length of transfer is changed, the *ccrtNGFC_MsgDma_Fire_Fifo()* call can be made repeatedly to perform the same DMA transfer.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE*. In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Fire_Fifo (void                                *Handle,
                              _ccrtngfc_msgdma_engine_t         MsgDmaEngine,
                              _ccrtngfc_msgdma_descriptors_id_t LastDescriptorId,
                              int                               UseInterrupts)
   Description: Fire ADC or DAC Fifo Modular Scatter-Gather DMA descriptor

   Input:   void                                    *Handle          (Handle pointer)
            _ccrtngfc_msgdma_engine_t               MsgDmaEngine
               # CCRTNGFC_MSGDMA_ENGINE_0       // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1       // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2       // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3       // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_4       // single-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_5       // single-word transfers
            _ccrtngfc_msgdma_descriptors_id_t LastDescriptorId  (Last Descriptor ID)
            int                               UseInterrupts     (Use interrupts flag)
               # CCRTNGFC_TRUE
               # CCRTNGFC_FALSE
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
               # CCRTNGFC_LIB_MSGDMA_FAILED        (MsgDma failed)
               # CCRTNGFC_LIB_MSGDMA_BUSY          (MsgDma Busy, cannot be reset)
               # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED (modular scatter-gather DMA not supported)
               # CCRTNGFC_LIB_NOT_OWNER_OF_MSGDMA  (not owner of modular scatter-gather)
 *************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.125 ccrtNGFC_MsgDma_Fire_Single()

This call is similar in functionality to the *ccrtNGFC_MsgDma_Fire()* call with the exception that it operates on the single descriptor ID-1. It can be used when a single DMA rather than scatter-gather DMA operation needs to be performed. This call can be called once the *ccrtNGFC_MsgDma_Configure_Single()* call has been issued to set up the read/write address offset and length of transfer. Unless the read/write address offset or length of transfer is changed, the *ccrtNGFC_MsgDma_Fire_Single()* call can be made repeatedly to perform the same DMA transfer.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE.* In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Fire_Single (void                      *Handle,
                                _ccrtngfc_msgdma_engine_t  MsgDmaEngine,
                                int                        UseInterrupts)

   Description: Fire Single Modular Scatter-Gather DMA descriptor

   Input:   void  *Handle                          (Handle pointer)
            _ccrtngfc_msgdma_engine_t              MsgDmaEngine
               # CCRTNGFC_MSGDMA_ENGINE_0          // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1          // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2          // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3          // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_4          // single-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_5          // single-word transfers
            int   UseInterrupts                    (Use interrupts flag)
               # CCRTNGFC_TRUE
               # CCRTNGFC_FALSE
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
               # CCRTNGFC_LIB_MSGDMA_FAILED        (MsgDma failed)
               # CCRTNGFC_LIB_MSGDMA_BUSY          (MsgDma Busy, cannot be reset)
               # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED (modular scatter-gather DMA not supported)
               # CCRTNGFC_LIB_NOT_OWNER_OF_MSGDMA  (not owner of modular scatter-gather)
 *************************************************************************/
```

UseInterrupts is a flag that can be set to specify if interrupt handling should be enabled.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.126 ccrtNGFC_MsgDma_Free_Descriptor()

This call can be used to free up already used descriptors.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE.* In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Free_Descriptor (void                                    *Handle,
                                    _ccrtngfc_msgdma_engine_t               MsgDmaEngine,
                                    _ccrtngfc_msgdma_descriptors_id_mask_t DescriptorIDMask)

   Description: Free Modular Scatter-Gather DMA descriptor

   Input:   void                                  *Handle (Handle pointer)
            _ccrtngfc_msgdma_engine_t             MsgDmaEngine
               # CCRTNGFC_MSGDMA_ENGINE_0        // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1        // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2        // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3        // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_4        // single-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_5        // single-word transfers
            _ccrtngfc_msgdma_descriptors_id_mask_t DescriptorIDMask (descriptor ID mask)
               # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_1_MASK ... CCRTNGFC_MSGDMA_DESCRIPTOR_ID_31_MASK
               # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_ALL_MASK
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN             (device not open)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
               # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED (modular scatter-gather DMA not supported)
               # CCRTNGFC_LIB_MSGDMA_BUSY          (MsgDma Busy, cannot be reset)
               # CCRTNGFC_LIB_NOT_OWNER_OF_MSGDMA  (not owner of modular scatter-gather)
 *************************************************************************/
```

2.2.127 ccrtNGFC_MsgDma_Get_Descriptor()

This call returns information on the selected descriptor.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE.* In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Get_Descriptor (void                                *Handle,
                                   _ccrtngfc_msgdma_engine_t         MsgDmaEngine,
                                   _ccrtngfc_msgdma_descriptors_id_t DescriptorID,
                                   ccrtngfc_msgdma_descriptor_t      *Descriptor,
                                   __u64                             *DescriptorAddress)

   Description: Get Modular Scatter-Gather DMA Descriptor

   Input:   void                                  *Handle (Handle pointer)
            _ccrtngfc_msgdma_engine_t             MsgDmaEngine
               # CCRTNGFC_MSGDMA_ENGINE_0         // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1         // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2         // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3         // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_4         // single-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_5         // single-word transfers
            _ccrtngfc_msgdma_descriptors_id_t DescriptorID (descriptor ID)
               # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_1 ... CCRTNGFC_MSGDMA_DESCRIPTOR_ID_31
   Output:  ccrtngfc_msgdma_descriptor_t *Descriptor (pointer to descriptor)
               __u64  ReadAddress
               __u64  WriteAddress
               __u64  NextDescriptorPointer
               __u32  Length
               __u32  Control
               __u32  ReadBurstCount
               __u32  WriteBurstCount
               __u32  ReadStride
               __u32  WriteStride
               __u32  ActualBytesTransferred
               __u32  Status
               __u32  SequenceNumber
            __u64                          *DescriptorAddress (descriptor address)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN             (device not open)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
               # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED (modular scatter-gather DMA not supported)
 *************************************************************************/
```

Pointer to *DescriptorAddress* can be specified to return its address offset within the configuration space. This argument can be set to *NULL* if address is not required.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.128 ccrtNGFC_MsgDma_Get_Dispatcher_CSR()

This call returns useful control and status register information on the dispatcher.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE*. In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Get_Dispatcher_CSR (void                          *Handle,
                                       _ccrtngfc_msgdma_engine_t     MsgDmaEngine,
                                       ccrtngfc_msgdma_dispatcher_t  *Dispatcher)

   Description: Get Modular Scatter-Gather DMA Dispatcher CSR

   Input:   void                              *Handle (Handle pointer)
            _ccrtngfc_msgdma_engine_t         MsgDmaEngine
                 # CCRTNGFC_MSGDMA_ENGINE_0       // NGFC quad-word, SDFC double-word transfers
                 # CCRTNGFC_MSGDMA_ENGINE_1       // NGFC quad-word, SDFC double-word transfers
                 # CCRTNGFC_MSGDMA_ENGINE_2       // NGFC quad-word, SDFC double-word transfers
                 # CCRTNGFC_MSGDMA_ENGINE_3       // NGFC quad-word, SDFC double-word transfers
                 # CCRTNGFC_MSGDMA_ENGINE_4       // single-word transfers
                 # CCRTNGFC_MSGDMA_ENGINE_5       // single-word transfers
   Output:  ccrtngfc_msgdma_dispatcher_t      *Dispatcher (pointer to dispatcher)
               __u32  Status
                  # CCRTNGFC_MSGD_DISP_STATUS_IRQ           :IRQ
                  # CCRTNGFC_MSGD_DISP_STATUS_STOPPED_ETERM  :Stopped on Early Termination
                  # CCRTNGFC_MSGD_DISP_STATUS_STOPPED_ERROR  :Stopped on Error
                  # CCRTNGFC_MSGD_DISP_STATUS_RESETTING      :Resetting
                  # CCRTNGFC_MSGD_DISP_STATUS_STOPPED        :Stopped
                  # CCRTNGFC_MSGD_DISP_STATUS_RESP_BUF_FULL  :Response Buffer Full
                  # CCRTNGFC_MSGD_DISP_STATUS_RESP_BUF_EMPTY :Response Buffer Empty
                  # CCRTNGFC_MSGD_DISP_STATUS_DESC_BUF_FULL  :Descriptor Buffer Full
                  # CCRTNGFC_MSGD_DISP_STATUS_DESC_BUF_EMPTY :Descriptor Buffer Empty
                  # CCRTNGFC_MSGD_DISP_STATUS_BUSY           :Busy
               __u32  Control
                  # CCRTNGFC_MSGD_DISP_CONTROL_STOP_DESC     :Stop Descriptors
                  # CCRTNGFC_MSGD_DISP_CONTROL_INT_ENA_MASK  :Global Interrupt Enable Mask
                  # CCRTNGFC_MSGD_DISP_CONTROL_STOP_ETERM    :Stop on Early Termination
                  # CCRTNGFC_MSGD_DISP_CONTROL_STOP_ON_ERROR :Stop on Error
                  # CCRTNGFC_MSGD_DISP_CONTROL_RESET_DISP    :Reset Dispatcher
                  # CCRTNGFC_MSGD_DISP_CONTROL_STOP_DISP     :Stop Dispatcher
               __u32  ReadFillLevel
               __u32  WriteFillLevel
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            __u32  ResponseFillLevel
            __u32  ReadSequenceNumber
            __u32  WriteSequenceNumber
   Return:  _ccrtngfc_lib_error_number_t
            # CCRTNGFC_LIB_NO_ERROR            (successful)
            # CCRTNGFC_LIB_BAD_HANDLE          (no/bad handler supplied)
            # CCRTNGFC_LIB_NOT_OPEN            (device not open)
            # CCRTNGFC_LIB_INVALID_ARG         (invalid argument)
            # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED (modular scatter-gather DMA not supported)
 ************************************************************************/
```

2.2.129 ccrtNGFC_MsgDma_Get_Info()

This call returns useful information about the selected MsgDma engine.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE*. In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Get_Info (void                       *Handle,
                             _ccrtngfc_msgdma_engine_t MsgDmaEngine,
                             ccrtngfc_msgdma_list_t    *Info)

   Description: Get Modular Scatter-Gather DMA Information

   Input:   void                                *Handle (Handle pointer)
            _ccrtngfc_msgdma_engine_t           MsgDmaEngine
              # CCRTNGFC_MSGDMA_ENGINE_0        // NGFC quad-word, SDFC double-word transfers
              # CCRTNGFC_MSGDMA_ENGINE_1        // NGFC quad-word, SDFC double-word transfers
              # CCRTNGFC_MSGDMA_ENGINE_2        // NGFC quad-word, SDFC double-word transfers
              # CCRTNGFC_MSGDMA_ENGINE_3        // NGFC quad-word, SDFC double-word transfers
              # CCRTNGFC_MSGDMA_ENGINE_4        // single-word transfers
              # CCRTNGFC_MSGDMA_ENGINE_5        // single-word transfers
   Output:  ccrtngfc_msgdma_list_t              *Info (pointer to info)
            unsigned long                             MsgDmaOwnerPid
            unsigned long                             MsgDmaOwnerPid
            unsigned long long                        MsgDmaExtDesOneCycleDelay
            __u64                                     MsgDmaDescriptorBaseOffset
            __u64                                     MsgDmaTerminatingDescriptorOffset
            ccrtngfc_msgdma_dispatcher_csr_t          *MsgDmaDispatcherCsrDriverPtr
            ccrtngfc_msgdma_prefetcher_csr_t          *MsgDmaPrefetcherCsrDriverPtr
            ccrtngfc_msgdma_extended_descriptor_t     *MsgDmaExtendedDescriptorDriverPtr
            ccrtngfc_msgdma_extended_descriptor_t     *MsgDmaTerminatingDescriptorDriverPtr
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            ccrtngfc_msgdma_dispatcher_csr_t        *MsgDmaDispatcherCsrLibraryPtr
            ccrtngfc_msgdma_prefetcher_csr_t        *MsgDmaPrefetcherCsrLibraryPtr
            ccrtngfc_msgdma_extended_descriptor_t   *MsgDmaExtendedDescriptorLibraryPtr
            ccrtngfc_msgdma_extended_descriptor_t   *MsgDmaTerminatingDescriptorLibraryPtr
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN             (device not open)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
               # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED (modular scatter-gather DMA not supported)
 ************************************************************************/
```

2.2.130 ccrtNGFC_MsgDma_Get_Prefetcher_CSR()

This call returns useful control and status register information on the prefetcher.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE*. In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Get_Prefetcher_CSR (void                          *Handle,
                                       _ccrtngfc_msgdma_engine_t     MsgDmaEngine,
                                       ccrtngfc_msgdma_prefetcher_t  *Prefetcher)

   Description: Get Modular Scatter-Gather DMA Prefetcher CSR

   Input:   void                              *Handle (Handle pointer)
            _ccrtngfc_msgdma_engine_t         MsgDmaEngine
               # CCRTNGFC_MSGDMA_ENGINE_0     // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1     // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2     // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3     // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_4     // single-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_5     // single-word transfers
   Output:  ccrtngfc_msgdma_prefetcher_t      *Prefetcher (pointer to prefetcher)
               __u32 Status
                  # CCRTNGFC_MSGD_PREF_STATUS_IRQ          :IRQ Occurred
               __u32 Control
                  # CCRTNGFC_MSGD_PREF_CONTROL_PARK_MODE    :Park Mode
                  # CCRTNGFC_MSGD_PREF_CONTROL_INT_ENA_MASK :Global Interrupt Enable Mask
                  # CCRTNGFC_MSGD_PREF_CONTROL_RESET        :Reset Prefetcher Core
                  # CCRTNGFC_MSGD_PREF_CONTROL_DESC_POLL_EN :Descriptor Polling Enable
                  # CCRTNGFC_MSGD_PREF_CONTROL_RUN          :Start Descriptor fetching operation
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            __u64 NextDescriptorPointer
            __u32 DescriptorPollingFrequency
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN             (device not open)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
               # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED (modular scatter-gather DMA not supported)
 ************************************************************************/
```

2.2.131 ccrtNGFC_MsgDma_Release()

This *ccrtNGFC_MsgDma_Release()* API call is used to free up the Modular Scatter-Gather DMA resource that has been previously reserved by the *ccrtNGFC_MsgDma_Seize()* API. At this point, another user can take control of the MsgDMA operation by issuing the *ccrtNGFC_MsgDma_Seize()* call.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE.* In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

```
/************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Release (void                       *Handle,
                            _ccrtngfc_msgdma_engine_t MsgDmaEngine)

   Description: Release MsgDMA operation for others to use

   Input:   void                                    *Handle (Handle pointer)
            _ccrtngfc_msgdma_engine_t               MsgDmaEngine
               # CCRTNGFC_MSGDMA_ENGINE_0           // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1           // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2           // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3           // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_4           // single-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_5           // single-word transfers
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR              (successful)
               # CCRTNGFC_LIB_BAD_HANDLE            (no/bad handler supplied)
               # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED  (modular scatter-gather DMA not supported)
               # CCRTNGFC_LIB_MSGDMA_BUSY           (MsgDma Busy, cannot be reset)
               # CCRTNGFC_LIB_NOT_OWNER_OF_MSGDMA   (not owner of modular scatter-gather)
               # CCRTNGFC_LIB_INVALID_ARG           (invalid argument)
 ************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.132 ccrtNGFC_MsgDma_Seize()

Modular Scatter-Gather DMA is a two part operation. The first part is to configure the Scatter-Gather DMA and the second part is to execute the DMA. Various MsgDma API calls have been provided for this. Since this two part operation is not atomic, it is necessary for the user of these calls to prevent other applications from configuring and using the same MsgDMA resources while it is being actively used by another application. For this reason, the *ccrtNGFC_MsgDma_Seize()* and *ccrtNGFC_MsgDma_Release()* API calls have been introduced to assist the user in preventing other applications from accessing the selected Scatter-Gather DMA resource while it is reserved. Basically, before any MsgDma API call is issued that could modify the setting and execution of the MsgDma operation, the user needs to issue the *ccrtNGFC_MsgDma_Seize()* API call once. In this way, no one else will have access to the MsgDma resource until the application has issued the *ccrtNGFC_MsgDma_Release()* API call or has terminated the aplication.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_IDLE

Since multiple MsgDma operations can be in use at the same time, the user can select a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE.* In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Seize (void                        *Handle,
                          _ccrtngfc_msgdma_engine_t *MsgDmaEngine)

   Description: Seize MsgDMA operation for private to use and become owner

   Input:   void                                     *Handle (Handle pointer)
            _ccrtngfc_msgdma_engine_t                *MsgDmaEngine
               # CCRTNGFC_MSGDMA_ENGINE_0           // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1           // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2           // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3           // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_4           // single-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_5           // single-word transfers
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN             (device not open)
               # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED (modular scatter-gather DMA not supported)
               # CCRTNGFC_LIB_MSGDMA_IN_USE        (modular scatter-gather DMA in use)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
 *************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.133 ccrtNGFC_MsgDma_Setup()

This call is used in conjunction with the *ccrtNGFC_MsgDma_Configure() and ccrtNGFC_MsgDma_Fire()* calls. This call is made after all the descriptors are first configured with the help of the *ccrtNGFC_MsgDma_Configure()* call. The purpose of this call is to specify the first descriptor in the chain. Additionally, the user can set the *ForceReset* flag to reset the dispatcher and prefetcher. Optionally, the user can request useful active descriptor information if *ActiveDescriptorsInfo* argument is specified *(i.e not NULL)*. In addition to returning useful active descriptor information, the descriptor chain and prefetcher settings are also validated for proper configuration.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_MsgDma_Setup (void                                        *Handle,
                          _ccrtngfc_msgdma_engine_t                   MsgDmaEngine,
                          _ccrtngfc_msgdma_descriptors_id_t           StartDescriptorID,
                          int                                         ForceReset,
                          ccrtngfc_msgdma_active_descriptors_info_t *ActiveDescriptorsInfo)

   Description: Setup MsgDMA Dispatcher and Prefetcher

   Input:   void                                      *Handle (Handle pointer)
            _ccrtngfc_msgdma_engine_t                 MsgDmaEngine
               # CCRTNGFC_MSGDMA_ENGINE_0            // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1            // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2            // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3            // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_4            // single-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_5            // single-word transfers
            _ccrtngfc_msgdma_descriptors_id_t            *StartDescriptorID (Set to valid ID)
               # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_1 ... CCRTNGFC_MSGDMA_DESCRIPTOR_ID_31
            int                                          ForceReset
   Output:  ccrtngfc_msgdma_active_descriptors_info_t    *ActiveDescriptorsInfo;
               _ccrtngfc_msgdma_descriptors_id_t       ID
                   # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_1 ... CCRTNGFC_MSGDMA_DESCRIPTOR_ID_31
               _ccrtngfc_msgdma_descriptors_id_mask_t  Mask
                   # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_1_MASK ... CCRTNGFC_MSGDMA_DESCRIPTOR_ID_31_MASK
                   # CCRTNGFC_MSGDMA_DESCRIPTOR_ID_ALL_MASK
               __u32                                   NumberOfDescriptors
               __u32                                   TotalBytes
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                   (successful)
               # CCRTNGFC_LIB_BAD_HANDLE                 (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                   (device not open)
               # CCRTNGFC_LIB_INVALID_ARG                (invalid argument)
               # CCRTNGFC_LIB_MSGDMA_BUSY                (MsgDma Busy, cannot be reset)
               # CCRTNGFC_LIB_ERROR_IN_DESCRIPTOR_LIST   (invalid descreptor list)
               # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED       (modular scatter-gather DMA not supported)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_LIB_NOT_OWNER_OF_MSGDMA       (not owner of modular scatter-gather)
 ****************************************************************************/
```

2.2.134 ccrtNGFC_Munmap_Physical_Memory()

This call simply removes a physical memory that was previously allocated by the *ccrtNGFC_MMap_Physical_Memory()* API call.

```
/****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Munmap_Physical_Memory (void   *Handle,
                                    void   *mmaped_user_mem_ptr)

   Description: Unmap a previously mapped physical DMA memory.

   Input:   void            *Handle                (Handle pointer)
            void            *mmaped_user_mem_ptr   (virtual memory pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN             (device not open)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
               # CCRTNGFC_LIB_MUNMAP_FAILED        (failed to un-map memory)
               # CCRTNGFC_LIB_NOT_MAPPED           (memory not mapped)
               # CCRTNGFC_LIB_MSGDMA_IN_USE        (modular scatter-gather DMA in use)
 ****************************************************************************/
```

2.2.135 ccrtNGFC_NanoDelay()

This call goes into a tight loop spinning for the requested nano seconds specified by the user.

```
/****************************************************************************
   void
   ccrtNGFC_NanoDelay (unsigned long long NanoDelay)

   Description: Delay (loop) for user specified nano-seconds

   Input:   unsigned long long NanoDelay       (number of nano-secs to delay)
   Output:  none
   Return:  none
 ****************************************************************************/
```

2.2.136 ccrtNGFC_Open()

This is the first call that needs to be issued by a user to open a device and access the board through the rest of the API calls. What is returned is a handle to a *void pointer* that is supplied as an argument to the other API calls. The *Board_Number* is a valid board number [0..39] that is associated with a physical card. There must exist a character special file */dev/ccrtngfc<Board_Number>* for the call to be successful. One character special file is created for each board found when the driver is successfully loaded.

The *oflag* is the flag supplied to the *open(2)* system call by this API. It is normally '0' *(zero)*, however the user may use the *O_NONBLOCK* option for *read(2)* calls which will change the default reading in block mode.

This driver allows multiple applications to open the same board by specifying an additional *oflag O_APPEND*. It is then the responsibility of the user to ensure that the various applications communicating with the same cards are properly synchronized. Various tests supplied in this package has the *O_APPEND* flags enabled, however, it is strongly recommended that only one application be run with a single card at a time, unless the user is well aware of how the applications are going to interact with each other and accept any unpredictable results.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

In case of error, *errno* is also set for some non-system related errors encountered.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Open (void     **My_Handle,
                  int      Board_Number,
                  int      oflag)

   Description: Open a device.

   Input:   void            **Handle               (Handle pointer to pointer)
            int             Board_Number           (0-9 board number)
            int             oflag                  (open flags)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_INVALID_ARG          (invalid argument)
               # CCRTNGFC_LIB_ALREADY_OPEN         (device already opened)
               # CCRTNGFC_LIB_OPEN_FAILED          (device open failed)
               # CCRTNGFC_LIB_ALREADY_MAPPED       (memory already mmapped)
               # CCRTNGFC_LIB_MMAP_SELECT_FAILED   (mmap selection failed)
               # CCRTNGFC_LIB_MMAP_FAILED          (mmap failed)
 *************************************************************************/
```

2.2.137 ccrtNGFC_Pause_UserProcess()

This call causes a running User Process to sleep for user specified micro-seconds. *(This is an experimental API for debugging and testing).*

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Pause_UserProcess(void *UFuncHandle,
                              int  usleep)

   Description: Pause running user process

   Input:   void                      *UFuncHandle (UF Handle pointer)
            int                       usleep       (micro-seconds sleep)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR             (successful)
               # CCRTNGFC_LIB_BAD_HANDLE           (no/bad handler supplied)
 *************************************************************************/
```

2.2.138 ccrtNGFC_PowerModule_Control()

This call issues some control commands to the power module.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_PowerModule_Control (void                        *Handle,
                                 _ccrtngfc_fpga_pm_command_t  Command)

    Description: Control Power Module

    Input:  void                            *Handle         (Handle pointer)
            _ccrtngfc_fpga_pm_command_t     Command;
                # CCRTNGFC_PM_CMD_CLEAR_FAULTS
                # CCRTNGFC_PM_CMD_CLEAR_PEAK_VALUES
    Ouput:  none
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   Return: _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                    (successful)
               # CCRTNGFC_LIB_INVALID_ARG                 (invalid argument)
               # CCRTNGFC_LIB_BAD_HANDLE                  (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                    (device not open)
               # CCRTNGFC_LIB_NO_LOCAL_REGION             (local region not present)
               # CCRTNGFC_LIB_FPGA_PM_BUSY                (power module busy)
               # CCRTNGFC_LIB_FPGA_PM_FAILURE             (power module failure)
 ***************************************************************************/
```

2.2.139 ccrtNGFC_Program_All_Output_Clocks()

This is the main call to program all the output clocks with a single call. All existing clock activity is stopped and replaced with the new clocks selection. Though the user can select the Input Clock Frequency with this call, it is expected that they will use the default CCRTNGFC_DEFAULT_INPUT_CLOCK_FREQUENCY value.

The input clock can be one of:

```
CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN0    → 10MHz TCXO (Temperature Compensated
                                        Oscillator Clock).
CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN1    → External Input
CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN2    → FPGA Supplied
CCRTNGFC_CG_INPUT_CLOCK_SELECT_INXAXB → Not used
```

When using this card, the default clock should be set to *CCRTNGFC_CG_INPUT_CLOCK_SELECT_N0* i.e. the 10MHz internal clock.

If the desired output clock frequencies are unable to be computed due to hardware limitation, they may wish to increase the desired tolerance *DesiredTolerancePPT* for the particular clock. Note that this tolerance is only applicable to computing a clock value as close to the desired frequency *DesiredFrequency* and not a representation of the accuracy of the output clocks.

Additionally, the programming could fail if the number of N-Divider resource gets exhausted due to the user selecting several output clocks with widely different output clocks.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Program_All_Output_Clocks(void                    *Handle,
                                     double                  InputClockFrequency,
               _ccrtngfc_cg_input_clock_select_register_t    InputClockSel,
               ccrtngfc_compute_all_output_clocks_t          *AllClocks,
               int                                           ProgramClocks,
               int                                           ActivateClocks)


   Description: Program All Output Clocks

   Input:   void                                      *Handle             (Handle pointer)
            double                                    InputClockFrequency (input clock frequency)
            _ccrtngfc_cg_input_clock_select_register_t InputClockSel      (select input clock)
               # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN0
               # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN1
               # CCRTNGFC_CG_INPUT_CLOCK_SELECT_IN2
               # CCRTNGFC_CG_INPUT_CLOCK_SELECT_INXAXB
            ccrtngfc_compute_all_output_clocks_t      *AllClocks     (pointer to all Clocks)
               ccrtngfc_compute_single_output_clock_t *Clock         (Pointer to returned
                                                                      output clock info)
                  long double                              DesiredFrequency
                  double                                   DesiredTolerancePPT
             int                                           ProgramClocks  (program clocks)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            int                                             ActivateClocks (1=activate clocks
                                                                            after program)
   Output:  ccrtngfc_compute_all_output_clocks_t            *AllClocks     (Pointer to returned
                                                                            output clocks info)
               ccrtngfc_compute_single_output_clock_t       *Clock         (Pointer to returned
                                                                            output clock info)
                  _ccrtngfc_clock_generator_output_t        OutputClock
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_0
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_1
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_2
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_3
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_4
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_5   // RESERVED - PLL Clock
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_6
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_7
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_8
                     # CCRTNGFC_CLOCK_GENERATOR_OUTPUT_9   // RESERVED - FeedBack Clock
                  double                                    InputClockFrequency
                  long double                               FrequencyDeviation
                  int                                       FrequencyFound
                  long double                               ActualFrequency
                  double                                    ActualTolerancePPT
                  __u64                                     Mdiv_Numerator
                  __u32                                     Mdiv_Denominator
                  __u64                                     Ndiv_Numerator
                  __u32                                     Ndiv_Denominator
                  _ccrtngfc_cg_outmux_ndiv_select_t         Ndiv_ToUse
                     # CCRTNGFC_CG_OUTPUT_MUX_NDIV_0
                     # CCRTNGFC_CG_OUTPUT_MUX_NDIV_1
                     # CCRTNGFC_CG_OUTPUT_MUX_NDIV_2
                     # CCRTNGFC_CG_OUTPUT_MUX_NDIV_3
                     # CCRTNGFC_CG_OUTPUT_MUX_NDIV_4
                  __u32                                     Rdiv_value
                  __u32                                     Rdivider
                  __u32                                     Pdivider
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                     (successful)
               # CCRTNGFC_LIB_BAD_HANDLE                   (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                     (device not open)
               # CCRTNGFC_LIB_NO_LOCAL_REGION              (local region error)
               # CCRTNGFC_LIB_IO_ERROR                     (device not ready)
               # CCRTNGFC_LIB_N_DIVIDERS_EXCEEDED          (number of N-Dividers exceeded)
               # CCRTNGFC_LIB_CANNOT_COMPUTE_OUTPUT_FREQ   (cannot compute output freq)
               # CCRTNGFC_LIB_INVALID_ARG                  (invalid argument)
               # CCRTNGFC_LIB_CLOCK_GENERATION_FAILED      (clock generation failed)
               # CCRTNGFC_LIB_NO_RESOURCE                  (specified clock is reserved)
*************************************************************************/
```

2.2.140 ccrtNGFC_Read()

This call performs a programmed I/O driver read of either the ADC *channel registers* or the *FIFO*. Prior to issuing this call, the user needs to set up the desired read mode of operation using the *ccrtNGFC_ADC_Set_Driver_Read_Mode()* with *CCRTNGFC_ADC_PIO_CHANNEL* or *CCRTNGFC_ADC_PIO_FIFO* argument. For *channel register* reads, the size is limited to *CCRTNGFC_MAX_ADC_CHANNELS* words and for *FIFO* reads, it is limited to *CCRTNGFC_ADC_FIFO_DATA_MAX* words.

It basically calls the *read(2)* system call with the exception that it performs necessary *locking* and returns the *errno* returned from the system call in the pointer to the *error* variable. An *errno* of *ENOBUFS* can occur for *FIFO* reads when it encounters an overflow condition.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

For specific information about the data being returned for the various read modes, refer to the *read(2)* system call description the *Driver Direct Access* section.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Read (void     *Handle,
                  void     *buf,
                  int      size,
                  int      *bytes_read,
                  int      *error)

   Description: Perform a read operation.

   Input:   void     *Handle               (Handle pointer)
            int      size                  (size of buffer in bytes)
   Output:  void     *buf                  (pointer to buffer)
            int      *bytes_read           (bytes read)
            int      *error                (returned errno)
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR      (successful)
               # CCRTNGFC_LIB_BAD_HANDLE    (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN      (device not open)
               # CCRTNGFC_LIB_IO_ERROR      (read failed)
 *************************************************************************/
```

2.2.141 ccrtNGFC_Reload_Firmware()

The purpose of this call is to power cycle the board which in turn will reload the latest firmware on the board.

```
/*************************************************************************
   ccrtNGFC_Reload_Firmware()

   Description: This call power-cycles the board which in turn forces it to
                reload its firmware. Typically, this is called after a new
                firmware has been installed in the board. This saves the need
                to perform a system reboot after a firmware installation.

   Input:   void *Handle                  (Handle pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR      (successful)
               # CCRTNGFC_LIB_BAD_HANDLE    (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN      (device not open)
               # CCRTNGFC_LIB_IOCTL_FAILED  (driver ioctl call failed)
 *************************************************************************/
```

2.2.142 ccrtNGFC_Remove_Irq()

The purpose of this call is to remove the interrupt handler that was previously set up. The interrupt handler is managed internally by the driver and the library. The user should not issue this call, otherwise reads will time out.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Remove_Irq (void *Handle)

   Description: By default, the driver sets up a shared IRQ interrupt handler
                when the device is opened. Now if for any reason, another
                device is sharing the same IRQ as this driver, the interrupt
                handler will also be entered every time the other shared
                device generates an interrupt. There are times that a user,
                for performance reasons may wish to run the board without
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
               interrupts enabled. In that case, they can issue this ioctl
               to remove the interrupt handling capability from the driver.

   Input:   void *Handle                    (Handle pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR      (successful)
               # CCRTNGFC_LIB_BAD_HANDLE    (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN      (device not open)
               # CCRTNGFC_LIB_IOCTL_FAILED  (driver ioctl call failed)
 ***************************************************************************/
```

2.2.143 ccrtNGFC_Reset_Board()

This call resets the board to a known hardware state. It may be a good idea to start an application by first resetting the board so that it is set to a known state.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Reset_Board (void *Handle)

   Description: Reset the board.

   Input:   void *Handle                      (Handle pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR        (successful)
               # CCRTNGFC_LIB_BAD_HANDLE      (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN        (device not open)
               # CCRTNGFC_LIB_IOCTL_FAILED    (driver ioctl call failed)
               # CCRTNGFC_LIB_NO_LOCAL_REGION (local region not present)
 ***************************************************************************/
```

2.2.144 ccrtNGFC_Reset_Clock()

This call performs a hardware reset of the clock. All active output clocks are stopped and set to default state. The user can activate clocks if they wish after a reset via the *activate* argument.

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Reset_Clock (void  *Handle,
                         int   activate)

   Description: Perform Hardware Clock Reset

   Input:   void                    *Handle   (Handle pointer)
            int                     activate  (1=activate after reset)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR        (successful)
               # CCRTNGFC_LIB_BAD_HANDLE      (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN        (device not open)
               # CCRTNGFC_LIB_IOCTL_FAILED    (driver ioctl call failed)
               # CCRTNGFC_LIB_NO_LOCAL_REGION (local region not present)
 ***************************************************************************/
```

2.2.145 ccrtNGFC_Resume_UserProcess()

Use this call to resume an already paused User Process. *(This is an experimental API for debugging and testing).*

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Resume_UserProcess(void *UFuncHandle)

   Description: Resume paused running user process

   Input:   void         *UFuncHandle           (UF Handle pointer)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
 *************************************************************************/
```

2.2.146 ccrtNGFC_Return_Board_Info_Description()

Return board information description

```
/*************************************************************************
   char *
   ccrtNGFC_Return_Board_Info_Description (_ccrtngfc_board_function_t BoardFunction)

   Description: Return Board Information Description

   Input:   _ccrtngfc_board_function_t   BoardFunction          (board function)
               # CCRTNGFC_BOARD_FUNCTION_MULTIFUNCTION_IO
               # CCRTNGFC_BOARD_FUNCTION_ENGINE_CONTROL
               # CCRTNGFC_BOARD_FUNCTION_BASE_LEVEL
               # CCRTNGFC_BOARD_FUNCTION_CUSTOM_IPCORE
               # CCRTNGFC_BOARD_FUNCTION_CONFIGURABLE_MFIO
               # CCRTNGFC_BOARD_FUNCTION_UNDEFINED
   Output:  none
   Return:  char                         *BoardFuncDesc         (board function description)
 *************************************************************************/
```

2.2.147 ccrtNGFC_Set_Board_CSR()

This call is used to set the board control register.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Set_Board_CSR (void                    *Handle,
                           ccrtngfc_board_csr_t    *bcsr)

   Description: Set Board Control and Status information

   Input:   void                                *Handle (Handle pointer)
            ccrtngfc_board_csr_t                *bcsr   (pointer to board csr)
               _ccrtngfc_bcsr_identify_board_t  identify_board
                  # CCRTNGFC_BCSR_IDENTIFY_BOARD_DISABLE
                  # CCRTNGFC_BCSR_IDENTIFY_BOARD_ENABLE
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                (successful)
               # CCRTNGFC_LIB_BAD_HANDLE              (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                (device not open)
               # CCRTNGFC_LIB_INVALID_ARG             (invalid argument)
               # CCRTNGFC_LIB_NO_LOCAL_REGION         (local region not present)
 *************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

2.2.148 ccrtNGFC_Set_Interrupt_Timeout_Seconds()

This call sets the read *timeout* maintained by the driver. It allows the user to change the default time out from 30 seconds to a user specified value. It is the time that the read call will wait before it times out. The call could time out if the DMA fails to complete. The device should have been opened in the blocking mode *(O_NONBLOCK not set)* for reads to wait for the operation to complete.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Set_Interrupt_Timeout_Seconds (void    *Handle,
                                           int     timeout_secs)

   Description: Set Interrupt Timeout Seconds

   Input:   void         *Handle            (Handle pointer)
            int          timeout_secs       (interrupt tout secs)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR      (successful)
               # CCRTNGFC_LIB_BAD_HANDLE    (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN      (device not open)
               # CCRTNGFC_LIB_INVALID_ARG   (invalid argument)
 *************************************************************************/
```

2.2.149 ccrtNGFC_Set_Value()

This call allows the advanced user to set the writable board registers. The actual data written will depend on the command register information that is requested. Refer to the hardware manual for more information on what can be written to.

Normally, users should not be changing these registers as it will bypass the API integrity and could result in an unpredictable outcome.

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Set_Value (void                *Handle,
                       CCRTNGFC_CONTROL    cmd,
                       void                *value)

   Description: Set the value of the specified board register.

   Input:   void             *Handle        (Handle pointer)
            CCRTNGFC_CONTROL cmd            (register definition)
               -- structure in ccrtngfc_lib.h
            void             *value         (pointer to value to be set)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR      (successful)
               # CCRTNGFC_LIB_BAD_HANDLE    (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN      (device not open)
               # CCRTNGFC_LIB_INVALID_ARG   (invalid argument)
 *************************************************************************/
```

2.2.150 ccrtNGFC_Transfer_Data()

This is the main call that the user can use to transfer data from physical memory that the user has previously allocated to a region in the local register, and vice-versa. The operation can be performed via DMA or programmed I/O mode. In the case of DMA mode, the user can select whether interrupts are to be used to wait for DMA to complete instead of polling. User can also specify which DMA engine to use during this operation.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

If the board supports modular scatter-gather DMA, then the user can specify that instead of the basic DMA engine. In this case, the user needs to first call the *ccrtNGFC_MsgDma_Configure_Single()* with the *NULL* argument to setup descriptor ID-1 for scatter-gather DMA operation.

There are currently six MsgDma engines available to the user. They can be selected via the *MsgDmaEngine* option. The first four MsgDma engines perform quad-word transfers for NGFC cards and double-word transfers for SDFC cards. For NGFC cards, they must be aligned on a quad-word boundary and the size must be multiples of four while on SDFC cards, they must be aligned on a double-word boundary and size must be multiple of two. They can be one of the following values:

- CCRTNGFC_MSGDMA_ENGINE_0 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_1 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_2 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_3 // NGFC quad-word, SDFC double-word transfers
- CCRTNGFC_MSGDMA_ENGINE_4 // single-word transfers
- CCRTNGFC_MSGDMA_ENGINE_5 // single-word transfers

The normal process to setup a MsgDma operation is to first call the *ccrtNGFC_MsgDma_Seize()* API with either a specific MsgDma engine or the optional argument *CCRTNGFC_MSGDMA_ENGINE_IDLE.* In this case, the first available MsgDma engine is returned to the user. This is the MsgDma engine number that needs to be used for all the MsgDma operations until the MsgDma is freed via the *ccrtNGFC_MsgDma_Release()* API.

There are certain limitations to modular scatter-gather feature:

1. Scatter-gather DMA is only supported in certain cards
2. Invalid memory address supplied could result in the scatter-gather IP to lock up and the only way to recover will be to reload the driver or reboot the system.
3. Read and write addresses must be at a minimum full-word aligned and for maximum performance, it is recommended to be quad-word aligned.
4. Lengths are in bytes and must be at a minimum a multiple of a full-word and for maximum performance, it is recommended to be quad-word multiple.
5. Scatter-gather chaining cannot be performed with this call.

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Transfer_Data(void                              *Handle,
                          volatile void                     *PciDmaMemory,
                          volatile void                     *AvalonMem,
                          uint                              TransferSize,
                          _ccrtngfc_direction_t             XferDirection,
                          _ccrtngfc_library_rw_mode_t       LibMode,
                          _ccrtngfc_msgdma_engine_t         MsgDmaEngine,
                          ccrtngfc_bool                     UseInterrupts,
                          int                               IoControl)

   Description: Routine to transfer data from PCI memory to Avalon memory
                or vice-versa

   Input:   void                          *Handle           (Handle pointer)
            volatile void                 *PciDmaMemory     (pointer to virtual memory)
            volatile void                 *AvalonMem        (pointer to virtual Avalon memory)
            uint                          TransferSize      (size of transfer in bytes)
            _ccrtngfc_direction_t         XferDirection     (direction of transfer)
               # CCRTNGFC_AVALON_2_PCIMEM
               # CCRTNGFC_PCIMEM_2_AVALON
            _ccrtngfc_library_rw_mode_t   LibMode           (Lib transfer mode)
               # CCRTNGFC_LIBRARY_PIO_MODE
               # CCRTNGFC_LIBRARY_MSGDMA_MODE
            _ccrtngfc_msgdma_engine_t     MsgDmaEngine
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
               # CCRTNGFC_MSGDMA_ENGINE_0          // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_1          // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_2          // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_3          // NGFC quad-word, SDFC double-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_4          // single-word transfers
               # CCRTNGFC_MSGDMA_ENGINE_5          // single-word transfers
            ccrtngfc_bool               UseInterrupts      (enable interrupts)
               # CCRTNGFC_TRUE
               # CCRTNGFC_FALSE
            int                         IoControl          (DMA or PIO control flags)
               # CCRTNGFC_PIO_CONTROL_RCON                 (PIO read constant)
               # CCRTNGFC_PIO_CONTROL_WCON                 (PIO write constant)
               # CCRTNGFC_PIO_CONTROL_INCREMENT            (PIO increment)
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                     (no error)
               # CCRTNGFC_LIB_BAD_HANDLE                   (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN                     (library not open)
               # CCRTNGFC_LIB_INVALID_ARG                  (invalid argument)
               # CCRTNGFC_LIB_IOCTL_FAILED                 (driver ioctl call failed)
               # CCRTNGFC_LIB_MSGDMA_NOT_SUPPORTED  (modular scatter-gather DMA not supported)
               # CCRTNGFC_LIB_MSGDMA_READS_NOT_ALLOWED_FOR_SELECTED_ADDRESS
                                                   (MSG DMA Reads not allowed for
                                                    selected address)
               # CCRTNGFC_LIB_NOT_OWNER_OF_MSGDMA   (not owner of modular scatter-gather)
               # CCRTNGFC_LIB_DATA_WIDTH_NOT_MULTIPLE_OR_ALIGNED
                                                   (Data Width Not Multiple or Aligned)
 ***************************************************************************/
```

2.2.151 ccrtNGFC_Update_Clock_Generator_Divider()

Update the selected clock generator divider so that its changes take affect. *Normally, this call should not be used. It is recommended that only advanced users should use this call and with extreme care and intimate knowledge of the clock programming, otherwise results would be indeterminate.*

```
/***************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Update_Clock_Generator_Divider (void                        *Handle,
                            _ccrtngfc_clock_generator_divider_t    WhichDivider)

   Description: Update Clock Generator Divider

   Input:   void                                  *Handle         (Handle pointer)
            _ccrtngfc_clock_generator_divider_t  WhichDivider    (select divider)
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_M
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N0
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N1
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N2
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N3
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_N_ALL
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P0
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P1
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P2
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_PFB
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_P_ALL
               # CCRTNGFC_CLOCK_GENERATOR_DIVIDER_PXAXB
   Output:  none
   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR                 (successful)
               # CCRTNGFC_LIB_BAD_HANDLE               (no/bad handler supplied)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            # CCRTNGFC_LIB_NOT_OPEN                 (library not open)
            # CCRTNGFC_LIB_NO_LOCAL_REGION          (local region error)
            # CCRTNGFC_LIB_INVALID_ARG              (invalid argument)
            # CCRTNGFC_LIB_CLOCK_IS_NOT_ACTIVE      (Clock is not active)
*************************************************************************/
```

2.2.152 ccrtNGFC_UserProcess_Command()

The user can control the execution of the created User Process with the help of this call. *(This is an experimental API for debugging and testing).*

```
/*************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_UserProcess_Command(void                  *Handle,
                                void                  *UFuncHandle,
                                ccrtngfc_uf_action_t  Action)

   Description: Command User process

   Input:   void                  *UFuncHandle  (User Process Handle pointer)
            ccrtngfc_uf_action_t  Action        (command action)
               # CCRTNGFC_UF_ACTION_STOP
               # CCRTNGFC_UF_ACTION_RUN
               # CCRTNGFC_UF_ACTION_TERMINATE
   Output:  none
   Return:  none
 *************************************************************************/
```

2.2.153 ccrtNGFC_VoltsToData()

This call returns to the user the raw converted value for the requested voltage in the specified format. Voltage supplied must be within the input range of the selected board type. If the voltage is out of range, the call sets the voltage to the appropriate limit value.

```
/*************************************************************************
   uint
   ccrtNGFC_VoltsToData (double                  volts,
                         ccrtngfc_volt_convert_t *conv)

   Description: Convert Volts to data

   Input:   double                       volts        (volts to convert)
            ccrtngfc_volt_convert_t      *conv     (pointer to conversion struct)
              double                     VoltageRange (maximum voltage range)
              _ccrtngfc_csr_dataformat_t Format       (format)
                 # CCRTNGFC_OFFSET_BINARY
                 # CCRTNGFC_TWOS_COMPLEMENT
              ccrtngfc_bool              BiPolar      (bi-polar)
                 # CCRTNGFC_TRUE
                 # CCRTNGFC_FALSE
              int                   ResolutionBits (Number of resolution bits)
   Output:  none
   Return:  uint                    data           (returned data)
 *************************************************************************/
```

2.2.154 ccrtNGFC_Wait_For_Interrupt()

This call is made available to advanced users to bypass the API and perform their own data collection. The user can wait for a DMA complete interrupt. If a time out value greater than zero is specified, the call will time out after the specified seconds, otherwise it will not time out.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
/*****************************************************************************
   _ccrtngfc_lib_error_number_t
   ccrtNGFC_Wait_For_Interrupt (void                    *Handle,
                                ccrtngfc_driver_int_t  *drv_int)

   Description: Wait For Interrupt

   Input:   void                    *Handle         (Handle pointer)
            ccrtngfc_driver_int_t  *drv_int        (pointer to drv_int struct)
               uint                 WakeupInterruptMask
                  # CCRTNGFC_ALL_MSGDMA_INTMASK
                     # CCRTNGFC_MSGDMA0_INTMASK
                     # CCRTNGFC_MSGDMA1_INTMASK
                     # CCRTNGFC_MSGDMA2_INTMASK
                     # CCRTNGFC_MSGDMA3_INTMASK
                     # CCRTNGFC_MSGDMA4_INTMASK
                     # CCRTNGFC_MSGDMA5_INTMASK
                  # CCRTNGFC_ALL_ANALOG_INTMASK
                     # CCRTNGFC_ADC0_FIFO_INTMASK
                     # CCRTNGFC_DAC0_FIFO_INTMASK
                     # CCRTNGFC_ADC1_FIFO_INTMASK
                     # CCRTNGFC_DAC1_FIFO_INTMASK
               int                  timeout_seconds
   Output:  ccrtngfc_driver_int_t   *drv_int       (pointer to drv_int struct)
               long long unsigned   count
               long long unsigned   MsgDma_count[CCRTNGFC_MAX_MSGDMA_ENGINES]
               uint                 InterruptsOccurredMask
               uint                 WakeupInterruptMask

   Return:  _ccrtngfc_lib_error_number_t
               # CCRTNGFC_LIB_NO_ERROR          (successful)
               # CCRTNGFC_LIB_BAD_HANDLE        (no/bad handler supplied)
               # CCRTNGFC_LIB_NOT_OPEN          (device not open)
               # CCRTNGFC_LIB_NO_LOCAL_REGION   (local region not present)
               # CCRTNGFC_LIB_INVALID_ARG       (invalid argument)
 *****************************************************************************/
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

3. Test Programs

This driver and API are accompanied with an extensive set of test examples. Examples under the *Direct Driver Access* do not use the API, while those under *Application Program Interface Access* use the API.

3.1 Direct Driver Access Example Tests

These set of tests are located in the *.../test* directory and do not use the API. They communicate directly with the driver. Users should be extremely familiar with both the driver and the hardware registers if they wish to communicate directly with the hardware.

3.1.1 ccrtngfc_chip_temperature

This program displays the chip temperature of the board. It is useful in monitoring the temperature of the card if you suspect that there is insufficient cooling in the chassis or there is some obstruction to the airflow.

```
Usage: ./ccrtngfc_chip_temperature [-b BoardNo] [-d Delay] [-l LoopCnt]
 -b BoardNo  (Board number -- default is 0)
 -d Delay    (Delay between screen refresh -- default is to select all boards)
 -l LoopCnt  (Loop count -- default is 0)

e.g. ./ccrtngfc_chip_temperature            (Display temperature of all boards)
     ./ccrtngfc_chip_temperature -b0 -b2    (Display temperature of boards 0 and 2)
```

Example display:

./ccrtngfc_chip_temperature *(Custom firmware with SimWB running)*

```
 Board Number    [-b]: 0, 1, 2, 3, 4, 5
 Delay           [-d]: 1000 milli-seconds
 Loop Count      [-l]: ***Forever***

 ScanCount =      303

 b0  (SN=720327  ): Chip Temp[0x1ED]:  68.6 deg C (155.6 deg F) [HWM:0x1ED/ 68.6 C/155.6 F]
 b1  (SN=720326  ): Chip Temp[0x1DB]:  56.5 deg C (133.6 deg F) [HWM:0x1DB/ 56.5 C/133.6 F]
 b2  (SN=720330  ): Chip Temp[0x1DB]:  56.5 deg C (133.6 deg F) [HWM:0x1DC/ 57.1 C/134.8 F]
 b3  (SN=720321  ): Chip Temp[0x1ED]:  68.6 deg C (155.6 deg F) [HWM:0x1ED/ 68.6 C/155.6 F]
 b4  (SN=720329  ): Chip Temp[0x1E0]:  59.8 deg C (139.7 deg F) [HWM:0x1E1/ 60.5 C/140.9 F]
 b5  (SN=720328  ): Chip Temp[0x1EC]:  68.0 deg C (154.3 deg F) [HWM:0x1ED/ 68.6 C/155.6 F]
```

./ccrtngfc_chip_temperature *(Base Level)*

```
 Board Number    [-b]: 0, 1, 2, 3, 4, 5
 Delay           [-d]: 1000 milli-seconds
 Loop Count      [-l]: ***Forever***

 ScanCount =      402

 b0  (SN=720327  ): Chip Temp[0x1D2]:  50.4 deg C (122.7 deg F) [HWM:0x1D3/ 51.0 C/123.9 F]
 b1  (SN=720326  ): Chip Temp[0x1C4]:  40.9 deg C (105.6 deg F) [HWM:0x1C5/ 41.6 C/106.8 F]
 b2  (SN=720330  ): Chip Temp[0x1C8]:  43.6 deg C (110.5 deg F) [HWM:0x1C9/ 44.3 C/111.7 F]
 b3  (SN=720321  ): Chip Temp[0x1CD]:  47.0 deg C (116.6 deg F) [HWM:0x1CE/ 47.7 C/117.8 F]
 b4  (SN=720329  ): Chip Temp[0x1C8]:  43.6 deg C (110.5 deg F) [HWM:0x1C9/ 44.3 C/111.7 F]
 b5  (SN=720328  ): Chip Temp[0x1CD]:  47.0 deg C (116.6 deg F) [HWM:0x1CE/ 47.7 C/117.8 F]
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

3.1.2 ccrtngfc_disp

Useful program to display the local board registers. This program uses the *curses* library.

```
Usage: ./ccrtngfc_disp [-b BoardNo] [-d Delay] [-l LoopCnt] [-o Offset] [-s Size]
 -b BoardNo  (Board number -- default is 0)
 -d Delay    (Delay between screen refresh -- default is 0)
 -l LoopCnt  (Loop count -- default is 0)
 -o Offset   (Hex offset to read from -- default is 0x0)
 -s Size     (Number of bytes to read -- default is 0x400)
```

Example display:

./ccrtngfc_disp

```
 Board Number    [-b]: 0
 Delay           [-d]: 0 milli-seconds
 Loop Count      [-l]: ***Forever***
 Offset          [-o]: 0x00000000
 Size            [-s]: 1024 (bytes)

 ScanCount =    59758

         00       04       08       0C       10       14       18       1C
         ======== ======== ======== ======== ======== ======== ======== ========
000000   93200101 04172023 00400000 00120001 00000000 00000000 00000020 00000000
000020   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000040   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000060   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000080   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0000a0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0000c0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0000e0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000100   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000120   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000140   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000160   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000180   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0001a0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0001c0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0001e0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000200   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000220   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000240   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000260   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000280   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0002a0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0002c0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0002e0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000300   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000320   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000340   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000360   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000380   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0003a0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0003c0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0003e0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
```

3.1.3 ccrtngfc_dump

This test is for debugging purpose. It dumps all the hardware registers.

Usage: ccrtngfc_dump [-b board]
 -b board: board number -- default board is 0

Example display:

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

./ccrtngfc_dump

```
Device Name: /dev/ccrtngfc0

  LOCAL REGION: Physical Addr=0xfbe00000 Size=524288 (0x00080000)
 CONFIG REGION: Physical Addr=0xfbe80000 Size=32768 (0x00008000)

     LOCAL: Register 0x7ffff7f55000 Offset=0x0 Size=0x00080000
    CONFIG: Register 0x7ffff7fef000 Offset=0x0 Size=0x00008000
    LIBPTR: Register 0x7ffff7fde000 Offset=0x0 Size=0x000105a0

======= LOCAL BOARD REGISTERS =========
LBR: @0x000000 --> 0x93200101
LBR: @0x000004 --> 0x04172023
LBR: @0x000008 --> 0x00400000
LBR: @0x00000c --> 0x00120001
LBR: @0x000010 --> 0x00000000
LBR: @0x000014 --> 0x00000000
LBR: @0x000018 --> 0x00000020
LBR: @0x00001c --> 0x00000000
LBR: @0x000020 --> 0x00000000
LBR: @0x000024 --> 0x00000000
LBR: @0x000028 --> 0x00000000
LBR: @0x00002c --> 0x00000000
LBR: @0x000030 --> 0x00000000
.
.
.
LBR: @0x07ffcc --> 0x00000000
LBR: @0x07ffd0 --> 0x00000000
LBR: @0x07ffd4 --> 0x00000000
LBR: @0x07ffd8 --> 0x00000000
LBR: @0x07ffdc --> 0x00000000
LBR: @0x07ffe0 --> 0x00000000
LBR: @0x07ffe4 --> 0x00000000
LBR: @0x07ffe8 --> 0x00000000
LBR: @0x07ffec --> 0x00000000
LBR: @0x07fff0 --> 0x00000000
LBR: @0x07fff4 --> 0x00000000
LBR: @0x07fff8 --> 0x00000000
LBR: @0x07fffc --> 0x00000000
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
======= LOCAL CONFIG REGISTERS =========
#### CONFIG REGS (PCIeLinkPartnerRegs) ####
LCR: @0x0000 --> 0x00000000
LCR: @0x0004 --> 0x00000000
LCR: @0x0008 --> 0x00000000
LCR: @0x000c --> 0x00000000
LCR: @0x0010 --> 0x00000000
LCR: @0x0014 --> 0x00000000
LCR: @0x0018 --> 0x00000000
LCR: @0x001c --> 0x00000000
LCR: @0x0020 --> 0x00000000
LCR: @0x0024 --> 0x00000000
LCR: @0x0028 --> 0x00000000
LCR: @0x002c --> 0x00000000
LCR: @0x0030 --> 0x00000000
.
.
.
LCR: @0x0fc0 --> 0x00000000
LCR: @0x0fc4 --> 0x00000000
LCR: @0x0fc8 --> 0x00000000
LCR: @0x0fcc --> 0x00000000
LCR: @0x0fd0 --> 0x00000000
LCR: @0x0fd4 --> 0x00000000
LCR: @0x0fd8 --> 0x00000000
LCR: @0x0fdc --> 0x00000000
LCR: @0x0fe0 --> 0x00000000
LCR: @0x0fe4 --> 0x00000000
LCR: @0x0fe8 --> 0x00000000
LCR: @0x0fec --> 0x00000000
LCR: @0x0ff0 --> 0x00000000
LCR: @0x0ff4 --> 0x00000000
LCR: @0x0ff8 --> 0x00000000
LCR: @0x0ffc --> 0x00000000

#### CONFIG REGS (AvalonMM_2_PCIeAddrTrans) ####
LCR: @0x1000 --> 0x00000000
LCR: @0x1004 --> 0x00000000
LCR: @0x1008 --> 0x00000000
LCR: @0x100c --> 0x00000000
LCR: @0x1010 --> 0x00000000
LCR: @0x1014 --> 0x00000000
LCR: @0x1018 --> 0x00000000
LCR: @0x101c --> 0x00000000
LCR: @0x1020 --> 0x00000000
LCR: @0x1024 --> 0x00000000
LCR: @0x1028 --> 0x00000000
LCR: @0x102c --> 0x00000000
LCR: @0x1030 --> 0x00000000
LCR: @0x1034 --> 0x00000000
LCR: @0x1038 --> 0x00000000
LCR: @0x103c --> 0x00000000
.
.
.
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
LCR: @0x1fb0 --> 0x00000000
LCR: @0x1fb4 --> 0x00000000
LCR: @0x1fb8 --> 0x00000000
LCR: @0x1fbc --> 0x00000000
LCR: @0x1fc0 --> 0x00000000
LCR: @0x1fc4 --> 0x00000000
LCR: @0x1fc8 --> 0x00000000
LCR: @0x1fcc --> 0x00000000
LCR: @0x1fd0 --> 0x00000000
LCR: @0x1fd4 --> 0x00000000
LCR: @0x1fd8 --> 0x00000000
LCR: @0x1fdc --> 0x00000000
LCR: @0x1fe0 --> 0x00000000
LCR: @0x1fe4 --> 0x00000000
LCR: @0x1fe8 --> 0x00000000
LCR: @0x1fec --> 0x00000000
LCR: @0x1ff0 --> 0x00000000
LCR: @0x1ff4 --> 0x00000000
LCR: @0x1ff8 --> 0x00000000
LCR: @0x1ffc --> 0x00000000

======= PCI CONFIG REG ADDR MAPPING =========
PCR: @0x0000 --> 0x93201542
PCR: @0x0004 --> 0x00100546
PCR: @0x0008 --> 0x08800001
PCR: @0x000c --> 0x00000008
PCR: @0x0010 --> 0xfbe80000
PCR: @0x0014 --> 0x00000000
PCR: @0x0018 --> 0xfbe00000
PCR: @0x001c --> 0x00000000
PCR: @0x0020 --> 0x00000000
PCR: @0x0024 --> 0x00000000
PCR: @0x0028 --> 0x00000000
PCR: @0x002c --> 0x01001542
PCR: @0x0030 --> 0x00000000
PCR: @0x0034 --> 0x00000050
PCR: @0x0038 --> 0x00000000
PCR: @0x003c --> 0x0000010b
PCR: @0x0040 --> 0x00000000
PCR: @0x0044 --> 0x00000000
PCR: @0x0048 --> 0x00000000
PCR: @0x004c --> 0x00000000
PCR: @0x0050 --> 0x00857805
PCR: @0x0054 --> 0xfee00078
PCR: @0x0058 --> 0x00000000
PCR: @0x005c --> 0x00000000
PCR: @0x0060 --> 0x00000000
PCR: @0x0064 --> 0x00000000
PCR: @0x0068 --> 0x00007811
PCR: @0x006c --> 0x00000000
PCR: @0x0070 --> 0x00000000
PCR: @0x0074 --> 0x00000000
PCR: @0x0078 --> 0x00038001
PCR: @0x007c --> 0x00000000
PCR: @0x0080 --> 0x00020010
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
PCR: @0x0084 --> 0x00008001
PCR: @0x0088 --> 0x00002834
PCR: @0x008c --> 0x01406042
PCR: @0x0090 --> 0x10420000
PCR: @0x0094 --> 0x00000000
PCR: @0x0098 --> 0x00000000
PCR: @0x009c --> 0x00000000
PCR: @0x00a0 --> 0x00000000
PCR: @0x00a4 --> 0x0010001f
PCR: @0x00a8 --> 0x00000000
PCR: @0x00ac --> 0x00000006
PCR: @0x00b0 --> 0x00010002
PCR: @0x00b4 --> 0x00000000
PCR: @0x00b8 --> 0x00000000
PCR: @0x00bc --> 0x00000000
PCR: @0x00c0 --> 0x00000000
PCR: @0x00c4 --> 0x00000000
PCR: @0x00c8 --> 0x00000000
PCR: @0x00cc --> 0x00000000
PCR: @0x00d0 --> 0x00000000
PCR: @0x00d4 --> 0x00000000
PCR: @0x00d8 --> 0x00000000
PCR: @0x00dc --> 0x00000000
PCR: @0x00e0 --> 0x00000000
PCR: @0x00e4 --> 0x00000000
PCR: @0x00e8 --> 0x00000000
PCR: @0x00ec --> 0x00000000
PCR: @0x00f0 --> 0x00000000
PCR: @0x00f4 --> 0x00000000
PCR: @0x00f8 --> 0x00000000
PCR: @0x00fc --> 0x00000000
```

3.1.4 ccrtngfc_rdreg

This is a simple program that returns the local register value for a given offset.

```
Usage: ./ccrtngfc_rdreg [-b Board] [-C] [-f] [-o Offset] [-s Size]
 -b Board   : Board number -- default board is 0
 -C         : Select Config Registers instead of Local Registers
 -f         : Fast Memory Reads
 -o Offset  : Hex offset to read from -- default offset is 0x0
 -s Size    : Number of bytes to read in decimal -- default size is 0x4
```

Example display:
./ccrtngfc_rdreg –s64

```
Device Name: /dev/ccrtngfc0

  LOCAL REGION: Physical Addr=0xfbe00000 Size=524288 (0x00080000)
 CONFIG REGION: Physical Addr=0xfbe80000 Size=32768 (0x00008000)

         LOCAL: Register 0x7ffff7f55000 Offset=0x0 Size=0x00080000
        CONFIG: Register 0x7ffff7fef000 Offset=0x0 Size=0x00008000
        LIBPTR: Register 0x7ffff7fde000 Offset=0x0 Size=0x000105a0

#### LOCAL REGS #### (length=64)
+LCL+        0   93200101  04172023  00400000  00120001 *. .... #.@......*
+LCL+     0x10   00000000  00000000  00000020  00000000 *.......... ....*
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
+LCL+     0x20   00000000  00000000  00000000  00000000 *................*
+LCL+     0x30   00000000  00000000  00000000  00000000 *................*
  28.978us (   2.21 MB/s)

./ccrtngfc_rdreg -C -o4020 -s20

Device Name: /dev/ccrtngfc0

  LOCAL REGION: Physical Addr=0xfbe00000 Size=524288 (0x00080000)
 CONFIG REGION: Physical Addr=0xfbe80000 Size=32768 (0x00008000)

         LOCAL: Register 0x7ffff7f55000 Offset=0x0 Size=0x00080000
        CONFIG: Register 0x7ffff7fef000 Offset=0x0 Size=0x00008000
        LIBPTR: Register 0x7ffff7fde000 Offset=0x0 Size=0x000105a0

#### CONFIG REGS #### (length=20)
+CFG+   0x4020   00000000  00000000  00000000  00000000 *................*
+CFG+   0x4030   00000000                                *....            *
   8.056us (   2.48 MB/s)
```

3.1.5 ccrtngfc_reg

This call displays all the boards local and configuration registers.

```
Usage: ./ccrtngfc_reg [-b board]
 -b board: Board number -- default board is 0
```

Example display:

./ccrtngfc_reg

```
Device Name: /dev/ccrtngfc0

  LOCAL REGION: Physical Addr=0xfb800000 Size=4194304 (0x00400000)
 CONFIG REGION: Physical Addr=0xfbc00000 Size=32768 (0x00008000)

     LOCAL: Register 0x7ffff7800000 Offset=0x0 Size=0x00400000
    CONFIG: Register 0x7ffff7fb7000 Offset=0x0 Size=0x00008000
    LIBPTR: Register 0x7ffff7ebf000 Offset=0x0 Size=0x00013e58
LOCAL Register 0x7ffff7800000 size=0x00400000

#### LOCAL REGS #### (length=4194304)
+LCL+        0   93200101  08252023  00010000  00120000 *. ...% #........*
+LCL+     0x10   00000000  00000000  00000020  00010001 *.......... ....*
+LCL+     0x20   00000000  00000000  00000000  00000000 *................*
+LCL+     0x30   00000000  00000000  00000000  00000000 *................*
+LCL+     0x40   00000000  00000000  00000000  00000000 *................*
+LCL+     0x50   00000000  00000000  00000000  00000000 *................*
+LCL+     0x60   00000000  00000000  00000000  00000000 *................*
+LCL+     0x70   00000000  00000000  00000000  00000000 *................*
+LCL+     0x80   00000000  00000000  00000000  00000000 *................*
+LCL+     0x90   00000000  00000000  00000000  00000000 *................*
+LCL+     0xa0   00000000  00000000  00000000  00000000 *................*
+LCL+     0xb0   00000000  00000000  00000000  00000000 *................*
+LCL+     0xc0   00000000  00000000  00000000  00000000 *................*
+LCL+     0xd0   00000000  00000000  00000000  00000000 *................*
+LCL+     0xe0   00000000  00000000  00000000  00000000 *................*
+LCL+     0xf0   00000000  00000000  00000000  00000000 *................*
+LCL+    0x100   00000000  00000000  00000000  00000000 *................*
+LCL+    0x110   00000000  00000000  00000000  00000000 *................*
+LCL+    0x120   00000000  00000000  00000000  00000000 *................*
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
+LCL+    0x130   00000000  00000000  00000000  00000000 *................*
+LCL+    0x140   00000000  00000000  00000000  00000000 *................*
+LCL+    0x150   00000000  00000000  00000000  00000000 *................*
+LCL+    0x160   00000000  00000000  00000000  00000000 *................*
+LCL+    0x170   00000000  00000000  00000000  00000000 *................*
+LCL+    0x180   00000000  00000000  00000000  00000000 *................*
+LCL+    0x190   00000000  00000000  00000000  00000000 *................*
+LCL+    0x1a0   00000000  00000000  00000000  00000000 *................*
+LCL+    0x1b0   00000000  00000000  00000000  00000000 *................*
+LCL+    0x1c0   00000000  00000000  00000000  00000000 *................*
+LCL+    0x1d0   00000000  00000000  00000000  00000000 *................*
+LCL+    0x1e0   00000000  00000000  00000000  00000000 *................*
+LCL+    0x1f0   00000000  00000000  00000000  00000000 *................*
+LCL+    0x200   00000000  00000000  00000000  00000000 *................*
.
.
.
+LCL+ 0x3fff00   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fff10   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fff20   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fff30   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fff40   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fff50   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fff60   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fff70   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fff80   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fff90   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fffa0   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fffb0   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fffc0   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fffd0   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3fffe0   00000000  00000000  00000000  00000000 *................*
+LCL+ 0x3ffff0   00000000  00000000  00000000  00000000 *................*

#### CONFIG REGS (PCIeLinkPartnerRegs) #### (length=4096)
+CFG+        0   00000000  00000000  00000000  00000000 *................*
+CFG+     0x10   00000000  00000000  00000000  00000000 *................*
+CFG+     0x20   00000000  00000000  00000000  00000000 *................*
+CFG+     0x30   00000000  00000000  00000000  00000000 *................*
+CFG+     0x40   00000000  00000000  00000000  00000000 *................*
+CFG+     0x50   00000000  00000000  00000000  00000000 *................*
+CFG+     0x60   00000004  00000004  00000008  00000008 *................*
+CFG+     0x70   00000000  00000000  00000000  00000000 *................*
+CFG+     0x80   00000000  00000000  00000000  00000000 *................*
+CFG+     0x90   00000000  00000000  00000000  00000000 *................*
+CFG+     0xa0   00000000  00000000  00000000  00000000 *................*
+CFG+     0xb0   00000000  00000000  00000000  00000000 *................*
+CFG+     0xc0   00000000  00000000  00000000  00000000 *................*
+CFG+     0xd0   00000000  00000000  00000000  00000000 *................*
+CFG+     0xe0   00000004  00000004  00000008  00000008 *................*
+CFG+     0xf0   00000000  00000000  00000000  00000000 *................*
+CFG+    0x100   00000000  00000000  00000000  00000000 *................*
.
.
.
+CFG+    0xf00   00000000  00000000  00000000  00000000 *................*
+CFG+    0xf10   00000000  00000000  00000000  00000000 *................*
+CFG+    0xf20   00000000  00000000  00000000  00000000 *................*
+CFG+    0xf30   00000000  00000000  00000000  00000000 *................*
+CFG+    0xf40   00000000  00000000  00000000  00000000 *................*
+CFG+    0xf50   00000000  00000000  00000000  00000000 *................*
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
+CFG+    0xf60   00000000  00000000  00000000  00000000 *................*
+CFG+    0xf70   00000000  00000000  00000000  00000000 *................*
+CFG+    0xf80   00000000  00000000  00000000  00000000 *................*
+CFG+    0xf90   00000000  00000000  00000000  00000000 *................*
+CFG+    0xfa0   00000000  00000000  00000000  00000000 *................*
+CFG+    0xfb0   00000000  00000000  00000000  00000000 *................*
+CFG+    0xfc0   00000000  00000000  00000000  00000000 *................*
+CFG+    0xfd0   00000000  00000000  00000000  00000000 *................*
+CFG+    0xfe0   00000000  00000000  00000000  00000000 *................*
+CFG+    0xff0   00000000  00000000  00000000  00000000 *................*

#### CONFIG REGS (AvalonMM_2_PCIeAddrTrans) #### (length=4096)
+CFG+   0x1000   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1010   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1020   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1030   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1040   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1050   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1060   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1070   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1080   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1090   00000000  00000000  00000000  00000000 *................*
+CFG+   0x10a0   00000000  00000000  00000000  00000000 *................*
+CFG+   0x10b0   00000000  00000000  00000000  00000000 *................*
+CFG+   0x10c0   00000000  00000000  00000000  00000000 *................*
+CFG+   0x10d0   00000000  00000000  00000000  00000000 *................*
+CFG+   0x10e0   00000000  00000000  00000000  00000000 *................*
+CFG+   0x10f0   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1100   00000000  00000000  00000000  00000000 *................*
.
.
.
+CFG+   0x1f00   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1f10   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1f20   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1f30   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1f40   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1f50   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1f60   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1f70   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1f80   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1f90   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1fa0   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1fb0   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1fc0   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1fd0   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1fe0   00000000  00000000  00000000  00000000 *................*
+CFG+   0x1ff0   00000000  00000000  00000000  00000000 *................*

======= LOCAL REGISTERS =========
    BoardInfo                                           =0x93200101     @0x00000000
    FirmwareDate                                        =0x08252023     @0x00000004
    FirmwareRevision                                    =0x00010000     @0x00000008
    FirmwareTime                                        =0x00120000     @0x0000000c
    FirmwareFlavorCode                                  =0x00000000     @0x00000010
    NumberAdvancedIPCores                               =0x00000000     @0x00000014
    NumberMsgDmaDescriptors                             =0x00000020     @0x00000018
    BoardCSR                                            =0x00000000     @0x00002000
    InterruptStatus                                     =0x00000000     @0x00002010
    SPI_CommandStatus                                   =0x03004000     @0x000020f0
    SPI_FirmwareAddress                                 =0x03fff024     @0x000020f4
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
    SPI_Ram[0]                                              =0x80c02000     @0x00002100
    FPGA_ChipIdentification[0]                              =0x0059e200     @0x00002400
    FPGA_ChipIdentification[1]                              =0x08a2f910     @0x00002404
    FPGA_ChipTemperature                                    =0x000001c8     @0x00002410
    FPGA_VoltageMonitoring_ADC.VS1_8                        =0x0000001e     @0x00002420
    FPGA_VoltageMonitoring_ADC.VS3_3                        =0x00000038     @0x00002424
    FPGA_VoltageMonitoring_ADC.VCC                          =0x0000002e     @0x00002428
    FPGA_VoltageMonitoring_ADC.VCCP                         =0x0000002e     @0x0000242c
    FPGA_VoltageMonitoring_ADC.VCCPT                        =0x0000002e     @0x00002430
    FPGA_VoltageMonitoring_ADC.VCCERAM                      =0x0000002e     @0x00002434
    FPGA_VoltageMonitoring_ADC.VCCL_HPS                     =0x00000000     @0x00002438
    FPGA_VoltageMonitoring_ADC.ADCGND                       =0x00000000     @0x0000243c
    ClockGen_CSR                                            =0x00000001     @0x00002500
    ClockGen_access                                         =0x00000000     @0x00002504

======= Daughter Card ADC 0 REGISTERS =========
    ADC_Enable                                              =0x00000001     @0x00000000
    ADC_ControlStatus[CCRTNGFC_ADC_0]                       =0x00000020     @0x00000010
    ADC_ControlStatus[CCRTNGFC_ADC_1]                       =0x00000020     @0x00000014
    ADC_ControlStatus[CCRTNGFC_ADC_2]                       =0x00000020     @0x00000018
    ADC_FifoCSR                                             =0x81000000     @0x00000030
    ADC_FifoThreshold                                       =0x00020000     @0x00000034
    ADC_FifoChannelSelect                                   =0x00000fff     @0x00000038
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_0]         =0x80000000     @0x00000100
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_1]         =0x80000000     @0x00000104
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_2]         =0x80000000     @0x00000108
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_3]         =0x80000000     @0x0000010c
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_4]         =0x80000000     @0x00000110
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_5]         =0x80000000     @0x00000114
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_6]         =0x80000000     @0x00000118
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_7]         =0x80000000     @0x0000011c
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_8]         =0x80000000     @0x00000120
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_9]         =0x80000000     @0x00000124
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_10]        =0x80000000     @0x00000128
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_11]        =0x80000000     @0x0000012c
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_0]         =0x80000000     @0x00000140
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_1]         =0x80000000     @0x00000144
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_2]         =0x80000000     @0x00000148
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_3]         =0x80000000     @0x0000014c
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_4]         =0x80000000     @0x00000150
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_5]         =0x80000000     @0x00000154
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_6]         =0x80000000     @0x00000158
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_7]         =0x80000000     @0x0000015c
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_8]         =0x80000000     @0x00000160
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_9]         =0x80000000     @0x00000164
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_10]        =0x80000000     @0x00000168
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_11]        =0x80000000     @0x0000016c
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_0]           =0x00000000     @0x00000180
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_1]           =0x00000000     @0x00000184
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_2]           =0x00000000     @0x00000188
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_3]           =0x00000000     @0x0000018c
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_4]           =0x00000000     @0x00000190
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_5]           =0x00000000     @0x00000194
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_6]           =0x00000000     @0x00000198
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_7]           =0x00000000     @0x0000019c
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_8]           =0x00000000     @0x000001a0
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_9]           =0x00000000     @0x000001a4
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_10]          =0x00000000     @0x000001a8
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_11]          =0x00000000     @0x000001ac
    ADC_Data[CCRTNGFC_ADC_CHANNEL_0]                        =0x00000000     @0x00000200
    ADC_Data[CCRTNGFC_ADC_CHANNEL_1]                        =0x00000000     @0x00000204
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
    ADC_Data[CCRTNGFC_ADC_CHANNEL_2]                        =0x00000000     @0x00000208
    ADC_Data[CCRTNGFC_ADC_CHANNEL_3]                        =0x00000000     @0x0000020c
    ADC_Data[CCRTNGFC_ADC_CHANNEL_4]                        =0x00000000     @0x00000210
    ADC_Data[CCRTNGFC_ADC_CHANNEL_5]                        =0x00000000     @0x00000214
    ADC_Data[CCRTNGFC_ADC_CHANNEL_6]                        =0x00000000     @0x00000218
    ADC_Data[CCRTNGFC_ADC_CHANNEL_7]                        =0x00000000     @0x0000021c
    ADC_Data[CCRTNGFC_ADC_CHANNEL_8]                        =0x00000000     @0x00000220
    ADC_Data[CCRTNGFC_ADC_CHANNEL_9]                        =0x00000000     @0x00000224
    ADC_Data[CCRTNGFC_ADC_CHANNEL_10]                       =0x00000000     @0x00000228
    ADC_Data[CCRTNGFC_ADC_CHANNEL_11]                       =0x00000000     @0x0000022c

======= Daughter Card ADC 1 REGISTERS =========
    ADC_Enable                                              =0x00000001     @0x00000000
    ADC_ControlStatus[CCRTNGFC_ADC_0]                       =0x00000020     @0x00000010
    ADC_ControlStatus[CCRTNGFC_ADC_1]                       =0x00000020     @0x00000014
    ADC_ControlStatus[CCRTNGFC_ADC_2]                       =0x00000020     @0x00000018
    ADC_FifoCSR                                             =0x81000000     @0x00000030
    ADC_FifoThreshold                                       =0x00020000     @0x00000034
    ADC_FifoChannelSelect                                   =0x00000fff     @0x00000038
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_0]         =0x80000000     @0x00000100
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_1]         =0x80000000     @0x00000104
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_2]         =0x80000000     @0x00000108
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_3]         =0x80000000     @0x0000010c
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_4]         =0x80000000     @0x00000110
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_5]         =0x80000000     @0x00000114
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_6]         =0x80000000     @0x00000118
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_7]         =0x80000000     @0x0000011c
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_8]         =0x80000000     @0x00000120
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_9]         =0x80000000     @0x00000124
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_10]        =0x80000000     @0x00000128
    ADC_PositiveCalibration[CCRTNGFC_ADC_CHANNEL_11]        =0x80000000     @0x0000012c
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_0]         =0x80000000     @0x00000140
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_1]         =0x80000000     @0x00000144
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_2]         =0x80000000     @0x00000148
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_3]         =0x80000000     @0x0000014c
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_4]         =0x80000000     @0x00000150
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_5]         =0x80000000     @0x00000154
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_6]         =0x80000000     @0x00000158
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_7]         =0x80000000     @0x0000015c
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_8]         =0x80000000     @0x00000160
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_9]         =0x80000000     @0x00000164
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_10]        =0x80000000     @0x00000168
    ADC_NegativeCalibration[CCRTNGFC_ADC_CHANNEL_11]        =0x80000000     @0x0000016c
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_0]           =0x00000000     @0x00000180
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_1]           =0x00000000     @0x00000184
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_2]           =0x00000000     @0x00000188
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_3]           =0x00000000     @0x0000018c
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_4]           =0x00000000     @0x00000190
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_5]           =0x00000000     @0x00000194
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_6]           =0x00000000     @0x00000198
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_7]           =0x00000000     @0x0000019c
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_8]           =0x00000000     @0x000001a0
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_9]           =0x00000000     @0x000001a4
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_10]          =0x00000000     @0x000001a8
    ADC_OffsetCalibration[CCRTNGFC_ADC_CHANNEL_11]          =0x00000000     @0x000001ac
    ADC_Data[CCRTNGFC_ADC_CHANNEL_0]                        =0x00000000     @0x00000200
    ADC_Data[CCRTNGFC_ADC_CHANNEL_1]                        =0x00000000     @0x00000204
    ADC_Data[CCRTNGFC_ADC_CHANNEL_2]                        =0x00000000     @0x00000208
    ADC_Data[CCRTNGFC_ADC_CHANNEL_3]                        =0x00000000     @0x0000020c
    ADC_Data[CCRTNGFC_ADC_CHANNEL_4]                        =0x00000000     @0x00000210
    ADC_Data[CCRTNGFC_ADC_CHANNEL_5]                        =0x00000000     @0x00000214
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
    ADC_Data[CCRTNGFC_ADC_CHANNEL_6]                        =0x00000000     @0x00000218
    ADC_Data[CCRTNGFC_ADC_CHANNEL_7]                        =0x00000000     @0x0000021c
    ADC_Data[CCRTNGFC_ADC_CHANNEL_8]                        =0x00000000     @0x00000220
    ADC_Data[CCRTNGFC_ADC_CHANNEL_9]                        =0x00000000     @0x00000224
    ADC_Data[CCRTNGFC_ADC_CHANNEL_10]                       =0x00000000     @0x00000228
    ADC_Data[CCRTNGFC_ADC_CHANNEL_11]                       =0x00000000     @0x0000022c

======= Daughter Card DAC 0 REGISTERS =========
    DAC_Enable                                              =0x00000000     @0x00000000
    DAC_UpdateSelect                                        =0x00000000     @0x00000004
    DAC_ChannelSelect                                       =0x00000000     @0x00000008
    DAC_ControlStatus[CCRTNGFC_DAC_0]                       =0x00000000     @0x00000010
    DAC_ControlStatus[CCRTNGFC_DAC_1]                       =0x00000000     @0x00000014
    DAC_ControlStatus[CCRTNGFC_DAC_2]                       =0x00000000     @0x00000018
    DAC_ControlStatus[CCRTNGFC_DAC_3]                       =0x00000000     @0x0000001c
    DAC_ControlStatus[CCRTNGFC_DAC_4]                       =0x00000000     @0x00000020
    DAC_ControlStatus[CCRTNGFC_DAC_5]                       =0x00000000     @0x00000024
    DAC_FifoCSR                                             =0x00000000     @0x00000030
    DAC_FifoThreshold                                       =0x00000000     @0x00000034
    DAC_FifoWriteCount                                      =0x00000000     @0x00000038
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_0]         =0x00000000     @0x00000140
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_1]         =0x00000000     @0x00000144
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_2]         =0x00000000     @0x00000148
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_3]         =0x00000000     @0x0000014c
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_4]         =0x00000000     @0x00000150
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_5]         =0x00000000     @0x00000154
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_6]         =0x00000000     @0x00000158
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_7]         =0x00000000     @0x0000015c
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_8]         =0x00000000     @0x00000160
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_9]         =0x00000000     @0x00000164
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_10]        =0x00000000     @0x00000168
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_11]        =0x00000000     @0x0000016c
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_0]           =0x00000000     @0x00000180
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_1]           =0x00000000     @0x00000184
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_2]           =0x00000000     @0x00000188
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_3]           =0x00000000     @0x0000018c
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_4]           =0x00000000     @0x00000190
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_5]           =0x00000000     @0x00000194
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_6]           =0x00000000     @0x00000198
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_7]           =0x00000000     @0x0000019c
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_8]           =0x00000000     @0x000001a0
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_9]           =0x00000000     @0x000001a4
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_10]          =0x00000000     @0x000001a8
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_11]          =0x00000000     @0x000001ac
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_0]         =0x00000000     @0x00000100
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_1]         =0x00000000     @0x00000104
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_2]         =0x00000000     @0x00000108
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_3]         =0x00000000     @0x0000010c
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_4]         =0x00000000     @0x00000110
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_5]         =0x00000000     @0x00000114
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_6]         =0x00000000     @0x00000118
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_7]         =0x00000000     @0x0000011c
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_8]         =0x00000000     @0x00000120
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_9]         =0x00000000     @0x00000124
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_10]        =0x00000000     @0x00000128
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_11]        =0x00000000     @0x0000012c
    DAC_Data[CCRTNGFC_DAC_CHANNEL_0]                        =0x00000000     @0x00000200
    DAC_Data[CCRTNGFC_DAC_CHANNEL_1]                        =0x00000000     @0x00000204
    DAC_Data[CCRTNGFC_DAC_CHANNEL_2]                        =0x00000000     @0x00000208
    DAC_Data[CCRTNGFC_DAC_CHANNEL_3]                        =0x00000000     @0x0000020c
    DAC_Data[CCRTNGFC_DAC_CHANNEL_4]                        =0x00000000     @0x00000210
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
    DAC_Data[CCRTNGFC_DAC_CHANNEL_5]                          =0x00000000     @0x00000214
    DAC_Data[CCRTNGFC_DAC_CHANNEL_6]                          =0x00000000     @0x00000218
    DAC_Data[CCRTNGFC_DAC_CHANNEL_7]                          =0x00000000     @0x0000021c
    DAC_Data[CCRTNGFC_DAC_CHANNEL_8]                          =0x00000000     @0x00000220
    DAC_Data[CCRTNGFC_DAC_CHANNEL_9]                          =0x00000000     @0x00000224
    DAC_Data[CCRTNGFC_DAC_CHANNEL_10]                         =0x00000000     @0x00000228
    DAC_Data[CCRTNGFC_DAC_CHANNEL_11]                         =0x00000000     @0x0000022c

======= Daughter Card DAC 1 REGISTERS =========
    DAC_Enable                                                =0x00000000     @0x00000000
    DAC_UpdateSelect                                          =0x00000000     @0x00000004
    DAC_ChannelSelect                                         =0x00000000     @0x00000008
    DAC_ControlStatus[CCRTNGFC_DAC_0]                         =0x00000000     @0x00000010
    DAC_ControlStatus[CCRTNGFC_DAC_1]                         =0x00000000     @0x00000014
    DAC_ControlStatus[CCRTNGFC_DAC_2]                         =0x00000000     @0x00000018
    DAC_ControlStatus[CCRTNGFC_DAC_3]                         =0x00000000     @0x0000001c
    DAC_ControlStatus[CCRTNGFC_DAC_4]                         =0x00000000     @0x00000020
    DAC_ControlStatus[CCRTNGFC_DAC_5]                         =0x00000000     @0x00000024
    DAC_FifoCSR                                               =0x00000000     @0x00000030
    DAC_FifoThreshold                                         =0x00000000     @0x00000034
    DAC_FifoWriteCount                                        =0x00000000     @0x00000038
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_0]           =0x00000000     @0x00000140
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_1]           =0x00000000     @0x00000144
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_2]           =0x00000000     @0x00000148
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_3]           =0x00000000     @0x0000014c
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_4]           =0x00000000     @0x00000150
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_5]           =0x00000000     @0x00000154
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_6]           =0x00000000     @0x00000158
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_7]           =0x00000000     @0x0000015c
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_8]           =0x00000000     @0x00000160
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_9]           =0x00000000     @0x00000164
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_10]          =0x00000000     @0x00000168
    DAC_NegativeCalibration[CCRTNGFC_DAC_CHANNEL_11]          =0x00000000     @0x0000016c
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_0]             =0x00000000     @0x00000180
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_1]             =0x00000000     @0x00000184
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_2]             =0x00000000     @0x00000188
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_3]             =0x00000000     @0x0000018c
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_4]             =0x00000000     @0x00000190
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_5]             =0x00000000     @0x00000194
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_6]             =0x00000000     @0x00000198
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_7]             =0x00000000     @0x0000019c
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_8]             =0x00000000     @0x000001a0
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_9]             =0x00000000     @0x000001a4
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_10]            =0x00000000     @0x000001a8
    DAC_OffsetCalibration[CCRTNGFC_DAC_CHANNEL_11]            =0x00000000     @0x000001ac
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_0]           =0x00000000     @0x00000100
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_1]           =0x00000000     @0x00000104
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_2]           =0x00000000     @0x00000108
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_3]           =0x00000000     @0x0000010c
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_4]           =0x00000000     @0x00000110
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_5]           =0x00000000     @0x00000114
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_6]           =0x00000000     @0x00000118
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_7]           =0x00000000     @0x0000011c
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_8]           =0x00000000     @0x00000120
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_9]           =0x00000000     @0x00000124
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_10]          =0x00000000     @0x00000128
    DAC_PositiveCalibration[CCRTNGFC_DAC_CHANNEL_11]          =0x00000000     @0x0000012c
    DAC_Data[CCRTNGFC_DAC_CHANNEL_0]                          =0x00000000     @0x00000200
    DAC_Data[CCRTNGFC_DAC_CHANNEL_1]                          =0x00000000     @0x00000204
    DAC_Data[CCRTNGFC_DAC_CHANNEL_2]                          =0x00000000     @0x00000208
    DAC_Data[CCRTNGFC_DAC_CHANNEL_3]                          =0x00000000     @0x0000020c
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
    DAC_Data[CCRTNGFC_DAC_CHANNEL_4]                        =0x00000000     @0x00000210
    DAC_Data[CCRTNGFC_DAC_CHANNEL_5]                        =0x00000000     @0x00000214
    DAC_Data[CCRTNGFC_DAC_CHANNEL_6]                        =0x00000000     @0x00000218
    DAC_Data[CCRTNGFC_DAC_CHANNEL_7]                        =0x00000000     @0x0000021c
    DAC_Data[CCRTNGFC_DAC_CHANNEL_8]                        =0x00000000     @0x00000220
    DAC_Data[CCRTNGFC_DAC_CHANNEL_9]                        =0x00000000     @0x00000224
    DAC_Data[CCRTNGFC_DAC_CHANNEL_10]                       =0x00000000     @0x00000228
    DAC_Data[CCRTNGFC_DAC_CHANNEL_11]                       =0x00000000     @0x0000022c

======= Daughter Card ADC and DAC FIFO REGISTERS =========
    M0Adc_Fifo                                              =0xbaadbeef     @0x00010000
    M0Dac_Fifo                                              =0x00000000     @0x00014000
    M1Adc_Fifo                                              =0xbaadbeef     @0x00018000
    M1Dac_Fifo                                              =0x00000000     @0x0001c000

======= LDIO REGISTERS =========
    LDIO_Enable                                             =0x00000000     @0x00003000
    LDIO_InputSnapshot                                      =0x00000000     @0x00003008
    LDIO_OutputSync                                         =0x00000000     @0x0000300c
    DIO_Direction[CCRTNGFC_MAIN_DIO_MODULE_0]               =0x00000000     @0x00003020
    DIO_Set_OutputDirection[CCRTNGFC_MAIN_DIO_MODULE_0]     =0x00000000     @0x00003030
    DIO_Set_InputDirection[CCRTNGFC_MAIN_DIO_MODULE_0]      =0x00000000     @0x00003040
    LDIO_OutputChannels[CCRTNGFC_MAIN_DIO_MODULE_0]         =0x00000000     @0x00003100
    LDIO_OutputChannels[CCRTNGFC_MAIN_LIO_MODULE_1]         =0x00000000     @0x00003104
    LDIO_Set_OutputChannelsHigh[CCRTNGFC_MAIN_DIO_MODULE_0] =0x00000000     @0x00003110
    LDIO_Set_OutputChannelsHigh[CCRTNGFC_MAIN_LIO_MODULE_1] =0x00000000     @0x00003114
    LDIO_Set_OutputChannelsLow[CCRTNGFC_MAIN_DIO_MODULE_0]  =0x00000000     @0x00003120
    LDIO_Set_OutputChannelsLow[CCRTNGFC_MAIN_LIO_MODULE_1]  =0x00000000     @0x00003124
    LDIO_InputChannels[CCRTNGFC_MAIN_DIO_MODULE_0]          =0x00000000     @0x00003140
    LDIO_InputChannels[CCRTNGFC_MAIN_LIO_MODULE_1]          =0x00000000     @0x00003144
    LDIO_InputChannelsFilter[CCRTNGFC_MAIN_DIO_MODULE_0]    =0x00000000     @0x00003150
    LDIO_InputChannelsFilter[CCRTNGFC_MAIN_LIO_MODULE_1]    =0x00000000     @0x00003154
    LDIO_ChannelsPolarity[CCRTNGFC_MAIN_DIO_MODULE_0]       =0x00000000     @0x00003160
    LDIO_ChannelsPolarity[CCRTNGFC_MAIN_LIO_MODULE_1]       =0x00000000     @0x00003164
    LDIO_COS_ChannelsEnable[CCRTNGFC_MAIN_DIO_MODULE_0]     =0x00000000     @0x00003170
    LDIO_COS_ChannelsEnable[CCRTNGFC_MAIN_LIO_MODULE_1]     =0x00000000     @0x00003174
    LDIO_COS_ChannelsMode[CCRTNGFC_MAIN_DIO_MODULE_0]       =0x00000000     @0x00003180
    LDIO_COS_ChannelsMode[CCRTNGFC_MAIN_LIO_MODULE_1]       =0x00000000     @0x00003184
    LDIO_COS_ChannelsEdgeSense[CCRTNGFC_MAIN_DIO_MODULE_0]  =0x00000000     @0x00003190
    LDIO_COS_ChannelsEdgeSense[CCRTNGFC_MAIN_LIO_MODULE_1]  =0x00000000     @0x00003194
    LDIO_COS_ChannelsOverflow[CCRTNGFC_MAIN_DIO_MODULE_0]   =0x00000000     @0x000031a0
    LDIO_COS_ChannelsOverflow[CCRTNGFC_MAIN_LIO_MODULE_1]   =0x00000000     @0x000031a4
    LDIO_COS_ChannelsStatus[CCRTNGFC_MAIN_DIO_MODULE_0]     =0x00000000     @0x000031b0
    LDIO_COS_ChannelsStatus[CCRTNGFC_MAIN_LIO_MODULE_1]     =0x00000000     @0x000031b4

======= DIAG RAM REGISTERS =========
    DiagRam[0]                                              =0x00000000     @0x00008000

======= CONFIG REGISTERS =========
    PcieLinkPartners.a2p_interrupt_status                   =0x00000000     @0x00000040
    PcieLinkPartners.a2p_interrupt_enable                   =0x00000000     @0x00000050

#### PCIe Link Partners (p2a_mailbox) #### (length=32)
+P2A+    0x800   00000000  00000000  00000000  00000000 *................*
+P2A+    0x810   00000000  00000000  00000000  00000000 *................*

#### PCIe Link Partners (a2p_mailbox) #### (length=32)
+A2P+    0x900   00000000  00000000  00000000  00000000 *................*
+A2P+    0x910   00000000  00000000  00000000  00000000 *................*

    AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x00001004
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001000
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x0000100c
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001008
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x00001014
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001010
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x0000101c
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001018
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x00001024
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001020
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x0000102c
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001028
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x00001034
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001030
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x0000103c
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001038
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x00001044
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001040
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x0000104c
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001048
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x00001054
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001050
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x0000105c
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001058
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x00001064
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001060
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x0000106c
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001068
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x00001074
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001070
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_High  =0x00000000      @0x0000107c
                AvalonMM_2_PCIeAddrTrans[Entry].PCI_Physical_Address_Low   =0x00000000      @0x00001078

============== MsgDma Engine 0 ==============

    === Dispatcher Csr ===
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.Status                                      =0x0000000a     @0x00004000
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.Control                                     =0x00000000     @0x00004004
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.ReadFillLevel                               =0x00000000     @0x00004008
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.WriteFillLevel                              =0x00000000     @0x0000400a
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.ResponseFillLevel                           =0x00000000     @0x0000400c
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.ReadSequenceNumber                          =0x00000000     @0x00004010
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.WriteSequenceNumber                         =0x00000000     @0x00004012

    === Prefetcher Csr ===
    MsgDmaRegs[Eng].MsgDmaPrefetcherCsr.Control                                     =0x00000000     @0x00004020
    MsgDmaRegs[Eng].MsgDmaPrefetcherCsr.NextDescriptorPointerLow                    =0x00000000     @0x00004024
    MsgDmaRegs[Eng].MsgDmaPrefetcherCsr.NextDescriptorPointerHigh                   =0x00000000     @0x00004028
    MsgDmaRegs[Eng].MsgDmaPrefetcherCsr.DescriptorPollingFrequency                  =0x00000000     @0x0000402c
    MsgDmaRegs[Eng].MsgDmaPrefetcherCsr.Status                                      =0x00000000     @0x00004030

    === Descriptor at offset 0 ===
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].ReadAddressLow           =0x00000000     @0x00005000
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].WriteAddressLow          =0x00000000     @0x00005004
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].Length                   =0x00000000     @0x00005008
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].NextDescriptorPointerLow =0x00000000     @0x0000500c
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].ActualBytesTransferred   =0x00000000     @0x00005010
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].Status                   =0x00000000     @0x00005014
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].SequenceNumber           =0x00000000     @0x0000501c
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].ReadBurstCount           =0x00000000     @0x0000501e
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].WriteBurstCount          =0x00000000     @0x0000501f
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].ReadStride               =0x00000000     @0x00005020
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].WriteStride              =0x00000000     @0x00005022
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].ReadAddressHigh          =0x00000000     @0x00005024
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].WriteAddressHigh         =0x00000000     @0x00005028
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].NextDescriptorPointerHigh=0x00000000     @0x0000502c
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].Control                  =0x00000000     @0x0000503c
    .
    .
    .
    === Terminating Descriptor at offset 31 ===
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.ReadAddressLow            =0x00000000     @0x000057c0
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.WriteAddressLow           =0x00000000     @0x000057c4
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.Length                    =0x00000000     @0x000057c8
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.NextDescriptorPointerLow  =0x00000000     @0x000057cc
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.ActualBytesTransferred    =0x00000000     @0x000057d0
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.Status                    =0x00000000     @0x000057d4
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.SequenceNumber            =0x00000000     @0x000057dc
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.ReadBurstCount            =0x00000000     @0x000057de
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.WriteBurstCount           =0x00000000     @0x000057df
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.ReadStride                =0x00000000     @0x000057e0
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.WriteStride               =0x00000000     @0x000057e2
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.ReadAddressHigh           =0x00000000     @0x000057e4
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.WriteAddressHigh          =0x00000000     @0x000057e8
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.NextDescriptorPointerHigh =0x00000000     @0x000057ec
    MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.Control                   =0x00000000     @0x000057fc
    .
    .
    .
============== MsgDma Engine 5 ==============

    === Dispatcher Csr ===
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.Status                                      =0x0000000a     @0x00004140
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.Control                                     =0x00000000     @0x00004144
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.ReadFillLevel                               =0x00000000     @0x00004148
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.WriteFillLevel                              =0x00000000     @0x0000414a
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.ResponseFillLevel                           =0x00000000     @0x0000414c
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.ReadSequenceNumber                          =0x00000000     @0x00004150
    MsgDmaRegs[Eng].MsgDmaDispatcherCsr.WriteSequenceNumber                         =0x00000000     @0x00004152

    === Prefetcher Csr ===
    MsgDmaRegs[Eng].MsgDmaPrefetcherCsr.Control                                     =0x00000000     @0x00004160
    MsgDmaRegs[Eng].MsgDmaPrefetcherCsr.NextDescriptorPointerLow                    =0x00000000     @0x00004164
    MsgDmaRegs[Eng].MsgDmaPrefetcherCsr.NextDescriptorPointerHigh                   =0x00000000     @0x00004168
    MsgDmaRegs[Eng].MsgDmaPrefetcherCsr.DescriptorPollingFrequency                  =0x00000000     @0x0000416c
    MsgDmaRegs[Eng].MsgDmaPrefetcherCsr.Status                                      =0x00000000     @0x00004170

    === Descriptor at offset 0 ===
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].ReadAddressLow           =0x00000000     @0x00007800
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].WriteAddressLow          =0x00000000     @0x00007804
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].Length                   =0x00000000     @0x00007808
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].NextDescriptorPointerLow =0x00000000     @0x0000780c
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].ActualBytesTransferred   =0x00000000     @0x00007810
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].Status                   =0x00000000     @0x00007814
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].SequenceNumber           =0x00000000     @0x0000781c
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].ReadBurstCount           =0x00000000     @0x0000781e
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].WriteBurstCount          =0x00000000     @0x0000781f
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].ReadStride               =0x00000000     @0x00007820
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].WriteStride              =0x00000000     @0x00007822
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].ReadAddressHigh          =0x00000000     @0x00007824
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].WriteAddressHigh         =0x00000000     @0x00007828
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].NextDescriptorPointerHigh=0x00000000     @0x0000782c
    MsgDmaDescriptorRegs[Eng].MsgDmaExtendedDescriptor[Id].Control                  =0x00000000     @0x0000783c
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
.
.
.
=== Terminating Descriptor at offset 31 ===
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.ReadAddressLow            =0x00000000     @0x00007fc0
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.WriteAddressLow           =0x00000000     @0x00007fc4
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.Length                    =0x00000000     @0x00007fc8
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.NextDescriptorPointerLow  =0x00000000     @0x00007fcc
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.ActualBytesTransferred    =0x00000000     @0x00007fd0
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.Status                    =0x00000000     @0x00007fd4
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.SequenceNumber            =0x00000000     @0x00007fdc
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.ReadBurstCount            =0x00000000     @0x00007fde
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.WriteBurstCount           =0x00000000     @0x00007fdf
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.ReadStride                =0x00000000     @0x00007fe0
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.WriteStride               =0x00000000     @0x00007fe2
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.ReadAddressHigh           =0x00000000     @0x00007fe4
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.WriteAddressHigh          =0x00000000     @0x00007fe8
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.NextDescriptorPointerHigh =0x00000000     @0x00007fec
MsgDmaDescriptorRegs[Eng].MsgDmaTerminatingDescriptor.Control                   =0x00000000     @0x00007ffc
```

3.1.6 ccrtngfc_regedit

This is an interactive test to display and write to local, configuration and physical memory.

Usage: ./ccrtngfc_regedit [-b board]
 -b board: Board number -- default board is 0

Example display:

./ccrtngfc_regedit

```
Device Name: /dev/ccrtngfc0

  LOCAL REGION: Physical Addr=0xfb800000 Size=4194304 (0x00400000)
 CONFIG REGION: Physical Addr=0xfbc00000 Size=32768 (0x00008000)

         LOCAL: Register 0x7ffff7800000 Offset=0x0 Size=0x00400000
        CONFIG: Register 0x7ffff7fb7000 Offset=0x0 Size=0x00008000
        LIBPTR: Register 0x7ffff7ebf000 Offset=0x0 Size=0x00013e58

Initialize_Board: Firmware Rev. 0x10000 successful

Virtual Address: 0x7ffff7800000
   1 = Create Physical Memory         2 = Destroy Physical memory
   3 = Display Channel Data           4 = Display Driver Information
   5 = Display Physical Memory Info   6 = Display Registers (CONFIG)
   7 = Display Registers (LOCAL)      8 = Dump Physical Memory
   9 = Reset Board                   10 = Write Register (LOCAL)
  11 = Write Register (CONFIG)       12 = Write Physical Memory

Main Selection ('h'=display menu, 'q'=quit)->
```

3.1.7 ccrtngfc_tst

This is an interactive test to exercise some of the driver features.

Usage: ./ccrtngfc_tst [-b board]
 -b board: Board number -- default board is 0

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

Example display:

./ccrtngfc_tst

```
Device Name: /dev/ccrtngfc0

  LOCAL REGION: Physical Addr=0xfb800000 Size=4194304 (0x00400000)
 CONFIG REGION: Physical Addr=0xfbc00000 Size=32768 (0x00008000)

         LOCAL: Register 0x7ffff7800000 Offset=0x0 Size=0x00400000
        CONFIG: Register 0x7ffff7fb7000 Offset=0x0 Size=0x00008000
        LIBPTR: Register 0x7ffff7ebf000 Offset=0x0 Size=0x00013e58
Initialize_Board: Firmware Rev. 0x10000 successful

  01 = add irq                       02 = disable pci interrupts
  03 = enable pci interrupts         04 = get device error
  05 = get driver info               06 = get physical memory
  07 = init board                    08 = mmap select
  09 = mmap(CONFIG registers)        10 = mmap(LOCAL registers)
  11 = mmap(physical memory)         12 = munmap(physical memory)
  13 = no command                    14 = read operation
  15 = remove irq                    16 = reset board
  17 = restore config registers      18 = write operation

Main Selection ('h'=display menu, 'q'=quit)->
```

3.1.8 ccrtngfc_wreg

This is a simple test to write to the local registers at the user specified offset.

```
Usage: ./ccrtngfc_wreg [-b Board] [-C] [-o Offset] [-s Size] [-v Value] [-x]
 -b Board   : Board selection --  default board is 0
 -C         : Select Config Registers instead of Local Registers
 -o Offset  : Hex offset to write to -- default offset is 0x0
 -s Size    : Number of bytes to write in decimal -- default size is 0x4
 -v Value   : Hex value to write at offset -- default value is 0x0
 -x         : Do not read back just written values -- default read back values
```

Example display:

./ccrtngfc_wreg -v12345678 -o0x8000 -s400

```
Device Name: /dev/ccrtngfc0

  LOCAL REGION: Physical Addr=0xfb800000 Size=4194304 (0x00400000)
 CONFIG REGION: Physical Addr=0xfbc00000 Size=32768 (0x00008000)

         LOCAL: Register 0x7ffff7800000 Offset=0x0 Size=0x00400000
        CONFIG: Register 0x7ffff7fb7000 Offset=0x0 Size=0x00008000
        LIBPTR: Register 0x7ffff7ebf000 Offset=0x0 Size=0x00013e58

Writing 0x12345678 to offset 0x8000 for 400 bytes

#### LOCAL REGS #### (length=400)
+LCL+   0x8000   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8010   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8020   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8030   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8040   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8050   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8060   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
+LCL+   0x8070   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8080   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8090   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x80a0   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x80b0   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x80c0   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x80d0   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x80e0   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x80f0   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8100   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8110   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8120   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8130   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8140   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8150   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8160   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8170   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
+LCL+   0x8180   12345678  12345678  12345678  12345678 *.4Vx.4Vx.4Vx.4Vx*
```

3.1.9 Flash/ccrtngfc_flash

This program is used to burn new firmware or update the license of an already installed firmware. It can also be used to reload the firmware on the card. This must only be done at the direction of Concurrent Real-Time support team, otherwise, they could render the board useless.

```
./ccrtngfc_flash -b[Board] -B -F[!] -i -L -q -Q -r[OutFile] -R -v -w[InFile] -X
-b [Board]        : Board number. Must be specified
-B                : Reload Base Level Firmware if MultiFirmware support present
-F                : Force Read Flash:  Overwrite output file if exists
-F                : Force Write Flash: Do not abort Flash burn for header label mismatch
-F!               : Force Write Flash: Serious override required to continue burning
-i                : Query chip, on-board flash and InFile if specified
-L                : Update License only. (default is to update entire firmware)
-q                : Quite (non-interactive) mode
-Q                : Quite (non-interactive) mode. Also dump FPGAWB message
-r                : Read Flash and write to output file created by ./ccrtngfc_flash
-r [OutFile]      : Read Flash and write to output file 'OutFile'
-R                : Reload Firmware at sector address in Flash
-R [SectorNumber] : Reload Firmware at sector address 'SectorNumber'
-v                : Enable verbose mode
-w [InFile]       : Read input FPGA file and Flash the board
-X                : Use Full File. Do not truncate for firmware write

======================================== Notes ========================================
  Board must be specifed. Use '-b' option
  Query option '-i' not allowed with '-B', '-R#', '-L', 'r' or '-X' options
  Firmware reload '-B' or '-R' not allowed with '-i', '-L', '-r', '-w' or '-X' options
  Firmware read flash '-r' not allowed with '-B', '-i', '-L', '-R', '-w' or '-X' options
  Base Run Level '-B' or '-R#' option not allowed with '-i', '-L', 'r', '-w' or '-X' options
  Must specify write flash option '-w' when License only option '-L' is specified
  License only option '-L' not allowed with '-B', '-i', '-R', '-w' or '-X' options
  Don't truncate file option '-X' cannot be selected with the license only update '-L' option
  Don't truncate file option '-X' can only be used with the '-w' option
  Inquiry '-i' can be used '-w' options
================================================================================

e.g. ./ccrtngfc_flash -b0                 (Query chip and on-board Flash)
     ./ccrtngfc_flash -b0 -i              (Query chip and on-board Flash)
     ./ccrtngfc_flash -b0 -i -w InFile    (Query chip, on-board Flash and InFile)
     ./ccrtngfc_flash -b0 -r OutFile      (On-board FPGA ===> OutFile)
     ./ccrtngfc_flash -b0 -w InFile       (InFile ===> On-board FPGA - use truncated file)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
./ccrtngfc_flash -b0 -w InFile -v     (InFile ===> On-board FPGA - use truncated file
                                       - verbose)
./ccrtngfc_flash -b0 -w InFile -X     (InFile ===> On-board FPGA - use entire file)
./ccrtngfc_flash -b0 -w InFile -L     (InFile ===> On-board FPGA - only license
                                       updated - interactive)
./ccrtngfc_flash -b0 -w InFile -L -q  (InFile ===> On-board FPGA - only license
                                       updated - non-interactive)
./ccrtngfc_flash -b0 -R               (Reload Firmware - i.e. power-cycle the card)
                                       - Run Level
./ccrtngfc_flash -b0 -B               (Reload Firmware - i.e. power-cycle the card)
                                       - Base Leve)
./ccrtngfc_flash -b0 -R 0             (Reload Firmware - i.e. power-cycle the card)
                                       - Base Level
./ccrtngfc_flash -b0 -R 200           (Reload Firmware - i.e. power-cycle the card)
                                       - at sector 200
```

If the installed firmware is a Multi-Level firmware and you are running at Base Level, then the only utility that will be able to access the card will be this ***ccrtngfc_flash*** *utility. You will need to switch to Run Level before un-restricted access is allowed to the card.*

Caution: *You can use this utility to reload or access the firmware for a specific card. If you have some time critical applications running on another card, its execution may be affected due to the access to the specific card.*

3.1.10 Flash/ccrtngfc_label

This utility is only supplied for those customers that are creating their own firmware and need to install in a RedHawk system. In its simplest form, the customer will request a License file from Concurrent Real-Time for the option to burn their custom firmware. The license file (*.lic) supplied by Concurrent Real-Time, along with the customer firmware (*.rpd) file will be supplied to this utility to create a burnable FPGA file (*.cust), that will be supplied to the *ccrtngfc_flash* utility to burn the firmware on the card.

The user can also supply the '-x' option to additionally create a license only file (*.cust.liconly) file that is associated with the firmware (.rpd). This is useful if you only wish to update the license information of a card that already has the same firmware installed. This is similar to having a (*.cust) file and using the '-L' option when running the *ccrtngfc_flash* utility.

```
./ccrtngfc_label -d[OutputDirectory] -c[ChipName] -F -i[InputFile] -K[FpgawbKey]
                 -L[LicenseFile] -m[MemberCode] -o[OutputFile] -S[RunLevelSectorAddress]
                 -t[Tag] -x
-d [OutputDirectory]       : Directory to use for Output File
-c [ChipName]              : Chip Name. One of:
                             EPCQ16 EPCQ32 EPCQ64 EPCQ128 EPCQ256 MTQU512
                             (This option is mandatory if not specified in license file)
-F                         : Force overwriting of output file if it exists
-i [InputFile]             : Raw input file. (.rpd extension)
-K [FpgawbKey]             : Fpgawb Key is required if license contains FPGA workbench restriction
-L [LicenseFile]           : License file (.lic extension) to restrict firmware access
                             If '-i' option is not specified, the license file is dumped to stderr
-m [MemberCode]            : Specify Member Code (048, 115, C9)
                             (This option is mandatory if not specified in license file)
-o [OutputFile]            : Use output file instead of the default file created by the program
-S [RunLevelSectorAddress] : Run Level Sector Address. (This option is mandatory if not
                             specified in license file)
                           : S0=Base Level, S#=Run Level Number
-t [Tag]                   : Insert this tag name in the default file created by the program
-x                         : Create an additional License only file (*.liconly)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
==== Notes ====
- At least one of option '-L' or '-i' must be specified
- If option '-L' is specified and option '-i' is not specified, license file is dumped
- If option '-i' is specified and option '-L' is not specified, input RPD file information
  is displayed
- Options 'c', '-m' and '-S' are required if they have not already been defined in LicenseFile
- You cannot specify a Run Level Sector '-S' with Single Level Firmware '-1' option
- Run Level Sector address of zero '-S0' represents the Base Level Firmware in Multi-Firmware
  support
- If option '-o' is not specified, the created customer FPGA file name will be as follows:
    <OutputDirectory>/<InputFile>_<Tag>_<Function>_<ChipName><MemberCode><RunLevel>.cust
- If the license file contains an FPGAWB restrict key, then the '-K' FpgawbKey is required

e.g. ./ccrtngfc_label -iraw_file.rpd -L LicenseFile.lic (in its simplest form)
       (output file created is: 'raw_file_<Function>_<ChipName><MemberCode><RunLevel>.cust')
     ./ccrtngfc_label -L LicenseFile.lic (this will display licensing information)
     ./ccrtngfc_label -iraw_RUN_file.rpd -ooutput_file.cust -S100 -L LicenseFile.lic
     ./ccrtngfc_label -iraw_SINGLE_file.rpd -L LicenseFile.lic
     ./ccrtngfc_label -iraw_RUN_file.rpd -ooutput_file.cust -S200 -L LicenseFile.lic
     ./ccrtngfc_label -iraw_BASE_file.rpd -S0 -L LicenseFile.lic
       (Will cause firmware to be loaded at start offset Base Run Level)
```

3.1.11 Flash/ccrtngfc_dump_license

This utility allows the customer to dump the license information from a firmware *(*.cust)* file or the *(*.liconly)* file.

```
Format: ./ccrtngfc_dump_license <Firmware file>

    This utility only dumps the license information from the *.cust or *.liconly files
    and not the *.lic license file

    e.g ./ccrtngfc_dump_license output_file_048.NGFC_NOLIMIT_MultiFunc_MTQU512048S350.cust
        ./ccrtngfc_dump_license output_file_048.NGFC_NOLIMIT_MultiFunc_MTQU512048S350.cust.liconly
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

3.2 Application Program Interface (API) Access Example Tests

These set of tests are in the *.../test/lib* directory and use the API.

3.2.1 lib/ccrtngfc_acquire_physmem

This is a simple test to acquire physical memory and pause. This is used to test the Cloning region addressing functionality.

```
Usage: ./ccrtngfc_acquire_physmem -[b Board] [-s PhysMemSize]
          -b <board>            (board #, default = 0)
          -s <PhysMemSize>      (Physical Memory Size, default = NONE)
```

Example display:

./ccrtngfc_acquire_physmem -s 100

```
           Physical Memory Information:
             UserPID            =184103
             PhysMemPtr         =0x65d27000
             DriverVirtMemPtr   =0xffff993ee5d27000
             MmapedUserMemPtr   =0x7ffff7fdd000
             PhysMemSize        =0x00001000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =0
             NumOfEntriesUsed   =1
             Flags              =0x0000
....pausing... use <CTRL-C> to terminate
```

3.2.2 lib/ccrtngfc_adc

This test performs validation of the Multi-Function ADC card.

```
Usage: ./ccrtngfc_adc [-A] [-a RollingAve] [-b BoardNo] [-C AdcUpdateClock] [-d Delay]
                      [-e MsgDmaEngine] [-E ExpInpVolt] [-f DataFormat] [-F DebugFile] [-i]
                      [-l LoopCnt] [-m XferMode] [-M SelectAdcModule] [-n NumChans] [-N]
                      [-s InputSignal] [-t Compare] [-T TestBus]
 -A                      (Perform Auto Calibration first using reference voltage)
 -a RollingAve           (Rolling average -- default "=== None ===")
 -b BoardNo              (Board number -- default is 0)
 -C AdcUpdateClock       (select ADC update clock, 0..4 or 'n|N')
    -C 0,5,4             (Ch0..3=Clock0, Ch4..7=Clock5, Ch8..11=Clock4 at MAX SPS)
    -C ^2,3              (Ch0..3=Clock2, Ch4..11=Clock3 assignment only) [** Skip Programming
                          Clock **]
    -C 3@20000.0/n       (Ch0..3=Clock3 at 20000 SPS, Ch4..11=No Clock)
    -C 4                 (Ch0..11=Clock4 at MAX SPS)
    -C 4@150000.0        (Ch0..11=Clock4) at 150000 SPS)
 -d Delay                (Delay between screen refresh -- default is 0 milli-seconds)
 -e MsgDmaEngine         (Select MsgDma Engine -- default "=== get free engine ===")
 -E <ExpInpVolts>@<Tol>  (Expected Input Volts@Tolerance -- default Tol=0.003000)
    +@<Tol>              (Positive Calibration Ref Volt@Tolerance)
    -@<Tol>              (Negative Calibration Ref Volt@Tolerance)
    s@<Tol>              (Requires '-s' input signal option to specify voltage Volt@Tolerance)
                         (valid '-s' arguments are 'g','+','-','f')
 -f DataFormat           (select data format, '2' or 'b')
    -f b,2,b             (Ch0..3 & Ch8..11=Offset binary, Ch4..7=Two's complement)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   -f 2/b               (Ch0..3=Two's complement, Ch4..11=Offset binary)
   -f b                 (Ch0..11=Offset binary)
 -F DebugFile           (Debug file with menu display -- default "=== None ===")
   #DebugFile           (Debug file without display (only summary) -- default "=== None ===")
   @DebugFile           (Debug file without display -- default "=== None ===")
   ~DebugFile           (For gnuplot, no header or summary -- default "=== None ===")
   @, # or ~            (No debug file and no display -- default "=== None ===")
 -i                     (Enable Interrupts -- default = Disable)
 -l LoopCnt             (Loop count -- default is 0)
 -m XferMode            (Transfer Mode -- default = 'MSGDMA Channel')
   -mlm                 (Library: (Channel Registers) Modular scatter-gather DMA mode)
   -mlx                 (Library: (Channel Registers) Clone (ADC->MEM) Modular scatter-gather
                         DMA mode)
   -mlz                 (Library: (Channel Registers) Clone (ADC->DIAG->MEM) Modular
                         scatter-gather DMA mode)
   -mdp                 (Driver:  (Channel Registers) PIO mode)
   -mlc                 (Library: (Channel Registers) program I/O Fast Memory Copy)
   -mlp                 (Library: (Channel Registers) PIO)
   -mdP                 (Driver:  (FIFO) PIO mode)
   -mlP                 (Library: (FIFO) PIO mode)
 -M SelectAdcModule     (Select ADC Module -- default is module 0)
 -n NumChans            (Number of channels -- default is 12)
 -N                     (Open device with O_NONBLOCK flag)
 -s InputSignal         (select input signal, 'e', 'g', '+', '-', 'f', '0..11')
   -s e,g,e             (Ch0..3 & 8..11=External input, Ch4..7=ground calibration)
   -s +/e               (Ch0..3=Postive calibration, Ch8..11=external reference)
   -s -                 (Ch0..11=Negative calibration)
   -s e/e,f             (Ch0..7=external reference, Ch8..11=4 volt calibration)
   -s e/10              (Ch0..3=external reference, Ch4..11=DAC Channel 10)
 -t Compare             (Compare two channels for +/- -- default is "=== None ===")
   -t0,10               (Compare channel 0 and 10 for being in sync)
   -t5/7                (Compare channel 5 and 7 for being in sync)
   -t2,11@0.500         (Compare channel 2 and 11 for being in sync with 0.5V tolerance)
 -T TestBus             (Test Bus Control 'b' or 'o'. Exit after programming this option)
   -T b                 (Calibration Bus Control)
   -T o                 (Open Bus Control)

 e.g. ./ccrtngfc_adc -A -C0@150000.0/1@1234.0 -se/+ (Autocal, ADC0=150000Hz external input,
                                                     ADC1=1234Hz Positive Cal.)
      ./ccrtngfc_adc -A -C0 -s+ -E+          (Autocal, Max Clock, Positive cal.
                                              input, validate result)
      ./ccrtngfc_adc -A -C0 -s- -t0,11 -a100 (Autocal, Max Clock, Negative cal.
                                              input, compare ch0 and ch11, rolling ave=100)
      ./ccrtngfc_adc -C0 -s- -Es             (Max Clock, -9.91V input, validate against -9.91V)
      ./ccrtngfc_adc -C0 -sf -Es             (Max Clock, +4V input, validate against +4V)


If you wish to run both ADC and DAC concurrently, you can try the following:
-------------------------------------------------------------------------
   1) ./ccrtngfc_clock -C0@4500000 -C1@1000000 -l1 (Program ADC Clock 0 at 4.5 MHz and DAC
                                                    Clock 1 at 1.0 MHz)
   2) ./ccrtngfc_dac   -C^1                        (Start DAC using 1 MHz Clock 1 in first
                                                    window)
   3) ./ccrtngfc_adc   -C^0                        (Start ADC using 4.5 MHz Clock 0 in second
                                                    window)
```

Example display:

./ccrtngfc_adc -A -C0@150000.0/1@1234.0 -se/+

```
 ADC Information:
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
              Flags              = 0x00000001
              ModuleNumber       = 0
              Handle             = 0x76da40
              local_ptr          = 0x7ffff7e67000
              local_adc_ptr      = 0x7ffff7e6b000
              local_adc_fifo_ptr = 0x7ffff7e77000
              AdcFp              = 4
              AdcDeviceName      = /dev/ccrtngfc0_adc0
              AdcSerialNumber    = 729512

local_ptr=0x7ffff7e67000

            Physical Memory Information:
              UserPID            =184544
              PhysMemPtr         =0x65d27000
              DriverVirtMemPtr   =0xffff993ee5d27000
              MmapedUserMemPtr   =0x7ffff7fdd000
              PhysMemSize        =0x00001000
              PhysMemSizeFreed   =0x00000000
              EntryInTxTbl       =0
              NumOfEntriesUsed   =1
              Flags              =0x0000
Auto Calibration started...done. (0.602 seconds)

 Board Number          [-b]: 0
 Update Clock Selected [-C]: Ch00..03 OutputClock=0 (0x7) (150000.000 SPS)
                           : Ch04..07 OutputClock=1 (0x1) (1234.000 SPS)
                           : Ch08..11 OutputClock=1 (0x1) (1234.000 SPS)
 Delay                 [-d]: 0 milli-seconds
 MSGDMA Engine         [-e]: 0
 Expected Input Volts  [-E]: === Not Specified ===
 Data Format           [-f]: Ch00..03 Offset binary (0x0)
                           : Ch04..07 Offset binary (0x0)
                           : Ch08..11 Offset binary (0x0)
 Interrupts            [-i]: Disabled
 Loop Count            [-l]: ***Forever***
 Transfer Mode         [-m]: Library: (Channels Registers) MODULAR SCATTER-GATHER DMA I/O
 Selected ADC Module   [-M]: 0
 Number of Channels    [-n]: 12
 Input Signal          [-s]: Ch00..03 [0]External Input
                           : Ch04..07 [1]Calibration Input (0x01: Positive 9.91)
                           : Ch08..11 [1]Calibration Input (0x01: Positive 9.91)
 Scan Count                : 33495           (0:00:00:04)
 Read Duration (microsecs) : TotalDelta:     3.651 (min=   3.576/max=   9.599/ave=   3.679)

          ##### Raw Data #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          ====     ====     ====     ====     ====     ====     ====     ====     ====     ====
  [0]     7fef     8023     803f     801f     fedf     feda     fedc     feda     fed9     fedb

  [1]     fed4     fedb

          ##### Volts #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          =======  =======  =======  =======  =======  =======  =======  =======  =======  =======
  [0]     -0.0052  +0.0107  +0.0192  +0.0095  +9.9118  +9.9103  +9.9109  +9.9103  +9.9100  +9.9106

  [1]     +9.9084  +9.9106

==================================================
                  Date: Tue May 16 15:07:20 2023
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   Expected Input Volts: === Not Specified ===
           Scan Counter: 263107
   WorstMinChanVoltsHWM:  -0.007324 (Ch00)
   WorstMaxChanVoltsHWM:   9.913635 (Ch10)
=====================================================
      <-------- (volts) -------->
Chan  Min       Max       Ave      TolerExeededCnt
====  =======   =======   =======  ===============
 00   -0.0073   -0.0027   -0.0052         -
 01    0.0089    0.0131    0.0110         -
 02    0.0171    0.0217    0.0193         -
 03    0.0070    0.0110    0.0090         -
 04    9.9078    9.9133    9.9105         -
 05    9.9078    9.9133    9.9106         -
 06    9.9078    9.9133    9.9107         -
 07    9.9078    9.9133    9.9108         -
 08    9.9078    9.9130    9.9105         -
 09    9.9078    9.9133    9.9106         -
 10    9.9072    9.9136    9.9102         -
 11    9.9078    9.9133    9.9104         -
=====================================================
```

3.2.3 lib/ccrtngfc_adc_calibrate

This test is useful for performing, saving and restoring ADC calibration.

```
Usage: ./ccrtngfc_adc_calibrate [-A] [-b board] [-i inCalFile] [-o outCalFile]
                                [-R]
 -A                    (perform Auto Calibration)
 -b <board>            (board #, default = 0)
 -i <In Cal File>      (input calibration file [input->board_reg])
 -o <Out Cal File>     (output calibration file [board_reg->output])
 -R                    (reset ADC calibration)

 e.g. ./ccrtngfc_adc_calibrate              (Dump calibration information to
                                             stdout)
      ./ccrtngfc_adc_calibrate -A -o Calfile (Perform Auto calibration and dump
                                             information to 'Calfile')
      ./ccrtngfc_adc_calibrate -i Calfile    (Update board calibration with
                                             supplied 'Calfile')
      ./ccrtngfc_adc_calibrate -R            (Reset ADC calibration)
```

Example display:

./ccrtngfc_adc_calibrate -A

```
           ADC Information:
             Flags              = 0x00000001
             ModuleNumber       = 0
             Handle             = 0x75a4c0
             local_ptr          = 0x7ffff7f55000
             local_adc_ptr      = 0x7ffff7f59000
             local_adc_fifo_ptr = 0x7ffff7f65000
             AdcFp              = 4
             AdcDeviceName      = /dev/ccrtngfc0_adc0
             AdcSerialNumber    = 729512

Device Name    : /dev/ccrtngfc0
Board Serial No: 0 (0x00000000)
Auto Calibration started...done. (0.607 seconds)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
===> Dump to 'stdout'
#Date           : Tue May 16 15:09:50 2023

#Chan   Negative                Offset                  Positive
#====   ========                ======                  ========
 ch00:  0.99966217717155814171 -0.00152587890625000000  1.00019804341718554497
 ch01:  0.99926335178315639496 -0.00610351562500000000  1.00064194900915026665
 ch02:  0.99926836881786584854 -0.00854492187500000000  1.00128439348191022873
 ch03:  1.00097584817558526993  0.00030517578125000000  1.00129837542772293091
 ch04:  1.00159255694597959518  0.01129150390625000000  1.00023180851712822914
 ch05:  1.00036927126348018646 -0.00396728515625000000  1.00088152382522821426
 ch06:  0.99907627562060952187 -0.00518798828125000000  1.00044342176988720894
 ch07:  0.99927996192127466202 -0.00366210937500000000  1.00012438092380762100
 ch08:  0.99944108212366700172 -0.01129150390625000000  1.00134854065254330635
 ch09:  0.99980337964370846748 -0.00488281250000000000  1.00099764997139573097
 ch10:  0.99926861049607396126 -0.01037597656250000000  1.00179374404251575470
 ch11:  1.00017620576545596123  0.00213623046875000000  1.00001918524503707886
```

3.2.4 lib/ccrtngfc_adc_fifo

This test performs validation of the Multi-Function ADC FIFO operation of the card. If two daughter cards are present, both are run concurrently.

```
Usage: ./ccrtngfc_adc_fifo [-A] [-b BoardNo] [-c ChannelSelectMask] [-C AdcUpdateClock]
                           [-d Delay] [-e MsgDmaEngine] [-E ExpInpVolt] [-f DataFormat]
                           [-F DebugFile] [-i] [-l LoopCnt] [-m XferMode]
                           [-M SelectAdcModule] [-N] [-s InputSignal] [-S NumberOfSamples]
                           [-T TestBus] [-V] [-W JitterAndOrDebug] [-X]
 -A                      (Perform Auto Calibration first using reference voltage)
 -b BoardNo              (Board number -- default is 0)
 -c ChannelSelectMask    (Specify channel selection mask 0x0..0xfff)
 -C AdcUpdateClock       (Select ADC update clock, 0..4 or 'n|N'. If '^' first arg, Skip
                          Programming Clock)
    -C 0,3,4             (Ch0..3=Clock0, Ch4..7=Clock3, Ch8..11=Clock4 at MAX SPS)
    -C ^2,3              (Ch0..3=Clock2, Ch4..11=Clock3 assignment only) [** Skip Programming
                          Clock **]
    -C 3@20000.0/n       (Ch0..3=Clock3 at 20000 SPS, Ch4..11=No Clock)
    -C 4                 (Ch0..11=Clock4 at MAX SPS)
    -C 4@150000.0        (Ch0..11=Clock4) at 150000 SPS)
 -d Delay                (Delay between screen refresh -- default is 1 milli-seconds)
 -e MsgDmaEngine         (Select MsgDma Engine -- default "=== get free engine ===")
    -e 0,2               (MsgDma Engine 0 for ADC Module 0 and MsgDma Engine 2 for ADC Module 1)
    -e 3,1               (MsgDma Engine 3 for ADC Module 0 and MsgDma Engine 1 for ADC Module 1)
    -e ,3                (MsgDma Engine Default for ADC Module 0 and MsgDma Engine 3 for ADC
                          Module 1)
 -E <ExpInpVolts>@<Tol>  (Expected Input Volts@Tolerance -- default Tol=0.003000)
    +@<Tol>              (Positive Calibration Ref Volt@Tolerance)
    -@<Tol>              (Negative Calibration Ref Volt@Tolerance)
    s@<Tol>              (Requires '-s' input signal option to specify voltage Volt@Tolerance)
                         (valid '-s' arguments are 'g','+','-','f','t')
 -f DataFormat           (select data format, '2' or 'b')
    -f b,2,b             (Ch0..3 & Ch8..11=Offset binary, Ch4..7=Two's complement)
    -f 2/b               (Ch0..3=Two's complement, Ch4..11=Offset binary)
    -f b                 (Ch0..11=Offset binary)
 -F DebugFile            (Debug file [formatted] -- default "=== None ===")
    /dev/null            (No debug output)
    @DebugFile           (Debug file [raw])
    #DebugFile           (Debug file [raw] followed by creation of 'FORMATTED' file)
 -i                      (Enable Interrupts -- default = Disable)
 -l LoopCnt              (Loop count -- default is 0)
 -m XferMode             (Transfer Mode -- default = Library MSGDMA)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
    -mdP                (Driver:  (FIFO) PIO mode)
    -mlM                (Library: (FIFO) Modular Scatter-Gather DMA mode)
    -mlP                (Library: (FIFO) PIO mode)
 -M SelectAdcModule     (Select ADC Module -- default is module 0)
 -N                     (Open device with O_NONBLOCK flag for driver operations)
-s InputSignal         (select input signal, 'e', 'f', 'g', 'n', 'p', '+', '-', '0..11')
    -s e,g,e            (Ch0..3 & 8..11=External input, Ch4..7=ground calibration)
    -s +/e              (Ch0..3=Postive calibration, Ch8..11=external reference)
    -s -                (Ch0..11=Negative calibration)
    -s e/e,f            (Ch0..7=external reference, Ch8..11=4 volt calibration)
    -s e/10             (Ch0..3=external reference, Ch4..11=DAC Channel 10)
 -S NumberOfSamples     (Number of Samples -- default is 49152)
 -T TestBus             (Test Bus Control 'b' or 'o'. Exit after programming this option)
    -T b                (Calibration Bus Control)
    -T o                (Open Bus Control)
 -V                     (Perform Data Validation, default is not to validate data)
 -W JitterAndOrDebug    (External A/C input signal - Sine Wave - Valid args are 'j' or 'd')
 -W                     (External A/C input signal - Sine Wave)
 -W j                   (External A/C input signal - Sine Wave, add jitter for low input
                         frequencies)
 -W d                   (External A/C input signal - Sine Wave, enable debug)
 -W jd                  (External A/C input signal - Sine Wave, add jitter and enable debug)
 -X                     (Disable Curses Statistics Display)

Note: If '^' is specified as first argument to '-C' option, then skip programming clocks
      When specifying the '-W' A/C option, you must specify the -E, -l and -F# options
      When specifying the '-W' A/C option, the expected voltage '-E' supplied is half of P-P
      Low Input A/C frequency correction option '-Wj' must only be used for frequencies <= 10KHz

 e.g. ./ccrtngfc_adc_fifo -C0,1@100000 -se/+      (ADC0=4.5MHz external input, ADC1=100000Hz
                                                   Positive Cal.)
      ./ccrtngfc_adc_fifo -C^0,1 -s- -Es R-V      (Max Clock, -9.91V input, validate against
                                                   -9.91V) - [** Skip Programming Clock **]
      ./ccrtngfc_adc_fifo -C0,1@100000 -sf -Es -V (Max Clock, +4.030 V input, validate against
                                                   +4.030 V)
      ./ccrtngfc_adc_fifo -C0 -M0 -V              (Max Clock, module 0, validation data)
      ./ccrtngfc_adc_fifo -C0 -l1000 -F#Debug     (Max Clock, create 'Debug.n' raw and
                                                   'Debug.n.FORMATTED' files for both modules)
      ./ccrtngfc_adc_fifo -l50 -E9 -F#Out -W -c1  (external 9V amplitude A/C input into channel
                                                   0 for 50 loop count)
```

If you wish to test A/C input try the following:

1) Connect a 562500 Hz, +/-2 Volts (4.0 Volts P-P) Sine wave to Channel 0 of the ADC
2) ./ccrtngfc_adc_fifo -A -l100 -E2@0.35 -F#DEBUG -W -c1 -M0 -se -C0 (At 4.5MSPS, you should get 8 sample points per Sine Wave)

You should see a display similar to below:

```
    Expected Input Sine Wave: 4.00 volts P-P (Tolerance 0.350000 volts)
Total Tolerance Exceed Count: 0

Chan   MinVolts   MaxVolts   MinPpAmp   MaxPpAmp   MinError   MaxError    dB       Freq(Hz) TolerExcedCnt
====   ========   ========   ========   ========   ========   ========    =======  ======== =============
   0  -2.017822  +2.017212  +3.704834  +4.032898  -0.000061  -0.295166   -0.66582    562500          -
```

If you wish to run both ADC and DAC concurrently, you can try the following:

1) ./ccrtngfc_clock -C0@4500000 -C1@1000000 -l1 (Program ADC Clock 0 at 4.5 MHz and DAC Clock 1 at 1.0 MHz)
2) ./ccrtngfc_dac_fifo -C^1   (Start DAC Fifo using 1 MHz Clock 1 in first window)
3) ./ccrtngfc_adc_fifo -C^0   (Start ADC Fifo using 4.5 MHz Clock 0 in second window)

Example display:

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
./ccrtngfc_adc_fifo  -C0@300000,1@100000 -se/+ -l1000 -V

########### ADC Module 0 ###########
           ADC Information:
             Flags              = 0x00000001
             ModuleNumber       = 0
             Handle             = 0x76c3a0
             local_ptr          = 0x7ffff7f52000
             local_adc_ptr      = 0x7ffff7f56000
             local_adc_fifo_ptr = 0x7ffff7f62000
             AdcFp              = 4
             AdcDeviceName      = /dev/ccrtngfc0_adc0
             AdcSerialNumber    = 729512
           Physical Memory Information:
             UserPID            =184570
             PhysMemPtr         =0x65e80000
             DriverVirtMemPtr   =0xffff993ee5e80000
             MmapedUserMemPtr   =0x7ffff7ed2000
             PhysMemSize        =0x00080000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =0
             NumOfEntriesUsed   =1
             Flags              =0x0000
    NumOfChannels=12, FirstChannel=0, LastChannel=11, NumAdc0Chans=4 NumAdc1Chans=4 NumAdc2Chans=4
########### ADC Module 1 ###########
           ADC Information:
             Flags              = 0x00000001
             ModuleNumber       = 1
             Handle             = 0x76c3a0
             local_ptr          = 0x7ffff7f52000
             local_adc_ptr      = 0x7ffff7f58000
             local_adc_fifo_ptr = 0x7ffff7f6a000
             AdcFp              = 5
             AdcDeviceName      = /dev/ccrtngfc0_adc1
             AdcSerialNumber    = 729513
           Physical Memory Information:
             UserPID            =184570
             PhysMemPtr         =0x65f00000
             DriverVirtMemPtr   =0xffff993ee5f00000
             MmapedUserMemPtr   =0x7ffff7e52000
             PhysMemSize        =0x00080000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =1
             NumOfEntriesUsed   =1
             Flags              =0x0000
    NumOfChannels=12, FirstChannel=0, LastChannel=11, NumAdc0Chans=4 NumAdc1Chans=4 NumAdc2Chans=4
======= CpuCountAssignedToThisTask=12
    Measuring how long it takes to collect 49152 samples...    Measuring how long it takes
    to collect 49152 samples...

local_ptr=0x7ffff7f52000

           Number of Samples =49152
           Transfer Mode     =Library Modular Scatter-Gather DMA Mode

### Board 0: Time in microseconds (TT=Total, FT=Free, FF=FIFO fill, RT=Read, mi=min,
                                   ma=max, av=ave)

ADC0: Eng0:      269: TT=24471.08 FT=   7.81 FF=23013.55 RT= 502.43
(min=501.70/max=566.51/ave=513.58)  391.31 MBytes/Sec (fifo=128156 - 97.78%)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
ADC1: Eng1:      269: TT=24558.13 FT=   5.96 FF=23072.54 RT= 503.51
(min=501.59/max=565.34/ave=513.49)  390.47 MBytes/Sec (fifo=128100 - 97.73%)

##########################################
###           ADC Module '0'           ###
##########################################

============================================================
                  Date: Tue May 16 15:21:03 2023
   Expected Input Volts: === Not Specified ===
           Scan Counter: ADC0=7372800 ADC1=2457600 ADC2=2457600
  Approx. Sample/Second: ADC0=300000 ADC1=100000 ADC2=100000
          NumberOfChans: ADC0=4 ADC1=4 ADC2=4
 ### Overflow Count ###: 0 (First Overflow Scan Count: 0)
   WorstMinChanVoltsHWM:  -0.008240 (Ch00)
   WorstMaxChanVoltsHWM:   9.913635 (Ch07)
============================================================
      <-------- (volts) -------->
Chan  Min       Max       Ave      DetectedCnt TolerExeededCnt
====  =======   =======   =======  =========== ===============
 00   -0.0082   -0.0024   -0.0052      7372800       -
 01    0.0085    0.0134    0.0112      7372800       -
 02    0.0171    0.0220    0.0194      7372800       -
 03    0.0070    0.0113    0.0092      7372800       -
 04    9.9063    9.9130    9.9098      2457600       -
 05    9.9066    9.9130    9.9100      2457600       -
 06    9.9063    9.9133    9.9101      2457600       -
 07    9.9066    9.9136    9.9101      2457600       -
 08    9.9060    9.9127    9.9096      2457600       -
 09    9.9069    9.9133    9.9100      2457600       -
 10    9.9063    9.9130    9.9097      2457600       -
 11    9.9066    9.9130    9.9098      2457600       -
============================================================

Below are the statistics for 49152 samples:
   Estimated time to collect samples:   24579.621 usecs
   Total work time breakdown            24577.287 usecs
      Average time to fill FIFO:        23077.097 usecs
      Average time to read samples:       502.957 usecs
      Average time to process samples:    991.382 usecs
      Average time other:                   5.851 usecs
   Approximate free time available:     23085.282 usecs

##########################################
###           ADC Module '1'           ###
##########################################

============================================================
                  Date: Tue May 16 15:21:03 2023
   Expected Input Volts: === Not Specified ===
           Scan Counter: ADC0=7372800 ADC1=2457600 ADC2=2457600
  Approx. Sample/Second: ADC0=300000 ADC1=100000 ADC2=100000
          NumberOfChans: ADC0=4 ADC1=4 ADC2=4
 ### Overflow Count ###: 0 (First Overflow Scan Count: 0)
   WorstMinChanVoltsHWM:  -0.001221 (Ch03)
   WorstMaxChanVoltsHWM:   9.911804 (Ch07)
============================================================
      <-------- (volts) -------->
Chan  Min       Max       Ave      DetectedCnt TolerExeededCnt
====  =======   =======   =======  =========== ===============
 00    0.0134    0.0253    0.0166      7372800       -
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
 01    0.0064    0.0116    0.0090      7372800       -
 02    0.0073    0.0128    0.0101      7372800       -
 03   -0.0012    0.0040    0.0012      7372800       -
 04    9.8996    9.9069    9.9033      2457600       -
 05    9.8972    9.9036    9.9005      2457600       -
 06    9.8944    9.9014    9.8982      2457600       -
 07    9.9051    9.9118    9.9086      2457600       -
 08    9.8904    9.8978    9.8944      2457600       -
 09    9.8987    9.9054    9.9021      2457600       -
 10    9.8941    9.9011    9.8976      2457600       -
 11    9.9042    9.9109    9.9076      2457600       -
============================================================

Below are the statistics for 49152 samples:
   Estimated time to collect samples:   24582.412 usecs
   Total work time breakdown            24577.313 usecs
      Average time to fill FIFO:        23076.040 usecs
      Average time to read samples:       503.000 usecs
      Average time to process samples:    992.396 usecs
      Average time other:                   5.876 usecs
   Approximate free time available:     23087.015 usecs
```

3.2.5 lib/ccrtngfc_adc_sps

This is a useful tool to display the sample rate of various channels.

```
Usage: ./ccrtngfc_adc_sps [-b Board] [-c StartChan,StopChan] [-C AdcUpdateClock]
                          [-e MsgDmaEngine] [-E ExpSPS@Tol] [-l LoopCnt]
                          [-M SelectAdcModule] [-t TolerancePPT]
 -b Board                (Board number -- default is 0)
 -c StartChan,EndChan    (Select start and end channel numners -- default 0,11)
    -c 4,11              (select channels 4 through 11 for processing)
    -c 7                 (select channels 7 through 11 for processing)
 -C AdcUpdateClock       (select ADC update clock, 0..4 or 'n|N')
    -C 0,5,4             (Ch0..3=Clock0, Ch4..7=Clock5, Ch8..11=Clock4 at MAX SPS)
    -C 3@20000.0/n       (Ch0..3=Clock3 at 20000 SPS, Ch4..11=No Clock)
    -C 4                 (Ch0..11=Clock4 at MAX SPS)
    -C 4@150000.0        (Ch0..11=Clock4) at 150000 SPS)
 -e MsgDmaEngine         (Select MsgDma Engine -- default "=== get free engine ===")
 -E ExpSPS@Tol           (specify expected samples/second and tolerance for each ADC)
    -E C                 (All ADC's to use clock samples/second and default tolerance 0.010%)
    -E c@0.02,30000      (ADC 0 uses clock samples/second and tolerance 0.02%, remaining
                          use 30,000 SPS and default tolerance 0.010%)
    -E C@0.02,C          (All ADC's to use clock samples/second and default tolerance
                          except for ADC 0 tolerance of 0.02%)
    -E 10000,c           (ADC 0 to use 10000 SPS, rest of ADCs to use clock samples/second.
                          Default tolerance for all ADCs)
    -E 10000,20000,30000 (ADC 0, 1 and 2 to use 10000 SPS, 2000 SPS and 3000 SPS
                          respectively. Default tolerance for all ADCs)
 -F DebugFile            (Debug file with menu display -- default "=== None ===")
    @DebugFile           (Debug file without menu display (only summary and rate display)
                          -- default "=== None ===")
    @                    (No debug file and no menu display (only summary and rate display)
                          -- default "=== None ===")
 -l LoopCnt              (Loop Count -- default is 10000000)
 -l 0                    (Loop forever)
 -M SelectAdcModule      (Select ADC Module -- default is module 0)
 -t TolerancePPT         (Tolerance in Parts/Trillion -- default is 0.020000 PPT)

 e.g. ./ccrtngfc_adc_sps -C0@123456,1@78912 (ADC0 is 123456Hz, ADC1 is 78912Hz)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

Example display:

./ccrtngfc_adc_sps -C0@123456,1@78912

```
           ADC Information:
             Flags              = 0x00000001
             ModuleNumber       = 0
             Handle             = 0x76aec0
             local_ptr          = 0x7ffff7f52000
             local_adc_ptr      = 0x7ffff7f56000
             local_adc_fifo_ptr = 0x7ffff7f62000
             AdcFp              = 4
             AdcDeviceName      = /dev/ccrtngfc0_adc0
             AdcSerialNumber    = 729512

local_ptr=0x7ffff7f52000

           Physical Memory Information:
             UserPID            =184607
             PhysMemPtr         =0x65e58000
             DriverVirtMemPtr   =0xffff993ee5e58000
             MmapedUserMemPtr   =0x7ffff7f4a000
             PhysMemSize        =0x00008000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =0
             NumOfEntriesUsed   =1
             Flags              =0x0000

Read: Size 32736, Count 19 (FIFO wait: 7155.4us, Read time/rate: 87.7us/373.2MBPS)

          ============================== Samples/Second ==============================
            [0]        [1]        [2]        [3]        [4]        [5]        [6]        [7]
          =======    =======    =======    =======    =======    =======    =======    =======
 [00 07]   123460     123460     123460     123460      78914      78914      78914      78914
 [08 15]    78915      78915      78915      78915


==== No overflow occurred (HWM Samples In fifo 8200) ====

==================================
       <--- (Samples/Second) ---->
Chan   Min       Max       Ave
====   =======   =======   =======
  0     123456    123462    123460
  1     123456    123462    123460
  2     123456    123462    123460
  3     123456    123462    123460
  4      78913     78916     78914
  5      78913     78916     78914
  6      78913     78916     78914
  7      78913     78916     78914
  8      78913     78916     78914
  9      78913     78916     78914
 10      78913     78916     78914
 11      78913     78916     78914
```

3.2.6 lib/ccrtngfc_check_bus

This is a simple test to check whether there is intereference from other cards that may be sharing the same bus. It simply computes the time it takes to perform hardware reads and computes the jitter. It must be run as *root*.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
Usage: ./ccrtngfc_check_bus [-b Board] [-c CPU] [-l LoopCnt] [-o Offset] [-t Tolerance] [-w]
 -b Board     (Board number -- default is 0)
 -c CPU       (CPU number -- default is 1)
 -l LoopCnt   (Loop Count -- default is 10000000)
 -l 0         (Loop forever)
 -o Offset    (Hex offset to read/write from -- default offset is 0x00000000)
 -t Tolernace (Tolerance -- default is 1.00 micro-seconds)
 -w           (Use writes instead of reads)
```

Example display:

sudo ./ccrtngfc_check_bus

```
local_ptr=0x7ffff7fd7000
10000000: usec/read: Cur=1.181 (Min=1.159 Max=1.794 Ave= 1.181335)
          [Bus Jitter (usec): 0.635 ===> LOW]
```

3.2.7 lib/ccrtngfc_clock

This is a useful tool to display information of the various clocks and also program them.

```
Usage: ./ccrtngfc_clock [-b BoardNo] [-C UpdateClock] [-d Delay] [-l LoopCnt]
                        [-O ClockGeneratorOutputs] [-R] [-S ClockSource] [-t TolerancePPT]
                        [-V] [-z]
 -b BoardNo               (Board number -- default is 0)
 -C <Clock>@<Frequency>   (set update clock '0..4' & '6..8' with frequency)
 -d Delay                 (Delay between screen refresh -- default is 10 milli-seconds)
 -l LoopCnt               (Loop count -- default is 0)
 -O ClockGeneratorOutputs (0=Disable, 1=Enable -- default is no change)
 -R                       (Reset/Clear all clocks)
 -S ClockSource           (Select Clock Source 'g' or 'o')
    -Sg                   (Select Clock Generator Source)
    -So                   (Select Clock Oscillator Source)
 -t <TolerancePPT>        (Tolerance in Parts/Trillion -- default is 0.020000 PPT)
 -V                       (Validate Clock Status)
 -z                       (Zap display, default is not to zap display)

 e.g. ./ccrtngfc_clock -C 1@300000
                        (Set Clock 1 to 300000 SPS - do not change any other running clocks)
      ./ccrtngfc_clock -R -C0@100000 -C4@12345 -t0.5
                        (Reset all clocks and then set Clock 0 to 100000 SPS and Clock 4 to
                         12345 SPS and 0.5 PPT)

 If the '-V' option is specified, there is no display of clocks and the test will exit
 with one of the following return codes:
    (0) - good clock status
    (1) - PLL has become unlocked at some point
    (2) - PLL is no longer locked on frequency
    (3) - PLL Oscillator clock not present
    (4) - PLL Generator clock selected, but Oscillator clock is active
    (5) - PLL Oscillator clock selected, but Generator clock is active
```

Example display:

./ccrtngfc_clock -R -C0@100000 -C4@12345

```
local_ptr=0x7ffff7f52000
                            Board Number [-b]: 0
                                   Delay [-d]: 10 milli-seconds
                              Loop Count [-l]: ***Forever***
                                   Scan Count: 54
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
_________ Clock Revision ________
           Silicon Revision: A2
           Base Part Number: 5341
         Device Speed Grade: A
            Device Revision: B

_________ Clock CSR ________
            Clock Interface: Idle
               Clock Output: Enabled
                Clock State: Active

_________ Input Clock Status _________
                 Calibration: Not In-Progress
              SMBUS Timeout: Not Timed Out
                   PLL Lock: Locked
                Input Signal: Present
               Input_0 Clock: Present
               Input_1 Clock: *** Not Present ***
               Input_2 Clock: *** Not Present ***
              Input_FB Clock: Present
            XAXB Input Clock: *** Not Present ***

_________ PLL Clock Status (*** Firmware Supports PLL Sync ***) _________
      Clock Source Selected: Clock Generator Source
           PLL Unlock Error: PLL Never Unlocked       [*** GOOD ***]
          PLL Locked Status: PLL Locked on Frequency
             Clock 0 Status: Clock Generator Present  [*** SELECTED CLOCK ***]
             Clock 1 Status: Clock Oscillator Present
       Current Active Clock: Clock Generator is Currently Active

_____________________ Output Clock Setting _____________________
          User output clock frequency 0:   100000.000 Samples/Second/Channel
          User output clock frequency 1: *** Not Set ***
          User output clock frequency 2: *** Not Set ***
          User output clock frequency 3: *** Not Set ***
          User output clock frequency 4:    12345.000 Samples/Second/Channel
Clock Generator output clock frequency 5: 100000000.000 Samples/Second/Channel
       External output clock frequency 6: *** Not Set ***
  HighSpeed DC1 output clock frequency 7: *** Not Set ***
HighSpeed DC1 & DC2 output clock frequency 8: *** Not Set ***
      Feed-Back output clock frequency 9: 10000000.000 Samples/Second/Channel
```

3.2.8 lib/ccrtngfc_compute_output_clock

This test is useful for displaying actual versus requested clock frequencies without actually programming the clock. Normally, the actual frequency is computed the moment the user supplied tolerance is reached. In this case, if the user selected a lower tolerance, it is possible to get a better frequency match. If you use the '-M' option, the test starts with a tolerance of 0 and increments by 0.01 up to the user supplied tolerance to see if a valid frequency can be computed. In this case, it will return the best frequency match available by the hardware, however, this option takes a lot longer to compute the best frequency match as opposed to the first frequency match without the '-M' option.

```
Usage: ./ccrtngfc_compute_output_clock [-b BoardNo] [-c ClockSelect] [-f FrequencyRange]
                                       [-M] [-t MaxTolerancePPT]
 -b BoardNo                 (Board number -- default is 0)
 -c ClockSelect             (select clock '0..4' & '6..8' -- default is 0)
 -f <Min>,<Max>,<Inc>       (Minimum,Maximum,Increment -- default is
                             1.000000,1000000.000000,1.000000)
 -M                         (Compute Best Frequency Match Upto Given Tolerance)
 -t <MaxTolerancePPT>       (Maximum Tolerance in Parts/Trillion -- default is 0.500000 PPT)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

Example display:

./ccrtngfc_compute_output_clock -f 1000,1020,1

```
================================================================================
Minimum Frequency     :       1000.000000000000000 Hz
Maximum Frequency     :       1020.000000000000000 Hz
Frequency Increment   :          1.000000000000000 Hz
Maximum Tolerance     :          0.500000000000000 PPT (Parts/Trillion)
Best Frequency Match  :                        No
================================================================================
```

Desired Frequency (Hz)	Actual Frequency (Hz)	Tolerance	%Error
1000.000000000000000	1000.000000000000000	0.000000	+0.000000000000000 (5.551115e-18)
1001.000000000000000	1001.000000000183367	0.183194	-0.000000000018318 (-1.831840e-11)
1002.000000000000000	1002.000000000232276	0.231799	-0.000000000023181 (-2.318123e-11)
1003.000000000000000	1003.000000000035654	0.035591	-0.000000000003555 (-3.554739e-12)
1004.000000000000000	1004.000000000288517	0.287388	-0.000000000028737 (-2.873674e-11)
1005.000000000000000	1005.000000000282783	0.281333	-0.000000000028138 (-2.813758e-11)
1006.000000000000000	1006.000000000050984	0.050628	-0.000000000005068 (-5.067997e-12)
1007.000000000000000	1007.000000000443982	0.440861	-0.000000000044090 (-4.408960e-11)
1008.000000000000000	1008.000000000412877	0.409634	-0.000000000040960 (-4.095999e-11)
1009.000000000000000	1009.000000000079106	0.078420	-0.000000000007840 (-7.840007e-12)
1010.000000000000000	1010.000000000000101	0.000113	-0.000000000000010 (-9.997503e-15)
1011.000000000000000	1011.000000000118566	0.117285	-0.000000000011728 (-1.172762e-11)
1012.000000000000000	1012.000000000088667	0.087624	-0.000000000008762 (-8.761601e-12)
1013.000000000000000	1013.000000000163023	0.160935	-0.000000000016093 (-1.609310e-11)
1014.000000000000000	1014.000000000090047	0.088797	-0.000000000008880 (-8.880399e-12)
1015.000000000000000	1015.000000000063438	0.062500	-0.000000000006250 (-6.250003e-12)
1016.000000000000000	1016.000000000260579	0.256467	-0.000000000025648 (-2.564755e-11)
1017.000000000000000	1017.000000000030087	0.029623	-0.000000000002958 (-2.958395e-12)
1018.000000000000000	1018.000000000077547	0.076163	-0.000000000007618 (-7.617597e-12)
1019.000000000000000	1019.000000000076502	0.075085	-0.000000000007508 (-7.507597e-12)
1020.000000000000000	1020.000000000026112	0.025635	-0.000000000002560 (-2.560000e-12)
Desired Frequency (Hz)	Actual Frequency (Hz)	Tolerance	%Error

./ccrtngfc_compute_output_clock -f 1000,1020,1 -M

```
================================================================================
Minimum Frequency     :       1000.000000000000000 Hz
Maximum Frequency     :       1020.000000000000000 Hz
Frequency Increment   :          1.000000000000000 Hz
Maximum Tolerance     :          0.500000000000000 PPT (Parts/Trillion)
Best Frequency Match  :                        Yes
================================================================================
```

Desired Frequency (Hz)	Actual Frequency (Hz)	Tolerance	%Error
1000.000000000000000	1000.000000000000000	0.000000	+0.000000000000000 (5.551115e-18)
1001.000000000000000	1001.000000000000001	0.000000	-0.000000000000000 (-1.053658e-16)
1002.000000000000000	1002.000000000000036	0.000000	-0.000000000000004 (-3.573323e-15)
1003.000000000000000	1003.000000000000046	0.000000	-0.000000000000005 (-4.577041e-15)
1004.000000000000000	1004.000000000004112	0.004076	-0.000000000000410 (-4.095993e-13)
1005.000000000000000	1004.999999999999984	0.000000	+0.000000000000002 (1.618385e-15)
1006.000000000000000	1006.000000000005876	0.005876	-0.000000000000584 (-5.841197e-13)
1007.000000000000000	1006.999999999999976	0.000000	+0.000000000000002 (2.408974e-15)
1008.000000000000000	1008.000000000000035	0.000000	-0.000000000000003 (-3.480461e-15)
1009.000000000000000	1009.000000000003768	0.003718	-0.000000000000373 (-3.733991e-13)

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
     1010.000000000000000        1009.999999999999955   0.000000    +0.000000000000004 ( 4.429900e-15)
     1011.000000000000000        1011.000000000006863   0.006747    -0.000000000000679 (-6.788338e-13)
     1012.000000000000000        1012.000000000000049   0.000000    -0.000000000000005 (-4.821571e-15)
     1013.000000000000000        1012.999999999999953   0.000000    +0.000000000000005 ( 4.663375e-15)
     1014.000000000000000        1014.000000000006323   0.006279    -0.000000000000624 (-6.235479e-13)
     1015.000000000000000        1015.000000000006039   0.005936    -0.000000000000595 (-5.949975e-13)
     1016.000000000000000        1016.000000000000008   0.000000    -0.000000000000001 (-7.922359e-16)
     1017.000000000000000        1016.999999999999945   0.000000    +0.000000000000005 ( 5.420115e-15)
     1018.000000000000000        1017.999999999999971   0.000000    +0.000000000000003 ( 2.851899e-15)
     1019.000000000000000        1019.000000000003521   0.003459    -0.000000000000345 (-3.454875e-13)
     1020.000000000000000        1020.000000000006196   0.006019    -0.000000000000607 (-6.074335e-13)
========================    ========================   =========   ================================
   Desired Frequency (Hz)       Actual Frequency (Hz)   Tolerance                            %Error
```

3.2.9 lib/ccrtngfc_dac

This test is useful in programming the DAC interface and displaying the DAC registers.

```
Usage: ././ccrtngfc_dac [-A] [-a RollingAve] [-b BoardNo] [-C DacUpdateClock] [-d Delay]
                        [-E ExpInpVolt] [-f DataFormat] [-F DebugFile] [-l LoopCnt]
                        [-M SelectDacModule] [-n NumChans] [-o OutputSelect]
                        [-s InputSignal] [-v DacVoltage] [-Z]
 -A                      (Perform DAC Auto Calibration first using reference voltage)
 -a RollingAve           (Rolling average -- default "=== None ===")
 -b BoardNo              (Board number -- default is 0)
 -C DacUpdateClock       (select DAC update clock, 0..4 or 'n|N')
    -C 0,3,4             (Ch0..3=Clock0, Ch4..7=Clock3, Ch8..11=Clock4 at MAX SPS)
    -C ^2,3              (Ch0..3=Clock2, Ch4..11=Clock3 assignment only) [** Skip Programming
                          Clock **]
    -C 3@20000.0/n       (Ch0..3=Clock3 at 20000 SPS, Ch4..11=No Clock)
    -C 4                 (Ch0..11=Clock4 at MAX SPS)
    -C 4@150000.0        (Ch0..11=Clock4) at 150000 SPS)
 -d Delay                (Delay between screen refresh -- default is 0 milli-seconds)
 -E <ExpInpVolts>@<Tol>  (Expected Input Volts@Tolerance -- default Tol=0.006000)
    +@<Tol>              (Positive Calibration Ref Volt@Tolerance)
    -@<Tol>              (Negative Calibration Ref Volt@Tolerance)
    c@<Tol>              (DAC Channel 0 Volt@Tolerance)
    s@<Tol>              (Requires '-s' input signal option to specify voltage Volt@Tolerance)
                         (valid '-s' arguments are 'g','+','-','f','t')
    Note:                (For differential bipolar, even channels, voltage read is half supplied)
                         (For differential bipolar, odd channels, voltage read is neg. half
                          supplied)
 -f DataFormat           (select data format, '2' or 'b')
    -f b,2,b             (Ch0..1 & Ch4..11=Offset binary, Ch2..3=Two's complement)
    -f 2/b               (Ch0..1=Two's complement, Ch4..11=Offset binary)
    -f b                 (Ch0..11=Offset binary)
 -F DebugFile            (Debug file with menu display -- default "=== None ===")
    #DebugFile           (Debug file without display (only summary) -- default "=== None ===")
    @DebugFile           (Debug file without display -- default "=== None ===")
    @ or #               (No debug file and no display -- default "=== None ===")
 -j SpeedMode            (DAC Speed Mode: 'h' or 'n' [high/normal])
 -l LoopCnt              (Loop count -- default is 0)
 -M SelectDacModule      (Select DAC Module -- default is module 0)
 -n NumChans             (Number of channels (1..12) -- default is 12)
 -o OutputSelect         (DAC output select, 's' or 'd')
    -o d,s               (Ch0..1=differential, Ch2..11=single_ended)
    -o s/d,s             (Ch0..1 & Ch4..11=single_ended, Ch2..3=differential)
    -o d                 (Ch0..11=differential)
 -s InputSignal          (ADC select input signal, 'a', 'e', 'g', '+', '-', 'f', '0..11')
    -s a,e               (Ch0..3=All DAC Channels 0..7, Ch8..11=External ADC Input)
    -s e,g               (Ch0..7=External ADC input, Ch8..11=ground calibration)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   -s +/e              (Ch0..7=Postive calibration, Ch8..11=External ADC input)
   -s -                (Ch0..11=Negative calibration)
   -s e/f              (Ch0..3=External ADC input, Ch4..11=4 volt calibration)
   -s e/11             (Ch0..3=External ADC input, Ch4..11=DAC Channel 11)
 -v DacVoltage         (DAC Voltage. -10.0  to +10.0)
   -v 1.5,9.9          (Ch0=1.5 volts, Ch1..11= 9.9 volts)
   -v2.5/7.5,9.7       (Ch0=2.5 volts, Ch1=7.5 volts, Ch2..11=9.7 volts)
   -v 9.95             (Ch0..11=9.95 volts)
 -Z                    (Display Calibration Offset & Gain Channels)

 e.g. ./ccrtngfc_dac -os -s7 -v4.5 -E4.5      (Internal Loopback Testing. Generate 4.5V and
                                               compare)
      ./ccrtngfc_dac -os -se -v4.5 -E4.5      (External DAC/ADC Loopback Testing. Generate
                                               4.5V and compare)
      ./ccrtngfc_dac -od -s2 -v5.0 -E2.5      (Internal Loopback Testing. Generate 5.0V and
                                               compare diff 2.5V)
      ./ccrtngfc_dac -od -s3 -v5.0 -E-2.5     (Internal Loopback Testing. Generate 5.0V and
                                               compare diff -2.5V)
      ./ccrtngfc_dac -os -sa -v1,2,3,4 -a100  (display all DAC 0..11 channels with rolling
                                               average of 100)
      ./ccrtngfc_dac -os -sa -v3.5 -E3.5@0.01 (Internal Loopback Testing. Generate 3.5V and
                                               compare diff on all chans)
      ./ccrtngfc_dac -C0 -s- -Es              (Max Clock, -9.91V input, validate against -9.91V)

If you wish to run both ADC and DAC concurrently, you can try the following:
-------------------------------------------------------------------------
   1) ./ccrtngfc_clock -C0@4500000 -C1@1000000 -l1 (Program ADC Clock 0 at 4.5 MHz and DAC Clock 1
                                                    at 1.0 MHz)
   2) ./ccrtngfc_dac   -C^1                       (Start DAC using 1 MHz Clock 1 in first window)
   3) ./ccrtngfc_adc   -C^0                       (Start ADC using 4.5 MHz Clock 0 in second
                                                    window)
```

Example display:

./ccrtngfc_dac -A -os -s7 -Vb5 -v4.5 -E4.5@0.010 -C0

```
 local_ptr=0x7ffff7e67000

          Physical Memory Information:
            UserPID            =352833
            PhysMemPtr         =0x65d26000
            DriverVirtMemPtr   =0xffff9a30e5d26000
            MmapedUserMemPtr   =0x7ffff7fdd000
            PhysMemSize        =0x00001000
            PhysMemSizeFreed   =0x00000000
            EntryInTxTbl       =0
            NumOfEntriesUsed   =1
            Flags              =0x0000

          DAC Information:
            Flags              = 0x00000001
            ModuleNumber       = 0
            Handle             = 0x7819a0
            local_ptr          = 0x7ffff7e67000
            local_dac_ptr      = 0x7ffff7e6c000
            local_dac_fifo_ptr = 0x7ffff7e7b000
            DacFp              = 4
            DacDeviceName      = /dev/ccrtngfc0_dac0
            DacSerialNumber    = 729512
Auto Calibration started...done. (3.019 seconds)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
 Board Number          [-b]: 0
 Update Clock Selected [-C]: Ch00..03 OutputClock=0 (0x7) (4500000.000 SPS)
                           : Ch04..07 OutputClock=0 (0x7) (4500000.000 SPS)
                           : Ch08..11 OutputClock=0 (0x7) (4500000.000 SPS)
 Delay                 [-d]: 0 milli-seconds
 Expected Input Volts  [-E]: 4.500000 volts (Tolerance 0.100000 volts)
 DAC Data Format       [-f]: Ch00..01=Obin Ch02..03=Obin Ch04..05=Obin Ch06..07=Obin Ch08..09=Obin
                             Ch10..11=Obin
 DAC Speed Mode        [-j]: Normal Speed
 DAC Output Select     [-o]: Ch00..01=Sngl Ch02..03=Sngl Ch04..05=Sngl Ch06..07=Sngl Ch08..09=Sngl
                             Ch10..11=Sngl
 ADC Input Signal      [-s]: Ch00..03 [1]Calibration Input (0x27: DAC Channel 7)
                           : Ch04..07 [1]Calibration Input (0x27: DAC Channel 7)
                           : Ch08..11 [1]Calibration Input (0x27: DAC Channel 7)
 DAC Voltage           [-v]: Ch00=4.50 Ch01=4.50 Ch02=4.50 Ch03=4.50 Ch04=4.50 Ch05=4.50
                           : Ch06=4.50 Ch07=4.50 Ch08=4.50 Ch09=4.50 Ch10=4.50 Ch11=4.50
 DAC Voltage Range     [-V]: Ch00..01=b10 Ch02..03=b10 Ch04..05=b10 Ch06..07=b10 Ch08..09=b10 Ch10..11=b10

 Loop Count            [-l]: ***Forever***
 SelectedDacModule     [-M]: 0
 Number of Channels    [-n]: 12
 Scan Count                : 157703          (0:00:00:27)
 Tolerance Exceeded Count  : 0               (=== Passed ===)
 Read Duration (microsecs) :    25.497 (min=  25.333/max=  41.804/ave=  25.716)

          ##### Raw Data (DAC Channels) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          ====     ====     ====     ====     ====     ====     ====     ====     ====     ====
  [0]     b99a     b99a     b99a     b99a     b99a     b99a     b99a     b99a     b99a     b99a
  [1]     b99a     b99a

          ##### Volts (DAC Channels) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          =======  =======  =======  =======  =======  =======  =======  =======  =======  =======
  [0]     +4.5001  +4.5001  +4.5001  +4.5001  +4.5001  +4.5001  +4.5001  +4.5001  +4.5001  +4.5001
  [1]     +4.5001  +4.5001
-------------------------------------------------------------------------------------------------

          ##### Raw Data (ADC_Readback, ADC_Readback, ADC_Readback - 4.50v) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          ====     ====     ====     ====     ====     ====     ====     ====     ====     ====
  [0]      --       --       --       --       --       --       --      804f      --       --
  [1]      --       --

          ##### Volts (ADC_Readback, ADC_Readback, ADC_Readback - 4.50v) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          =======  =======  =======  =======  =======  =======  =======  =======  =======  =======
  [0]       ---      ---      ---      ---      ---      ---      ---    +0.0241    ---      ---
  [1]       ---      ---

=====================================================
                  Date: Wed Jun 14 08:18:57 2023
   Expected Input Volts: 4.500000 volts (Tolerance 0.100000 volts)
 Tolerance Exceed Count: 0
           Scan Counter: 470894
   WorstMinChanVoltsHWM:   0.020264 (Ch07)
   WorstMaxChanVoltsHWM:   0.027283 (Ch07)
=====================================================
      <-------- (volts) -------->
Chan  Min       Max       Ave      TolerExeededCnt
====  =======   =======   =======  ===============
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
 07    0.0203    0.0273    0.0236         -
==================================================
```

./ccrtngfc_dac -C0 -Z

```
 local_ptr=0x7ffff7e67000

           Physical Memory Information:
             UserPID            =352843
             PhysMemPtr         =0x65d26000
             DriverVirtMemPtr   =0xffff9a30e5d26000
             MmapedUserMemPtr   =0x7ffff7fdd000
             PhysMemSize        =0x00001000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =0
             NumOfEntriesUsed   =1
             Flags              =0x0000

           DAC Information:
             Flags              = 0x00000001
             ModuleNumber       = 0
             Handle             = 0x7819a0
             local_ptr          = 0x7ffff7e67000
             local_dac_ptr      = 0x7ffff7e6c000
             local_dac_fifo_ptr = 0x7ffff7e7b000
             DacFp              = 4
             DacDeviceName      = /dev/ccrtngfc0_dac0
             DacSerialNumber    = 729512

 Board Number          [-b]: 0
 Update Clock Selected [-C]: Ch00..03 OutputClock=0 (0x7) (4500000.000 SPS)
                           : Ch04..07 OutputClock=0 (0x7) (4500000.000 SPS)
                           : Ch08..11 OutputClock=0 (0x7) (4500000.000 SPS)
 Delay                 [-d]: 0 milli-seconds
 Expected Input Volts  [-E]: === Not Specified ===
 DAC Data Format       [-f]: Ch00..01=Obin Ch02..03=Obin Ch04..05=Obin Ch06..07=Obin Ch08..09=Obin
                             Ch10..11=Obin
 DAC Speed Mode        [-j]: Normal Speed
 DAC Output Select     [-o]: Ch00..01=Sngl Ch02..03=Sngl Ch04..05=Sngl Ch06..07=Sngl Ch08..09=Sngl
                             Ch10..11=Sngl
 ADC Input Signal      [-s]: Ch00..03 [1]Calibration Input (0x27: DAC Channel 7)
                           : Ch04..07 [1]Calibration Input (0x27: DAC Channel 7)
                           : Ch08..11 [1]Calibration Input (0x27: DAC Channel 7)
 DAC Voltage           [-v]: Ch00=99.00 Ch01=99.00 Ch02=99.00 Ch03=99.00 Ch04=99.00 Ch05=99.00
                           : Ch06=99.00 Ch07=99.00 Ch08=99.00 Ch09=99.00 Ch10=99.00 Ch11=99.00
 DAC Voltage Range     [-V]: Ch00..01=b10 Ch02..03=b10 Ch04..05=b10 Ch06..07=b10 Ch08..09=b10 Ch10..11=b10

 Loop Count            [-l]: ***Forever***
 SelectedDacModule     [-M]: 0
 Number of Channels    [-n]: 12
 Scan Count                : 69521           (0:00:00:21)
 Read Duration (microsecs) :    25.584 (min=  25.385/max=  38.632/ave=  25.735)

          ##### Raw Data (Offset Calibration DAC Channels) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          ====     ====     ====     ====     ====     ====     ====     ====     ====     ====
  [0]     fff7     ffeb     ffed     ffe5     ffe2     ffe3     fff2     fff8     ffee     ffe9
  [1]     ffe0     ffe6

          ##### Volts (Offset Calibration DAC Channels) #####
          [0]     [1]     [2]     [3]     [4]     [5]     [6]     [7]     [8]     [9]
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
          =======  =======  =======  =======  =======  =======  =======  =======  =======  =======
  [0]     -0.0027  -0.0064  -0.0058  -0.0082  -0.0092  -0.0089  -0.0043  -0.0024  -0.0055  -0.0070
  [1]     -0.0098  -0.0079
-------------------------------------------------------------------------------------------------
          ##### Raw Data (Negative Calibration DAC Channels) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          ====     ====     ====     ====     ====     ====     ====     ====     ====     ====
  [0]     5c3a     1ea3     64bd     950b     ccf1     f7b2     e582     9bf0     c084     f7f6
  [1]     a517     ff9d

          ##### Volts (Negative Calibration DAC Channels) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          =======  =======  =======  =======  =======  =======  =======  =======  =======  =======
  [0]     +0.9973  +0.9972  +0.9973  +0.9971  +0.9970  +0.9970  +0.9972  +0.9974  +0.9970  +0.9971
  [1]     +0.9971  +0.9972
-------------------------------------------------------------------------------------------------
          ##### Raw Data (Positive Calibration DAC Channels) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          ====     ====     ====     ====     ====     ====     ====     ====     ====     ====
  [0]     a7b3     0bc3     0460     1f36     0943     edff     4957     967c     7b0b     f99e
  [1]     f51d     4af6

          ##### Volts (Positive Calibration DAC Channels) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          =======  =======  =======  =======  =======  =======  =======  =======  =======  =======
  [0]     +0.9983  +0.9983  +0.9984  +0.9982  +0.9981  +0.9982  +0.9983  +0.9983  +0.9981  +0.9983
  [1]     +0.9982  +0.9984
-------------------------------------------------------------------------------------------------
          ##### Raw Data (DAC Channels) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          ====     ====     ====     ====     ====     ====     ====     ====     ====     ====
  [0]     b99a     b99a     b99a     b99a     b99a     b99a     b99a     b99a     b99a     b99a
  [1]     b99a     b99a

          ##### Volts (DAC Channels) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          =======  =======  =======  =======  =======  =======  =======  =======  =======  =======
  [0]     +4.5001  +4.5001  +4.5001  +4.5001  +4.5001  +4.5001  +4.5001  +4.5001  +4.5001  +4.5001
  [1]     +4.5001  +4.5001
-------------------------------------------------------------------------------------------------
          ##### Raw Data (ADC_Readback, ADC_Readback, ADC_Readback) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          ====     ====     ====     ====     ====     ====     ====     ====     ====     ====
  [0]      --       --       --       --       --       --       --      b9eb      --       --
  [1]      --       --

          ##### Volts (ADC_Readback, ADC_Readback, ADC_Readback) #####
          [0]      [1]      [2]      [3]      [4]      [5]      [6]      [7]      [8]      [9]
          =======  =======  =======  =======  =======  =======  =======  =======  =======  =======
  [0]       ---      ---      ---      ---      ---      ---      ---    +4.5248    ---      ---
  [1]       ---      ---

==================================================
                  Date: Wed Jun 14 08:22:45 2023
   Expected Input Volts: === Not Specified ===
           Scan Counter: 206508
   WorstMinChanVoltsHWM:   4.519958 (Ch07)
   WorstMaxChanVoltsHWM:   4.526978 (Ch07)
==================================================
      <-------- (volts) -------->
Chan  Min       Max       Ave      TolerExeededCnt
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
====  =======   =======   =======  ===============
 07    4.5200    4.5270    4.5235         -
=================================================
```

3.2.10 lib/ccrtngfc_dac_calibrate

This test is useful for performing, saving and restoring DAC calibration. If calibration '-A' is specified along with voltage '-V', the board voltage range will first be programmed prior to initiaiing calibration.

```
Usage: ./ccrtngfc_dac_calibrate [-A] [-b board] [-c ChanMask] [-f DataFormat]
                                [-i inCalFile] [-M SelectDacModule] [-o outCalFile] [-R]
 -A                    (perform Auto Calibration)
 -b <board>            (board #, default = 0)
 -c <ChanMask>         (channel selection mask, default = all channels)
 -f DataFormat         (select data format, '2' or 'b')
    -f b,2,b           (Ch0..1 & Ch4..11=Offset binary, Ch2..3=Two's complement)
    -f 2/b             (Ch0..1=Two's complement, Ch4..11=Offset binary)
    -f b               (Ch0..11=Offset binary)
 -i <In Cal File>      (input calibration file [input->board_reg])
 -M SelectDacModule    (Select DAC Module -- default is module 0)
 -o <Out Cal File>     (output calibration file [board_reg->output])
 -R                    (reset DAC calibration)

 e.g. ./ccrtngfc_dac_calibrate              (Dump calibration information to stdout)
      ./ccrtngfc_dac_calibrate -A -o Calfile (Perform Auto calibration and dump information
                                              to 'Calfile')
      ./ccrtngfc_dac_calibrate -i Calfile    (Update board calibration with supplied
                                              'Calfile')
```

Example display:

./ccrtngfc_dac_calibrate -A -oOutputCal

```
           DAC Information:
             Flags              = 0x00000001
             ModuleNumber       = 0
             Handle             = 0x76c5a0
             local_ptr          = 0x7ffff7f55000
             local_dac_ptr      = 0x7ffff7f5a000
             local_dac_fifo_ptr = 0x7ffff7f69000
             DacFp              = 4
             DacDeviceName      = /dev/ccrtngfc0_dac0

Device Name    : /dev/ccrtngfc0
Board Serial No: 706503 (0x000ac7c7)
Auto Calibration started...done. (3.026 seconds)

===> Dump of 'OutputCal' file
#Date           : Wed Jun 14 08:26:33 2023

#Chan   Negative               Offset                  Positive
#====   ========               ======                  ========
 ch00:  0.99730931594967842102 -0.00213623046875000000  0.99823938077315688133
 ch01:  0.99721193406730890274 -0.00640869140625000000  0.99833755288273096085
 ch02:  0.99734734417870640755 -0.00549316406250000000  0.99839489161968231201
 ch03:  0.99713751301169395447 -0.00793457031250000000  0.99821293447166681290
 ch04:  0.99702146509662270546 -0.00885009765625000000  0.99811642197892069817
 ch05:  0.99705506581813097000 -0.00854492187500000000  0.99814362032338976860
 ch06:  0.99724035896360874176 -0.00396728515625000000  0.99825175246223807335
 ch07:  0.99738377984613180161 -0.00213623046875000000  0.99833340803161263466
 ch08:  0.99702031910419464111 -0.00518798828125000000  0.99806922534480690956
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
ch09:  0.99714408721774816513 -0.00671386718750000000  0.99827769445255398750
ch10:  0.99705672170966863632 -0.00976562500000000000  0.99821040173992514610
ch11:  0.99724986264482140541 -0.00762939453125000000  0.99835348222404718399
```

===> Board calibration data written to 'OutputCal' file

3.2.11 lib/ccrtngfc_dac_fifo

This test performs validation of the Multi-Function DAC FIFO operation of the card. If two daughter cards are present, both are run concurrently.

```
Usage: ./ccrtngfc_dac_fifo [-b board] [-c ChannelSelectMask] [-C DacUpdateClock]
                           [-e MsgDmaEngine] [-f format] [-j SpeedMode] [-l LoopCnt]
                           [-M SelectDacModule] [-N] [-o OutputSelect] [-S NumSamples]
                           [-u UpdateMode] [-v OutputVolts] [-w WaveType]
 -A                       (Perform DAC Auto Calibration first using reference voltage)
 -b <board>               (board #, default = 0)
 -c <ChannelSelectMask>   (channel selection mask, default = all channels)
 -C DacUpdateClock        (Select DAC update clock, 0..4 for each module. If '^' first arg,
                           Skip Programming Clock)
    -C 2@20000.0          (Ch0..11=Clock2 at 20000 SPS for both modules)
    -C 4                  (Ch0..11=Clock4 at MAX SPS for both modules)
    -C ^3                 (Ch0..11=Clock3 both modules assignment only) [** Skip Programming
                           Clock **]
    -C 1@100000,2@200000 (Ch0..11=Clock1 at 100000 SPS for module 1 and Clock 2 @200000 SPS
                           for module 2)
 -e MsgDmaEngine          (Select MsgDma Engine -- default "=== get free engine ===")
    -e 0,2                (MsgDma Engine 0 for DAC Module 0 and MsgDma Engine 2 for DAC Module 1)
    -e 3,1                (MsgDma Engine 3 for DAC Module 0 and MsgDma Engine 1 for DAC Module 1)
    -e ,3                 (MsgDma Engine Default for DAC Module 0 and MsgDma Engine 3 for DAC
                           Module 1)
 -f DataFormat            (select data format, '2' or 'b')
    -f b,2,b              (Ch0..1 & Ch4..11=Offset binary, Ch2..3=Two's complement)
    -f 2/b                (Ch0..1=Two's complement, Ch4..11=Offset binary)
    -f b                  (Ch0..11=Offset binary)
 -j SpeedMode             (DAC Speed Mode: 'h' or 'n' [high/normal])
 -l LoopCnt               (Loop count -- default is 0)
 -M SelectDacModule       (Select DAC Module -- default is all available modules)
 -o OutputSelect          (DAC output select, 's' or 'd')
    -o d,s                (Ch0..1=differential, Ch2..11=single_ended)
    -o s/d,s              (Ch0..1 & Ch4..11=single_ended, Ch2..3=differential)
    -o d                  (Ch0..11=differential)
 -S <NumSamples>          (Number of Samples per channel, default = 512)
 -u                       (Set DAC Update Mode)
    -ui                   (Set DAC Update Mode to Immediate Mode)
    -us                   (Set DAC Update Mode to Synchronized Mode)
 -v DacVoltage            (DAC Voltage. -10.0  to +10.0)
    -v 1.5,9.9            (Ch0=1.5 volts, Ch1..11= 9.9 volts)
    -v2.5/7.5,9.7         (Ch0=2.5 volts, Ch1=7.5 volts, Ch2..11=9.7 volts)
    -v 9.95               (Ch0..11=9.95 volts)
 -w <WaveType>            (default  = 's' Sine Wave)
    -wu                      (Saw Wave [up])
    -wd                      (Saw Wave [down])
    -ws                      (Sine Wave)
    -wx                      (Square Wave)
    -wX                      (Square Wave - Alternate Sample)
    -wy                      (Step Wave [down])
    -wz                      (Step Wave [up])
    -wt                      (Triangle Wave)
    -ww                      (All Wave [Sine/Square/StepUp/Triangle/StepDown])
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
Note: If high speed mode is enabled, only even channels are used
      If high speed mode is enabled, maximum clock speed is 2000000.0 SPS, otherwise it is
      1000000.0 SPS
      If '^' is specified as first argument to '-C' option, then skip programming clocks

 e.g. ./ccrtngfc_dac_fifo -od,s,d,s -v8,10,5,1 -wx       (dac0&2 differential, dac1&3 single_ended)
      ./ccrtngfc_dac_fifo -ws -ui -od                    (sine wave, immediate)


If you wish to run both ADC and DAC concurrently, you can try the following:
   1) ./ccrtngfc_clock -C0@4500000 -C1@1000000 -l1 (Program ADC Clock 0 at 4.5 MHz and DAC
                                                    Clock 1 at 1.0 MHz)
   2) ./ccrtngfc_dac_fifo -C^1                     (Start DAC Fifo using Clock at 1 in first
                                                    window)
   3) ./ccrtngfc_adc_fifo -C^0                     (Start ADC Fifo using Clock at 0 in second
                                                    window)
```

Example display:

./ccrtngfc_dac_fifo -C0

```
MyHandle=0xa37f700
DacModule0: Programming Clock0: Desired Frequency 1000000.000, Tolerance=0.020000 PPT
DacModule1: Programming Clock0: Desired Frequency 1000000.000, Tolerance=0.020000 PPT

StartChannelNumber=0
EndChannelNumber  =11


           DAC Information:
             Flags              = 0x00000001
             ModuleNumber       = 0
             Handle             = 0xa37f700
             local_ptr          = 0x7ffff7f52000
             local_dac_ptr      = 0x7ffff7f57000
             local_dac_fifo_ptr = 0x7ffff7f66000
             DacFp              = 4
             DacDeviceName      = /dev/ccrtngfc0_dac0
             DacSerialNumber    = 729512

#### Output Clock 0 Frequency = 1000000.000 Samples/Second/Channel
 DAC 0....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x0 (Single-Ended)
     Output Range = 10
 DAC 1....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x0 (Single-Ended)
     Output Range = 10
 DAC 2....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x0 (Single-Ended)
     Output Range = 10
 DAC 3....
            State = 0x0 (Idle)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x0 (Single-Ended)
     Output Range = 10
 DAC 4....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x0 (Single-Ended)
     Output Range = 10
 DAC 5....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x0 (Single-Ended)
     Output Range = 10
DacModule0: DAC Update Selection (7): DacModule0: Clock Generator 0 Selected (Desired
Frequency=1000000.00)

StartChannelNumber=0
EndChannelNumber  =11


           DAC Information:
             Flags              = 0x00000001
             ModuleNumber       = 1
             Handle             = 0xa37f700
             local_ptr          = 0x7ffff7f52000
             local_dac_ptr      = 0x7ffff7f59000
             local_dac_fifo_ptr = 0x7ffff7f6e000
             DacFp              = 5
             DacDeviceName      = /dev/ccrtngfc0_dac1
             DacSerialNumber    = 729513

#### Output Clock 0 Frequency = 1000000.000 Samples/Second/Channel
 DAC 0....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x0 (Single-Ended)
     Output Range = 10
 DAC 1....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x0 (Single-Ended)
     Output Range = 10
 DAC 2....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x0 (Single-Ended)
     Output Range = 10
 DAC 3....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x0 (Single-Ended)
     Output Range = 10
 DAC 4....
            State = 0x0 (Idle)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x0 (Single-Ended)
     Output Range = 10
 DAC 5....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x0 (Single-Ended)
     Output Range = 10
DacModule1: DAC Update Selection (7): DacModule1: Clock Generator 0 Selected (Desired
Frequency=1000000.00)
======= CpuCountAssignedToThisTask=12

Device Name    : /dev/ccrtngfc0
          Physical Memory Information:
            UserPID            =354912
            PhysMemPtr         =0x65e78000
            DriverVirtMemPtr   =0xffff9a30e5e78000
            MmapedUserMemPtr   =0x7ffff7f4c000
            PhysMemSize        =0x00006000
            PhysMemSizeFreed   =0x00000000
            EntryInTxTbl       =0
            NumOfEntriesUsed   =1
            Flags              =0x0000

#### Output Clock 0 Frequency = 1000000.000 Samples/Second/Channel
#### Expected Transfer Rate   =       4.000 MBytes/Second
#### Expected Wave Period     =       0.512 msecs
#### Expected Wave Frequency  =    1953.125 Hz
       Speed Mode: 0 (Normal speed)
     Channel Mask: 0xfff
    Samples/Write: 512
Voltage Selection: Ch00=10.00 Ch01=10.00 Ch02=10.00 Ch03=10.00 Ch04=10.00 Ch05=10.00
                 : Ch06=10.00 Ch07=10.00 Ch08=10.00 Ch09=10.00 Ch10=10.00 Ch11=10.00
Generating a continuous Sine Wave on selected channels: <CTRL-C> to abort

### Board 0: All Selected Channels Output: (Raw=0xfffe Volts=  9.999)

DAC0: Eng0: 512.266 usec/write: 3.998 MBytes/sec, 511.998 usec period, 1.953 KHz (fifo=129696 - 98.95%)
DAC1: Eng1: 512.987 usec/write: 3.992 MBytes/sec, 512.006 usec period, 1.953 KHz (fifo=129660 - 98.92%)

#### DISABLING CLOCK OUTPUT ####
DAC0: DaughterCardThreadId=140737333200640
DACHandle=0xa737140
########### DacStartCount=1 thread=140737333200640
DAC1: DaughterCardThreadId=140737324807936
DACHandle=0xa73b198
########### DacStartCount=2 thread=140737324807936
#### ENABLING CLOCK OUTPUT ####
#### DISABLING CLOCK OUTPUT ####
```

3.2.12 lib/ccrtngfc_dac_setchan

This test generates voltages on various Analog Output channels.

```
Usage: ./ccrtngfc_dac_setchan [-b board] [-c ChannelSelectMask] [-C DacUpdateClock]
                              [-e MsgDmaEngine] [-f format] [-i] [-j SpeedMode] [-l LoopCnt]
                              [-m WriteMode] [-M SelectDacModule] [-N] [-o OutputSelect]
                              [-S NumSamples] [-u UpdateMode] [-v OutputVolts] [-w WaveType]
 -A                      (Perform DAC Auto Calibration first using reference voltage)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
 -b <board>              (board #, default = 0)
 -c <ChannelSelectMask>  (channel selection mask, default = all channels)
 -C DacUpdateClock       (select DAC update clock, 0..4 or 's|S')
    -C s                 (Ch0..11=Software Update)
    -C ^2                (Ch0..11=Clock2 assignment only) [** Skip Programming Clock **]
    -C 3@20000.0         (Ch0..11=Clock3 at 20000 SPS)
    -C 4                 (Ch0..11=Clock4 at MAX SPS)
 -e MsgDmaEngine         (Select MsgDma Engine -- default "=== get free engine ===")
 -f DataFormat           (select data format, '2' or 'b')
    -f b,2,b             (Ch0..1 & Ch4..11=Offset binary, Ch2..3=Two's complement)
    -f 2/b               (Ch0..1=Two's complement, Ch4..11=Offset binary)
    -f b                 (Ch0..11=Offset binary)
 -i                      (Enable Interrupts -- default = Disable)
 -j SpeedMode            (DAC Speed Mode: 'h' or 'n' [high/normal])
 -l LoopCnt              (Loop count -- default is 0)
 -m <WriteMode>          (Write Mode)
    -mdp                    (Driver:  [Channel Registers] PIO mode)
    -mlc                    (Library: [Channel Registers] program I/O Fast Memory Copy)
    -mlp                    (Library: [Channel Registers] PIO mode)
    -mlm                    (Library: [Channel Registers] Modular scatter-gather DMA mode)
    -mlx                    (Library: [Channel Registers] Clone [MEM->DAC] Modular
                             scatter-gather DMA mode)
    -mup                    (User:    [Channel Registers] PIO mode)
    -mdP                    (Driver:  [FIFO] PIO mode)
    -mlM                    (Library: [FIFO] Modular scatter-gather DMA mode)
    -mlP                    (Library: [FIFO] PIO mode)
 -M SelectDacModule      (Select DAC Module -- default is module 0)
 -N                      (Open device with O_NONBLOCK flag for driver operations)
 -o OutputSelect         (DAC output select, 's' or 'd')
    -o d,s               (Ch0..1=differential, Ch2..11=single_ended)
    -o s/d,s             (Ch0..1 & Ch4..11=single_ended, Ch2..3=differential)
    -o d                 (Ch0..11=differential)
 -S <NumSamples>         (Number of Samples per channel, default = 512)
 -u                      (Set DAC Update Mode)
    -ui                  (Set DAC Update Mode to Immediate Mode)
    -us                  (Set DAC Update Mode to Synchronized Mode)
 -v DacVoltage           (DAC Voltage. -10.0  to +10.0)
    -v 1.5,9.9           (Ch0=1.5 volts, Ch1..11= 9.9 volts)
    -v2.5/7.5,9.7        (Ch0=2.5 volts, Ch1=7.5 volts, Ch2..11=9.7 volts)
    -v 9.95              (Ch0..11=9.95 volts)
 -w <WaveType>           (default  = 'c' Constant Voltage)
    -wc                     (Constant Voltage)
    -wu                     (Saw Wave [up])
    -wd                     (Saw Wave [down])
    -ws                     (Sine Wave)
    -wx                     (Square Wave)
    -wX                     (Square Wave - Alternate Sample)
    -wy                     (Step Wave [down])
    -wz                     (Step Wave [up])
    -wt                     (Triangle Wave)
    -ww                     (All Wave [Sine/Square/StepUp/Triangle/StepDown])

Note: If high speed mode is enabled, only even channels are used
      If high speed mode is enabled, maximum clock speed is 2000000.0 SPS, otherwise it is
      1000000.0 SPS

 e.g. ./ccrtngfc_dac_setchan -od,s,d,s -v8,10,5,1 -wx -mdP (dac0&2 differential, dac1&3
                                                           single_ended)
      ./ccrtngfc_dac_setchan -ws -ui -od                  (sine wave, immediate)

If you wish to run both ADC and DAC concurrently, you can try the following:
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
------------------------------------------------------------------------------
   1) ./ccrtngfc_clock -C0@4500000 -C1@1000000 -l1 (Program ADC Clock 0 at 4.5 MHz and DAC
                                                    Clock 1 at 1.0 MHz)
   2) ./ccrtngfc_dac_setchan -C^1 -ws -mlM         (Start DAC Chan using 1 MHz Clock 1 in
                                                    first window)
   3) ./ccrtngfc_adc         -C^0 -mlP             (Start ADC using 4.5 MHz Clock 0 in second
                                                    window)
```

Example display:

./ccrtngfc_dac_setchan -ws -ui -od

```
Device Name    : /dev/ccrtngfc0

StartChannelNumber=0
EndChannelNumber  =11

           Physical Memory Information:
             UserPID            =355245
             PhysMemPtr         =0x65e78000
             DriverVirtMemPtr   =0xffff9a30e5e78000
             MmapedUserMemPtr   =0x7ffff7f4c000
             PhysMemSize        =0x00006000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =0
             NumOfEntriesUsed   =1
             Flags              =0x0000

           DAC Information:
             Flags              = 0x00000001
             ModuleNumber       = 0
             Handle             = 0xa37ec60
             local_ptr          = 0x7ffff7f52000
             local_dac_ptr      = 0x7ffff7f57000
             local_dac_fifo_ptr = 0x7ffff7f66000
             DacFp              = 4
             DacDeviceName      = /dev/ccrtngfc0_dac0
             DacSerialNumber    = 729512

#### Output Clock 0 Frequency = 1000000.000 Samples/Second/Channel
 DAC 0....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x1 (Differential)
     Output Range = 20
 DAC 1....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x1 (Differential)
     Output Range = 20
 DAC 2....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x1 (Differential)
     Output Range = 20
 DAC 3....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x1 (Differential)
     Output Range = 20
 DAC 4....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x1 (Differential)
     Output Range = 20
 DAC 5....
            State = 0x0 (Idle)
      Update Mode = 0x0 (Immediate)
      Data Format = 0x0 (Offset Binary)
    Output Select = 0x1 (Differential)
     Output Range = 20

       Write Mode: -mlp: Library: (CHANNEL) PIO Mode
       Speed Mode: 0 (Normal speed)
     Channel Mask: 0xfff
    Samples/Write: 512 (per active channel)
Voltage Selection: Ch00=20.00 Ch01=20.00 Ch02=20.00 Ch03=20.00 Ch04=20.00 Ch05=20.00
                 : Ch06=99.00 Ch07=99.00 Ch08=99.00 Ch09=99.00 Ch10=99.00 Ch11=99.00
Generating a continuous Sine Wave on selected channels: <CTRL-C> to abort

5795531: 4.307 usec/write: 928.721 KBytes/sec, 2.309 msec period, 433.007 Hz
```

3.2.13 lib/ccrtngfc_daughtercard_info

This test returns information that is located in the EEPROMs on the daughter cards.

```
Usage: ./ccrtngfc_daughtercard_info [-b Board] [-d DaughterCard]
 -b Board           (Board number -- default is 0)
 -d DaughterCard    (Daughter Card Selection -- default is 0)
```

Example display:

./ccrtngfc_daughtercard_info -b0

```
========================= Daughter Card 0 ==========================

(0.128 seconds)
######################################################################
               Board Number: 0
                   Board ID: 9320

              Daughter Card: 0
           Daughter Card Id: 1
     Daughter Card Assembly: 1579321-901
                   Revision: 'D'
              Serial Number: 729514
                       Date: 02/21/2023      (mm/dd/yyyy)
                Description: 'High Speed Analog Daughter Card'
                      Notes: 'Calibrated 2/21/2023'
######################################################################

========================= Daughter Card 1 ==========================

(0.128 seconds)
######################################################################
               Board Number: 0
                   Board ID: 9320
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            Daughter Card: 1
   Loaded Firmware Function: 1 (Installed Daughter Card Supported)
          Daughter Card Id: 1
     Daughter Card Assembly: 1579321-901
                  Revision: 'D'
            Serial Number: 729512
                     Date: 02/21/2023      (mm/dd/yyyy)
              Description: 'High Speed Analog Daughter Card'
                    Notes: 'Calibrated 2/21/2023'
######################################################################
```

./ccrtngfc_daughtercard_info -b1

```
========================= Daughter Card 0 =========================

(0.128 seconds)
######################################################################
             Board Number: 1
                 Board ID: 9330
            Daughter Card: 0
   Loaded Firmware Function: 2 (Installed Daughter Card Supported)
          Daughter Card Id: 2
     Daughter Card Assembly: 1579322-901
                  Revision: 'A'
            Serial Number: 710023
                     Date: 01/22/2024      (mm/dd/yyyy)
              Description: 'High Speed Digital Daughter Card'
                    Notes: 'No Calibration Required'
######################################################################
```

3.2.14 lib/ccrtngfc_dio

This test generates, views and tests various digital channels.

```
Usage: ./ccrtngfc_dio [-b BoardNo] [-c] [-d Delay] [-F DebugFile] [-l LoopCnt]
                      [-M SelectLDioModule] [-n NumChans] [-p PatternSelect] [-r RunOption]
                      [-s SkipChannelsMask]
 -b BoardNo               (Board number -- default is 0)
 -c                       (Switch to Continuous mode -- default is SYNC)
 -d Delay                 (Delay between screen refresh -- default is 100)
 -F DebugFile             (Debug file -- default "=== None ===")
 -l LoopCnt               (Loop count -- default is 0)
 -M SelectLDioModule      (Select LDIO Module -- default is DIO module 0)
 -n NumChans              (number of channels -- default is 32)
 -p PatternSelect         (LDIO mode -- default is to sequence through all patterns)
    -p0                   (Rolling Ones)
    -p1                   (Rolling Zeros)
    -p2                   (Adding Bit)
    -p3                   (Toggling 'A' & '5')
    -p@XXXXXXXX           (Fixed Pattern XXXXXXXX selection in Hex)
 -r RunOption             (Run option -- default is 4)
    -rd                   (Digital Isolators test)
    -rD                   (Fast [no curses] Digital Isolators test)
    -re                   (External Loopback DIO test - Loopback breakout box requried)
    -rE                   (Fast [no curses] external loopback DIO test - Loopback breakout
                           box requried)
    -ri                   (Read DIO input channels)
    -rl                   (Internal Loopback DIO test - No inputs/outputs must be connected)
    -rL                   (Fast [no curses] internal loopback DIO test - No inputs/outputs
                           must be connected)
    -ro                   (Write pattern to DIO output channels)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   -rt                  (Digital Terminators test)
   -rT                  (Fast Digital Terminators test)
 -s SkipChannelsMask    (Skip channels mask -- default is @0x00000000)
   -sXXXXXXXX           (LDIO Channels 31..00=XXXXXXXX in Hex)
e.g. ./ccrtngfc_dio -rl -sf0        (Internal Loopback Testing. Skip LDIO Channels 04-07)
     ./ccrtngfc_dio -rE -sf0        (External Loopback w/o Curses Testing. Skip LDIO
                                     Channels 04-07)
```

Example display:

./ccrtngfc_dio -rl -sF

In this example we are performing an internal loopback test. In this case, none of the DIO channels should be connected to any external lines, otherwise, the test will fail.

```
Board Number          [-b]: 0
Output Sync Mode      [-c]: 1 [SYNC]
Delay                 [-d]: 100 milli-seconds
LDIO Module           [-M]: 0
Loop Count            [-l]: ***Forever***
Number of Channels    [-n]: 32
Pattern Selection     [-p]: 2 (Adding Bit)
Run Option            [-r]: 5 (Internal Loopback Test)
Skip Channels Mask    [-s]: 0x0000000F (31..00)

Channel Mismatch Count    : 0 (=== Passed ===)
DIO Direction             : 0xFFFFFFFF (All Output)
DIO Channels Terminator   : 0x00000000 (All Off)
LDIO Enable               : 0x00000001 (Enable)
Input Snapshot            : 0x00000001 (Snapshot)
Scan Count                : 970

Write Duration (microsecs) :    1.953 (min=   1.844/max=   6.046/ave=   1.968)
Read  Duration (microsecs) :    3.928 (min=   3.874/max=  30.171/ave=   3.992)

Channels     Output    Input     Expected
===========  ========  ========  ========
 30..00 [0]: 000001F0  000001F0  000001F0

          <------------------------ Input Channels ----------------------->
          [0]    [1]    [2]    [3]    [4]    [5]    [6]    [7]    [8]    [9]
          ===    ===    ===    ===    ===    ===    ===    ===    ===    ===
   [0]   skip   skip   skip   skip     +      +      +      +      +      .

   [1]     .      .      .      .      .      .      .      .      .      .

   [2]     .      .      .      .      .      .      .      .      .      .

   [3]     .      .

AvalonPtr=0x7ffff7f52000

#### Abort Received ####

=== Test Passed ===
```

3.2.15 lib/ccrtngfc_disp

Useful program to display the local board registers. This program uses the *curses* library. This test is similar to the previous non-library test.

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
Usage: ./ccrtngfc_disp [-b Board] [-d Delay] [-e MsgDmaEngine] [-H] [-i] [-l LoopCnt]
                       [-m XferMode] [-o Offset] [-P Pause] [-s XferSize] [-S DispSize]
 -b Board        (Board number -- default board is 0)
 -d Delay        (Delay between screen refresh -- default is 0)
 -e MsgDmaEngine (Select MsgDma Engine -- default "=== get free engine ===")
 -H              (Enable Hyper-Drive Mode -- default "=== Disabled ===")
 -i              (Enable Interrupts -- default = Disable)
 -l LoopCnt      (Loop Count - default = 0)
 -m XferMode     (Transfer Mode -- default = MSGDMA)
    -mm          (Avalon Memory: Modular Scatter-Gather DMA mode)
    -mp          (Avalon Memory: Programmed I/O mode)
 -o Offset       (Hex offset to read from -- default is 0x0)
 -P Pause        (Microseconds to sleep in User Function loop -- default is 0)
 -s XferSize     (Number of bytes to transfer -- default is 0x1000)
 -S DispSize     (Number of bytes to display -- default is 0x200)
```

Example display:

./ccrtngfc_disp

```
local_ptr=0x7ffff7f52000

           Physical Memory Information:
             UserPID            =186992
             PhysMemPtr         =0x65d28000
             DriverVirtMemPtr   =0xffff993ee5d28000
             MmapedUserMemPtr   =0x7ffff7fdd000
             PhysMemSize        =0x00001000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =0
             NumOfEntriesUsed   =1
             Flags              =0x0000

 Board Number          [-b]: 0
 Delay                 [-d]: 0 milli-seconds
 MSGDMA Engine         [-e]: 0
 Hyper-Drive           [-H]: Disabled
 Interrupts            [-i]: Disabled
 Loop Count            [-l]: ***Forever***
 Transfer Mode         [-m]: Modular Scatter-Gather DMA I/O (Avalon Memory)
 Offset                [-o]: 0x00000000
 Transfer Size         [-s]: 0x00001000 (4096) bytes ( 146.952 MBytes/Second)
 Display Size          [-S]: 0x00000200 (512) bytes

 ScanCount                 : 192177
 Read Duration (microsecs) :    27.873 (min=  26.258/max=  40.341/ave=  27.914)

         00       04       08       0C       10       14       18       1C
         ======== ======== ======== ======== ======== ======== ======== ========
000000   93200101 08252023 00010000 00120000 00000000 00000000 00000020 00010001
000020   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000040   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000060   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000080   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0000a0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0000c0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0000e0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000100   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000120   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000140   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
000160   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
000180   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0001a0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0001c0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
0001e0   00000000 00000000 00000000 00000000 00000000 00000000 00000000 00000000
```

3.2.16 lib/ccrtngfc_dma

This test transfers data from physical memory to the Local register area and back. There are three modes of operation. One is regular DMA, the second is Modular Scatter-Gather DMA and the third is programmed I/O. Depending on the number of DMA engines supported by the card, the user can select one of them to perform the DMA. Additionally, if the card supports Modular Scatter-Gather DMA, then they can also select that. Area select is one of three areas the user can specify. They represent the area in physical memory and local register where the transfer is to occur. The test automatically switches to a different area corresponding to the regular DMA engine supplied. If multiple copies of this application is run on the same card using the same DMA engine, then the user needs to manually select a different area '-A' so the data mismatch does not occur due to using the same area region.

```
Usage: ./ccrtngfc_dma [-A Area2Select] [-b Board] [-e MsgDmaEngine] [-i] [-l LoopCnt]
                      [-m XferMode] [-s Size] [-v VerboseNo]
 -A Area2Select  (Area to select -- default = -1)
 -b Board        (Board number -- default = 0)
 -e MsgDmaEngine (Select MsgDma Engine -- default "=== get free engine ===")
 -i              (Enable Interrupts -- default = Disable)
 -l LoopCnt      (Loop Count - default = 1000)
 -m XferMode     (Transfer Mode -- default = MSGDMA)
    -mm          (MsgDma mode)
    -mp          (Programmed I/O mode)
 -s Size         (Transfer Size in bytes (multiple of byte width) - default = 12288)
 -V VerboseNo    (verbose -- default = 0)

 e.g. ./ccrtngfc_dma -A1     (perform dma using MsgDMA on area 1 )
      ./ccrtngfc_dma -i -mm  (perform dma using MsgDMA with interrupts on area 0)
      ./ccrtngfc_dma -mp     (perform Programmed I/O on area 0)
```

Example display:

./ccrtngfc_dma

```
Device Name: /dev/ccrtngfc0

local_ptr=0x7ffff7f55000

           Physical Memory Information:
             UserPID            =186997
             PhysMemPtr         =0x65800000
             DriverVirtMemPtr   =0xffff993ee5800000
             MmapedUserMemPtr   =0x7ffff7065000
             PhysMemSize        =0x00200000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =0
             NumOfEntriesUsed   =2
             Flags              =0x0000
### Avalon Address[A0]: 0x00001000 - 0x00004000
### MSGDMA Address[A0]: 0x00100400 - 0x00103400
###      Transfer Size: 12288 (0x00003000) bytes (MsgDMA without Interrupts: MsgDma Engine)
###
  1000: A2P: Total:   36.262us ( 338.87 MB/s): first=0xface0000 last=0xface0bff

          (micro-seconds)          (MBytes/second)
       Min     Max     Ave      Min     Max     Ave
    ----------------------  ------------------------
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
P2A:   37.83   43.73   38.97    280.99  324.84  315.34
A2P:   36.15   42.53   36.33    288.95  339.91  338.22
```

3.2.17 lib/ccrtngfc_example

This test provides a simple example of programming ADC, DAC and DIO.

```
Usage: ./ccrtngfc_example [-b Board] [-M SelectModule]
 -b Board             (Board number -- default is 0)
 -M SelectModule      (Select Module -- default is module 0)
```

Example display:

./ccrtngfc_example

```
           DAC Information:
             Flags              = 0x00000001
             ModuleNumber       = 0
             Handle             = 0x48d8c0
             local_ptr          = 0x7ffff7800000
             local_dac_ptr      = 0x7ffff7805000
             local_dac_fifo_ptr = 0x7ffff7814000
             DacFp              = 4
             DacDeviceName      = /dev/ccrtngfc0_dac0
             DacSerialNumber    = 729512

           ADC Information:
             Flags              = 0x00000001
             ModuleNumber       = 0
             Handle             = 0x48d8c0
             local_ptr          = 0x7ffff7800000
             local_adc_ptr      = 0x7ffff7804000
             local_adc_fifo_ptr = 0x7ffff7810000
             AdcFp              = 5
             AdcDeviceName      = /dev/ccrtngfc0_adc0
             AdcSerialNumber    = 729512

local_ptr=0x7ffff7800000

           Physical Memory Information:
             UserPID            =4416
             PhysMemPtr         =0x6c1d2000
             DriverVirtMemPtr   =0xffff8a782c1d2000
             MmapedUserMemPtr   =0x7ffff7fb6000
             PhysMemSize        =0x00001000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =1
             NumOfEntriesUsed   =1
             Flags              =0x0000
### Configuring ADC ###
  - Activate ADC
  - Configure ADC
  - Set Calibration to Positive Reference Voltage
  - Calibrate ADC
### Configuring DAC ###
  - Activate DAC
  - Select Software Update
  - Configure DAC
  - Write 0 to DAC outputs
  - Make DAC operational
  - Calibrate DAC
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
### Programming Clocks ###
### Reading ADC Channels Using Transfer API ###
  - First Seize MsgDma Engine before multiple ADC transfers
  - Perform ADC transfers
  - Finally Release MsgDma Engine when done
  - Dump ADC channel data

     ==== ADC Channels - Using ccrtNGFC_Transfer_Data() ==== (length=48)
     +DMP+        0   00007eda  00007ed8  00007edb  00007edb *..~...~...~...~.*
     +DMP+     0x10   00007ee0  00007edc  00007eda  00007ed7 *..~...~...~...~.*
     +DMP+     0x20   00007edb  00007edb  00007edd  00007edd *..~...~...~...~.*
### Writing DAC Channels Using Transfer API ###
  - First Seize MsgDma Engine before multiple ADC transfers
  - Generate DAC data
  DacCh00: 0x80000000 (0.000000 volts)
  DacCh01: 0x80000000 (0.000000 volts)
  DacCh02: 0x80000000 (0.000000 volts)
  DacCh03: 0x80000000 (0.000000 volts)
  DacCh04: 0x80000000 (0.000000 volts)
  DacCh05: 0x80000000 (0.000000 volts)
  DacCh06: 0x80000000 (0.000000 volts)
  DacCh07: 0x80000000 (0.000000 volts)
  DacCh08: 0x80000000 (0.000000 volts)
  DacCh09: 0x80000000 (0.000000 volts)
  DacCh10: 0x80000000 (0.000000 volts)
  DacCh11: 0x80000000 (0.000000 volts)
  - Perform DAC transfers
  - Finally Release MsgDma Engine when done
### Configuring LIO ###
  - Activate LVDS I/O Module
  - Set LDIO output sync mode to SYNC
  - Set LDIO input snapshot mode
  - Set LIO ports direction
### Reading LIO Channels 00..15 ###
  - CCRTNGFC_LIO_CHAN_00_15=0x00000000
### Writing LIO Channels 16..31 ###
  - CCRTNGFC_LIO_CHAN_16_31=0xbabe0000
### Configuring DIO ###
  - Activate DIO Module
  - Set LDIO output sync mode to SYNC
  - Set LDIO input snapshot mode
  - Set DIO ports direction
### Reading DIO Channels 00..15 ###
  - CCRTNGFC_DIO_CHAN_00_15=0x00002000
### Writing DIO Channels 16..31 ###
  - CCRTNGFC_DIO_CHAN_16_31=0xbabe0000
### Single (one descriptor) Modular Scatter-Gather DMA ###
  - Allocating memory and seeding with pattern
  - Seizing MSGDMA
  - Configure Single MSGDMA (PCIe ==> Avalon)
  - Fire Single MSGDMA: Xfer 0x8000 bytes: Pcie ==> Avalon (@0x8000)
  - Validating data
  - Configure Single MSGDMA (Avalon ==> PCIe)
  - Fire Single MSGDMA: Xfer 0x8000 bytes: Avalon (@0x8000) ==> PCIe
  - Validating data
  - Releasing MSGDMA
### Multi (four descriptor) Modular Scatter-Gather DMA (Single-Shot) ###
  - Allocating memory and seeding with pattern
  - Seizing MSGDMA
  - Configure multi MSGDMA (PCIe ==> Avalon ==> PCIe ==> Avalon ==> PCIe)
  - Setup Multi MSGDMA
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
  - Fire Multi MSGDMA (Single-Shot)
  - Validating data
  - Releasing MSGDMA
### Multi (four descriptor) Modular Scatter-Gather DMA (Clone) ###
  - Allocating memory and seeding with pattern
  - Seizing MSGDMA
  - Configure multi MSGDMA (PCIe ==> Avalon ==> PCIe ==> Avalon ==> PCIe)
  - Setup Multi MSGDMA
  - Stop and Initialize Multi MSGDMA (Clone)
  - Fire Multi MSGDMA and wait one cycle (Clone: Once cycle wait)
  - Validating data
  - Releasing MSGDMA
```

3.2.18 lib/ccrtngfc_expires

This test is useful in displaying board expires information.

```
Usage: ./ccrtngfc_expires -[b Board] -[s]
          -b <board>            (board #, default = 0)
          -s                    (short display, default = verbose)
```

Example display:

./ccrtngfc_expires *(for card that has no restrictions)*

```
      Device Name: /dev/ccrtngfc0
   Board Serial No: 98765 (0x000181cd)

##############################################
###                                        ###
###         UNRESTRICTED FIRMWARE          ###
###                                        ###
##############################################
```

./ccrtngfc_expires *(for restricted card that has NO expiration date)*

```
          Device Name: /dev/ccrtngfc0
     Board Serial No: 98765 (0x000181cd)

##############################################
###                                        ###
###         RESTRICTED FIRMWARE            ###
###                                        ###
##############################################

=========================
=== No Expiration Date ===
=========================
```

./ccrtngfc_expires *(for restricted card that has expiration date)*

```
          Device Name: /dev/ccrtngfc0
     Board Serial No: 98765 (0x000181cd)

##############################################
###                                        ###
###         RESTRICTED FIRMWARE            ###
###                                        ###
##############################################

================================================================
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
Local Expiration Date: 03/11/2018 13:21:52
  GMT Expiration Date: 03/11/2018 17:21:52
   Duration to Expire: Days=122, Hours=2, Minutes=49, Seconds=20
================================================================
```

./ccrtngfc_expires -s *(for card that has no restructions)*

```
Unrestricted
```

./ccrtngfc_expires -s *(for restricted card that has NO expiration date)*

```
Restricted: No expiration date
```

./ccrtngfc_expires -s *(for restricted card that has expiration date)*

```
Restricted: Expire in 10550462 seconds
```

3.2.19 lib/ccrtngfc_identify

This test is useful in identifying a particular card by displaying its LED.

```
Usage: ./ccrtngfc_identify -[absx]
          -a                    (Identify all cards through a light sequence)
          -b <board>            (board #, default = 0)
          -s <seconds)          (Identify Board: ENABLED for number of seconds,
                                 default = 10)
          -s 0                  (Identify Board: DISABLED)
          -s <negative value>   (Identify Board: ENABLED forever)
          -x                    (silent)

If the '-a' option is selected, all other options are ignored. This option will
sequence through all the cards found in turn as follows:
  1) The first device number will flash its LED for 10 seconds
  2) The remaining devices numbers will be selected sequentially and flash their LEDs for 3
seconds
```

Example display:

./ccrtngfc_identify

```
Device Name       : /dev/ccrtngfc0
Board ID          : 9320
Board Type        : 01
Board Function    : 01
Board Serial No   : 706503 (0x000ac7c7)
Firmware Revision : 1.0 (Major.Minor)
LDIO Module 0     : DIO
LDIO Module 1     : LIO
MsgDma Support    : 31 descriptors (Yes)
Cloning Support   : 3 (Yes) Cloning is supported. Region addressing allowed for any user

Identify ENABLED on board 0 (LED should start flashing for 10 seconds)
Sleeping for 10 seconds...
Identify DISABLED on board 0 (LED should stop flashing)
```

./ccrtngfc_identify -a

```
TotalBoardCount=1
 # DNum IRQ MSI Bu:Sl:Fn VnID:Sub  BdID:Ty:Fu:Sub  FMaj.Min(mm:dd:yy hh:mm:ss)   MC  FmFlvCod
FwbRev   IPCores  Temp:C/F   SerialNo RLS# Func
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
 0  0   162  Y  b9:00:00 1542:1542 9320.01.01:0100 1.0(08/25/23 12:00:00)       048 00000000
00000000    0     41.6/106.8 706503   350  MultiFunc

Device Numbers: (enter <CTRL-C> to terminate)
============================================
 0*
```

3.2.20 lib/ccrtngfc_info

This test is useful in getting information for all the *ccrtngfc* devices in the system.

```
Usage: ./ccrtngfc_info -[b Board] -[l] -[v]
          -b <board>            (board #, default = 0)
          -l                    (long display, default = short)
          -v                    (long display and verbose, default = no verbose)
          -l -v                 (long display and verbose, default = no verbose)
```

Example display:

./ccrtngfc_info

```
# IRQ MSI Bu:Sl:Fn VnID:Sub  BdID:Ty:Fu:Sub  FMaj.Min(mm:dd:yy hh:mm:ss)  MC  FmFlvCod FwbRev   IPCores  Temp:C/F
SerialNo RLS# Func
 0 162  Y  b9:00:00 1542:1542 9320.01.01:0100 0001.000(08/25/23 12:00:00)  048 00000000 00000000    0
41.6/106.8 706503   350  MultiFunc
```

./ccrtngfc_info -l

```
        ###################### Board 0 ######################
                        Version:  2023.6.0
                          Build:  Wed May 17 09:19:29 EDT 2023
                         Module:  ccrtngfc
                    Board Index:  0 (PCIe-CCRT_FPGA_NGFC)
                            Bus:  0xb9
                           Slot:  0x00
                           Func:  0x00
                      Vendor ID:  0x1542
                  Sub-Vendor ID:  0x1542
                     Board Info:  0x93200101 (id=9320, type=0x01, func=0x01 (MultiFunc))
                    Member Code:  1 (048)
                  Sub-Device ID:  0x0100
              Firmware Date/Time:  0x08252023 0x00120000 (08/25/2023 12:00:00)
               Firmware Revision:  0x00010000 (1.0)
                 Fpgawb Revision:  0x00000000 (0000.00-00) (Not Supported)
            Firmware Flavor Code:  0x00000000 (0) (****)
    Number of Advanced IP Cores:  0x00000000 (0)
            Board Serial Number:  0x000ac7c7 (706503)
          FPGA Chip Temperature:  0x1be (36.8 degree C, 98.3 degree F)
      FPGA Chip Temperature HWM:  0x1c0 (38.2 degree C, 100.7 degree F)
      FPGA Chip Voltage (1.8VS):  0x01e (1.76 Volts)
      FPGA Chip Voltage (3.3VS):  0x038 (3.28 Volts)
        FPGA Chip Voltage (VCC):  0x02e (0.90 Volts)
       FPGA Chip Voltage (VCCP):  0x02e (0.90 Volts)
      FPGA Chip Voltage (VCCPT):  0x02e (1.80 Volts)
    FPGA Chip Voltage (VCCERAM):  0x02e (0.90 Volts)
   FPGA Chip Voltage (VCCL_HPS):  0x000 (0.00 Volts)
     FPGA Chip Voltage (ADCGND):  0x000 (0.00 Volts)
FPGA Chip Temp Monitor Debugging:  == Disabled ==
   FPGA Chip Temperature Monitor:  60 Seconds
  FPGA Chip Temp Monitor Warning:  80 degree C
 FPGA Chip Temp Monitor Critical:  100 degree C
        Run Level Sector Number:  0x15e (350)
         Multi-Firmware Support:  0x1 (Yes)
                    MSI Support:  Enabled
     Scatter-Gather DMA Support:  Yes
  Number of MSG DMA Descriptors:  31
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
            Double-Word Support:  Yes
                      IRQ Level:  162
             Maximum Link Width:  4
          Negotiated Link Width:  4
                Cloning Support:  3 (Cloning is supported. Region addressing allowed for any user)
          Calibration Reference:  9.91 Volts
```

./ccrtngfc_info -l –v

```
       ###################### Board 0 ######################
                       Version:  2023.6.0
                         Build:  Wed May 17 09:19:29 EDT 2023
                        Module:  ccrtngfc
                   Board Index:  0 (PCIe-CCRT_FPGA_NGFC)
                           Bus:  0xb9
                          Slot:  0x00
                          Func:  0x00
                     Vendor ID:  0x1542
                  Sub-Vendor ID:  0x1542
                     Board Info:  0x93200101 (id=9320, type=0x01, func=0x01 (MultiFunc))
                    Member Code:  1 (048)
                  Sub-Device ID:  0x0100
              Firmware Date/Time:  0x08252023 0x00120000 (08/25/2023 12:00:00)
               Firmware Revision:  0x00010000 (1.0)
                 Fpgawb Revision:  0x00000000 (0000.00-00) (Not Supported)
           Firmware Flavor Code:  0x00000000 (0) (****)
    Number of Advanced IP Cores:  0x00000000 (0)
            Board Serial Number:  0x000ac7c7 (706503)
         FPGA Chip Temperature:  0x1c4 (40.9 degree C, 105.6 degree F)
      FPGA Chip Temperature HWM:  0x1c0 (38.2 degree C, 100.7 degree F)
      FPGA Chip Voltage (1.8VS):  0x01e (1.76 Volts)
      FPGA Chip Voltage (3.3VS):  0x038 (3.28 Volts)
        FPGA Chip Voltage (VCC):  0x02e (0.90 Volts)
       FPGA Chip Voltage (VCCP):  0x02e (0.90 Volts)
      FPGA Chip Voltage (VCCPT):  0x02e (1.80 Volts)
    FPGA Chip Voltage (VCCERAM):  0x02e (0.90 Volts)
   FPGA Chip Voltage (VCCL_HPS):  0x000 (0.00 Volts)
     FPGA Chip Voltage (ADCGND):  0x000 (0.00 Volts)
FPGA Chip Temp Monitor Debugging:  == Disabled ==
   FPGA Chip Temperature Monitor:  60 Seconds
  FPGA Chip Temp Monitor Warning:  80 degree C
 FPGA Chip Temp Monitor Critical:  100 degree C
        Run Level Sector Number:  0x15e (350)
         Multi-Firmware Support:  0x1 (Yes)
                    MSI Support:  Enabled
     Scatter-Gather DMA Support:  Yes
  Number of MSG DMA Descriptors:  31
            Double-Word Support:  Yes
                      IRQ Level:  162
             Maximum Link Width:  4
          Negotiated Link Width:  4
                Cloning Support:  3 (Cloning is supported. Region addressing allowed for any user)
          Calibration Reference:  9.91 Volts

              ---ADC Information---
          Maximum Voltage Range:  10 Volts
                 Number of ADCs:  3
        Number of ADC Channels:  12
       Number of ADC Resolution:  16 Bits
          All ADC Channels Mask:  0x00000fff
     Maximum ADC Fifo Threshold:  0x00020000

              ---DAC Information---
Maximum Single-Ended Voltage Range:  10 Volts
Maximum Differential Voltage Range:  20 Volts
                 Number of DACs:  6
        Number of DAC Channels:  12
       Number of DAC Resolution:  16 Bits
          All DAC Channels Mask:  0x00000fff
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
   ---LDIO Module0 (DIO) Information---
          Number of Channels:  32
             Number of Ports:  32
     Number of Channels/Port:  1
         Number of Registers:  1
Number of Channels/Register:  32

   ---LDIO Module0 (DIO) COS Interrupt Information---
           Module COS Count:  0
       Module COS OVFL Count:  0
                  COS Status:  0x00000000
            COS Ovfl Status:  0x00000000

   ---LDIO Module1 (LIO) Information---
          Number of Channels:  32
             Number of Ports:  8
     Number of Channels/Port:  4
         Number of Registers:  1
Number of Channels/Register:  32

   ---LDIO Module1 (LIO) COS Interrupt Information---
           Module COS Count:  0
       Module COS OVFL Count:  0
                  COS Status:  0x00000000
            COS Ovfl Status:  0x00000000

          ---Physical Memory Information---
   Num of Trans Tbl Entries:  16
Num of Physical Memory Entries:  512
            Avalon Page Bits:  20
            Avalon Page Size:  1048576
           TX Interface Base:  16777216

        ---Analog/MsgDMA Interrupt Information---
             Interrupt Count:  0
            MSG DMA %d Count:  0
            MSG DMA %d Count:  0
            MSG DMA %d Count:  0
            MSG DMA %d Count:  0
            MSG DMA %d Count:  0
            MSG DMA %d Count:  0
   Interrupts Occurred Mask:  0x00000000
      Wakeup Interrupt Mask:  0x00000000
             Timeout Seconds:  0
   Interrupts Occurred Mask:  0x00000000
      Wakeup Interrupt Mask:  0x00000000

        ---Memory Regions Information---
                   Region 0:  Addr=0xfbe80000  Size=32768 (0x8000)
                   Region 2:  Addr=0xfbe00000  Size=524288 (0x80000)
```

3.2.21 lib/ccrtngfc_ldio_intr

This test allows the user to check out the Digital I/O and LVDS I/O components of the cards using interrupts.

```
Usage: ./ccrtngfc_ldio_intr [-b Board] [-d Delay] [-F FallCh] [-l LoopCnt] [-L LevelCh]
                            [-M SelectLDioModule_First] [-R RiseCh] [-X DeleteCh]
 -b <board>                (board #, default = 0)
 -d Delay                  (Delay between screen refresh -- default is 100 milli-seconds)
 -F FallCh                 (Falling Edge Channel_List)
 -l LoopCnt                (Loop count -- default is 0)
 -L LevelCh                (Level State Channel_List)
 -M SelectLDioModule_First (Select LDIO Module -- default module is 'module 0')
 -R RiseCh                 (Rising Edge Channel_List)
 -X DeleteCh               (Delete COS Channel_List)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
 Examples of Channel_List. Unchanged channels default to Level State Channels:
    -F -                  (set all LDIO channels to falling edge)
    -R 1,2,7,9            (set channels 1,2,7,9 to rising edge, rest are level state)
    -X 5,7-12             (delete channels 5, and 7 to 12. rest are level state)

 Example of running LIO and DIO concurrently:
      1) Connect 17 KHz square wave to DIO (M0) channel 0 with a voltage of 0 to +4
         volts and load of High-Z
      2) Connect 15 KHz square wave to LIO (M1) channel 3 with a voltage of +/- 200
         milli-volts and load of 50 Ohms
      3) shield -a 2,4-5                        (shield processor 2, 4 & 5)
      4) ./ccrtngfc_smp_affinity -c4            (force driver to CPU 2)
      5) run -b4-5 ./ccrtngfc_ldio_intr -M0 -M1 (run DIO & LIO test on CPU 4 & 5)
      -- or --
      6) run -b4-5 ./ccrtngfc_ldio_intr -M0 -M1 -F0 -R3 (run DIO & LIO test on CPU 4 & 5,
                                                          Rise Ch3, Fall Ch0)
```

Example display:

```
# Connect 20KHz square wave to DIO channel 0 with a voltage of 0 to +4 volts and load of High-Z
# shield -a 2, 4-5
# ./ccrtngfc_smp_affinity -c4
# run -b4-5 ./ccrtngfc_ldio_intr -M0

 Rising Edge[-R]: ### No Channels Selected ###
Falling Edge[-F]: ### No Channels Selected ###
 Level State[-L]: Number of Channels = 32
        Module 0:  0  1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
                   25 26 27 28 29 30 31
 Disable COS[-X]: ### No Channels Selected ###

====================================  [DIO Module 0]  ======================================
                           Scan Count:       417       (ddd:hh:mm:ss = 000:00:00:41)
                 COS Interrupt Handler: (Active)
          COS Interrupt Duration (usec):      24.69 min=16.51 max=51.73 run_ave=24.96 (40056.86 Hz)
   Driver Interrupt Response Time (usec):      12.24 min=11.03 max=18.99 run_ave=12.19
         Driver Interrupts Occurred Mask: 0x00000300
            Driver Wakeup Interrupt Mask: 0x00000100
         Driver Spurious Interrupt Count:          0
    Driver Repeat on New Interrupt Count:          0
                Driver User Wakeup Count:    1673552
                     User Callback Count:    1673552
            Missed User Callback Count:          0

                                       [DIO Module 0]
                   COS Enable (Ch31..00): 0xffffffff
                     COS Mode (Ch31..00): 0x00000000
              COS Edge Sense (Ch31..00): 0x00000000
                   COS Status (Ch31..00): 0x00000001
         COS OVERFLOW Status (Ch31..00): 0x00000000
                      Module COS Counts:    1673554
                    Module COS Rate (Hz):   40000.19
               Module Queued COS Counts:          2
     Module Hardware Overflow COS Counts:          0

     <--------- [DIO Module 0] Channels COS Status Count    ('+' Rise, '-' Fall, '.' Level, 'NC' No COS) -------->
            [0]        [1]        [2]        [3]        [4]        [5]        [6]        [7]        [8]        [9]
     ========== ========== ========== ========== ========== ========== ========== ========== ========== ==========
 [0]    1673554.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [1]          0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [2]          0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [3]          0.         0.
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
    <-------- [DIO Module 0] Channels COS Overflow Count    ('+' Rise, '-' Fall, '.' Level, 'NC' No COS) ------->
           [0]        [1]        [2]        [3]        [4]        [5]        [6]        [7]        [8]        [9]
    ========== ========== ========== ========== ========== ========== ========== ========== ========== ==========
 [0]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [1]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [2]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [3]         0.         0.
```

Connect 20KHz square wave to LIO channel 3 with a voltage of +/- 200 milli-volts and load of 50 ohms
shield -a 2, 4-5
./ccrtngfc_smp_affinity -c4
run -b4-5 ./ccrtngfc_ldio_intr -M1

```
 Rising Edge[-R]: ### No Channels Selected ###
Falling Edge[-F]: ### No Channels Selected ###
 Level State[-L]: Number of Channels = 32
        Module 1:  0  1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
                  25 26 27 28 29 30 31
 Disable COS[-X]: ### No Channels Selected ###

=====================================  [LIO Module 1]  =====================================
                           Scan Count:       757       (ddd:hh:mm:ss = 000:00:01:16)
              COS Interrupt Handler: (Active)
        COS Interrupt Duration (usec):      24.63 min=15.17 max=58.51 run_ave=24.96 (40056.92 Hz)
 Driver Interrupt Response Time (usec):      13.36 min=12.09 max=23.49 run_ave=13.48
       Driver Interrupts Occurred Mask: 0x00000200
          Driver Wakeup Interrupt Mask: 0x00000200
       Driver Spurious Interrupt Count:          0
  Driver Repeat on New Interrupt Count:          0
            Driver User Wakeup Count:    3044519
                 User Callback Count:    3044519
          Missed User Callback Count:          0

                                       [LIO Module 1]
              COS Enable (Ch31..00): 0xffffffff
                COS Mode (Ch31..00): 0x00000000
           COS Edge Sense (Ch31..00): 0x00000000
              COS Status (Ch31..00): 0x00000008
     COS OVERFLOW Status (Ch31..00): 0x00000000
                 Module COS Counts:    3044556
               Module COS Rate (Hz):   39999.96
          Module Queued COS Counts:         37
  Module Hardware Overflow COS Counts:          0

    <--------- [LIO Module 1] Channels COS Status Count    ('+' Rise, '-' Fall, '.' Level, 'NC' No COS) -------->
           [0]        [1]        [2]        [3]        [4]        [5]        [6]        [7]        [8]        [9]
    ========== ========== ========== ========== ========== ========== ========== ========== ========== ==========
 [0]         0.         0.         0.   3044556.         0.         0.         0.         0.         0.         0.
 [1]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [2]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [3]         0.         0.

    <-------- [LIO Module 1] Channels COS Overflow Count    ('+' Rise, '-' Fall, '.' Level, 'NC' No COS) ------->
           [0]        [1]        [2]        [3]        [4]        [5]        [6]        [7]        [8]        [9]
    ========== ========== ========== ========== ========== ========== ========== ========== ========== ==========
 [0]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [1]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [2]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
```

Connect 15KHz square wave to LIO channe 3 with a voltage of +/- 200 milli-volts and load of 50 ohms
Connect 17KHz square wave to DIO channel 0 with a voltage of 0 to +4 volts and load of High-Z
shield -a 2, 4-5
./ccrtngfc_smp_affinity -c4
run -b4-5 ./ccrtngfc_ldio_intr -M0 -M1

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
        Rising Edge[-R]: ### No Channels Selected ###
       Falling Edge[-F]: ### No Channels Selected ###
        Level State[-L]: Number of Channels = 64
               Module 0:  0  1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
                          25 26 27 28 29 30 31
               Module 1:  0  1  2  3  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24
                          25 26 27 28 29 30 31
       Disable COS[-X]: ### No Channels Selected ###

====================================  [DIO Module 0]  [LIO Module 1]  ======================================
                            Scan Count:       537      (ddd:hh:mm:ss = 000:00:00:54)
                 COS Interrupt Handler: (Active)
          COS Interrupt Duration (usec):     28.86 min=13.84 max=70.14 run_ave=26.40 (37873.55 Hz)
   Driver Interrupt Response Time (usec):     19.24 min=10.78 max=25.28 run_ave=15.45
         Driver Interrupts Occurred Mask: 0x00000300
            Driver Wakeup Interrupt Mask: 0x00000300
         Driver Spurious Interrupt Count:         0
    Driver Repeat on New Interrupt Count:    868468
                Driver User Wakeup Count:   2052781
                     User Callback Count:   2052781
              Missed User Callback Count:         0

                                        [DIO Module 0]              [LIO Module 1]
                   COS Enable (Ch31..00): 0xffffffff                  0xffffffff
                     COS Mode (Ch31..00): 0x00000000                  0x00000000
                COS Edge Sense (Ch31..00): 0x00000000                  0x00000000
                   COS Status (Ch31..00): 0x00000000                  0x00000008
          COS OVERFLOW Status (Ch31..00): 0x00000000                  0x00000000
                      Module COS Counts:   1845314                     1625180
                    Module COS Rate (Hz):  34000.80                    30000.68
                Module Queued COS Counts:    115691                           2
      Module Hardware Overflow COS Counts:         0                           0

     <--------- [DIO Module 0] Channels COS Status Count    ('+' Rise, '-' Fall, '.' Level, 'NC' No COS) -------->
           [0]        [1]        [2]        [3]        [4]        [5]        [6]        [7]        [8]        [9]
     ========== ========== ========== ========== ========== ========== ========== ========== ========== ==========
 [0]    1841872.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [1]          0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [2]          0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [3]          0.         0.

     <-------- [DIO Module 0] Channels COS Overflow Count    ('+' Rise, '-' Fall, '.' Level, 'NC' No COS) ------->
           [0]        [1]        [2]        [3]        [4]        [5]        [6]        [7]        [8]        [9]
     ========== ========== ========== ========== ========== ========== ========== ========== ========== ==========
 [0]          0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [1]          0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [2]          0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [3]          0.         0.


     <--------- [LIO Module 1] Channels COS Status Count    ('+' Rise, '-' Fall, '.' Level, 'NC' No COS) -------->
           [0]        [1]        [2]        [3]        [4]        [5]        [6]        [7]        [8]        [9]
     ========== ========== ========== ========== ========== ========== ========== ========== ========== ==========
 [0]          0.         0.         0.   1625180.         0.         0.         0.         0.         0.         0.
 [1]          0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [2]          0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [3]          0.         0.

     <-------- [LIO Module 1] Channels COS Overflow Count    ('+' Rise, '-' Fall, '.' Level, 'NC' No COS) ------->
           [0]        [1]        [2]        [3]        [4]        [5]        [6]        [7]        [8]        [9]
     ========== ========== ========== ========== ========== ========== ========== ========== ========== ==========
 [0]          0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [1]          0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [2]          0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [3]          0.         0.
```

Connect 15KHz square wave to LIO channe 3 with a voltage of +/- 200 milli-volts and load of 50 ohms

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
        # Connect 17KHz square wave to DIO channel 0 with a voltage of 0 to +4 volts and load of High-Z
        # shield -a 2, 4-5
        # ./ccrtngfc_smp_affinity -c4
        # run -b4-5 ./ccrtngfc_ldio_intr -M0 -M1  -F0 -R3

        Rising Edge[-R]: Number of Channels = 2
                Module 0:  3
                Module 1:  3
        Falling Edge[-F]: Number of Channels = 2
                Module 0:  0
                Module 1:  0
         Level State[-L]: Number of Channels = 60
                Module 0:  1  2  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26
                           27 28 29 30 31
                Module 1:  1  2  4  5  6  7  8  9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26
                           27 28 29 30 31
         Disable COS[-X]: ### No Channels Selected ###

====================================  [DIO Module 0]  [LIO Module 1]  ======================================
                            Scan Count:       8018       (ddd:hh:mm:ss = 000:00:13:24)
                  COS Interrupt Handler: (Active)
           COS Interrupt Duration (usec):      63.01 min=17.02 max=89.75 run_ave=41.59 (24042.27 Hz)
   Driver Interrupt Response Time (usec):      18.25 min=0.07 max=37.26 run_ave=15.32
         Driver Interrupts Occurred Mask: 0x00000300
            Driver Wakeup Interrupt Mask: 0x00000300
         Driver Spurious Interrupt Count:          0
    Driver Repeat on New Interrupt Count:    3218271
                Driver User Wakeup Count:   19320260
                     User Callback Count:   19320260
              Missed User Callback Count:          0

                                       [DIO Module 0]               [LIO Module 1]
                   COS Enable (Ch31..00): 0xffffffff                   0xffffffff
                     COS Mode (Ch31..00): 0x00000009                   0x00000009
                COS Edge Sense (Ch31..00): 0x00000008                   0x00000008
                    COS Status (Ch31..00): 0x00000001                   0x00000008
          COS OVERFLOW Status (Ch31..00): 0x00000000                   0x00000000
                       Module COS Counts:   13673976                     12065273
                    Module COS Rate (Hz):   17000.00                     15000.00
                  Module Queued COS Counts:     803864                           15
     Module Hardware Overflow COS Counts:          0                            0

     <--------- [DIO Module 0] Channels COS Status Count    ('+' Rise, '-' Fall, '.' Level, 'NC' No COS) -------->
            [0]        [1]        [2]        [3]        [4]        [5]        [6]        [7]        [8]        [9]
     ========== ========== ========== ========== ========== ========== ========== ========== ========== ==========
 [0]   13673976-         0.         0.         0+         0.         0.         0.         0.         0.         0.
 [1]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [2]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [3]         0.         0.

     <-------- [DIO Module 0] Channels COS Overflow Count    ('+' Rise, '-' Fall, '.' Level, 'NC' No COS) ------->
            [0]        [1]        [2]        [3]        [4]        [5]        [6]        [7]        [8]        [9]
     ========== ========== ========== ========== ========== ========== ========== ========== ========== ==========
 [0]         0-         0.         0.         0+         0.         0.         0.         0.         0.         0.
 [1]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [2]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [3]         0.         0.


     <--------- [LIO Module 1] Channels COS Status Count    ('+' Rise, '-' Fall, '.' Level, 'NC' No COS) -------->
            [0]        [1]        [2]        [3]        [4]        [5]        [6]        [7]        [8]        [9]
     ========== ========== ========== ========== ========== ========== ========== ========== ========== ==========
 [0]         0-         0.         0.  12065273+         0.         0.         0.         0.         0.         0.
 [1]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [2]         0.         0.         0.         0.         0.         0.         0.         0.         0.         0.
 [3]         0.         0.
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
    <-------- [LIO Module 1] Channels COS Overflow Count    ('+' Rise, '-' Fall, '.' Level, 'NC' No COS) ------->
          [0]       [1]       [2]       [3]       [4]       [5]       [6]       [7]       [8]       [9]
    ========== ========== ========== ========== ========== ========== ========== ========== ========== ==========
[0]         0-        0.        0.        0+        0.        0.        0.        0.        0.        0.
[1]         0.        0.        0.        0.        0.        0.        0.        0.        0.        0.
[2]         0.        0.        0.        0.        0.        0.        0.        0.        0.        0.
```

3.2.22 lib/ccrtngfc_lio

This test validates the proper operation of the LVDS I/O. It can be run with various run options to test the component.

```
Usage: ./ccrtngfc_lio [-b BoardNo] [-c] [-d Delay] [-F DebugFile] [-l LoopCnt]
                      [-M SelectLDioModule] [-n NumChans] [-p PatternSelect]
                      [-r RunOption] [-s SkipChannelsMask]
 -b BoardNo               (Board number -- default is 0)
 -c                       (Switch to Continuous mode -- default is SYNC)
 -d Delay                 (Delay between screen refresh -- default is 100)
 -F DebugFile             (Debug file -- default "=== None ===")
 -l LoopCnt               (Loop count -- default is 0)
 -M SelectLDioModule      (Select LDIO Module -- default is LIO module 1)
 -n NumChans              (number of channels -- default is 32)
 -p PatternSelect         (LDIO mode -- default is to sequence through all patterns)
    -p0                   (Rolling Ones)
    -p1                   (Rolling Zeros)
    -p2                   (Adding Bit)
    -p3                   (Toggling 'A' & '5')
    -p@XXXXXXXX           (Fixed Pattern XXXXXXXX selection in Hex)
 -r RunOption             (Run option -- default is 0)
    -rd                   (Digital Output Isolation Test)
    -rD                   (Fast [no curses] Digital Output Isolation Test)
    -re                   (External Loopback LIO test - Loopback breakout box requried)
    -rE                   (Fast [no curses] external loopback LIO test - Loopback breakout
                           box requried)
    -ri                   (Read LIO input channels)
    -rl                   (Internal Loopback LIO test - No inputs/outputs must be connected)
    -rL                   (Fast [no curses] internal loopback LIO test - No inputs/outputs
                           must be connected)
    -ro                   (Write pattern to LIO output channels)
 -s SkipChannelsMask      (Skip channels mask -- default is @0x00000000)
    -sXXXXXXXX            (LDIO Channels 31..00=XXXXXXXX in Hex)
 e.g. ./ccrtngfc_lio -rl -sf0         (Internal Loopback Testing. Skip LDIO Channels 04-07)
      ./ccrtngfc_lio -rE -sf0         (External Loopback w/o Curses Testing. Skip LDIO
                                       Channels 04-07)
```

Example display:

./ccrtngfc_lio

```
AvalonPtr=0x7ffff7f52000

 Board Number          [-b]: 0
 Output Sync Mode      [-c]: 1 [SYNC]
 Delay                 [-d]: 100 milli-seconds
 LDIO Module           [-M]: 1
 Loop Count            [-l]: ***Forever***
 Number of Channels    [-n]: 32
 Run Option            [-r]: 0 (Digital Input)
 Skip Channels Mask    [-s]: 0x00000000 (31..00)

 LIO Direction             : 0x00       (All Input)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
 LDIO Enable              : 0x00000001 (Enable)
 Input Snapshot           : 0x00000001 (Snapshot)
 Scan Count               : 239

 Read Duration (microsecs) :    3.824 (min=   3.749/max=  13.590/ave=   3.905)

 Channels     Inputs
 ===========  ========
  31..00 [1]: FFFFFFFF

           <------------------------ Input Channels ------------------------>
           [0]    [1]    [2]    [3]    [4]    [5]    [6]    [7]    [8]    [9]
           ===    ===    ===    ===    ===    ===    ===    ===    ===    ===
   [0]     +      +      +      +      +      +      +      +      +      +

   [1]     +      +      +      +      +      +      +      +      +      +

   [2]     +      +      +      +      +      +      +      +      +      +

   [3]     +      +
```

./ccrtngfc_lio -rl

```
AvalonPtr=0x7ffff7f52000

 Board Number          [-b]: 0
 Output Sync Mode      [-c]: 1 [SYNC]
 Delay                 [-d]: 100 milli-seconds
 LDIO Module           [-M]: 1
 Loop Count            [-l]: ***Forever***
 Number of Channels    [-n]: 32
 Pattern Selection     [-p]: 0 (Rolling Ones)
 Run Option            [-r]: 2 (Internal Loopback Test)
 Skip Channels Mask    [-s]: 0x00000000 (31..00)

 Channel Mismatch Count    : 0 (=== Passed ===)
 LIO Direction             : 0xFF       (All Output)
 LDIO Enable               : 0x00000001 (Enable)
 Input Snapshot            : 0x00000001 (Snapshot)
 Scan Count                : 97

 Write Duration (microsecs) :    1.863 (min=   1.833/max=   2.215/ave=   1.898)
 Read  Duration (microsecs) :  198.889 (min= 198.861/max= 216.188/ave= 200.349)

 Channels     Output    Input     Expected
 ===========  ========  ========  ========
  31..00 [1]: 00000001  00000001  00000001

           <------------------------ Input Channels ------------------------>
           [0]    [1]    [2]    [3]    [4]    [5]    [6]    [7]    [8]    [9]
           ===    ===    ===    ===    ===    ===    ===    ===    ===    ===
   [0]     +      .      .      .      .      .      .      .      .      .

   [1]     .      .      .      .      .      .      .      .      .      .

   [2]     .      .      .      .      .      .      .      .      .      .

   [3]     .      .
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

3.2.23 lib/ccrtngfc_msgdma

This test performs a modular scatter-gather DMA test on boards that support it. Additionally, it displays performance information for each mode of operation.

```
Usage: ./ccrtngfc_msgdma [-a AddrOff,ToAddrOff] [-b Board] [-C] [-d NumDesc] [-e MsgDmaEngine]
                         [-f Input,Output] [-i] [-l LoopCnt] [-m Mode] [-s TotalXferSize] [-v]
                         [-X] [-z]
          -a <AddrOff,ToAddrOff> (First Avalon Address Offset, default DiagRam offset)
                                 (Second 'ToAddrOff' only for Avalon2Avalon mode)
          -b <Board>             (board #, default = 0)
          -C                     (Perform Clone mode scatter-gather instead of single-shot)
          -d <NumDesc>           (Number of Descriptors, default = 1)
          -e MsgDmaEngine        (Select MsgDma Engine -- default "=== get free engine ===")
          -f <Input>,<#Output>   (Use input file as input data. default None)
                                 (Use Output file to write 'to' data. default None)
                                 (Prepend with '#' to remove comments and address)
          -i                     (Use interrupts, default is poll)
          -l <LoopCnt>           (Loop Count, default = 1000)
          -m <Mode>              (Mode of Operation, default = all)
             'a2p'               (Avalon memory address to Pci memory address)
             'p2a'               (Pci memory address to Avalon memory address)
             'p2p'               (Pci memory address to Pci memory address)
             'a2a'               (Avalon memory address to Avalon memory address)
             'all'               (All above modes with only memory addresses)

             'A2p'               (Avalon FIFO address to Pci memory address - specify FIFO address '-a')
             'p2A'               (Pci memory address to Avalon FIFO address - specify FIFO address '-a')
             'A2A'               (Avalon FIFO address to Avalon FIFO address - specify FIFO address '-a')
          -s <TotalXferSize>     (Total Transfer Size in bytes, default size of DiagRam)
                                 (Maximum transfer size is 0x3FFFF0)
          -v                     (Verbose operation. default is quiet)
          -X                     (Skip Data Validation, default is to validate)
          -z                     (Zap messages, default is not to zap messages)

Notes:
     1) For modes 'p2a' or 'a2p' only the first address 'AddrOff' is used in option '-a'
     2) For modes 'a2a' the first address 'AddrOff' is "FROM" and second address 'ToAddrOff' is "TO"
     3) If Input file is specified in the '-f' option, its contents is used to seed input
     4) If '-X' option is specified, no pattern is written to input, unless '-f Input' option is
        specified
     5) Multiple '-m' options can be specified on a single command line
     6) When address '-a' option is not specified, DiagRam offset is used for Analog input/output
     7) Normal running process if no arguments specified is as follows:
          a) Incrementing pattern written to the input using programmed I/O and readback validated
          b) Output written with 'baadbeef' pattern using programmed I/O
          c) Scatter-Gather DMA performed from Input to Output
          d) Data is read back from both Input and Output using programmed I/O and compared
     8) An upper case 'A' in the -m option represents an Avalon FIFO address, while
        a lower case 'a' in the -m option represents a regular Avalon memory address
     9) If a regular memory Avalon address is specified as an Avalon FIFO address and vice-versa
        results will be unpredictable
    10) When either input or output Avalon address is pointing to a FIFO, then data validation is
        skipped
    11) If a size is specified for a memory or FIFO address that is greater than it can handle,
        the result
        will be unpredictable. You will need to reset the firmware to restore proper operation

e.g. ./ccrtngfc_msgdma -mall                    (Run all transfer modes with validation)
     ./ccrtngfc_msgdma -a0x8000 -s0x100         (Run all modes with Avalon Address 0x8000 and size 0x100)
     ./ccrtngfc_msgdma -a0xA000 -s0x200 -ma2a   (Run a2a with Avalon Address 0xA000 and size 0x200)
     ./ccrtngfc_msgdma -mp2a -l1 -d1 -fHexFile_16K -a0x10004 -X
                                (Transfer Input file to Avalon memory at 0x10004)
     ./ccrtngfc_msgdma -ma2p -l1 -d1 -f,OutFile -s0x4000 -a0x10004 -X
                                (Transfer Avalon memory at 0x10004 to output file 'OutFile')
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
     ./ccrtngfc_msgdma -mA2p -l10000 -s0x20000 -d16 -a0x18010
                                (Transfer Avalon FIFO at 0x18010 to PCI memory with 16 descriptors
                                 where each descriptor has a transfer size of 0x2000 bytes.
                                 No validation will be performed)
```

Example display:

./ccrtngfc_msgdma

```
### TotalXferSize = 0x00008000, individual descriptor length=0x008000 ###

driver_lib_ptr: 0x7ffff7fde000
    Eng0:     1000: P2P Total: Size 0x8000, Fire=  43.31us/ 756.56MB/s
                    (mi/ma/av:  730.25/ 889.30/ 819.46 MB/s,  36.85/  44.87/  39.99 us)
                    LastWord=0x007cffff
    Eng0:     1000: A2A Total: Size 0x4000, Fire=  84.70us/ 193.42MB/s
                    (mi/ma/av:  183.64/ 194.42/ 193.21 MB/s,  84.27/  89.22/  84.80 us)
                    LastWord=0x003e7fff
    Eng0:     1000: P2A Total: Size 0x8000, Fire=  86.95us/ 376.87MB/s
                    (mi/ma/av:  351.63/ 377.08/ 371.98 MB/s,  86.90/  93.19/  88.09 us)
                    LastWord=0x007cffff
    Eng0:     1000: A2P Total: Size 0x8000, Fire=  86.50us/ 378.84MB/s
                    (mi/ma/av:  360.20/ 383.21/ 378.55 MB/s,  85.51/  90.97/  86.56 us)
                    LastWord=0x007cffff
```

./ccrtngfc_msgdma -e0 -C *(Cloning Option)*

```
### Cloning Option Selected ###
### TotalXferSize = 0x00008000, individual descriptor length=0x008000 ###

driver_lib_ptr: 0x7ffff7fde000
    Eng0:     1000: P2P Total: Size 0x8000, Fire=  35.44us/ 924.68MB/s
                    (mi/ma/av:  814.17/ 926.02/ 924.43 MB/s,  35.39/  40.25/  35.45 us)
                    LastWord=0x007cffff
    Eng0:     1000: A2A Total: Size 0x4000, Fire=  90.39us/ 181.25MB/s
                    (mi/ma/av:  180.58/ 188.83/ 188.69 MB/s,  86.77/  90.73/  86.83 us)
                    LastWord=0x003e7fff
    Eng0:     1000: P2A Total: Size 0x8000, Fire=  83.71us/ 391.43MB/s
                    (mi/ma/av:  369.81/ 391.53/ 391.31 MB/s,  83.69/  88.61/  83.74 us)
                    LastWord=0x007cffff
    Eng0:     1000: A2P Total: Size 0x8000, Fire=  88.34us/ 370.92MB/s
                    (mi/ma/av:  370.87/ 374.50/ 374.28 MB/s,  87.50/  88.35/  87.55 us)
                    LastWord=0x007cffff
```

./ccrtngfc_msgdma -e4

```
### TotalXferSize = 0x00008000, individual descriptor length=0x008000 ###

driver_lib_ptr: 0x7ffff7fde000
Eng4:     1000: P2P Total: Size 0x8000, Fire= 107.70us/ 304.25MB/s
                (mi/ma/av:  290.85/ 306.83/ 304.46 MB/s, 106.80/ 112.66/ 107.63 us)
                LastWord=0x007cffff
Eng4:     1000: A2A Total: Size 0x4000, Fire=  84.90us/ 192.97MB/s
                (mi/ma/av:  183.67/ 194.40/ 192.75 MB/s,  84.28/  89.20/  85.00 us)
                LastWord=0x003e7fff
Eng4:     1000: P2A Total: Size 0x8000, Fire= 107.35us/ 305.24MB/s
                (mi/ma/av:  291.14/ 305.59/ 305.05 MB/s, 107.23/ 112.55/ 107.42 us)
                LastWord=0x007cffff
Eng4:     1000: A2P Total: Size 0x8000, Fire=  86.36us/ 379.43MB/s
                (mi/ma/av:  362.43/ 386.62/ 379.78 MB/s,  84.75/  90.41/  86.28 us)
                LastWord=0x007cffff
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

3.2.24 lib/ccrtngfc_msgdma_clone

Cloning is an optional feature of this card that can be purchased separately. The basic cloning option is an extremely powerful tool that gives the user the ability to continuously transfer the contents of a region on the card to a physical memory entirely under hardware control, once cloning has commenced. This continuous transfer is performed at MsgDma speeds. A more advanced cloning option that can be purchased is known as Region Addressing. This option allows the board to Clone any MsgDma location to another MsgDma location, i.e. the source and destination locations can be any valid MsgDma able physical address in the system.

Only one Cloning or MsgDma operation can be active at a given time. Additionally, it is meaningless to perform Cloning on a FIFO region for two reasons. Firstly, each data in a FIFO is synchronous, however, the Cloned region is accessed asynchronously. Secondly, when the FIFO runs empty *(underflow)* or cannot accept more data *(overflow)* the results are unpredictable.

***Caution**: Since physical addresses are supplied to this test, care must be taken to ensure that the supplied addresses are valid and that while cloning is in progress, the memory regions must not be freed or made inactive, otherwise, the results could be unpredictable and could lead to the possible corruption of the system.*

This test show the capabilities of this new cloning option.

```
Usage: ./ccrtngfc_msgdma_clone [-a FromAddr,ToAddr] [-b Board] [-d Delay] [-e MsgDmaEngine]
                               [-F DebugFile] [-l LoopCnt] [-P] [-q] [-s XferSize]
                               [-S DisplaySize] [-v Delay] [-X] [-Z]
          -a <FromAddr,ToAddr> (Clone address space From/To address in Hex)
                               (If address less than board size, board offset used)
          -b <Board>           (board #, default = 0)
          -d <Delay>           (Delay between screen refresh -- default is 0 milli-seconds)
          -e MsgDmaEngine      (Select MsgDma Engine -- default "=== get free engine ===")
          -F DebugFile         (Debug file -- default "=== None ===")
             @DebugFile        (Debug file and no display)
             @                 (No Debug file and no display)
          -l LoopCnt           (Loop count -- default is 0)
          -P                   (Program Board)
          -q                   (Quite (non-interactive) mode)
          -s <XferSize>        (Transfer size in bytes)
          -S <DisplaySize>     (Display size in bytes)
          -v Delay             (Verify data. Add additional one cycle delay in micro-seconds if
                                specified)
          -X                   (Disable region protection)
          -Z                   (Disable address cache - default is enabled)

e.g.
  ./ccrtngfc_msgdma_clone                          (Clone DiagRam to physical memory created by
                                                    this program)
  ./ccrtngfc_msgdma_clone -a,-1                    (Clone DiagRam to physical memory created by
                                                    this program)
  ./ccrtngfc_msgdma_clone -a-1,-1 -v               (Clone physical memory to physical memory
                                                    created by this program and verify)
  ./ccrtngfc_msgdma_clone -a,c000 -s0x1000 -v      (Clone DiagRam at 0x8000 to board DiagRam at
                                                    0xc000)
  ./ccrtngfc_msgdma_clone -a8000,c000 -s0x4000 -v  (Clone DiagRam at 0x8000 to DiagRam at 0xC000
                                                    and verify)
  ./ccrtngfc_msgdma_clone -a8000,-1 -s0x4000 -v    (Clone DiagRam at 0x8000 to physical memory
                                                    created and verify)
  ./ccrtngfc_msgdma_clone -a-1,8000 -s0x4000 -v    (Clone physical memory created to DiagRam at
                                                    0x8000 and verify)
  ./ccrtngfc_msgdma_clone -a,0xbd308000 -X         (Clone DiagRam to some other board at
                                                    specified physical address)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

Example display:

./ccrtngfc_msgdma_clone -b0

```
Device Name                 : /dev/ccrtngfc0
Board ID                    : 9320
Board Type                  : 01
Board Function              : 01
Board Serial No             : 706503 (0x000ac7c7)
Number of MsgDMA Descriptors: 31

Local Region  (BAR2) Size   : 0x00080000
Local Region  (BAR2) Address: 0xfbe00000
Config Region (BAR0) Size   : 0x00008000
Config Region (BAR0) Address: 0xfbe80000

>>>####### Processing 'From' Address (0x00008000) ######<<<

From_____________________________________
  TranslationRequired         = 0
  UserSuppliedPhysicalAddress = 0x00008000
  AvalonEquivalentAddress     = 0x00008000
  PhysicalMemoryToAttach      = 0xfbe08000
  PhysicalMemorySize          = 0x00004000
  VirtualUserAddress          = 0x7ffff7f5a000
  Flags                       = 0x0000

>>>####### Processing 'To' Address (0xfffffffffffffffc) ######<<<
           Physical Memory Information:
             UserPID            =209014
             PhysMemPtr         =0x65e58000
             DriverVirtMemPtr   =0xffff993ee5e58000
             MmapedUserMemPtr   =0x7ffff7fda000
             PhysMemSize        =0x00004000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =0
             NumOfEntriesUsed   =1
             Flags              =0x0000

To_______________________________________
  TranslationRequired         = 1
  UserSuppliedPhysicalAddress = 0x65e58000
  AvalonEquivalentAddress     = 0x01058000
  PhysicalMemoryToAttach      = 0x65e58000
  PhysicalMemorySize          = 0x00004000
  VirtualUserAddress          = 0x7ffff7fda000
  Flags                       = 0x0000

 Physical Address      [-a]: 0xFBE08000/0x65E58000 (From/To)
 Board Number          [-b]: 0
 Delay                 [-d]: 0       (milli-seconds)
 MSGDMA Engine         [-e]: 0
 Loop Count            [-l]: 0       (forever)
 Program Board         [-P]: 0       (no)
 Quiet Mode            [-q]: 0       (interactive)
 Transfer Size         [-s]: 16384   (bytes)
 Display Size          [-S]: 256     (bytes)
 Verify Data           [-v]: no
 Region Protection     [-X]: 1       (enabled)
 Address Cache         [-Z]: 0       (enabled)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
 One Cycle Time            : 42.953  (micro-seconds)

 From_____________________________________  To_____________________________________
 TranslationRequired      = 0               TranslationRequired      = 1
 UserSuppliedPhysicalAddr = 0x00008000      UserSuppliedPhysicalAddr = 0x65e58000
 AvalonEquivalentAddress  = 0x00008000      AvalonEquivalentAddress  = 0x01058000
 PhysicalMemoryToAttach   = 0xfbe08000      PhysicalMemoryToAttach   = 0x65e58000
 PhysicalMemorySize       = 0x00004000      PhysicalMemorySize       = 0x00004000
 VirtualUserAddress       = 0x7ffff7f5a000  VirtualUserAddress       = 0x7ffff7fda000
 Flags                    = 0x0000          Flags                    = 0x0000

ScanCount=3361       (XferSize=16384, DisplaySize=256) (CopyTime: From 10638.176 usecs,
                      To    3.454 usecs)

___From___   ___00___ ___04___ ___08___ ___0C___ ___10___ ___14___ ___18___ ___1C___
0x00008000  007d0000 007d0001 007d0002 007d0003 007d0004 007d0005 007d0006 007d0007
0x00008020  007d0008 007d0009 007d000a 007d000b 007d000c 007d000d 007d000e 007d000f
0x00008040  007d0010 007d0011 007d0012 007d0013 007d0014 007d0015 007d0016 007d0017
0x00008060  007d0018 007d0019 007d001a 007d001b 007d001c 007d001d 007d001e 007d001f
0x00008080  007d0020 007d0021 007d0022 007d0023 007d0024 007d0025 007d0026 007d0027
0x000080a0  007d0028 007d0029 007d002a 007d002b 007d002c 007d002d 007d002e 007d002f
0x000080c0  007d0030 007d0031 007d0032 007d0033 007d0034 007d0035 007d0036 007d0037
0x000080e0  007d0038 007d0039 007d003a 007d003b 007d003c 007d003d 007d003e 007d003f

____To____   ___00___ ___04___ ___08___ ___0C___ ___10___ ___14___ ___18___ ___1C___
0x65e58000  007d0000 007d0001 007d0002 007d0003 007d0004 007d0005 007d0006 007d0007
0x65e58020  007d0008 007d0009 007d000a 007d000b 007d000c 007d000d 007d000e 007d000f
0x65e58040  007d0010 007d0011 007d0012 007d0013 007d0014 007d0015 007d0016 007d0017
0x65e58060  007d0018 007d0019 007d001a 007d001b 007d001c 007d001d 007d001e 007d001f
0x65e58080  007d0020 007d0021 007d0022 007d0023 007d0024 007d0025 007d0026 007d0027
0x65e580a0  007d0028 007d0029 007d002a 007d002b 007d002c 007d002d 007d002e 007d002f
0x65e580c0  007d0030 007d0031 007d0032 007d0033 007d0034 007d0035 007d0036 007d0037
0x65e580e0  007d0038 007d0039 007d003a 007d003b 007d003c 007d003d 007d003e 007d003f
```

./ccrtngfc_msgdma_clone -e5

```
Device Name                : /dev/ccrtngfc0
Board ID                   : 9320
Board Type                 : 01
Board Function             : 01
Board Serial No            : 706503 (0x000ac7c7)
Number of MsgDMA Descriptors: 31

Local Region  (BAR2) Size   : 0x00080000
Local Region  (BAR2) Address: 0xfbe00000
Config Region (BAR0) Size   : 0x00008000
Config Region (BAR0) Address: 0xfbe80000

>>>####### Processing 'From' Address (0x00008000) ######<<<

From_____________________________________
  TranslationRequired         = 0
  UserSuppliedPhysicalAddress = 0x00008000
  AvalonEquivalentAddress     = 0x00008000
  PhysicalMemoryToAttach      = 0xfbe08000
  PhysicalMemorySize          = 0x00004000
  VirtualUserAddress          = 0x7ffff7f5a000
  Flags                       = 0x0000

>>>####### Processing 'To' Address (0xfffffffffffffffc) ######<<<
           Physical Memory Information:
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
                UserPID            =209761
                PhysMemPtr         =0x65e58000
                DriverVirtMemPtr   =0xffff993ee5e58000
                MmapedUserMemPtr   =0x7ffff7fda000
                PhysMemSize        =0x00004000
                PhysMemSizeFreed   =0x00000000
                EntryInTxTbl       =0
                NumOfEntriesUsed   =1
                Flags              =0x0000

To_____________________________________
  TranslationRequired         = 1
  UserSuppliedPhysicalAddress = 0x65e58000
  AvalonEquivalentAddress     = 0x01058000
  PhysicalMemoryToAttach      = 0x65e58000
  PhysicalMemorySize          = 0x00004000
  VirtualUserAddress          = 0x7ffff7fda000
  Flags                       = 0x0000

 Physical Address      [-a]: 0xFBE08000/0x65E58000 (From/To)
 Board Number          [-b]: 0
 Delay                 [-d]: 0       (milli-seconds)
 MSGDMA Engine         [-e]: 5
 Loop Count            [-l]: 0       (forever)
 Program Board         [-P]: 0       (no)
 Quiet Mode            [-q]: 0       (interactive)
 Transfer Size         [-s]: 16384   (bytes)
 Display Size          [-S]: 256     (bytes)
 Verify Data           [-v]: no
 Region Protection     [-X]: 1       (enabled)
 Address Cache         [-Z]: 0       (enabled)
 One Cycle Time            : 40.358  (micro-seconds)

 From_____________________________________  To_____________________________________
 TranslationRequired      = 0                TranslationRequired      = 1
 UserSuppliedPhysicalAddr = 0x00008000       UserSuppliedPhysicalAddr = 0x65e58000
 AvalonEquivalentAddress  = 0x00008000       AvalonEquivalentAddress  = 0x01058000
 PhysicalMemoryToAttach   = 0xfbe08000       PhysicalMemoryToAttach   = 0x65e58000
 PhysicalMemorySize       = 0x00004000       PhysicalMemorySize       = 0x00004000
 VirtualUserAddress       = 0x7ffff7f5a000   VirtualUserAddress       = 0x7ffff7fda000
 Flags                    = 0x0000           Flags                    = 0x0000

ScanCount=1171       (XferSize=16384, DisplaySize=256) (CopyTime: From 4692.005 usecs,
                      To    3.461 usecs)

___From___   ___00___ ___04___ ___08___ ___0C___ ___10___ ___14___ ___18___ ___1C___
0x00008000  007d0000 007d0001 007d0002 007d0003 007d0004 007d0005 007d0006 007d0007
0x00008020  007d0008 007d0009 007d000a 007d000b 007d000c 007d000d 007d000e 007d000f
0x00008040  007d0010 007d0011 007d0012 007d0013 007d0014 007d0015 007d0016 007d0017
0x00008060  007d0018 007d0019 007d001a 007d001b 007d001c 007d001d 007d001e 007d001f
0x00008080  007d0020 007d0021 007d0022 007d0023 007d0024 007d0025 007d0026 007d0027
0x000080a0  007d0028 007d0029 007d002a 007d002b 007d002c 007d002d 007d002e 007d002f
0x000080c0  007d0030 007d0031 007d0032 007d0033 007d0034 007d0035 007d0036 007d0037
0x000080e0  007d0038 007d0039 007d003a 007d003b 007d003c 007d003d 007d003e 007d003f

____To____   ___00___ ___04___ ___08___ ___0C___ ___10___ ___14___ ___18___ ___1C___
0x65e58000  007d0000 007d0001 007d0002 007d0003 007d0004 007d0005 007d0006 007d0007
0x65e58020  007d0008 007d0009 007d000a 007d000b 007d000c 007d000d 007d000e 007d000f
0x65e58040  007d0010 007d0011 007d0012 007d0013 007d0014 007d0015 007d0016 007d0017
0x65e58060  007d0018 007d0019 007d001a 007d001b 007d001c 007d001d 007d001e 007d001f
0x65e58080  007d0020 007d0021 007d0022 007d0023 007d0024 007d0025 007d0026 007d0027
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
0x65e580a0  007d0028 007d0029 007d002a 007d002b 007d002c 007d002d 007d002e 007d002f
0x65e580c0  007d0030 007d0031 007d0032 007d0033 007d0034 007d0035 007d0036 007d0037
0x65e580e0  007d0038 007d0039 007d003a 007d003b 007d003c 007d003d 007d003e 007d003f
```

./ccrtngfc_msgdma_clone -a8000,-1 -s0x4000 -v

```
Device Name                 : /dev/ccrtngfc0
Board ID                    : 9320
Board Type                  : 01
Board Function              : 01
Board Serial No             : 706503 (0x000ac7c7)
Number of MsgDMA Descriptors: 31

Local Region  (BAR2) Size   : 0x00080000
Local Region  (BAR2) Address: 0xfbe00000
Config Region (BAR0) Size   : 0x00008000
Config Region (BAR0) Address: 0xfbe80000

>>>####### Processing 'From' Address (0x00008000) ######<<<

From_____________________________________
  TranslationRequired         = 0
  UserSuppliedPhysicalAddress = 0x00008000
  AvalonEquivalentAddress     = 0x00008000
  PhysicalMemoryToAttach      = 0xfbe08000
  PhysicalMemorySize          = 0x00004000
  VirtualUserAddress          = 0x7ffff7f5a000
  Flags                       = 0x0000

>>>####### Processing 'To' Address (0xfffffffffffffffc) ######<<<
           Physical Memory Information:
             UserPID            =209765
             PhysMemPtr         =0x65e58000
             DriverVirtMemPtr   =0xffff993ee5e58000
             MmapedUserMemPtr   =0x7ffff7fda000
             PhysMemSize        =0x00004000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =0
             NumOfEntriesUsed   =1
             Flags              =0x0000

To_______________________________________
  TranslationRequired         = 1
  UserSuppliedPhysicalAddress = 0x65e58000
  AvalonEquivalentAddress     = 0x01058000
  PhysicalMemoryToAttach      = 0x65e58000
  PhysicalMemorySize          = 0x00004000
  VirtualUserAddress          = 0x7ffff7fda000
  Flags                       = 0x0000

Additional One Cycle Delay=  0.000 micro-seconds

 Physical Address      [-a]: 0xFBE08000/0x65E58000 (From/To)
 Board Number          [-b]: 0
 Delay                 [-d]: 0       (milli-seconds)
 MSGDMA Engine         [-e]: 0
 Loop Count            [-l]: 0       (forever)
 Program Board         [-P]: 0       (no)
 Quiet Mode            [-q]: 0       (interactive)
 Transfer Size         [-s]: 16384   (bytes)
 Display Size          [-S]: 256     (bytes)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
 Verify Data           [-v]: 0.000   (Additional One Cycle Delay in micro-seconds)
 Region Protection     [-X]: 1       (enabled)
 Address Cache         [-Z]: 0       (enabled)
 One Cycle Time            : 42.865  (micro-seconds)

 From_____________________________________  To_____________________________________
 TranslationRequired      = 0               TranslationRequired      = 1
 UserSuppliedPhysicalAddr = 0x00008000      UserSuppliedPhysicalAddr = 0x65e58000
 AvalonEquivalentAddress  = 0x00008000      AvalonEquivalentAddress  = 0x01058000
 PhysicalMemoryToAttach   = 0xfbe08000      PhysicalMemoryToAttach   = 0x65e58000
 PhysicalMemorySize       = 0x00004000      PhysicalMemorySize       = 0x00004000
 VirtualUserAddress       = 0x7ffff7f5a000  VirtualUserAddress       = 0x7ffff7fda000
 Flags                    = 0x0000          Flags                    = 0x0000

FailCount=0          (==== passed ====)
ScanCount=1784       (XferSize=16384, DisplaySize=256) (WaitAfterPatternWrite:   42.925 usecs)

___From___   ___00___ ___04___ ___08___ ___0C___ ___10___ ___14___ ___18___ ___1C___
0x00008000   006f7000 006f7001 006f7002 006f7003 006f7004 006f7005 006f7006 006f7007
0x00008020   006f7008 006f7009 006f700a 006f700b 006f700c 006f700d 006f700e 006f700f
0x00008040   006f7010 006f7011 006f7012 006f7013 006f7014 006f7015 006f7016 006f7017
0x00008060   006f7018 006f7019 006f701a 006f701b 006f701c 006f701d 006f701e 006f701f
0x00008080   006f7020 006f7021 006f7022 006f7023 006f7024 006f7025 006f7026 006f7027
0x000080a0   006f7028 006f7029 006f702a 006f702b 006f702c 006f702d 006f702e 006f702f
0x000080c0   006f7030 006f7031 006f7032 006f7033 006f7034 006f7035 006f7036 006f7037
0x000080e0   006f7038 006f7039 006f703a 006f703b 006f703c 006f703d 006f703e 006f703f

____To____   ___00___ ___04___ ___08___ ___0C___ ___10___ ___14___ ___18___ ___1C___
0x65e58000   006f7000 006f7001 006f7002 006f7003 006f7004 006f7005 006f7006 006f7007
0x65e58020   006f7008 006f7009 006f700a 006f700b 006f700c 006f700d 006f700e 006f700f
0x65e58040   006f7010 006f7011 006f7012 006f7013 006f7014 006f7015 006f7016 006f7017
0x65e58060   006f7018 006f7019 006f701a 006f701b 006f701c 006f701d 006f701e 006f701f
0x65e58080   006f7020 006f7021 006f7022 006f7023 006f7024 006f7025 006f7026 006f7027
0x65e580a0   006f7028 006f7029 006f702a 006f702b 006f702c 006f702d 006f702e 006f702f
0x65e580c0   006f7030 006f7031 006f7032 006f7033 006f7034 006f7035 006f7036 006f7037
0x65e580e0   006f7038 006f7039 006f703a 006f703b 006f703c 006f703d 006f703e 006f703f
```

3.2.25 lib/ccrtngfc_msgdma_info

This test provides useful modular scatter-gather DMA information for cards that support it.

```
Usage: ./ccrtngfc_msgdma_info [-b Board] [-e MsgDmaEngine] [-l] [-s]
          -b <Board>            (board #, default = 0)
          -e MsgDmaEngine       (Select MsgDma Engine -- default -1)
          -l                    (long format)
          -s                    (Usage Status)

Note! You cannot use both '-s' and '-l' options at the same time
```

Example display:

```
./ccrtngfc_msgdma_info -s
MsgDma Engine 0: ### IN-USE ###
        Pid: 210565
        Tid: 140737353964416
MsgDma Engine 1: ===  FREE  ===
MsgDma Engine 2: ===  FREE  ===
MsgDma Engine 3: ===  FREE  ===
MsgDma Engine 4: ===  FREE  ===
MsgDma Engine 5: ===  FREE  ===
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

./ccrtngfc_msgdma_info

```
driver_lib_ptr: 0x7ffff7fde000

========== MsgDma Engine 0 ==========
MsgDmaOwnerPid                          = 0                   === FREE ===
MsgDmaOwnerTid                          = 0                   === FREE ===
MsgDmaExtDesOneCycleDelay (nanosecs)    = 0
MsgDmaDescriptorBaseOffset              = 0x00005000
MsgDmaTerminatingDescriptorOffset       = 0x000057c0

Driver  MsgDmaDispatcherCsrPtr          = 0xffffaeaec5274000
Driver  MsgDmaPrefetcherCsrPtr          = 0xffffaeaec5274020
Driver  MsgDmaExtendedDescriptorPtr     = 0xffffaeaec5275000
Driver  MsgDmaTerminatingDescriptorPtr = 0xffffaeaec52757c0

Library MsgDmaDispatcherCsrPtr          = 0x7ffff7ff3000
Library MsgDmaPrefetcherCsrPtr          = 0x7ffff7ff3020
Library MsgDmaExtendedDescriptorPtr     = 0x7ffff7ff4000
Library MsgDmaTerminatingDescriptorPtr = 0x7ffff7ff47c0

 ============= Dispatcher (Addr: 4000) ==============
 Status                      = 0x0000000a
 Control                     = 0x0000000c
 ReadFillLevel               = 0x00000000
 WriteFillLevel              = 0x00000000
 ResponseFillLevel           = 0x00000000
 ReadSequenceNumber          = 0x00000001
 WriteSequenceNumber         = 0x00000001

 ============= Prefetcher (Addr: 4020) ==============
 Status                      = 0x00000000
 Control                     = 0x00000000
 NextDescriptorPointer       = 0xbaadbeef00005000 (### Descriptor ID 1 ###)
 DescriptorPollingFrequency = 0x00000000

================================================ Descriptors ================================================
ID  Addr   ReadAddr WritAddr Length Stat Control  SeqN Rbct Wbct Rstr Wstr ActBytXfr NextPtr
==  ====   ======== ======== ====== ==== ======== ==== ==== ==== ==== ==== ========= ====================
 1 (5000): 00008000 0000c000 004000 0000 80000000 0001 00   00   0000 0000 00000000  000057c0 (Terminator)
 2 (5040): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
 3 (5080): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
 4 (50c0): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
 5 (5100): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
 6 (5140): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
 7 (5180): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
 8 (51c0): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
 9 (5200): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
10 (5240): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
11 (5280): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
12 (52c0): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
13 (5300): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
14 (5340): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
15 (5380): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
16 (53c0): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
17 (5400): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
18 (5440): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
19 (5480): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
20 (54c0): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
21 (5500): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
22 (5540): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
23 (5580): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
24 (55c0): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
25 (5600): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
26 (5640): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
27 (5680): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
28 (56c0): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
29 (5700): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
30 (5740): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
31 (5780): 00000000 00000000 000000 0000 00000000 0000 00   00   0000 0000 00000000  00000000
```

./ccrtngfc_msgdma_info -l

```
driver_lib_ptr: 0x7ffff7fde000

========== MsgDma Engine 0 ==========
MsgDmaOwnerPid                          = 0                   === FREE ===
MsgDmaOwnerTid                          = 0                   === FREE ===
MsgDmaExtDesOneCycleDelay (nanosecs)    = 0
MsgDmaDescriptorBaseOffset              = 0x00005000
MsgDmaTerminatingDescriptorOffset       = 0x000057c0

Driver  MsgDmaDispatcherCsrPtr          = 0xffffaeaec5274000
Driver  MsgDmaPrefetcherCsrPtr          = 0xffffaeaec5274020
Driver  MsgDmaExtendedDescriptorPtr     = 0xffffaeaec5275000
Driver  MsgDmaTerminatingDescriptorPtr = 0xffffaeaec52757c0

Library MsgDmaDispatcherCsrPtr          = 0x7ffff7ff3000
Library MsgDmaPrefetcherCsrPtr          = 0x7ffff7ff3020
Library MsgDmaExtendedDescriptorPtr     = 0x7ffff7ff4000
Library MsgDmaTerminatingDescriptorPtr = 0x7ffff7ff47c0

 ============= Dispatcher (Addr: 4000) ==============
 Status                      = 0x0000000a
 Control                     = 0x0000000c
 ReadFillLevel               = 0x00000000
 WriteFillLevel              = 0x00000000
 ResponseFillLevel           = 0x00000000
 ReadSequenceNumber          = 0x00000001
 WriteSequenceNumber         = 0x00000001

 ============= Prefetcher (Addr: 4020) ==============
 Status                      = 0x00000000
 Control                     = 0x00000000
 NextDescriptorPointer       = 0xbaadbeef00005000 (### Descriptor ID 1 ###)
 DescriptorPollingFrequency = 0x00000000

 ============ Descriptor ID 1 (address: 0x5000) =============
 ReadAddress                 = 0x0000000000008000
 WriteAddress                = 0x000000000000c000
 NextDescriptorPointer       = 0x00000000000057c0 (### Terminator ###)
 Status                      = 0x0000
 Control                     = 0x80000000
 Length                      = 0x00004000 (16384)
 SequenceNumber              = 0x0001     (1)
 ReadBurstCount              = 0x00       (0)
 WriteBurstCount             = 0x00       (0)
 ReadStride                  = 0x0000     (0)
 WriteStride                 = 0x0000     (0)
 ActualBytesTransferred      = 0x00000000 (0)

 ============ Descriptor ID 2 (address: 0x5040) =============
 ReadAddress                 = 0x0000000000000000
 WriteAddress                = 0x0000000000000000
 NextDescriptorPointer       = 0x0000000000000000
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
 Status                     = 0x0000
 Control                    = 0x00000000
 Length                     = 0x00000000 (0)
 SequenceNumber             = 0x0000     (0)
 ReadBurstCount             = 0x00       (0)
 WriteBurstCount            = 0x00       (0)
 ReadStride                 = 0x0000     (0)
 WriteStride                = 0x0000     (0)
 ActualBytesTransferred     = 0x00000000 (0)
.
.
.
============ Descriptor ID 30 (address: 0x5740) =============
 ReadAddress                = 0x0000000000000000
 WriteAddress               = 0x0000000000000000
 NextDescriptorPointer      = 0x0000000000000000
 Status                     = 0x0000
 Control                    = 0x00000000
 Length                     = 0x00000000 (0)
 SequenceNumber             = 0x0000     (0)
 ReadBurstCount             = 0x00       (0)
 WriteBurstCount            = 0x00       (0)
 ReadStride                 = 0x0000     (0)
 WriteStride                = 0x0000     (0)
 ActualBytesTransferred     = 0x00000000 (0)

 ============ Descriptor ID 31 (address: 0x5780) =============
 ReadAddress                = 0x0000000000000000
 WriteAddress               = 0x0000000000000000
 NextDescriptorPointer      = 0x0000000000000000
 Status                     = 0x0000
 Control                    = 0x00000000
 Length                     = 0x00000000 (0)
 SequenceNumber             = 0x0000     (0)
 ReadBurstCount             = 0x00       (0)
 WriteBurstCount            = 0x00       (0)
 ReadStride                 = 0x0000     (0)
 WriteStride                = 0x0000     (0)
 ActualBytesTransferred     = 0x00000000 (0)
```

3.2.26 lib/ccrtngfc_msgdma_multi_clone

This test is a more powerful version of the *ccrtngfc_msgdma_clone* test above. It allows the users to specify multiple source and destination addresses during the cloning operation. There is a limit on the number of physical memory that can be created or mapped. When that limit is reached, the tests fail to run. Additionally, there is a limit to the number ofMsgDmadescriptors that can be specified. Once again, if that limit is exceed the test will fail to run.

***Caution**: Since physical addresses are supplied to this test, care must be taken to ensure that the supplied addresses are valid and that while cloning is in progress, the memory regions must not be freed or made inactive, otherwise, the results could be unpredictable and could lead to the possible corruption of the system.*

```
Usage: ./ccrtngfc_msgdma_multi_clone [-a FromAddr,ToAddr,Size] [-b Board] [-d Delay]
                                     [-e MsgDmaEngine] [-F DebugFile] [-l LoopCnt]
                                     [-M SelectAdcModule] [-P] [-q] [-s XferSize]
                                     [-S DisplaySize] [-t|T FromAddr,Size,ClockFreq] [-X] [-Z]
          -a <FromAddr,ToAddr,Size>    (Clone address space From/To address (hex) and size (bytes))
                                       (If address less than board size, board offset used)
          -b <Board>                   (board #, default = 0)
          -d <Delay>                   (Delay between screen refresh -- default is 5 milli-seconds)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
          -e MsgDmaEngine              (Select MsgDma Engine -- default "=== get free engine ===")
          -F DebugFile                 (Debug file -- default "=== None ===")
             @DebugFile                (Debug file and no curses display)
             @                         (No Debug file and no curses display)
          -l LoopCnt                   (Loop count -- default is 0)
          -M SelectAdcModule           (Select ADC Module -- default is module 0)
          -P                           (Program Board)
          -q                           (Quite (non-interactive) mode)
          -s <XferSize>                (Transfer size in bytes)
          -S <DisplaySize>             (Display size in bytes)
          -t <FromAddr,Size,ClockFreq> (Perform debug firmware testing - From address (hex), size
                                        (samples) and clock freq. - non-verbose)
          -T <FromAddr,Size,ClockFreq> (Perform debug firmware testing - From address (hex), size
                                        (samples) and clock freq. - verbose)
          -X                           (Disable region protection)
          -Z                           (Disable address cache - default is enabled)

Note: If the size is not specifed in the '-a' option, then the default size or that specifed in the
'-s' option is used
      If debug firmware is installed, you can use the '-t|T' option
      The debug firmware uses Clock 3 and its value is programmed by the 't|T' option

e.g.
  ./ccrtngfc_msgdma_multi_clone                          (Clone DiagRam to physical memory created
                                                          by this program)
  ./ccrtngfc_msgdma_multi_clone -a,-1                    (Clone DiagRam to physical memory created
                                                          by this program)
  ./ccrtngfc_msgdma_multi_clone -a-1,-1                  (Clone physical memory to physical memory
                                                          created by this program)
  ./ccrtngfc_msgdma_multi_clone -a,c000 -s0x1000         (Clone DiagRam at 0x8000 to board DiagRam
                                                          at 0xc000)
  ./ccrtngfc_msgdma_multi_clone -a8000,c000 -s0x4000     (Clone DiagRam at 0x8000 to DiagRam at
                                                          0xC000)
  ./ccrtngfc_msgdma_multi_clone -a,0xbd308000 -X         (Clone DiagRam to some other board at
                                                          specified physical address)
  ./ccrtngfc_msgdma_multi_clone -a8000,8800 -a8800,9000 -a9000,9800 -a9800,a000 -aa000,a800
                                -aa800,b000 -ab000,b800 -ab800,c000 -ac000,c800 -s256
                                                         (Clone through all 9 descriptors)
  ./ccrtngfc_msgdma_multi_clone -a8000,8800 -a8800,9000 -a9000,9800 -a9800,a000,128 -aa000,a800
                               -aa800,b000 -ab000,b800 -ab800,c000 -ac000,c800,288 -s256 -S288
                                                         (Clone through all 9 descriptors with
                                                          different sizes)
  ./ccrtngfc_msgdma_multi_clone -t                       (Perform non-verbose Debug Firmware
                                                          testing using default address 0x6000
                                                          and size 64 samples (256 bytes) with
                                                          default Clock Frequency)
  ./ccrtngfc_msgdma_multi_clone -T,256 -F/tmp/LOG        (Perform verbose Debug Firmware testing
                                                          using default address, 256 bytes and
                                                          send output to /tmp/LOG with default
                                                          Clock Frequency)
  ./ccrtngfc_msgdma_multi_clone -T,,450000 -F/tmp/LOG    (Perform verbose Debug Firmware testing
                                                          using default address and size and send
                                                          output to /tmp/LOG with 450000 SPS
                                                          Clock)
```

Example display:

./ccrtngfc_msgdma_multi_clone

```
Device Name                : /dev/ccrtngfc0
Board ID                   : 9320
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
Board Type                  : 01
Board Function              : 01
Board Serial No             : 706503 (0x000ac7c7)
Number of MsgDMA Descriptors: 31

Local Region  (BAR2) Size   : 0x00080000
Local Region  (BAR2) Address: 0xfbe00000
Config Region (BAR0) Size   : 0x00008000
Config Region (BAR0) Address: 0xfbe80000

>>>####### Processing 'From' Address (0x00008000) ######<<<

From_____________________________________
  TranslationRequired         = 0
  UserSuppliedPhysicalAddress = 0x00008000
  UserSuppliedSize            = 0x00004000
  AvalonEquivalentAddress     = 0x00008000
  PhysicalMemoryToAttach      = 0xfbe08000
  PhysicalMemorySize          = 0x00004000
  VirtualUserAddress          = 0x7ffff7f5a000

>>>####### Creating Physical Memory of size (0x00004000) for 'To' Address ######<<<
           Physical Memory Information:
             UserPID            =228731
             PhysMemPtr         =0x65e58000
             DriverVirtMemPtr   =0xffff993ee5e58000
             MmapedUserMemPtr   =0x7ffff7fda000
             PhysMemSize        =0x00004000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =0
             NumOfEntriesUsed   =1
             Flags              =0x0000

To_______________________________________
  TranslationRequired         = 1
  UserSuppliedPhysicalAddress = 0x65e58000
  UserSuppliedSize            = 0x00004000
  AvalonEquivalentAddress     = 0x01058000
  PhysicalMemoryToAttach      = 0x65e58000
  PhysicalMemorySize          = 0x00004000
  VirtualUserAddress          = 0x7ffff7fda000

 Physical Address      [-a]: 0xFBE08000/0x65E58000 (From/To)
 Board Number          [-b]: 0
 Delay                 [-d]: 5       (milli-seconds)
 MSGDMA Engine         [-e]: 0
 Loop Count            [-l]: 0       (forever)
 Program Board         [-P]: 0       (no)
 Quiet Mode            [-q]: 0       (interactive)
 Transfer Size         [-s]: 16384   (bytes)
 Display Size          [-S]: 256     (bytes)
 Region Protection     [-X]: 1       (enabled)
 Address Cache         [-Z]: 0       (enabled)
 One Cycle Time            : 42.944  (micro-seconds)
 Current Descriptor        : 0

 From_____________________________________  To_____________________________________
 TranslationRequired      = 0               TranslationRequired      = 1
 UserSuppliedPhysicalAddr = 0x00008000      UserSuppliedPhysicalAddr = 0x65e58000
 UserSuppliedSize         = 0x00004000      UserSuppliedSize         = 0x00004000
 AvalonEquivalentAddress  = 0x00008000      AvalonEquivalentAddress  = 0x01058000
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
 PhysicalMemoryToAttach   = 0xfbe08000      PhysicalMemoryToAttach   = 0x65e58000
 PhysicalMemorySize       = 0x00004000      PhysicalMemorySize       = 0x00004000
 VirtualUserAddress       = 0x7ffff7f5a000  VirtualUserAddress       = 0x7ffff7fda000
 Flags                    = 0x0000          Flags                    = 0x0000

ScanCount=534        (XferSize=16384, DisplaySize=256) (CopyTime: From 10639.312 usec,
                      To    3.478 usec)

___From___   ___00___ ___04___ ___08___ ___0C___ ___10___ ___14___ ___18___ ___1C___
0x00008000  00049000 00049001 00049002 00049003 00049004 00049005 00049006 00049007
0x00008020  00049008 00049009 0004900a 0004900b 0004900c 0004900d 0004900e 0004900f
0x00008040  00049010 00049011 00049012 00049013 00049014 00049015 00049016 00049017
0x00008060  00049018 00049019 0004901a 0004901b 0004901c 0004901d 0004901e 0004901f
0x00008080  00049020 00049021 00049022 00049023 00049024 00049025 00049026 00049027
0x000080a0  00049028 00049029 0004902a 0004902b 0004902c 0004902d 0004902e 0004902f
0x000080c0  00049030 00049031 00049032 00049033 00049034 00049035 00049036 00049037
0x000080e0  00049038 00049039 0004903a 0004903b 0004903c 0004903d 0004903e 0004903f

____To____   ___00___ ___04___ ___08___ ___0C___ ___10___ ___14___ ___18___ ___1C___
0x65e58000  00049000 00049001 00049002 00049003 00049004 00049005 00049006 00049007
0x65e58020  00049008 00049009 0004900a 0004900b 0004900c 0004900d 0004900e 0004900f
0x65e58040  00049010 00049011 00049012 00049013 00049014 00049015 00049016 00049017
0x65e58060  00049018 00049019 0004901a 0004901b 0004901c 0004901d 0004901e 0004901f
0x65e58080  00049020 00049021 00049022 00049023 00049024 00049025 00049026 00049027
0x65e580a0  00049028 00049029 0004902a 0004902b 0004902c 0004902d 0004902e 0004902f
0x65e580c0  00049030 00049031 00049032 00049033 00049034 00049035 00049036 00049037
0x65e580e0  00049038 00049039 0004903a 0004903b 0004903c 0004903d 0004903e 0004903f

Enter 'c|C' to clear the pattern
      'w|W' toggle pattern write  (Pattern Write Disabled)
      'q|Q' ->
```

3.2.27 lib/ccrtngfc_sdc

This test controls and displays the Serial Digital I/O daughter card. Run option other than '-rd' will test the card. If no control option is specified, the test will display the current settings of the SDC.

```
Usage: ./ccrtngfc_sdc [-b BoardNo] [-d Delay] [-l LoopCnt] [-L Turnaround]
                      [-M SelectSdcModule] [-P TransmitterPower] [-r RunOution] [-R]
                      [-T Terminator] [-w Transmitter] [-z]
 -b <BoardNo>          (BoardNo #, default = 0)
 -d Delay              (Delay between screen refresh -- default is 0 milli-seconds)
 -l LoopCnt            (Loop count -- default is 0)
 -L Turnaround         (Set Turnaround Loopback state)
 -M SelectSdcModule    (Select SDC Module -- default is module 0)
 -P TransmitterPower   (Set transmitter power ON/OFF (1/0) state)
 -r RunOption          (Run option -- default is 0)
    -rd                (Display SDC)
    -re                (External loopback DIO test - Loopback breakout box required)
    -rE                (Fast [no curses] external loopback DIO test - Loopback
                        breakout box requried)
    -rl                (Internal loopback DIO test - No inputs/outputs must be
                        connected)
    -rL                (Fast [no curses] internal loopback DIO test - No
                        inputs/outputs must be connected)
    -rt                (Digital terminators test)
    -rT                (Fast [no curses] digital terminators test)
 -R                    (reset SDC)
 -T Terminator         (Set Terminator ON/OFF (1/0) state)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
 -w Transmitter        (Write to transmitter NULL/HIGH/LOW (0/1/2) state)
 -z                    (Toggle Turn-Around During Testing -- default is not to
                        toggle)

 e.g. ./ccrtngfc_sdc               (Display SDC information)
      ./ccrtngfc_sdc -P 1          (turn ON transmitter power for all channels)
      ./ccrtngfc_sdc -P 1,0,1,0    (turn ON transmitter power for 0 & 2 and OFF for
                                    1 & 3 channels)
      ./ccrtngfc_sdc -P ,1,,1,     (turn ON transmitter power for 1 & 3 only)
      ./ccrtngfc_sdc -T ,1,1       (turn ON terminator for 1, 2 & 3 only)
      ./ccrtngfc_sdc -L ,1,1,,     (turn ON loopback for 1 & 2 only)
      ./ccrtngfc_sdc -w 1,2,1,0    (write 1,2,1,0 to transmitter channels 0,1,2,3)
```

3.2.28 lib/ccrtngfc_sensors

This test displays the various Power Module sensors and also allows to clear the faults and reset peak values.

```
Usage: ./ccrtngfc_sensors -[b Board] [-c Command] [-d Delay]
          -b <board>      (board #, default = 0)
          -c Command      (Commands [f,p])
             f            (Clear Faults)
             p            (Clear Peak Values)
          -d Delay        (Delay between screen refresh -- default is 1000)
```

Example display:

./ccrtngfc_sensor

```
               Board Number (-b):  0
                      Delay (-d):  1000 milli-seconds

             Board Serial Number:  720334
           FPGA Chip Temperature:  38.2 degree C  (100.7 degree F)
       FPGA Chip Temperature HWM:  38.9 degree C  (102.0 degree F)
       FPGA Chip Voltage (1.8VS):  1.76 Volts
       FPGA Chip Voltage (3.3VS):  3.28 Volts
         FPGA Chip Voltage (VCC):  0.90 Volts
        FPGA Chip Voltage (VCCP):  0.90 Volts
       FPGA Chip Voltage (VCCPT):  1.80 Volts
     FPGA Chip Voltage (VCCERAM):  0.90 Volts
    FPGA Chip Voltage (VCCL_HPS):  0.00 Volts
      FPGA Chip Voltage (ADCGND):  0.00 Volts
FPGA Chip Temp Monitor Debugging:  == Disabled ==
   FPGA Chip Temperature Monitor:  60 Seconds
  FPGA Chip Temp Monitor Warning:  80 degree C
 FPGA Chip Temp Monitor Critical:  100 degree C

 Power Module Information        PM Module 0              PM Module 1
 ============================  ==================     ==================
            Input Supply Voltage:    11.89062 Volts          11.89062 Volts
                  Output Voltage:     0.89990 Volts           0.89966 Volts
                  Output Current:     1.03320 Amps            0.98828 Amps
              Output Temperature:    33.68750 Degree C       33.43750 Degree C
                 DIE Temperature:    41.87500 Degree C       41.87500 Degree C
                   PWM Frequency:   352.00000 KHz          351.00000 KHz
                    Output Power:     0.93066 Watts           0.88965 Watts
             Peak Output Current:     1.44727 Amps            1.41992 Amps
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

3.2.29 lib/ccrtngfc_smp_affinity

This test provides a useful mechanism to display or set the IRQ to specific set of CPUs. This is useful when we want to make sure that the driver interrupts are not being interfered with other CPU activity.

```
Usage: ./ccrtngfc_smp_affinity [-b Board] [-c CpuMask]
 -b Board           (Board number -- default is 0)
 -c CpuMask         (CPU mask in HEX -- default is none)

 e.g. ./ccrtngfc_smp_affinity        (display IRQ CPU mask for selected board)
      ./ccrtngfc_smp_affinity -c2    (set IRQ CPU for cpu 1)
      ./ccrtngfc_smp_affinity -c4    (set IRQ CPU for cpu 2)
      ./ccrtngfc_smp_affinity -c0x8  (set IRQ CPU for cpu 3)
      ./ccrtngfc_smp_affinity -cE2   (set IRQ CPU for cpu 1,5,6,7)
```

Example display:

./ccrtngfc_smp_affinity
(IRQ57) fc user f8 actual

./ccrtngfc_smp_affinity -b1 -c8
(IRQ57) 08 user 08 actual

3.2.30 lib/ccrtngfc_transfer

This test performs various DMA and Programmed I/O transfers between the board components and the PCI memory.

```
Usage: ./ccrtngfc_transfer [-b Board] [-c CaseNum] [-e MsgDmaEngine] [-i] [-l LoopCnt]
                           [-M SelectAdcModule] [-s XferSize]
 -b Board                (Board number -- default is 0)
 -c CaseNum              (Select Case Numbers -- default = ALL CASES)
    -c 4,1,7-9            select case 1,4,7,8,9)
    -c 8-                 select case 8 to end)
    -c -3                 select case 1,2,3)
 -e MsgDmaEngine         (Select MsgDma Engine -- default "=== get free engine ===")
 -i                      (Enable Interrupts -- default = Disable)
 -l LoopCnt              (Loop Count -- default is 100)
 -M SelectAdcModule      (Select ADC Module -- default is module 0)
 -s XferSize             (Avalon Ram Xfer Size in bytes -- default is 32768)
```

Example display:

./ccrtngfc_transfer (for cards with modular scatter-gather DMA support)

```
local_ptr=0x7ffff7f55000

Size of Avalon RAM = 32768 (0x00008000)
           Physical Memory Information:
             UserPID            =324135
             PhysMemPtr         =0x65e78000
             DriverVirtMemPtr   =0xffff993ee5e78000
             MmapedUserMemPtr   =0x7ffff7f4d000
             PhysMemSize        =0x00008000
             PhysMemSizeFreed   =0x00000000
             EntryInTxTbl       =0
             NumOfEntriesUsed   =1
             Flags              =0x0000

  1: Memory -> Avalon RAM (MSGDMA) (Size=0x8000):               100 (  89.74 us,  365.15 MBytes/Sec)
  2: Memory -> Avalon RAM  (PIO) (Size=0x8000):                 100 ( 478.34 us,   68.50 MBytes/Sec)
  3: Avalon RAM -> Memory (MSGDMA) (Size=0x8000):               100 (  88.50 us,  370.25 MBytes/Sec)
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
  4: Avalon RAM -> Memory  (PIO) (Size=0x8000):                  100 (6566.20 us,    4.99 MBytes/Sec)
  5: Memory -> Avalon ADC Calibration  (PIO) (Size=0x30):       10000 (   0.07 us,  727.27 MBytes/Sec)
  6: Avalon ADC Calibration -> Memory  (PIO) (Size=0x30):       10000 (  12.72 us,    3.77 MBytes/Sec)
**** Test Passed ****
```

3.2.31 lib/ccrtngfc_tst_lib

This is an interactive test that accesses the various supported API calls.

```
Usage: ./ccrtngfc_tst_lib [-b Board] [-M SelectModule]
 -b Board           (Board number -- default board is 0)
 -M SelectModule    (Select Module -- default is all available modules)
```

Example display:

./ccrtngfc_tst_lib

```
Device Name: /dev/ccrtngfc0
=================================== Module Information ===================================
  Module Number 0: ADC Id= 1579321.901: SN#= 729514 (High Speed Analog Daughter Card)
==========================================================================================

=================================== Module Information ===================================
  Module Number 1: ADC Id= 1579321.901: SN#= 729512 (High Speed Analog Daughter Card)
==========================================================================================

=================================== Module Information ===================================
  Module Number 0: DAC Id= 1579321.901: SN#= 729514 (High Speed Analog Daughter Card)
==========================================================================================

=================================== Module Information ===================================
  Module Number 1: DAC Id= 1579321.901: SN#= 729512 (High Speed Analog Daughter Card)
==========================================================================================

  01 = Clear Driver Error                        02 = Clear Library Error
  03 = Display BOARD Registers                   04 = Display CONFIG Registers
  05 = Dump Physical Memory List                 06 = Get All Boards Driver Information
  07 = Get Board CSR                             08 = Get Board Information
  09 = Get Driver Error                          10 = Get Driver Information
  11 = Get Library Error                         12 = Get Mapped Config Pointer
  13 = Get Mapped Driver/Library Pointer         14 = Get Mapped Local Pointer
  15 = Get Physical Memory                       16 = Get Power Module Information
  17 = Get Value                                 18 = Initialize Board
  19 = MMap Physical Memory                      20 = Munmap Physical Memory
  21 = Reload Firmware                           22 = Reset Board
  23 = Set Board CSR                             24 = Set Value
  25 = ### ADC MENU ###                          26 = ### CALIBRATION MENU ###
  27 = ### CLOCK GENERATOR MENU ###              28 = ### DAC MENU ###
  29 = ### INTERRUPT MENU ###                    30 = ### IP CORE MENU ###
  31 = ### LDIO MENU ###                         32 = ### SDC MENU ###

Main Selection ('h'=display menu, 'q'=quit)->
_____________________________________________________________________________________
Main Selection ('h'=display menu, 'q'=quit)-> 25
   Command: ADC_menu()
  01 = -- ADC Activate                           02 = -- ADC Clear FIFO Interrupt Status
  03 = -- ADC Close                              04 = -- ADC Disable
  05 = -- ADC Driver Read Operation              06 = -- ADC Get Calibration Bus CSR
  07 = -- ADC Get CSR                            08 = -- ADC Get Driver Read Mode
  09 = -- ADC Get FIFO Channel Select            10 = -- ADC Get FIFO Information
  11 = -- ADC Get FIFO Threshold                 12 = -- ADC Get Information
  13 = -- ADC Get FIFO Interrupt Status          14 = -- ADC Get Interrupt Timeout Seconds
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
  15 = -- ADC Get Power Up Status               16 = -- ADC Get Test Bus Control
  17 = -- ADC Get Value                         18 = -- ADC Open
  19 = -- ADC Read Channels                     20 = -- ADC Reset (disable followed by enable)
  21 = -- ADC Reset FIFO                        22 = -- ADC Set Calibration Bus CSR
  23 = -- ADC Set CSR                           24 = -- ADC Set Driver Read Mode
  25 = -- ADC Set FIFO Channel Select           26 = -- ADC Set FIFO Threshold
  27 = -- ADC Set Interrupt Timeout Seconds     28 = -- ADC Set Test Bus Control
  29 = -- ADC Set Value

ADC Selection ('h'=display menu, 'q'=quit)->
_____________________________________________________________________________
Main Selection ('h'=display menu, 'q'=quit)-> 26
   Command: calibration_menu()
  01 = -- ADC: Get Negative Calibration         02 = -- ADC: Get Offset Calibration
  03 = -- ADC: Get Positive Calibration         04 = -- ADC: Perform Auto Calibration
  05 = -- ADC: Perform External Negative Calib. 06 = -- ADC: Perform External Offset Calib.
  07 = -- ADC: Perform External Positive Calib. 08 = -- ADC: Perform Negative Calibration
  09 = -- ADC: Perform Offset Calibration       10 = -- ADC: Perform Positive Calibration
  11 = -- ADC: Read Channels Calibration        12 = -- ADC: Reset Calibration
  13 = -- ADC: Write Channels Calibration       14 = -- DAC: Get Negative Calibration
  15 = -- DAC: Get Offset Calibration           16 = -- DAC: Get Positive Calibration
  17 = -- DAC: Perform Auto Calibration         18 = -- DAC: Perform Negative Calibration
  19 = -- DAC: Perform Offset Calibration       20 = -- DAC: Perform Positive Calibration
  21 = -- DAC: Read Channels Calibration        22 = -- DAC: Reset Calibration
  23 = -- DAC: Write Channels Calibration

Calibration Selection ('h'=display menu, 'q'=quit)->
_____________________________________________________________________________
Main Selection ('h'=display menu, 'q'=quit)-> 27
   Command: clock_generator_menu()
  01 = Clock Get Generator CSR                  02 = Clock Get Generator Dividers
  03 = Clock Get Generator Information          04 = Clock Get Generator Input Clock Enable
  05 = Clock Get Generator Input Clock Select   06 = Clock Get Generator Input Clock Status
  07 = Clock Get Generator Output Config        08 = Clock Get Generator Output Format
  09 = Clock Get Generator Output Mode          10 = Clock Get Generator Output Mux
  11 = Clock Get Generator P-Divider Enable     12 = Clock Get Generator Revision
  13 = Clock Get Generator Value                14 = Clock Get Generator Voltage Select
  15 = Clock Get Generator Zero Delay           16 = Clock Get PLL CSR
  17 = Clock Set Generator CSR                  18 = Clock Set Generator Dividers
  19 = Clock Set Generator Input Clock Enable   20 = Clock Set Generator Input Clock Select
  21 = Clock Set Generator Output Config        22 = Clock Set Generator Output Format
  23 = Clock Set Generator Output Mode          24 = Clock Set Generator Output Mux
  25 = Clock Set Generator P-Divider Enable     26 = Clock Set Generator Value
  27 = Clock Set Generator Voltage Select       28 = Clock Set Generator Zero Delay
  29 = Clock Set PLL CSR                        30 = Compute All Output Clocks
  31 = Program All Output Clocks                32 = Read Clock Registers
  33 = Reset Clock (Hardware)                   34 = Soft Reset
  35 = Update Clock Generator Divider           36 = Write Clock Registers
Clock Generator Selection ('h'=display menu, 'q'=quit)->
_____________________________________________________________________________
Main Selection ('h'=display menu, 'q'=quit)-> 28
   Command: DAC_menu()
  01 = -- DAC Activate                          02 = -- DAC Clear FIFO Interrupt Status
  03 = -- DAC Close                             04 = -- DAC Disable
  05 = -- DAC Driver Write Operation            06 = -- DAC Get CSR
  07 = -- DAC Get Driver Write Mode             08 = -- DAC Get FIFO Channel Select
  09 = -- DAC Get FIFO Information              10 = -- DAC Get FIFO Threshold
  11 = -- DAC Get FIFO Write Count              12 = -- DAC Get Information
  13 = -- DAC Get FIFO Interrupt Status         14 = -- DAC Get Interrupt Timeout Seconds
  15 = -- DAC Get Power Up Status               16 = -- DAC Get Speed Mode
  17 = -- DAC Get Update Source Select          18 = -- DAC Get Value
  19 = -- DAC Open                              20 = -- DAC ReadBack Channels
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
  21 = -- DAC Read Channels                     22 = -- DAC Reset (disable followed by enable)
  23 = -- DAC Reset FIFO                        24 = -- DAC Set CSR
  25 = -- DAC Set Driver Write Mode             26 = -- DAC Set FIFO Channel Select
  27 = -- DAC Set FIFO Threshold                28 = -- DAC Set FIFO Write Count
  29 = -- DAC Set Interrupt Timeout Seconds     30 = -- DAC Set Speed Mode
  31 = -- DAC Set Update Source Select          32 = -- DAC Set Value
  33 = -- DAC Write Channels

DAC Selection ('h'=display menu, 'q'=quit)->
_____________________________________________________________________________
Main Selection ('h'=display menu, 'q'=quit)-> 29
   Command: interrupt_menu()
  01 = Add Irq                                  02 = Clear Interrupt Status
  03 = Disable Pci Interrupts                   04 = Enable Pci Interrupts
  05 = Get Interrupt Status                     06 = Get Interrupt Timeout
  07 = Remove Irq                               08 = Set Interrupt Timeout

Interrupt Selection ('h'=display menu, 'q'=quit)->
_____________________________________________________________________________
Main Selection ('h'=display menu, 'q'=quit)-> 30
   Command: IPCORE_menu()
  01 = IpCore Get Ip Information                02 = IpCore Get Ip Mapped Pointer

IP Core Selection ('h'=display menu, 'q'=quit)->
_____________________________________________________________________________
Main Selection ('h'=display menu, 'q'=quit)-> 31
   Command: LDIO_menu()
  01 = DIO Get Channels Terminator              02 = DIO Get Ports Direction
  03 = DIO Set Channels Terminator              04 = DIO Set Channels Terminator to Off
  05 = DIO Set Channels Terminator to On        06 = DIO Set Ports Direction
  07 = DIO Set Ports Direction to Inputs        08 = DIO Set Ports Direction to Outputs
  09 = LDIO Activate                            10 = LDIO Disable
  11 = LDIO Get Channels Polarity               12 = LDIO Get COS Channels Edge Sense
  13 = LDIO Get COS Channels Enable             14 = LDIO Get COS Channels Mode
  15 = LDIO Get COS Channels Overflow           16 = LDIO Get COS Channels Status
  17 = LDIO Get Input Channels Filter           18 = LDIO Get Input Snapshot
  19 = LDIO Get Output Sync                     20 = LDIO Information
  21 = LDIO Read Input Channels                 22 = LDIO Read Output Channels
  23 = LDIO Reset (disable followed by enable)  24 = LDIO Set Channels Polarity
  25 = LDIO Set COS Channels Edge Sense         26 = LDIO Set COS Channels Enable
  27 = LDIO Set COS Channels Mode               28 = LDIO Set Input Channels Filter
  29 = LDIO Set Input Snapshot                  30 = LDIO Set Output Sync
  31 = LDIO Write Output Channels               32 = LDIO Write Output Channels High
  33 = LDIO Write Output Channels Low           34 = LIO Get Ports Direction
  35 = LIO Module Off                           36 = LIO Module On
  37 = LIO Set Ports Direction                  38 = LIO Set Ports Direction to Inputs
  39 = LIO Set Ports Direction to Outputs

LDIO Selection ('h'=display menu, 'q'=quit)->
_____________________________________________________________________________
Main Selection ('h'=display menu, 'q'=quit)-> 32
   Command: SDC_menu()
  01 = -- SDC Activate                          02 = -- SDC Close
  03 = -- SDC Disable                           04 = -- SDC Get Information
  05 = -- SDC Get Power Control                 06 = -- SDC Get Power Up Status
  07 = -- SDC Get Terminator                    08 = -- SDC Get Turn Around
  09 = -- SDC Get Value                         10 = -- SDC Open
  11 = -- SDC Reset (disable followed by enable) 12 = -- SDC Read Receiver
  13 = -- SDC Read Transmitter                  14 = -- SDC Set Value
  15 = -- SDC Set Power Control                 16 = -- SDC Set Terminator
  17 = -- SDC Set Turn Around                   18 = -- SDC write Transmitter
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

```
SDC Selection ('h'=display menu, 'q'=quit)->
```

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.

This page intentionally left blank

All information contained in this document is confidential and proprietary to Concurrent Real-Time. No part of this document may be reproduced, transmitted, in any form, without the prior written permission of Concurrent Real-Time. No license, expressed or implied, under any patent, copyright or trade secret right is granted or implied by the conveyance of this document.